

# DIN EN 15698-1:2025-07 (E)

District heating pipes - Bonded twin pipe systems for directly buried hot water networks - Part 1: Factory made twin pipe assembly of steel service pipes, polyurethane thermal insulation and one casing of polyethylene

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Requirements .....	6
4.1	Steel service pipe .....	6
4.1.1	Specification .....	6
4.1.2	Diameter and wall thickness .....	7
4.1.3	Surface condition .....	7
4.2	Casing .....	7
4.3	Polyurethane foam thermal insulation .....	7
4.4	Twin pipe assembly .....	7
4.4.1	General .....	7
4.4.2	Thermal insulation series .....	7
Table 1 --	Casing diameters .....	8
4.4.3	End alignment of flow and return steel service pipes .....	8
4.4.4	Distance between flow and return steel service pipes .....	8
Table 2 --	Distance between steel service pipes .....	9
4.4.5	Twisting of steel service pipes .....	9
Figure 1 --	Twisting, w, and distance between steel service pipes, Lp .....	10
4.4.6	Centre line deviation .....	10
Table 3 --	Centre line deviation related to nominal outside diameters .....	10
4.4.7	Ends of twin pipe assembly .....	10
4.4.8	Expected thermal life and long-term temperature resistance .....	11
4.4.9	Axial shear strength .....	11
4.4.10	Thermal conductivity in unaged condition .....	11
4.4.11	Impact resistance .....	11
4.4.12	Surface conditions at delivery .....	11
4.4.13	Linear water tightness .....	11
4.4.14	Measuring wires for surveillance systems .....	11
5	Test methods .....	11
5.1	General .....	11
5.2	Test specimens .....	11
Figure 2 --	Areas for test specimens .....	12
5.3	Polyurethane foam thermal insulation .....	12
5.4	Twin pipe assembly .....	12
5.4.1	Axial shear strength .....	12

<b>Figure 3 -- Axial shear test arrangement .....</b>	<b>13</b>
<b>5.4.2 Expected thermal life and long-term temperature resistance .....</b>	<b>14</b>
<b>5.4.3 Thermal conductivity in unaged condition .....</b>	<b>14</b>
<b>5.4.4 Thermal conductivity at artificially aged condition .....</b>	<b>14</b>
<b>5.4.5 Impact resistance .....</b>	<b>14</b>
<b>5.4.6 Linear water tightness .....</b>	<b>14</b>
<b>6 Marking .....</b>	<b>14</b>
<b>Annex A (informative) Guidelines for inspection and testing .....</b>	<b>15</b>
<b>A.1 General .....</b>	<b>15</b>
<b>A.2 Manufacturer's type test .....</b>	<b>15</b>
<b>A.3 Manufacturer's quality control .....</b>	<b>15</b>
<b>A.4 Additional inspection .....</b>	<b>15</b>
<b>Table A.1 -- Twin pipe assembly inspection .....</b>	<b>16</b>
<b>Annex B (informative) Waste treatment and recycling .....</b>	<b>17</b>
<b>Bibliography .....</b>	<b>18</b>