

DIN EN 15316-3-2:2008-01 (E)

Heating systems in buildings - Method for calculation of system energy requirements and system efficiencies - Part 3-2: Domestic hot water systems, distribution

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 7 |
| 4 | Symbols, units and indices | 10 |
| 5 | Domestic hot water system characteristics | 11 |
| 5.1 | General | 11 |
| 5.2 | Single zone and single system | 12 |
| 5.3 | Single zone and multiple systems | 12 |
| 5.4 | Multiple zones with single system | 13 |
| 6 | Distribution thermal losses | 13 |
| 6.1 | Total distribution thermal losses | 13 |
| 6.2 | Thermal losses from individual distribution pipe section | 14 |
| 6.2.1 | General | 14 |
| 6.2.2 | Thermal losses from pipes based on dwelling area | 14 |
| 6.2.3 | Thermal losses from pipes based on pipe lengths and number of tapplings per day | 15 |
| 6.2.4 | Thermal losses from pipes based on pipe lengths and distribution efficiencies | 15 |
| 6.2.5 | Thermal losses from pipes based on pipe lengths and tapping profiles | 16 |
| 6.2.6 | Thermal losses from pipes based on pipe lengths and average temperature | 16 |
| 6.2.7 | Heat energy lost due to wasted hot water | 16 |
| 6.2.8 | Time periods | 16 |
| 6.3 | Thermal losses from circulation loop | 16 |
| 6.3.1 | General | 16 |
| 6.3.2 | Thermal losses from circulation loop based on pipe length and a fixed value of heat loss | 16 |
| 6.3.3 | Thermal losses from circulation loop based on a physical approach | 17 |
| 6.3.4 | Additional thermal losses from circulation loop during periods of no circulation | 17 |
| 6.3.5 | Total thermal loss from circulation loop | 17 |
| 6.4 | Thermal losses due to accessories | 18 |
| 6.5 | User outlets | 18 |
| 7 | Auxiliary energy | 18 |
| 7.1 | Total auxiliary energy consumption | 18 |
| 7.2 | Auxiliary energy consumption for ribbon heating | 18 |
| 7.3 | Auxiliary energy consumption for pumps | 19 |
| 7.3.1 | General | 19 |
| 7.3.2 | Simplified method | 19 |
| 7.3.3 | Detailed calculation method | 20 |
| 8 | Recoverable, recovered and unrecoverable system losses | 20 |
| Annex A (informative) | Calculation of thermal losses from pipes based on pipe lengths and the number of tapplings per day | 22 |

| | |
|---|-----------|
| Annex B (informative) Calculation of thermal losses from pipes based on pipe lengths and distribution efficiencies | 24 |
| Annex C (informative) Calculation of thermal losses from pipes based on pipe lengths and tapping profiles | 26 |
| Annex D (informative) Calculation of thermal losses from circulation loop | 28 |
| D.1 Calculation of thermal losses based on pipe length | 28 |
| D.2 Thermal losses based on a detailed calculation method | 28 |
| D.2.1 General | 28 |
| D.2.2 Determination of length of pipe sections | 28 |
| D.2.3 Determination of heat transfer coefficients | 31 |
| D.2.4 Tabulated method for calculation of linear thermal transmittance | 33 |
| D.2.5 Determination of average ambient temperature | 34 |
| D.2.6 Determination of average hot water temperature of pipe section | 34 |
| Annex E (informative) Calculation of thermal losses from user outlets | 35 |
| Annex F (informative) Calculation of auxiliary energy requirement of a circulation pump | 36 |
| F.1 Simplified method for calculation of auxiliary energy requirement of a circulation pump . | 36 |
| F.2 Detailed method for calculation of auxiliary energy requirement of a circulation pump | 36 |
| F.2.1 Hydraulic energy requirement | 36 |
| F.2.2 Hydraulic power required by the pump | 36 |
| F.2.3 Duration of the provision of domestic hot water | 37 |
| F.2.4 Pump performance coefficient | 38 |
| F.2.5 Intermittent pump operation | 39 |
| F.2.6 Expenditure value coefficient | 39 |
| F.3 Auxiliary energy recoverable factor | 40 |
| Bibliography | 41 |