

# ISO/IEC 19794-7:2007-06 (E)

## Information technology - Biometric data interchange formats - Part 7: Signature/sign time series data

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Conformance .....</b>	<b>1</b>
<b>3</b>	<b>Normative references .....</b>	<b>1</b>
<b>4</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>5</b>	<b>Conventions .....</b>	<b>4</b>
<b>5.1</b>	<b>Coordinate system .....</b>	<b>4</b>
<b>5.2</b>	<b>Octet order .....</b>	<b>4</b>
<b>5.3</b>	<b>Registered format type identifiers .....</b>	<b>4</b>
<b>6</b>	<b>Channels .....</b>	<b>5</b>
<b>6.1</b>	<b>General .....</b>	<b>5</b>
<b>6.2</b>	<b>Pen position channels: X, Y, Z .....</b>	<b>5</b>
<b>6.3</b>	<b>Pen velocity channels: VX, VY .....</b>	<b>6</b>
<b>6.4</b>	<b>Pen acceleration channels: AX, AY .....</b>	<b>6</b>
<b>6.5</b>	<b>Time channel: T .....</b>	<b>6</b>
<b>6.6</b>	<b>Time difference channel: DT .....</b>	<b>6</b>
<b>6.7</b>	<b>Pen tip force channel: F .....</b>	<b>6</b>
<b>6.8</b>	<b>Tip switch state channel: S .....</b>	<b>6</b>
<b>6.9</b>	<b>Pen orientation channels: TX, TY, Az, El, R .....</b>	<b>6</b>
<b>7</b>	<b>Full format .....</b>	<b>7</b>
<b>7.1</b>	<b>Introduction .....</b>	<b>7</b>
<b>7.2</b>	<b>BDB organisation .....</b>	<b>7</b>
<b>7.3</b>	<b>BDB header .....</b>	<b>7</b>
<b>7.4</b>	<b>BDB body .....</b>	<b>11</b>
<b>8</b>	<b>Compact format .....</b>	<b>12</b>
<b>8.1</b>	<b>Introduction .....</b>	<b>12</b>
<b>8.2</b>	<b>Matching algorithm parameters template .....</b>	<b>13</b>
<b>8.3</b>	<b>Embedment in a CBEFF data structure .....</b>	<b>14</b>
<b>8.4</b>	<b>BDB body .....</b>	<b>15</b>
<b>Annex A (informative) Best practices -- Data acquisition .....</b>		<b>16</b>
<b>Annex B (informative) ASN.1 specification of the data interchange formats .....</b>		<b>17</b>
<b>Annex C (informative) Signature/sign coding examples .....</b>		<b>21</b>
<b>Bibliography .....</b>		<b>23</b>