

ISO/IEC 14443-4:2008-07 (E)

Identification cards - Contactless integrated circuit cards - Proximity cards - Part 4: Transmission protocol

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
5	Protocol activation of PICC Type A	4
5.1	Request for answer to select	5
5.2	Answer to select	6
5.2.1	Structure of the bytes	7
5.2.2	Length byte	7
5.2.3	Format byte	7
5.2.4	Interface byte TA(1)	8
5.2.5	Interface byte TB(1)	9
5.2.6	Interface byte TC(1)	9
5.2.7	Historical bytes	10
5.3	Protocol and parameter selection request	10
5.3.1	Start byte	10
5.3.2	Parameter 0	11
5.3.3	Parameter 1	11
5.4	Protocol and parameter selection response	12
5.5	Activation frame waiting time	12
5.6	Error detection and recovery	12
5.6.1	Handling of RATS and ATS	12
5.6.2	Handling of PPS request and PPS response	13
5.6.3	Handling of the CID during activation	13
6	Protocol activation of PICC Type B	14
7	Half-duplex block transmission protocol	14
7.1	Block format	14
7.1.1	Prologue field	15
7.1.2	Information field	18
7.1.3	Epilogue field	18
7.2	Frame waiting time	18
7.3	Frame waiting time extension	18
7.4	Power level indication	19
7.5	Protocol operation	20
7.5.1	Multi-Activation	20
7.5.2	Chaining	20
7.5.3	Block numbering rules	21
7.5.4	Block handling rules	22
7.5.5	PICC presence check	23
7.5.6	Error detection and recovery	23

8	Protocol deactivation of PICC Type A and Type B	24
8.1	Deactivation frame waiting time	24
8.2	Error detection and recovery	24
Annex A (informative) Multi-Activation example		25
Annex B (informative) Protocol scenarios		26
B.1	Notation	26
B.2	Error-free operation	26
B.2.1	Exchange of I-blocks	26
B.2.2	Request for waiting time extension	27
B.2.3	DESELECT	27
B.2.4	Chaining	27
B.2.5	PICC Presence check	28
B.3	Error handling	29
B.3.1	Exchange of I-blocks	29
B.3.2	Request for waiting time extension	30
B.3.3	DESELECT	32
B.3.4	Chaining	32
Annex C (informative) Block and frame coding overview		35
Bibliography		37