

ISO/IEC 18000-3:2008-09 (E)

Information technology - Radio frequency identification for item management - Part 3: Parameters for air interface communications at 13,56 MHz

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Conformance	1
2.1	Claiming conformance	1
3	Normative references	1
4	Terms and definitions	2
5	Symbols and abbreviated terms	2
6	Requirements: Physical layer, collision management system and protocol values for 13,56 MHz systems	2
6.0	General and applicable to both Modes of this part of ISO/IEC 18000	2
6.0.1	Presentation as determined in ISO/IEC 18000-1	2
6.0.2	ISO/IEC 18000-3 Interoperability	2
6.0.3	ISO/IEC 18000-3 reader conformance/compliance	3
6.0.4	ISO/IEC 18000-3 tag compliance	3
6.0.5	Command structure and extensibility	3
6.0.6	Mandatory commands	3
6.0.7	Optional commands	3
6.0.8	Custom commands	3
6.0.9	Proprietary commands	3
6.1	Physical layer, collision management system and protocols for MODE 1 of this part of ISO/IEC 18000	4
6.1.1	Read/Write system	4
6.1.2	Normative Aspects	4
6.1.3	Conformance and performance measurement aspects	4
6.1.4	Physical Layer	4
6.1.5	Protocol and collision management operating method	4
6.1.6	Commands	4
6.1.7	Parameter tables for interrogator to tag link	4
6.1.8	Parameter tables for tag to interrogator link	4
6.2	MODE 2: Physical layer, collision management system and protocols for MODE 2 of this part of ISO/IEC 18000	4
6.2.1	Normative aspects: physical and media access control (MAC) parameters: interrogator to tag link	5
6.2.2	Tag to interrogator link	7
6.2.3	Description of operating method	10
6.2.4	Protocol parameters	16
6.2.5	Description of protocol operating method	16
6.2.6	Collision management parameters	33
6.2.7	Description of collision management parameters operating method (informative)	33
6.2.8	Tag order sequencing	41
6.2.9	Commands	41
6.2.10	Air interface application layer	41
6.2.11	Optional Functionality	41

7	Marking of equipment	44
8	Table of characteristic differences between the MODES specified in this part of ISO/IEC 18000	44
	Annex A (normative) Phase jitter modulation (PJM)	45
	Annex B (informative) Known possible interferences between the MODES determined in this part of ISO/IEC 18000	49
	Annex C (informative) Interrogator pseudo-code for collision management (Mode 1)	50
	Annex D (informative) Cyclic Redundancy Check (CRC) (16 bit)	51
D.1	The CRC error detection method	51
C.2	CRC calculation example	51
	Annex E (informative) Cyclic redundancy check (CRC) mode 2 (32 bit)	53
E.1	The CRC 32 error detection method	53
E.2	CRC 32 calculation example	53
E.3	Practical example of CRC 32 calculation	55
	Annex F (informative) Mode 1 IC reference	56
	Annex G (informative) A description of Mode 1 based on the ISO/IEC 15693 protocol as used for Item Management	57
G.1	Parameter tables for interrogator to tag link	57
G.2	Parameter tables for tag to interrogator link	62
G.3	Description of operating method	66
G.3.1	Communications signal interface interrogator to tag	66
G.3.2	Modulation	66
G.3.3	Data rate and data coding	67
G.3.4	Interrogator to tag frames	70
G.3.5	Communications signal interface tag to interrogator	71
G.4	Protocol parameters	75
G.4.1	Table of protocol parameters	75
G.5	Description of protocol operating method	80
G.5.1	Definition of data elements	80
G.5.2	Data storage format identifier (DSFID)	82
G.5.3	CRC	82
G.5.4	Overall protocol description	83
G.5.5	Modes	84
G.5.6	Response format	86
G.5.7	RF tag states	88
G.6	Collision management	90
G.7	Description of collision management operating method (Informative)	95
G.7.1	Request parameters	95
G.7.2	Request processing by the RF tag	96
G.7.3	Explanation of a collision management sequence	98
G.7.4	Timing specifications	100
G.8	Commands	102
G.8.1	Command types	102
G.8.2	Command codes	103
G.8.3	Mandatory commands	104
G.8.4	Optional commands	105
G.8.5	Custom commands	120
G.8.6	Proprietary commands	121
	Bibliography	122