

ISO/IEC 18000-4:2008-09 (E)

Information technology - Radio frequency identification for item management - Part 4: Parameters for air interface communications at 2,45 GHz

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	2
5 2,45 GHz RFID protocols that support this part of ISO/IEC 18000	3
5.1 General	3
5.1.1 Protocols	3
5.1.2 Frequency	3
5.1.3 Tag identification number	4
5.1.4 Potential interference	4
5.2 MODE 1: Passive backscatter RFID system	4
5.2.1 MODE 1: Physical and media access control (MAC) parameters	5
5.2.2 Physical layer and data coding	10
5.2.3 Protocol and collision arbitration	20
5.3 MODE 2: Long range high data rate RFID system	47
5.3.1 MODE 2: Physical and media access control (MAC) parameters	47
5.3.2 Modulation and coding	52
5.3.3 General system description	55
5.3.4 Frame structure	55
5.3.5 CCC 6.2.5 Channel coding and sequences	77
5.3.6 Command set for the command slot channel: CS-CH (only for R/W-tag)	78
6 Table of characteristic differences between the modes specified in this part of ISO/IEC 18000	82
Annex A (informative) Mode 1: Memory Map	83
A.1 Tag memory map	83
A.2 Unique identifier	83
A.3 Manufacturer ID and tag hardware	85
A.4 Tag Memory layout	86
A.5 Application (USER) memory	88
Annex B (informative) Mode 1: CRC	89
B.1 Interrogator to tag and tag to interrogator CRC-16	89
B.2 CRC calculation examples	90
Annex C (normative) Mode 2: Memory Map	93
C.1 Tag Memory map	93
C.2 Tag Serial number - UserTagID	94
C.3 Tag manufacturer's identifiers - MfrTagID	95

Annex D (informative) Mode 2: CRC	96
D.1 Cyclic redundancy check (CRC)	96
D.2 CRC calculation example	96
Bibliography	98