ISO/IEC 24771:2009-04 (E)

Information technology - Telecommunications and information exchange between systems - MAC/PHY standard for ad hoc wireless network to support QoS in an industrial work environment

Contents

Page

Foreword vii

1 Scope 1

2 Terms and definitions, and abbreviated terms 1
2.1 Terms and definitions 1
2.2 Abbreviated terms 3

3 Overview 6
3.1 Characteristics 6
3.2 Components of network 6
3.3 Functional overview 7
3.4 Summary of operations 9
3.5 Summary of states 10

4 Inter-layer interfaces 11
4.1 Summary 11
4.2 General format of management primitives 12
4.3 MLME SAP 15
4.4 MAC management 48
4.5 MAC SAP 49
4.6 PHY specification 53

5 Mac frame format 69
5.1 Overview 69
5.2 General format of MAC frames 70
5.3 Frame formats 73
5.4 Information block 77
5.5 Command block 81

6 MAC feature description 93
6.1 Network formation and association 93
6.2 Media access 95
6.3 Synchronization 98
6.4 Resource allocation 99
6.5 Fragmentation and defragmentation 101
6.6 Acknowledgement and retransmission 101
6.7 Power saving 102
6.8 Dynamic channel management 103
6.9 MAC parameters 104

7 PHY specifications 105
7.1 General specifications 105
7.2 General requirements 105
7.3 PHY Protocol Data Unit (PDU) format 106
7.4 Modulation and coding 110
7.5 PHY layer constants and PHY MIB attribute 116
7.6 Transmitter specification 117
7.7 Receiver specifications 119

Annex A (informative) Example scheduler and admission control 121

Figures

Figure 1 - Network 7

Figure 2 - Superframe 8

Figure 3 - Protocol stack configuration 12

Figure 4 - Format of MAC frame 70

Figure 5 - Format of frame control fields 70

Figure 6 - Format of stream ID field 72

Figure 7 - Beacon frame format 73

Figure 8 - Immediate acknowledgement frame format 75

Figure 9 - Delayed acknowledgement frame payload format 75

Figure 10 - Format of record for stream-m 75

Figure 11 - Format of record for stream-m 76

Figure 12 - Data frame format 76

Figure 13 - RTS frame format 76

Figure 14 - CTS frame format 77

Figure 15 - Information block format 77

Figure 16 - Station UID information block format 78

Figure 17 - Station name information block format 78

Figure 18 - Station type information block format 78

Figure 19 - Network synchronization information block format 78

Figure 20 - Capability information block format 79

Figure 21 - Capability fields format 79

Figure 22 - Maximum support timeslot information block format 79

Figure 23 - Maximum transmit power information block format 80

Figure 24 - Resource allocation information block format 80

Figure 25 - Resource allocation block format 80

Figure 26 - New master notification information block format 81

Figure 27 - Sleep state notification information block format 81

Figure 28 - Command block format 81

Figure 29 - Associate request command block format 83

Figure 30 - Associate response command block format 83

Figure 31 - Disassociate request payload format 84

Figure 32 - Master handover command block format 85

Figure 33 - Resource allocation request command block format 85

Figure 34 - Resource allocation request record format 85

Figure 35 - Resource allocation response command block format 86

Figure 36 - Resource allocation modification command block format 87

Figure 37 - Resource allocation modification request record format 87

Figure 38 - Resource allocation termination command block format 87

Figure 39 - Delayed acknowledgement resynchronization command block format 88

Figure 40 - Delayed acknowledgement resynchronization command record format 88

Figure 41 - Sleep state request command block format 88

Figure 42 - Sleep state response command block format 89

Figure 43 - Activation indication command block format 89

Figure 44 - Transmit power adjustment command block format 89

Figure 45 - Station information request command block format 90

Figure 46 - Station information response command block format 90

Figure 47 - Station information block format 90

Figure 48 - Data query command block format 91

Figure 49 - Channel state request command block format 91

Figure 50 - Channel state response command block format 91

Figure 51 - Remote channel scan request command block format 92

Figure 52 - Remote channel scan response command block format 92

Figure 53 - Channel information block format 92

Figure 54 - Application specific command format 93

Figure 55 - Association Process 95

Figure 56 - Inter-frame space in the allocated time slots 98

Figure 57 - Superframe synchronization 98

Figure 58 - Stream connection process for synchronized data transmission 100

Figure 59 - Operating frequency channels 105

Figure 60 - PHY Protocol Data Unit (PDU) format 107
Figure 61 - Preamble format 108
Figure 62 - PHY Header 108
Figure 63 - LFSR generating the (15,10) shortened Hamming code 109
Figure 64 - LFSR circuit generating the HEC 109
Figure 65 - Scrambler Block Diagram 110
Figure 66 - QPSK modulation 111
Figure 67 - RATE1 block diagram 112
Figure 68 - RATE2 block diagram 112
Figure 69 - RATE3 block diagram 114
Figure 70 - RATE4 block diagram 114
Figure 71 - Preamble modulation 115
Figure 72 - Header modulation 115
Figure 73 - Payload modulation 115
Figure 74 - Signal constellation- of QPSK 116
Figure 75 - Error vector calculation 117
Figure 76 - Transmit power spectrum mask 118
Figure 77 - Transmitter RF response time 119
Figure A.1 - Stream info table in master 121
Figure A.2 - Calculation of ATS Position 121
Figure A.3 - Fragmentation of ATS(a) and enhance for it(b) 122
Figure A.4 - Slot allocation algorithm 123

Tables

Table 1 - General management primitive overview 12
Table 2 - MLME/PLME general management primitive parameters 13
Table 3 - MLME primitive summary 15
Table 4 - MLME-RESET primitive parameters 15
Table 5 - MLME-SCAN primitive parameters 17
Table 6 - PiconetDescription elements 17
Table 7 - MLME-START primitive parameters 19

Table 8 - MLME-SYNCH primitive parameters 20

Table 9 - MLME-ASSOCIATE.primitive parameters 22

Table 10 - MLME-DISASSOCIATE primitive parameters 25

Table 11 - MLME-Master-HANDOVER primitive parameters 27

Table 12 - MLME-MASTER-INFO primitive parameters 29

Table 13 - MLME-PROBE primitive parameters 31

Table 14 - MLME-CREATE-STREAM, MLME-MODIFY-STREAM, MLME-TERMINATE-STREAM primitive parameters 33

Table 15 - MLME-CHANNEL-STATUS primitive parameters 37

Table 16 - MLME-REMOTE-SCAN primitive parameters 40

Table 17 - RemotePiconetDescription elements 40

Table 18 - MLME-NETWORK-PARM-CHANGE primitive parameters 43

Table 19 - MLME-TX-POWER-CHANGE primitive parameters 44

Table 20 - MLME-SLEEP primitive parameters 46

Table 21 - MAC MIB master group parameters 48

Table 22 - MAC MIB attribute group parameters 48

Table 23 - MAC MIB association group parameters 49

Table 24 - MAC SAP primitive summary 49

Table 25 - MAC-ASYNC-DATA and MAC-ISOCH-DATA primitive parameters 50

Table 26 - PD-SAP primitives 53

Table 27 - PD-SAP parameters 54

Table 28 - PLME-SAP primitives 63

Table 29 - PLME-CCA.confirm parameters 64

Table 30 - Physical layer enumerated values 69

Table 31 - Frame types 70

Table 32 - Usage codes by frame type 73

Table 33 - Beacon frame body 74

Table 34 - Setting the control field of the beacon frame 74

Table 35 - Setting the control field of the beacon frame 75

Table 36 - Information blocks 77

Table 37 - Command types 82

Table 38 - Order of preference when comparing capability 84

Table 39 - MAC layer parameters 104

Table 40 - Center frequency of 10 channels 105

Table 41 - PHY layer timing parameters 106

Table 42 - Interframe space parameter 106

Table 43 - CAZAC sequence 107

Table 44 - Forward Error Correction 108

Table 45 - Constant Envelope Coding 109

Table 46 - Data rate according to modulation type 115

Table 47 - PHY layer constants 116

Table 48 - PHY MIB characteristics group parameters 116

Table 49 - Transmit PSD limits 118

Table 50 - Transmit power 119