

# ISO/IEC 24771:2009-04 (E)

## Information technology - Telecommunications and information exchange between systems - MAC/PHY standard for ad hoc wireless network to support QoS in an industrial work environment

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vii
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Terms and definitions, and abbreviated terms .....</b>	<b>1</b>
2.1	Terms and definitions .....	1
2.2	Abbreviated terms .....	3
<b>3</b>	<b>Overview .....</b>	<b>6</b>
3.1	Characteristics .....	6
3.2	Components of network .....	6
3.3	Functional overview .....	7
3.4	Summary of operations .....	9
3.5	Summary of states .....	10
<b>4</b>	<b>Inter-layer interfaces .....</b>	<b>11</b>
4.1	Summary .....	11
4.2	General format of management primitives .....	12
4.3	MLME SAP .....	15
4.4	MAC management .....	48
4.5	MAC SAP .....	49
4.6	PHY specification .....	53
<b>5</b>	<b>Mac frame format .....</b>	<b>69</b>
5.1	Overview .....	69
5.2	General format of MAC frames .....	70
5.3	Frame formats .....	73
5.4	Information block .....	77
5.5	Command block .....	81
<b>6</b>	<b>MAC feature description .....</b>	<b>93</b>
6.1	Network formation and association .....	93
6.2	Media access .....	95
6.3	Synchronization .....	98
6.4	Resource allocation .....	99
6.5	Fragmentation and defragmentation .....	101
6.6	Acknowledgement and retransmission .....	101
6.7	Power saving .....	102
6.8	Dynamic channel management .....	103
6.9	MAC parameters .....	104
<b>7</b>	<b>PHY specifications .....</b>	<b>105</b>
7.1	General specifications .....	105
7.2	General requirements .....	105
7.3	PHY Protocol Data Unit (PDU) format .....	106
7.4	Modulation and coding .....	110
7.5	PHY layer constants and PHY MIB attribute .....	116
7.6	Transmitter specification .....	117
7.7	Receiver specifications .....	119

<b>Annex A (informative) Example scheduler and admission control .....</b>	<b>121</b>
<b>Figures</b>	
<b>Figure 1 - Network .....</b>	<b>7</b>
<b>Figure 2 - Superframe .....</b>	<b>8</b>
<b>Figure 3 - Protocol stack configuration .....</b>	<b>12</b>
<b>Figure 4 - Format of MAC frame .....</b>	<b>70</b>
<b>Figure 5 - Format of frame control fields .....</b>	<b>70</b>
<b>Figure 6 - Format of stream ID field .....</b>	<b>72</b>
<b>Figure 7 - Beacon frame format .....</b>	<b>73</b>
<b>Figure 8 - Immediate acknowledgement frame format .....</b>	<b>75</b>
<b>Figure 9 - Delayed acknowledgement frame payload format .....</b>	<b>75</b>
<b>Figure 10 - Format of record for stream-m .....</b>	<b>75</b>
<b>Figure 11 - Format of record for stream-m .....</b>	<b>76</b>
<b>Figure 12 - Data frame format .....</b>	<b>76</b>
<b>Figure 13 - RTS frame format .....</b>	<b>76</b>
<b>Figure 14 - CTS frame format .....</b>	<b>77</b>
<b>Figure 15 - Information block format .....</b>	<b>77</b>
<b>Figure 16 - Station UID information block format .....</b>	<b>78</b>
<b>Figure 17 - Station name information block format .....</b>	<b>78</b>
<b>Figure 18 - Station type information block format .....</b>	<b>78</b>
<b>Figure 19 - Network synchronization information block format .....</b>	<b>78</b>
<b>Figure 20 - Capability information block format .....</b>	<b>79</b>
<b>Figure 21 - Capability fields format .....</b>	<b>79</b>
<b>Figure 22 - Maximum support timeslot information block format .....</b>	<b>79</b>
<b>Figure 23 - Maximum transmit power information block format .....</b>	<b>80</b>
<b>Figure 24 - Resource allocation information block format .....</b>	<b>80</b>
<b>Figure 25 - Resource allocation block format .....</b>	<b>80</b>
<b>Figure 26 - New master notification information block format .....</b>	<b>81</b>
<b>Figure 27 - Sleep state notification information block format .....</b>	<b>81</b>
<b>Figure 28 - Command block format .....</b>	<b>81</b>

Figure 29 - Associate request command block format .....	83
Figure 30 - Associate response command block format .....	83
Figure 31 - Disassociate request payload format .....	84
Figure 32 - Master handover command block format .....	85
Figure 33 - Resource allocation request command block format .....	85
Figure 34 - Resource allocation request record format .....	85
Figure 35 - Resource allocation response command block format .....	86
Figure 36 - Resource allocation modification command block format .....	87
Figure 37 - Resource allocation modification request record format .....	87
Figure 38 - Resource allocation termination command block format .....	87
Figure 39 - Delayed acknowledgement resynchronization command block format .....	88
Figure 40 - Delayed acknowledgement resynchronization command record format .....	88
Figure 41 - Sleep state request command block format .....	88
Figure 42 - Sleep state response command block format .....	89
Figure 43 - Activation indication command block format .....	89
Figure 44 - Transmit power adjustment command block format .....	89
Figure 45 - Station information request command block format .....	90
Figure 46 - Station information response command block format .....	90
Figure 47 - Station information block format .....	90
Figure 48 - Data query command block format .....	91
Figure 49 - Channel state request command block format .....	91
Figure 50 - Channel state response command block format .....	91
Figure 51 - Remote channel scan request command block format .....	92
Figure 52 - Remote channel scan response command block format .....	92
Figure 53 - Channel information block format .....	92
Figure 54 - Application specific command format .....	93
Figure 55 - Association Process .....	95
Figure 56 - Inter-frame space in the allocated time slots .....	98
Figure 57 - Superframe synchronization .....	98
Figure 58 - Stream connection process for synchronized data transmission .....	100
Figure 59 - Operating frequency channels .....	105

Figure 60 - PHY Protocol Data Unit (PDU) format .....	107
Figure 61 - Preamble format .....	108
Figure 62 - PHY Header .....	108
Figure 63 - LFSR generating the (15,10) shortened Hamming code .....	109
Figure 64 - LFSR circuit generating the HEC .....	109
Figure 65 - Scrambler Block Diagram .....	110
Figure 66 - QPSK modulation .....	111
Figure 67 - RATE1 block diagram .....	112
Figure 68 - RATE2 block diagram .....	112
Figure 69 - RATE3 block diagram .....	114
Figure 70 - RATE4 block diagram .....	114
Figure 71 - Preamble modulation .....	115
Figure 72 - Header modulation .....	115
Figure 73 - Payload modulation .....	115
Figure 74 - Signal constellation- of QPSK .....	116
Figure 75 - Error vector calculation .....	117
Figure 76 - Transmit power spectrum mask .....	118
Figure 77 - Transmitter RF response time .....	119
Figure A.1 - Stream info table in master .....	121
Figure A.2 - Calculation of ATS Position .....	121
Figure A.3 - Fragmentation of ATS(a) and enhance for it(b) .....	122
Figure A.4 - Slot allocation algorithm .....	123

## Tables

Table 1 - General management primitive overview .....	12
Table 2 - MLME/PLME general management primitive parameters .....	13
Table 3 - MLME primitive summary .....	15
Table 4 - MLME-RESET primitive parameters .....	15
Table 5 - MLME-SCAN primitive parameters .....	17
Table 6 - PiconetDescription elements .....	17
Table 7 - MLME-START primitive parameters .....	19

Table 8 - MLME-SYNCH primitive parameters .....	20
Table 9 - MLME-ASSOCIATE.primitive parameters .....	22
Table 10 - MLME-DISASSOCIATE primitive parameters .....	25
Table 11 - MLME-Master-HANDOVER primitive parameters .....	27
Table 12 - MLME-MASTER-INFO primitive parameters .....	29
Table 13 - MLME-PROBE primitive parameters .....	31
Table 14 - MLME-CREATE-STREAM, MLME-MODIFY-STREAM, MLME-TERMINATE-STREAM primitive parameters .....	33
Table 15 - MLME-CHANNEL-STATUS primitive parameters .....	37
Table 16 - MLME-REMOTE-SCAN primitive parameters .....	40
Table 17 - RemotePiconetDescription elements .....	40
Table 18 - MLME-NETWORK-PARM-CHANGE primitive parameters .....	43
Table 19 - MLME-TX-POWER-CHANGE primitive parameters .....	44
Table 20 - MLME-SLEEP primitive parameters .....	46
Table 21 - MAC MIB master group parameters .....	48
Table 22 - MAC MIB attribute group parameters .....	48
Table 23 - MAC MIB association group parameters .....	49
Table 24 - MAC SAP primitive summary .....	49
Table 25 - MAC-ASYNC-DATA and MAC-ISOCH-DATA primitive parameters .....	50
Table 26 - PD-SAP primitives .....	53
Table 27 - PD-SAP parameters .....	54
Table 28 - PLME-SAP primitives .....	63
Table 29 - PLME-CCA.confirm parameters .....	64
Table 30 - Physical layer enumerated values .....	69
Table 31 - Frame types .....	70
Table 32 - Usage codes by frame type .....	73
Table 33 - Beacon frame body .....	74
Table 34 - Setting the control field of the beacon frame .....	74
Table 35 - Setting the control field of the beacon frame .....	75
Table 36 - Information blocks .....	77
Table 37 - Command types .....	82

<b>Table 38 - Order of preference when comparing capability .....</b>	<b>84</b>
<b>Table 39 - MAC layer parameters .....</b>	<b>104</b>
<b>Table 40 - Center frequency of 10 channels .....</b>	<b>105</b>
<b>Table 41 - PHY layer timing parameters .....</b>	<b>106</b>
<b>Table 42 - Interframe space parameter .....</b>	<b>106</b>
<b>Table 43 - CAZAC sequence .....</b>	<b>107</b>
<b>Table 44 - Forward Error Correction .....</b>	<b>108</b>
<b>Table 45 - Constant Envelope Coding .....</b>	<b>109</b>
<b>Table 46 - Data rate according to modulation type .....</b>	<b>115</b>
<b>Table 47 - PHY layer constants .....</b>	<b>116</b>
<b>Table 48 - PHY MIB characteristics group parameters .....</b>	<b>116</b>
<b>Table 49 - Transmit PSD limits .....</b>	<b>118</b>
<b>Table 50 - Transmit power .....</b>	<b>119</b>