

ISO/IEC 22535:2009-04 (E)

Information technology - Telecommunications and information exchange between systems - Corporate telecommunication networks - Tunnelling of QSIG over SIP

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Abbreviated terms | 3 |
| 5 | Background and architecture | 3 |
| 5.1 | Architecture | 3 |
| 5.2 | Basic operation | 4 |
| 5.3 | QSIG connectionless transport | 5 |
| 5.4 | Late availability of SDP parameters at the egress gateway | 5 |
| 6 | Procedures | 5 |
| 6.1 | General | 5 |
| 6.2 | Encapsulation of QSIG messages in SIP messages | 5 |
| 6.3 | QSIG SETUP message handling at an ingress gateway | 6 |
| 6.3.1 | Sending a SIP INVITE request | 6 |
| 6.3.2 | Receipt of responses to the INVITE request | 6 |
| 6.4 | QSIG SETUP message handling at an egress gateway | 7 |
| 6.4.1 | Receiving a SIP INVITE request | 7 |
| 6.4.2 | Rejecting a QSIG message in an INVITE request | 8 |
| 6.5 | Subsequent QSIG messages | 8 |
| 6.6 | Terminating the SIP dialog | 8 |
| 6.7 | QSIG connectionless message handling at an ingress gateway | 9 |
| 6.7.1 | Sending a SIP INVITE request | 9 |
| 6.7.2 | Receipt of responses to the INVITE request | 9 |
| 6.8 | QSIG connectionless message handling at an egress gateway | 10 |
| 7 | Example message sequences | 10 |
| 7.1 | Call establishment | 10 |
| 7.2 | Call clearing | 11 |
| 7.3 | QSIG connectionless message | 12 |
| 7.4 | Call establishment with port=0 in first SDP answer | 13 |
| 7.5 | Backwards compatibility with early editions | 14 |
| 8 | Security considerations | 16 |
| Annex A (informative) Changes from early editions | | 17 |
| Bibliography | | 19 |