

ISO/IEC 29642:2009-06 (E)

Information technology - Data interchange on 120 mm and 80 mm optical disk using +R W DL format - Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed 2,4X)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | viii |
| Introduction | | ix |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 2.1 | Optical disk | 1 |
| 2.2 | Generating system | 1 |
| 2.3 | Receiving system | 2 |
| 2.4 | Compatibility statement | 2 |
| 3 | Normative references | 2 |
| 4 | Terms and definitions | 2 |
| 5 | Conventions and notations | 4 |
| 5.1 | Representation of numbers | 4 |
| 5.2 | Names | 5 |
| 6 | Abbreviated terms | 5 |
| 7 | General description of the optical disk | 5 |
| 8 | General Requirements | 6 |
| 8.1 | Environments | 6 |
| 8.1.1 | Test environment | 6 |
| 8.1.2 | Operating environment | 7 |
| 8.1.3 | Storage environment | 7 |
| 8.1.4 | Transportation | 7 |
| 8.2 | Safety requirements | 7 |
| 8.3 | Flammability | 7 |
| 9 | Reference Drive | 7 |
| 9.1 | Optical system | 8 |
| 9.2 | Optical beam | 8 |
| 9.3 | Read channel 1 | 9 |
| 9.4 | Disk clamping | 9 |
| 9.5 | Rotation of the disk | 10 |
| 9.6 | Wobble channel (Read channel 2) | 10 |
| 9.7 | Tracking channel (Read channel 2) | 10 |
| 9.8 | Reference servo systems | 10 |
| 9.8.1 | Normalized servo transfer function | 10 |
| 9.8.2 | Reference Servo for Axial Tracking | 11 |
| 9.8.3 | Reference Servo for Radial Tracking | 12 |
| 10 | Dimensional characteristics | 13 |
| 10.1 | Reference Planes | 14 |
| 10.2 | Overall dimensions | 15 |

| | | |
|---------|---|----|
| 10.3 | First transition area | 15 |
| 10.4 | Second transition area | 16 |
| 10.5 | Clamping Zone | 16 |
| 10.6 | Third transition area | 16 |
| 10.7 | Information Zone | 16 |
| 10.7.1 | Sub-division of the Information Zone | 17 |
| 10.7.2 | Track mode | 17 |
| 10.8 | Rim area | 18 |
| 10.9 | Remark on tolerances | 18 |
| 11 | Mechanical characteristics | 18 |
| 11.1 | Mass | 18 |
| 11.2 | Moment of inertia | 18 |
| 11.3 | Dynamic imbalance | 18 |
| 11.4 | Axial runout | 18 |
| 11.4.1 | Tracking requirements at the Reference velocity (CLV) | 18 |
| 11.5 | Radial runout | 19 |
| 11.5.1 | Tracking requirements at the Reference velocity (CLV) | 19 |
| 12 | Optical characteristics in the Information Zone | 19 |
| 12.1 | Index of refraction | 19 |
| 12.2 | Thickness of the substrate | 19 |
| 12.3 | Reflectivity | 20 |
| 12.4 | Birefringence | 21 |
| 12.5 | Angular deviation | 21 |
| 13 | Data format | 21 |
| 13.1 | Data Frames | 22 |
| 13.1.1 | Identification Data (ID) | 22 |
| 13.1.2 | ID Error Detection Code (IED) | 23 |
| 13.1.3 | RSV | 23 |
| 13.1.4 | Error Detection Code (EDC) | 23 |
| 13.2 | Scrambled Frames | 24 |
| 13.3 | ECC Blocks | 25 |
| 13.4 | Recording Frames | 26 |
| 13.5 | Modulation and NRZI conversion | 27 |
| 13.6 | Physical Sectors | 27 |
| 13.7 | Layout of a Recording UNit (RUN) | 28 |
| 13.7.1 | Recording Unit position | 29 |
| 13.8 | d.c. component suppression control | 29 |
| 14 | Track format | 31 |
| 14.1 | Track shape | 31 |
| 14.2 | Track path | 31 |
| 14.3 | Track pitch | 31 |
| 14.4 | Track layout | 31 |
| 14.4.1 | ADIP information | 31 |
| 14.4.2 | Physical format information in ADIP | 35 |
| 15 | General description of the Information Zone | 50 |
| 16 | Layout of the Information Zone | 51 |
| 16.1 | Usage of the Data Zone | 51 |
| 16.2 | Physical Sector Numbers (PSNs) | 52 |
| 17 | Lead-in Zone | 53 |
| 17.1 | Initial Zone | 53 |
| 17.2 | Inner Disk Test Zone | 53 |
| 17.3 | Guard Zone 1 | 54 |
| 17.4 | Reserved Zone 1 | 54 |
| 17.5 | Reserved Zone 2 | 54 |
| 17.6 | Inner Disk Identification Zone | 54 |
| 17.7 | Reserved Zone 3 | 55 |
| 17.8 | Reference Code Zone | 55 |
| 17.9 | Buffer Zone 1 | 55 |
| 17.10 | Control Data Zone | 55 |
| 17.10.1 | Physical format information | 55 |
| 17.10.2 | Disk manufacturing information | 57 |
| 17.10.3 | Content provider information | 58 |

| | | |
|--------|---|----|
| 17.11 | Buffer Zone 2 | 58 |
| 18 | Data Zone | 58 |
| 19 | Middle Zones | 58 |
| 19.1 | Buffer Zones 3 | 59 |
| 19.2 | Reserved Zones 4 | 59 |
| 19.3 | Guard Zones 2 | 59 |
| 20 | Outer Drive Areas | 60 |
| 20.1 | Reserved Zone 5 | 61 |
| 20.2 | Outer Disk Test Zone | 61 |
| 20.3 | Guard Zone 3 | 61 |
| 21 | Lead-out Zone | 61 |
| 21.1 | Buffer Zone 4 | 62 |
| 21.2 | Inner Disk Test Zone | 62 |
| 21.3 | Final Zone | 62 |
| 22 | Assignment of Logical Sector Numbers (LSNs) | 62 |
| 23 | Formatting | 62 |
| 23.1 | Pre-formatting | 63 |
| 23.1.1 | Verification | 63 |
| 23.2 | Background formatting | 63 |
| 23.2.1 | Initialization | 63 |
| 23.2.2 | De-icing | 63 |
| 23.2.3 | Finalization | 66 |
| 23.2.4 | Verification (optional) | 66 |
| 23.3 | Sequential recording without formatting | 66 |
| 24 | Disk Control Blocks | 68 |
| 24.1 | General format of Disk Control Blocks | 68 |
| 24.2 | Format of the Formatting DCB (FDCB) | 70 |
| 24.3 | Format of the Write inhibit DCB (WDCB) | 75 |
| 25 | General | 77 |
| 26 | Method of testing | 77 |
| 26.1 | Environment | 77 |
| 26.2 | Reference Drive | 77 |
| 26.2.1 | Optics and mechanics | 77 |
| 26.2.2 | Read power | 77 |
| 26.2.3 | Read channels | 77 |
| 26.2.4 | Tracking | 78 |
| 26.3 | Definition of signals | 78 |
| 27 | Characteristics of the groove signals | 79 |
| 27.1 | Phase depth | 79 |
| 27.2 | Push-pull signal | 79 |
| 27.3 | Track Cross signal | 79 |
| 27.4 | Normalized wobble signal | 79 |
| 27.5 | Characteristics of the wobble | 80 |
| 28 | Method of testing | 80 |
| 28.1 | Environment | 80 |
| 28.2 | Reference Drive | 80 |
| 28.2.1 | Optics and mechanics | 80 |
| 28.2.2 | Read power | 80 |
| 28.2.3 | Read channels | 80 |
| 28.2.4 | Tracking | 81 |
| 28.2.5 | Scanning velocity | 81 |
| 28.3 | Write conditions | 81 |
| 28.3.1 | Write pulse waveform | 81 |
| 28.3.2 | Write power | 81 |
| 28.3.3 | Write power shift for layer L1 due to recording on layer L0 | 82 |
| 28.4 | Measurement conditions | 82 |
| 29 | Characteristics of the recorded signals | 82 |
| 29.1 | Channel bit length | 82 |
| 29.2 | Definition of signals | 82 |
| 29.2.1 | High frequency signals (HF) | 82 |
| 29.2.2 | Modulated amplitude | 83 |

| | | |
|--|--|-----|
| 29.2.3 | Signal asymmetry | 83 |
| 29.2.4 | Normalized Slicing Level jump | 83 |
| 29.2.5 | Jitter | 84 |
| 29.3 | Read stability | 84 |
| 30 | Additional testing conditions | 85 |
| 30.1 | Test environment | 85 |
| 30.1.1 | Optics | 85 |
| 30.2 | Definition of signals | 85 |
| 30.2.1 | Modulated amplitude | 86 |
| 30.2.2 | Signal asymmetry | 86 |
| 30.2.3 | Jitter | 86 |
| 30.2.4 | Track Cross signal | 86 |
| 30.2.5 | Differential phase tracking error signal | 86 |
| 30.2.6 | Tangential push-pull signal | 87 |
| 31 | Quality of the recording layer | 88 |
| 31.1 | Defects | 88 |
| 31.2 | Data errors | 88 |
| 32 | Method of testing | 89 |
| 32.1 | Environment | 89 |
| 32.2 | Reference Drive | 89 |
| 32.2.1 | Optics and mechanics | 89 |
| 32.2.2 | Read power | 89 |
| 32.2.3 | Read channels | 89 |
| 32.2.4 | Error correction | 89 |
| 32.2.5 | Tracking | 89 |
| 33 | Minimum quality of a Recording Unit | 90 |
| 33.1 | Tracking | 90 |
| 33.2 | User-written data | 90 |
| Annex A (normative) 80 mm +RW DL disk | | 91 |
| Annex B (normative) Structure for Extended format information in the Data Zone | | 96 |
| Annex C (normative) Measurement of light reflectivity | | 99 |
| Annex D (normative) Measurement of birefringence | | 101 |
| Annex E (normative) Measuring conditions for operation signals | | 104 |
| Annex F (normative) Measurement of the differential phase tracking error | | 107 |
| Annex G (normative) The write pulse wave form for testing | | 111 |
| Annex H (normative) 8-to-16 Modulation | | 116 |
| Annex I (normative) Optimum Power Control | | 125 |
| Annex J (normative) Logical to Physical address translation | | 130 |
| Annex K (informative) Recommended access method for players | | 131 |
| Annex L (informative) Measurement of the groove wobble amplitude | | 132 |
| Annex M (informative) Transportation | | 134 |
| Annex N (informative) Defect Management and Physical Formatting | | 135 |
| Annex O (informative) Video Content Protection System | | 136 |
| Annex P (informative) How to use the Physical format information in ADIP | | 137 |
| Annex Q (informative) Values to be Implemented in Existing and Future Specifications | | 139 |
| Bibliography | | 143 |