

ISO/IEC 12862:2009-06 (E)

Information technology - 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD recordable disk for dual layer (DVD-R f or DL)

Contents		Page
Foreword		vii
Introduction		viii
1	Scope	1
2	Conformance	1
2.1	Optical disk	1
2.2	Generating system	2
2.3	Receiving system	2
3	Normative references	2
4	Terms and definitions	2
5	Conventions and notations	6
5.1	Representation of numbers	6
5.2	Names	6
6	Abbreviated terms	6
7	General description of a disk	8
8	General requirement	8
8.1	Environments	8
8.1.1	Test environment	8
8.1.2	Operating environment	9
8.1.3	Storage environment	9
8.1.4	Transportation	10
8.2	Safety requirements	10
8.3	Flammability	10
9	Reference measurement devices	10
9.1	Pick-Up Head (PUH)	10
9.1.1	PUH for measuring recorded disks	10
9.1.2	PUH for measuring unrecorded disks	12
9.2	Measurement conditions	13
9.2.1	Recorded and unrecorded disk	13
9.2.2	Recorded disk	13
9.2.3	Unrecorded disk	13
9.3	Normalized servo transfer function	13
9.4	Reference servo for axial tracking	14
9.4.1	Recorded disk	14
9.4.2	Unrecorded disk	15
9.5	Reference servo for radial tracking	16
9.5.1	Recorded disk	16
9.5.2	Unrecorded disk	17
10	Dimensional characteristics	18
10.1	Overall dimensions	20
10.2	First transition area	20

10.3	Second transition area	21
10.4	Clamping Zone	21
10.5	Third transition area	21
10.6	R-Information Zone	22
10.6.1	Sub-divisions of the R-Information Zone	22
10.7	Information Zone	22
10.7.1	Sub-divisions of the Information zone	22
10.8	Track geometry	23
10.8.1	Track Path	24
10.9	Channel bit length	24
10.10	Rim area	24
10.11	Remark on tolerances	25
10.12	Label	25
11	Mechanical parameters	25
11.1	Mass	25
11.2	Moment of inertia	25
11.3	Dynamic imbalance	25
11.4	Sense of rotation	25
11.5	Runout	26
11.5.1	Axial runout	26
11.5.2	Radial runout	26
12	Optical parameters	26
12.1	Recorded and unrecorded disk parameters	26
12.1.1	Index of refraction	26
12.1.2	Thickness of the transparent substrate	26
12.1.3	Angular deviation	27
12.1.4	Birefringence of the transparent substrate	27
12.2	Recorded disk reflectivity	27
12.3	Unrecorded disk parameters	28
12.3.1	Polarity of reflectivity modulation	28
12.3.2	Recording power sensitivity variation	28
13	Operational signals for recorded disk	28
13.1	Measurement conditions	28
13.2	Read conditions	28
13.3	Recorded disk high frequency (HF) signals	28
13.3.1	Modulated amplitude	28
13.3.2	Signal asymmetry	29
13.3.3	Cross-track signal	29
13.4	Quality of signals	29
13.4.1	Jitter	29
13.4.2	Random errors	29
13.4.3	Defects	30
13.5	Servo signals	30
13.5.1	Differential phase tracking error signal	30
13.5.2	Tangential push-pull signal	30
13.6	Groove wobble signal	32
14	Operational signals for the unrecorded disk	33
14.1	Measurement conditions	33
14.2	Recording conditions	33
14.3	Write strategy for media testing	33
14.3.1	Definition of the write pulse	34
14.4	Servo signals	35
14.4.1	Radial push-pull tracking error signal	35
14.4.2	Defects	36
14.5	Addressing signals	36
14.5.1	Land Pre-Pit signal	36
14.5.2	Groove wobble signal	38
14.5.3	Relation in phase between wobble and Land Pre-Pit	38
15	General	39
16	Data Frames	39
16.1	Identification Data (ID)	40
16.2	ID Error Detection Code	41

16.3	RSV	41
16.4	Error Detection Code	41
17	Scrambled Frames	42
18	ECC Block configuration	43
19	Recording Frames	44
20	Modulation	45
21	Physical Sectors	46
22	Suppress control of the d.c. component	47
23	Linking scheme	48
23.1	Structure of linking	48
23.2	2K-Link and 32K-Link	49
23.3	Lossless-Link	49
24	General description of the Information Zone	51
24.1	Layout of the Information Zone	51
24.2	Physical Sector numbering	52
25	Lead-in Zone, Middle Zone and Lead-out Zone	53
25.1	Lead-in Zone	53
25.1.1	Initial Zone	54
25.1.2	Buffer Zone 0	54
25.1.3	R-Physical Format Information Zone	54
25.1.4	Reference Code Zone	58
25.1.5	Buffer Zone 1	58
25.1.6	Control Data Zone	58
25.1.7	Extra Border Zone	73
25.2	Middle Zone	74
25.3	Lead-out Zone	74
25.3.1	Structure of Lead-out Zone with Format4 RMD	74
25.3.2	Superficial Extra Border Zone	75
26	General description of the Unrecorded Zone	75
26.1	Layout of the Unrecorded Zone	76
26.2	ECC Block address	77
26.3	ECC Block numbering	77
27	Pre-pit Data format	77
27.1	General description	77
27.2	Pre-pit block structure	80
27.3	Pre-pit data block configuration	82
27.3.1	Relative address	83
27.3.2	ECC Block address data configuration	83
27.3.3	Parity A and Parity B	83
27.3.4	Field ID0	84
27.3.5	Field ID1	85
27.3.6	Field ID2	86
27.3.7	Field ID3 and Field ID4	87
27.3.8	Field ID5	89
28	Data structure of R-Information Zone and ODTA	90
28.1	Layout of Disk Testing Area and Recording Management Area	90
28.2	Structure of the Disk Testing Area	91
28.3	Data configuration of the Recording Management Area (RMA)	93
28.3.1	Sector format of the Recording Management Area	93
28.3.2	Recording Management Data (Format1 RMD and Format4 RMD)	95
Annex A (normative) Measurement of the angular deviation		127
Annex B (normative) Measurement of birefringence		129
Annex C (normative) Measurement of the differential phase tracking error		132
Annex D (normative) Measurement of light reflectance		136
Annex E (normative) Tapered cone for disk clamping		138

Annex F (normative) Measurement of jitter	139
Annex G (normative) 8-to-16 Modulation with RLL (2,10) requirements	142
Annex H (normative) Optimum Power Control	152
Annex I (normative) Measurement of the groove wobble amplitude	154
Annex J (normative) Measurement methods for the operational signals for an unrecorded disk	156
Annex K (normative) NBCA Code	157
Annex L (normative) Border Zone	163
Annex M (normative) Measurement method of the Land Pre-Pit signal	176
Annex N (normative) Construction of Information Zone	177
Annex O (normative) Recording order	179
Annex P (normative) Clearance in the number of sectors	180
Annex Q (normative) Anchor Point Re-mapping	182
Annex R (informative) Measurement method of the Space layer thickness in a disk	184
Annex S (informative) Transportation	185