

ISO/IEC 18000-7:2009-08 (E)

Information technology - Radio frequency identification for item management - Part 7: Parameters for active air interface communications at 433 MHz

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Conformance	1
2.1	RF emissions general population	1
2.2	RF emissions and susceptibility health care setting	1
2.3	Command structure and extensibility	1
2.4	Mandatory commands	2
2.5	Optional commands	2
2.6	Custom commands	2
2.7	Proprietary commands	2
3	Normative references	2
4	Terms and definitions	3
5	Symbols and abbreviated terms	3
6	433,92 MHz active narrowband specification	3
6.1	Physical layer	3
6.2	Data Link layer	4
6.2.1	General	4
6.2.2	Preamble	5
6.2.3	Data bytes	5
6.2.4	Packet end period	5
6.2.5	Interrogator-to-tag message format	6
6.2.6	Tag-to-interrogator message format	9
6.3	Tag commands	16
6.3.1	Collection with Universal Data Block (UDB)	16
6.3.2	Sleep	21
6.3.3	Sleep all but	21
6.3.4	Security commands	22
6.3.5	Transit information commands	25
6.3.6	Manufacturing Information Commands	27
6.3.7	Memory commands	28
6.3.8	Delete Writeable Data	30
6.3.9	Read Universal Data Block	31
6.3.10	Database table commands	32
6.3.11	Beep ON/OFF	49
6.3.12	Sensor implementation	50
6.4	Tag collection and collision arbitration	51
6.5	Multi-packet UDB Collection	54
6.6	Physical and Media Access Control (MAC) parameters	56
6.6.1	Interrogator to tag link	56
6.6.2	Tag to interrogator link	58
6.6.3	Protocol parameters	59
6.6.4	Anti-collision parameters	60

Annex A (normative) Co-existence of different application standards based on ISO/IEC 18000-7	61
Bibliography	63