

ISO/IEC 26907:2009-11 (E)

Information technology - Telecommunications and information exchange between systems - High-rate ultra-wideband PHY and MAC standard

Contents		Page
Foreword		x
Introduction		xi
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	1
5	Notational conventions	4
6	Abbreviations and acronyms	4
7	General description	7
7.1	PHY general description	7
7.2	MAC general description	8
7.2.1	General description of the architecture	8
7.2.2	Device address	9
7.2.3	Features assumed from the PHY	9
7.2.4	Overview of MAC service functionality	9
7.2.5	MUX sublayer	13
7.2.6	MAC policies	13
7.2.7	Test vectors	13
8	PHY layer partitioning	13
8.1	PHY function	14
8.2	PLCP sublayer	14
8.3	PMD sublayer	14
8.4	PHY layer management entity (PLME)	14
9	Description of signal	14
9.1	Mathematical framework	14
9.2	Tone-Nulling	15
10	PLCP sublayer	16
10.1	PPDU	16
10.1.1	PSDU rate-dependent parameters	18
10.1.2	Timing-related parameters	18
10.1.3	Frame-related parameters	19
10.2	PLCP preamble	20
10.2.1	Standard PLCP preamble	20
10.2.2	Burst PLCP preamble	21
10.3	PLCP header	43
10.3.1	PHY header	44
10.3.2	Reed-Solomon outer code for the PLCP header	48
10.3.3	Header check sequence	50
10.4	PSDU	51
10.4.1	Pad bits	52

10.5	Data scrambler	53
10.6	Tail bits	54
10.7	Convolutional encoder	55
10.8	Bit interleaving	58
10.9	Constellation mapping	60
10.9.1	QPSK	60
10.9.2	Dual-carrier modulation (DCM)	61
10.10	OFDM modulation	63
10.10.1	Implementation considerations	67
10.10.2	Data subcarriers	67
10.10.3	Guard subcarriers	71
10.10.4	Pilot subcarriers	71
11	General requirements	73
11.1	Operating band frequencies	73
11.1.1	Operating frequency range	73
11.1.2	Band numbering	73
11.2	Channelization	74
11.3	PHY layer timing	78
11.3.1	Interframe spacing	78
11.3.2	Receive-to-transmit turnaround time	78
11.3.3	Transmit-to-receive turnaround time	79
11.3.4	Time between successive transmissions	79
11.3.5	Band frequency switch time	79
12	Transmitter specifications	79
12.1	Transmit PSD mask	79
12.2	Transmit centre frequency tolerance	80
12.3	Symbol clock frequency tolerance	80
12.4	Clock synchronization	80
12.5	Phase coherence	80
12.6	Transmit power control	80
12.7	Transmitter constellation error	81
13	Receiver specification	83
13.1	Receiver sensitivity	83
13.2	Receiver CCA performance	83
13.3	Link quality indicator	83
13.4	Receive Signal Strength Indicator	84
14	Ranging and location awareness	85
14.1	Ranging requirements	85
14.2	Ranging reference signal	85
14.3	PHY ranging resources	85
14.4	PHY ranging operation	85
14.5	Ranging calibration constants	85
14.6	Example range measurement (informative)	85
15	PHY and MAC service access points (informative)	86
15.1	Generic MIB management primitives	87
15.1.1	XX-GET.request	88
15.1.2	XX-GET.confirm	88
15.1.3	XX-SET.request	89
15.1.4	XX-SET.confirm	89
15.2	PHY SAP interface	90
15.2.1	Data transfer	90
15.2.2	PHY transmission control	91
15.2.3	PHY reception control	93
15.2.4	PHY CCA control	96
15.3	PLME SAP interface	97
15.3.1	PHY reset	99
15.3.2	PHY ranging timer control	100
15.4	MAC sublayer management primitives	101
15.5	MAC management information base (MIB)	101
15.6	MLME SAP interface	101
15.6.1	Reset	101
15.6.2	Scan	102

15.6.3	Beacon transmission and reception	104
15.6.4	IE management	109
15.6.5	PTK establishment	110
15.6.6	GTK solicitation/distribution	113
15.6.7	Temporal key update	116
15.6.8	Security violation report	118
15.6.9	Pseudo-random function (PRF)	119
15.6.10	Application-specific IE (ASIE) management	120
15.6.11	Multicast address binding	122
15.6.12	Link events	125
15.6.13	Probe	128
15.6.14	Hibernation and sleep cycle	131
15.6.15	Higher layer synchronization support	136
15.6.16	Reservation management	138
15.6.17	Connection configuration primitives	144
15.6.18	Range measurement	146
15.6.19	Application-specific command management	147
15.7	MAC SAP interface	149
15.7.1	MAC-DATA.request	151
15.7.2	MAC-DATA.indication	151
15.7.3	MAC-DATA.confirm	152
16	MAC frame formats	152
16.1	Frame format conventions	152
16.1.1	Figures	152
16.1.2	Octet order	152
16.1.3	Encoding	153
16.2	General MAC frame format	153
16.2.1	Frame control	154
16.2.2	DestAddr	155
16.2.3	SrcAddr	155
16.2.4	Sequence control	155
16.2.5	Access information	156
16.2.6	Frame payload	157
16.2.7	FCS	157
16.3	Beacon frames	158
16.4	Control frames	160
16.4.1	Immediate acknowledgement (Imm-ACK)	161
16.4.2	Block acknowledgement (B-ACK)	161
16.4.3	Request to send (RTS)	162
16.4.4	Clear to send (CTS)	162
16.4.5	Unused DRP reservation announcement (UDA)	162
16.4.6	Unused DRP reservation response (UDR)	162
16.4.7	Application-specific	162
16.5	Command frames	163
16.5.1	DRP reservation request	164
16.5.2	DRP reservation response	164
16.5.3	Probe	165
16.5.4	Pairwise temporal key (PTK)	165
16.5.5	Group temporal key (GTK)	166
16.5.6	Range measurement	167
16.5.7	Application-specific	168
16.6	Data frames	168
16.7	Aggregated data frames	169
16.8	Information elements	169
16.8.1	Application-specific IE (ASIE)	171
16.8.2	Application-specific probe IE	171
16.8.3	Beacon period occupancy IE (BPOIE)	172
16.8.4	BP switch IE	173
16.8.5	Channel change IE	173
16.8.6	Distributed reservation protocol (DRP) IE	173
16.8.7	DRP availability IE	175
16.8.8	Hibernation anchor IE	175

16.8.9	Hibernation mode IE	176
16.8.10	Identification IE	176
16.8.11	Link feedback IE	178
16.8.12	MAC capabilities IE	179
16.8.13	Master key identifier (MKID) IE	180
16.8.14	Multicast address binding (MAB) IE	180
16.8.15	PCA availability IE	181
16.8.16	PHY capabilities IE	181
16.8.17	Probe IE	184
16.8.18	Regulatory Domain IE	184
16.8.19	Relinquish request IE	185
16.8.20	Tone-nulling (TN) IE	186
16.8.21	Traffic indication map (TIM) IE	187
17	MAC sublayer functional description	187
17.1	Frame processing	187
17.1.1	Frame addresses	188
17.1.2	Frame reception	188
17.1.3	Frame transaction	188
17.1.4	Frame transfer	189
17.1.5	Frame retry	190
17.1.6	Inter-frame space (IFS)	190
17.1.7	Duplicate detection	190
17.1.8	RTS/CTS use	191
17.1.9	MAC header fields	191
17.1.10	Information elements	194
17.2	Beacon period	197
17.2.1	Beacon slot state	198
17.2.2	BP length	198
17.2.3	Beacon transmission and reception	199
17.2.4	Beacon slot collision detection	200
17.2.5	BP contraction	201
17.2.6	Merger of multiple BPs	201
17.3	Prioritized contention access (PCA)	204
17.3.1	PCA medium availability	205
17.3.2	NAV	205
17.3.3	Medium status	205
17.3.4	PCA parameters	205
17.3.5	Obtaining a TXOP	206
17.3.6	Using a TXOP	207
17.3.7	Invoking a backoff procedure	208
17.3.8	Decrementing a backoff counter	209
17.4	Distributed reservation protocol (DRP)	209
17.4.1	Reservation type	210
17.4.2	Medium access	211
17.4.3	DRP availability IE	211
17.4.4	DRP reservation negotiation	212
17.4.5	DRP reservation announcements	213
17.4.6	Resolution of DRP reservation conflicts	213
17.4.7	BPST realignment and existing DRP reservations	215
17.4.8	Modification and termination of existing DRP reservations	215
17.4.9	Release of hard or private DRP reservation blocks	215
17.4.10	Retransmit procedures in DRP reservations	216
17.5	Synchronization of devices	216
17.5.1	Clock accuracy	217
17.5.2	Synchronization for devices in hibernation mode	217
17.5.3	Guard times	217
17.6	Fragmentation and reassembly	218
17.7	Aggregation	219
17.8	Acknowledgement policies	219
17.8.1	No-ACK	219
17.8.2	Immediate ACK	219
17.8.3	Block ACK	219

17.9	Probe	221
17.10	Dynamic channel selection	222
17.11	Multi-rate support	222
17.12	Transmit power control	222
17.13	Power management mechanisms	223
17.13.1	Power management modes	223
17.13.2	Device power states	223
17.13.3	Power state transitions	223
17.13.4	Hibernation mode operation	224
17.13.5	Hibernation anchor operation	225
17.14	ASIE operation	226
17.15	Range measurement operation	226
17.16	MAC sublayer parameters	229
18	Security	230
18.1	Security mechanisms	231
18.1.1	Security operation	231
18.1.2	4-way handshake	231
18.1.3	Key transport	231
18.1.4	Freshness protection	231
18.1.5	Data encryption	231
18.1.6	Frame integrity protection	232
18.2	Security modes	232
18.2.1	Security mode 0	234
18.2.2	Security mode 1	234
18.2.3	Security mode 2	234
18.3	Temporal keys	235
18.3.1	Mutual authentication and PTK derivation	235
18.3.2	GTK exchange	236
18.3.3	Pseudo-random function (PRF) definition	237
18.3.4	PTK and KCK derivation	237
18.3.5	PTK MIC generation	238
18.3.6	Random number generation	238
18.4	Frame reception steps and replay prevention measures	239
18.4.1	Frame reception	239
18.4.2	Replay prevention	239
18.4.3	Implications on GTKs	240
18.5	AES-128 CCM Inputs	240
18.5.1	Overview	240
18.5.2	Nonce	240
18.5.3	CCM blocks	241
Annex A (normative) MUX sublayer		243
Annex B (normative) MAC Policies		246
Annex C (normative) Assigned number document		249
Annex D (informative) MAC test vectors		250
Annex E (informative) Example encoding of a PHY packet		261
Annex F (informative) Recommended out-of-band emission limits		306
Annex G (informative) Range measurement calculations		307
Bibliography		311