

ISO/IEC 29157:2010-06 (E)

Information technology - Telecommunications and information exchange between systems - PHY/MAC specifications for short-range wireless low-rate applications in the ISM band

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | viii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 2 |
| 5 | Overview | 3 |
| 6 | Interlayer service specification | 5 |
| 6.1 | Overview | 5 |
| 6.2 | General format of management primitives | 6 |
| 6.2.1 | MLME-GET.request and PLME-GET.request | 7 |
| 6.2.2 | MLME-GET.confirm and PLME-GET.confirm | 7 |
| 6.2.3 | MLME-SET.request and PLME-SET.request | 8 |
| 6.2.4 | MLME-SET.confirm and PLME-SET.confirm | 8 |
| 6.3 | MLME-SAP | 9 |
| 6.3.1 | MLME-GET.request | 10 |
| 6.3.2 | MLME-GET.confirm | 10 |
| 6.3.3 | MLME-MASTER-START.request | 10 |
| 6.3.4 | MLME-MASTER-START.confirm | 11 |
| 6.3.5 | MLME-RESET.request | 11 |
| 6.3.6 | MLME-RESET.confirm | 12 |
| 6.3.7 | MLME-SCAN.request | 12 |
| 6.3.8 | MLME-SCAN.confirm | 13 |
| 6.3.9 | MLME-SET.request | 13 |
| 6.3.10 | MLME-SET.confirm | 14 |
| 6.4 | MAC-SAP | 14 |
| 6.4.1 | MAC-DATA.request | 15 |
| 6.4.2 | MAC-DATA.confirm | 15 |
| 6.4.3 | MAC-DATA.indication | 16 |
| 6.5 | PLME-SAP | 16 |
| 6.5.1 | PLME-GET.request | 17 |
| 6.5.2 | PLME-GET.confirm | 17 |
| 6.5.3 | PLME-SET.request | 18 |
| 6.5.4 | PLME-SET.confirm | 18 |
| 6.5.5 | PLME-RESET.request | 19 |
| 6.5.6 | PLME-RESET.confirm | 19 |
| 6.6 | PD-SAP | 19 |
| 6.6.1 | PD-DATA.request | 20 |
| 6.6.2 | PD-DATA.confirm | 20 |
| 6.6.3 | PD-DATA.indication | 21 |
| 7 | MAC PDU format | 21 |
| 7.1 | MPDU of beacon frame (BF) | 22 |
| 7.1.1 | Open flag (OF, 2 bits) | 22 |

| | | |
|--------|--|----|
| 7.1.2 | MAC version (6 bits) | 22 |
| 7.1.3 | Address mode (ADDM, 2 bits) | 22 |
| 7.1.4 | PHY version (6 bits) | 22 |
| 7.1.5 | Frame type (8 bits) | 22 |
| 7.1.6 | Superframe mode control (SFMC, 2 bits) | 23 |
| 7.1.7 | Upper layer frame size (ULFS, 6 bits) | 23 |
| 7.1.8 | Source MAC address (64 bits) | 23 |
| 7.1.9 | Superframe counter (SFC, 4 bits) | 23 |
| 7.1.10 | Middleframe counter (FC, 4 bits) | 23 |
| 7.1.11 | Hopping sequence (32 bits) | 24 |
| 7.1.12 | BF frequency table (BFFT, 16 bytes) | 24 |
| 7.1.13 | Upper layer data (16 bytes) | 24 |
| 7.2 | MPDU of fast beacon frame (FBF) | 24 |
| 7.2.1 | Open flag (OF, 2 bits) | 24 |
| 7.2.2 | MAC version (6 bits) | 24 |
| 7.2.3 | Address mode (ADDM, 2 bits) | 24 |
| 7.2.4 | PHY version (6 bits) | 24 |
| 7.2.5 | Frame type (8 bits) | 24 |
| 7.2.6 | Superframe mode control (SFMC, 2 bits) | 24 |
| 7.2.7 | Upper layer frame size (ULFS, 6 bits) | 24 |
| 7.2.8 | Source MAC address (64 bits) | 25 |
| 7.2.9 | Superframe counter (SFC, 4 bits) | 25 |
| 7.2.10 | Middleframe counter (SC, 4 bits) | 25 |
| 7.2.11 | Hopping sequence (32 bits) | 25 |
| 7.2.12 | BF frequency table (BFFT, 16 bytes) | 25 |
| 7.2.13 | Upper layer data (16 Bytes) | 25 |
| 7.3 | MPDU of request control frame (RCF) | 26 |
| 7.3.1 | Open flag (OF, 2 bits) | 26 |
| 7.3.2 | MAC version (6 bits) | 26 |
| 7.3.3 | Address mode (ADDM, 2 bits) | 26 |
| 7.3.4 | PHY version (6 bits) | 26 |
| 7.3.5 | Frame type (8 bits) | 26 |
| 7.3.6 | Upper layer frame size (ULFS, 6 bits) | 26 |
| 7.3.7 | Source MAC address (64 bits) | 26 |
| 7.3.8 | Destination MAC address (64 bits) | 26 |
| 7.3.9 | Upper layer data | 26 |
| 7.4 | MPDU of master control frame (MCF) | 27 |
| 7.4.1 | Open flag (OF, 2 bits) | 27 |
| 7.4.2 | MAC version (6 bits) | 27 |
| 7.4.3 | Address mode (ADDM, 2 bits) | 28 |
| 7.4.4 | PHY version (6 bits) | 28 |
| 7.4.5 | Frame type (8 bits) | 28 |
| 7.4.6 | Upper layer frame size (ULFS, 6 bits) | 28 |
| 7.4.7 | Source MAC address (64 bits) | 28 |
| 7.4.8 | Destination MAC address (64 bits) | 28 |
| 7.4.9 | Upper layer data | 29 |
| 7.5 | MPDU of RCF acknowledge control frame (RACF) | 29 |
| 7.6 | MPDU of MCF acknowledge control frame (MACF) | 29 |
| 7.7 | MPDU of payload frame (PF) | 29 |
| 7.7.1 | Open flag (OF, 2 bits) | 29 |
| 7.7.2 | MAC version (6 bits) | 29 |
| 7.7.3 | Address mode (ADDM, 2 bits) | 29 |
| 7.7.4 | PHY version (6 bits) | 29 |
| 7.7.5 | Frame type (8 bits) | 29 |
| 7.7.6 | Upper layer frame size (ULFS, 6 bits) | 30 |
| 7.7.7 | Source MAC address (64 bits) | 30 |
| 7.7.8 | Destination MAC address (64 bits) | 30 |
| 7.7.9 | Upper layer data | 30 |
| 8 | MAC functional description | 31 |
| 8.1 | General description | 31 |
| 8.2 | System state diagram | 31 |

| | | |
|-------|---|-----------|
| 8.3 | Protocol structure | 33 |
| 8.3.1 | Middleframe structure | 34 |
| 8.3.2 | Superframe structure | 34 |
| 8.4 | Frequency operation | 36 |
| 8.4.1 | Frequency hopping control | 36 |
| 8.4.2 | Frame frequency mapping | 36 |
| 8.4.3 | Frequency diversity and time diversity | 37 |
| 8.4.4 | Orthogonal frequency offset | 37 |
| 8.4.5 | Frequency selection | 37 |
| 9 | PHY specification | 40 |
| 9.1 | General requirements | 40 |
| 9.1.1 | Operating frequency range | 40 |
| 9.1.2 | Frequency assignment | 40 |
| 9.1.3 | Frequency synthesizer stabilisation time | 40 |
| 9.1.4 | Frequency synthesizer turn off time | 41 |
| 9.2 | PHY protocol data unit (PPDU) format | 41 |
| 9.2.1 | Lock time | 41 |
| 9.2.2 | Preamble (128 bits) | 41 |
| 9.2.3 | Header (48 bits) | 42 |
| 9.2.4 | Message | 42 |
| 9.2.5 | EoF delimiter | 42 |
| 9.3 | Modulation and codes | 42 |
| 9.3.1 | Modulation | 42 |
| 9.3.2 | Codes | 43 |
| 9.4 | Transmitter specification | 44 |
| 9.4.1 | Pulse shaping filter | 44 |
| 9.4.2 | Transmitter power spectrum mask | 44 |
| | Bibliography | 45 |
| | Figures Figure 1 -- A group communication example | 4 |
| | Figure 2 -- Data formats: a frame, a middleframe, and a superframe | 5 |
| | Figure 3 -- The protocol model used in this International Standard | 6 |
| | Figure 4 -- MPDU in Frame structure | 22 |
| | Figure 5 -- MPDU format of Beacon Frame | 23 |
| | Figure 6 -- MPDU format of Fast Beacon Frame (FBF) | 25 |
| | Figure 7 -- MPDU format of RCF | 27 |
| | Figure 8 -- MPDU format of MCF | 28 |
| | Figure 9 -- MPDU format of PF | 30 |
| | Figure 10 -- A pico-net with only two devices | 31 |
| | Figure 11 -- A pico-net with more than two terminals | 31 |
| | Figure 12 -- State transition diagram | 33 |
| | Figure 13 -- The protocol structure | 34 |
| | Figure 14 -- Middleframe structure | 34 |
| | Figure 15 -- Structure of a normal superframe | 35 |
| | Figure 16 -- Structure of a fast synchronisation superframe | 35 |

| | |
|--|----|
| Figure 17 -- Superframe mode alternation | 35 |
| Figure 18 -- Middleframe counter | 36 |
| Figure 19 -- Superframe counter | 36 |
| Figure 20 -- The hopping sequence generator | 36 |
| Figure 21 -- Frame frequency mapping scheme | 37 |
| Figure 22 -- Middleframe structure of passive sounding | 38 |
| Figure 23 -- One cycle of passive sounding frames | 38 |
| Figure 24 -- Illustration of static sounding | 39 |
| Figure 25 -- Middleframe structure of static sounding | 39 |
| Figure 26 -- Static sounding value | 39 |
| Figure 27 -- The structure of the static sounding superframe | 40 |
| Figure 28 -- PHY Protocol Data Unit (PPDU) format | 41 |
| Figure 29 -- An example of Gold code generators | 42 |
| Figure 30 -- Scan code | 43 |
| Figure 31 -- Security code | 43 |
| Figure 32 -- Group code | 43 |
| Tables Table 1 -- General management primitive overview | 6 |
| Table 2 -- MLME/PLME general management primitive parameters | 7 |
| Table 3 -- MLME primitive summary | 9 |
| Table 4 -- MLME-SAP parameters | 9 |
| Table 5 -- MAC-SAP primitive summary | 14 |
| Table 6 -- MAC-SAP parameters | 14 |
| Table 7 -- PLME-SAP primitive summary | 16 |
| Table 8 -- PLME-SAP parameters | 17 |
| Table 9 -- PD-SAP primitives | 19 |
| Table 10 -- PD-SAP parameters | 20 |
| Table 11 -- Description of states | 32 |
| Table 12 -- The use of the fields in a frame | 41 |