

# ISO/IEC 24723:2010-08 (E)

## Information technology - Automatic identification and data capture techniques - GS1 Composite bar code symbology specification

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | v           |
| Introduction ..... |   | vi          |
| <b>1</b>           | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>   | <b>1</b>    |
| <b>3</b>           | <b>Terms, definitions, abbreviated terms and mathematical operators .....</b> | <b>2</b>    |
| 3.1                | Terms and definitions .....   | 2           |
| 3.2                | Abbreviated terms .....   | 3           |
| 3.3                | Mathematical operators and notational conventions .....                       | 3           |
| <b>4</b>           | <b>Symbol description .....</b>   | <b>3</b>    |
| 4.1                | Basic characteristics .....   | 3           |
| 4.2                | Summary of additional features .....  | 4           |
| 4.3                | Symbol structure .....  | 4           |
| 4.4                | Supported component combinations .....  | 6           |
| <b>5</b>           | <b>Source data encodation into a binary string .....</b>                      | <b>6</b>    |
| 5.1                | General .....   | 6           |
| 5.2                | Encodation Method field .....   | 7           |
| 5.3                | Compressed data field .....   | 7           |
| 5.4                | General-purpose data compaction field .....                                   | 11          |
| <b>6</b>           | <b>Error correction .....</b>   | <b>15</b>   |
| <b>7</b>           | <b>Linear component requirements .....</b>                                    | <b>15</b>   |
| 7.1                | General .....   | 15          |
| 7.2                | EAN/UPC linear components .....   | 15          |
| 7.3                | GS1 DataBar family linear components .....                                    | 16          |
| 7.4                | GS1-128 components .....  | 18          |
| <b>8</b>           | <b>CC-A component requirements .....</b>                                      | <b>19</b>   |
| 8.1                | CC-A -- General .....   | 19          |
| 8.2                | Overview of the CC-A component .....  | 19          |
| 8.3                | CC-A component structure .....  | 20          |
| 8.4                | Symbol character structure .....  | 22          |
| 8.5                | Base 928 compaction mode .....  | 24          |
| 8.6                | Reference decode algorithm .....  | 25          |
| <b>9</b>           | <b>CC-B component requirements .....</b>                                      | <b>26</b>   |
| <b>10</b>          | <b>CC-C component requirements .....</b>                                      | <b>27</b>   |
| <b>11</b>          | <b>Symbol dimensions .....</b>  | <b>28</b>   |
| 11.1               | Minimum width of a module (X) .....   | 28          |
| 11.2               | Linear component height .....   | 28          |
| 11.3               | 2D component row height (Y) .....   | 28          |
| 11.4               | Separator pattern and vertical separator bars .....                           | 28          |
| 11.5               | Quiet zones .....   | 29          |

|             |  |           |
|-------------|--|-----------|
| <b>12</b>   | <b>Graphical requirements .....</b>                            | <b>29</b> |
| <b>12.1</b> | <b>General .....</b>   | <b>29</b> |
| <b>12.2</b> | <b>Vertical alignment requirements .....</b>                   | <b>29</b> |
| <b>12.3</b> | <b>Horizontal alignment requirements .....</b>                 | <b>29</b> |
| <b>12.4</b> | <b>Human readable interpretation .....</b>                     | <b>30</b> |
| <b>13</b>   | <b>Symbol quality .....</b>                                    | <b>30</b> |
| <b>13.1</b> | <b>Linear component .....</b>                                  | <b>30</b> |
| <b>13.2</b> | <b>2D component .....</b>                                      | <b>30</b> |
| <b>13.3</b> | <b>Overall composite symbol grade .....</b>                    | <b>30</b> |
| <b>13.4</b> | <b>Additional pass/fail criteria .....</b>                     | <b>30</b> |
| <b>14</b>   | <b>Transmitted data .....</b>                                  | <b>30</b> |
| <b>14.1</b> | <b>General data transmission techniques .....</b>              | <b>30</b> |
| <b>14.2</b> | <b>GS1-128 Composite symbols .....</b>                         | <b>31</b> |
| <b>14.3</b> | <b>GS1 DataBar Composite symbols .....</b>                     | <b>31</b> |
| <b>14.4</b> | <b>EAN/UPC Composite symbols .....</b>                         | <b>31</b> |
| <b>14.5</b> | <b>Symbol separator character .....</b>                        | <b>32</b> |
| <b>14.6</b> | <b>2D component escape mechanism character .....</b>           | <b>32</b> |
| <b>14.7</b> | <b>Linear-only transmission mode .....</b>                     | <b>32</b> |
| <b>14.8</b> | <b>GS1-128 emulation .....</b>                                 | <b>32</b> |
| <b>14.9</b> | <b>Examples of transmitted data .....</b>                      | <b>33</b> |
| <b>15</b>   | <b>Application-defined parameters .....</b>                    | <b>33</b> |
|             | <b>Annex A (normative) Symbology identifiers .....</b>         | <b>34</b> |
|             | <b>Annex B (normative) Parsing AI element strings .....</b>    | <b>36</b> |
|             | <b>Annex C (normative) 2D component escape mechanism .....</b> | <b>38</b> |
|             | <b>Annex D (informative) Printing considerations .....</b>     | <b>39</b> |
|             | <b>Annex E (informative) Base 928 radix conversions .....</b>  | <b>42</b> |
|             | <b>Bibliography .....</b>                                      | <b>45</b> |