ISO/IEC 18000-3:2009-11 (E)

Information technology_- Radio frequency identification for item management_- Part_3: Parameters for air interface communications at 13,56_MHz

---

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 2

5 Symbols and abbreviated terms 3
5.1 Symbols 3
5.2 Abbreviated terms 4
5.3 Notation 5

6 Requirements: Physical layer, collision management system and protocol values for 13,56 MHz systems 6
6.0 General and applicable to All Modes 6
6.0.1 Presentation as determined in ISO/IEC 18000-1 6
6.0.2 ISO/IEC 18000-3 Interoperability 6
6.0.3 ISO/IEC 18000-3 interrogator conformance/compliance 6
6.0.4 ISO/IEC 18000-3 tag compliance 6
6.0.5 Command structure and extensibility 6
6.0.6 Mandatory commands 6
6.0.7 Optional commands 7
6.0.8 Custom commands 7
6.0.9 Proprietary commands 7
6.1 Physical layer, collision management system and protocols for MODE 1 7
6.1.1 Read/Write system 7
6.1.2 Normative Aspects 7
6.1.3 Conformance and performance measurement aspects 7
6.1.4 Physical Layer 7
6.1.5 Protocol and collision management operating method 7
6.1.6 Commands 8
6.1.7 Parameter tables for interrogator to tag link 8
6.1.8 Parameter tables for tag to interrogator link 11
6.2 MODE 2: Physical layer, collision management system and protocols for MODE 2 14
6.2.1 Normative aspects: physical and media access control (MAC) parameters: interrogator to tag link 15
6.2.2 Tag to interrogator link 17
6.2.3 Description of operating method 20
6.2.4 Protocol parameters 25
6.2.5 Description of protocol operating method 25
6.2.6 Collision management parameters 41
6.2.7 Description of collision management parameters operating method (informative) 41
6.2.8 Tag order sequencing 49
6.2.9 Commands 49
6.2.10 Air interface application layer 49
6.2.11 Optional Functionality 49
6.3 MODE 3: Physical layer, collision management system and protocols for MODE 3 52
6.3.1 Protocol overview 52
6.3.2 General 52
6.3.3 Physical layer, collision management system and protocols 53

7 Marking of equipment 124

Annex A (informative) **MODE 1: mandatory and optional commands required to support the ISO/IEC 15962 data protocol 125**

Annex B (informative) **MODE 2 and MODE 3: Phase Jitter Modulation 126**

Annex C (normative) **MODE3: State transition tables 129**
C.1 Present state: Ready 129
C.2 Present state: Arbitrate 130
C.3 Present state: Reply 131
C.4 Present state: Acknowledged 132
C.5 Present state: Open 133
C.6 Present state: Secured 134
C.7 Present state: Killed (optional) 136

Annex D (normative) **MODE 3: Command Response Tables 137**
D.1 Command response: Power-up 137
D.2 Command response: *BeginRound* 137
D.3 Command response: *NextSlot* 138
D.4 Command response: *ResizeRound* 138
D.5 Command response: *ACK* 138
D.6 Command response: *NAK* 139
D.7 Command response: *Req_RN* 139
D.8 Command response: *Select* 139
D.9 Command response: *Read* 140
D.10 Command response: *Write* 140
D.11 Command response: *Kill* 141
D.12 Command response: *Lock* 141
D.13 Command response: *Access* 142
D.14 Command response: *BlockWrite* 142
D.15 Command response: *BlockErase* 142
D.16 Command response: *BlockPermalock* 143
D.17 Command response: T_2 timeout 143
D.18 Command response: Invalid command 144

Annex E (normative) **MODE 3: Error codes 145**

Annex F (normative) **MODE 3: Slot counter 146**
F.1 Slot-counter operation 146

Annex G (informative) **MODE 3: Example slot-count (Q) selection algorithm 147**
G.1 Example algorithm an interrogator might use to choose Q 147

Annex H (informative) **MODE 3: Example of tag inventory and access 148**
H.1 ASK Method: Example inventory and access of a single tag 148
H.2 PJM Method: Example inventory and access of a single or multiple tags 149

Annex I (informative) **MODE 3: Calculation of 5-bit and 16-bit cyclic redundancy checks 150**
I.1 Example CRC-5 encoder/decoder 150
I.2 Example CRC-16 calculations 151
I.3 Example CRC-16c encoder/decoder 151

Annex J (informative) **MODE 3: ASK Method: Interrogator-to-tag link modulation 152**
J.1 Baseband waveforms, modulated RF, and detected waveforms 152

Annex K (informative) **MODE 3: Example data flow exchange 153**
K.1 Overview of the data-flow exchange 153
K.2 Tag memory contents and lock-field values 153
K.3 Data-flow exchange and command sequence 154

Annex L (informative) **MODE 3: Tag Features 155**
L.1 Optional Tag passwords 155
L.2 Optional Tag memory banks and memory-bank sizes 155
L.3 Optional Tag commands 155
L.4 Optional Tag error-code reporting format 155

L.5 Optional Tag functionality **156**
L.6 Optional Tag Feature **156**

Annex M (informative) **Cyclic Redundancy Check (CRC) (16 bit)** **157**
M.1 The CRC error detection method **157**
M.2 CRC calculation example **157**

Annex N (informative) **Cyclic redundancy check (CRC) mode 2 (32 bit)** **159**
N.1 The CRC 32 error detection method **159**
N.2 CRC 32 calculation example **159**
N.3 Practical example of CRC 32 calculation **161**

Annex O (informative) **Known possible interferences between the MODES determined in this part of ISO/IEC 18000** **162**

Bibliography **163**