ISO/IEC 13156:2011-10 (E)

Information technology - Telecommunications and information exchange between systems - High rate 60 GHz PHY, MAC and PALs

Contents

Page

Foreword ix

Introduction x

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 1

5 Notational conventions 3

6 Abbreviated terms 4

7 General description (informative) 7
7.1 PHY general description 7
7.2 MAC general description 7
7.2.1 General description of the architecture 7
7.2.2 Device address 8
7.2.3 Features assumed from the PHY 8
7.2.4 Overview of MAC service functionality 9
7.2.5 MAC policies 12
7.2.6 Support for higher-layer timer synchronization 12
7.3 MUX general description 12
7.4 HDMI PAL description 13

8 PHY layer (informative) 13

9 Description of signal 13
9.1 Mathematical framework for SCBT, OFDM, DBPSK, DQPSK, UEP-QPSK, OOK and 4ASK 13
9.2 Mathematical framework for the narrow band section of the discovery mode preamble 14

10 PLCP sublayer 14
10.1 General PPDU frame format 14
10.1.1 PLCP preamble 16
10.1.2 PLCP header 16
10.1.3 PPDU payload 19
10.1.4 Antenna training sequence 20
10.2 Type A PPDU 20
10.2.1 Mode dependent parameters 20
10.2.2 SCBT 21
10.2.3 OFDM 42
10.2.4 Constellation mapping 60
10.2.5 Discovery mode 69
10.3 Type B PPDU 71
10.3.1 Mode dependent parameters 71
10.3.2 Single carrier (DBPSK, DQPSK, UEP-QPSK) 72
10.3.3 Channel bonding 80
10.3.4 Discovery mode 80

11 General requirements 80
11.1 Operating band frequencies 80
11.1.1 Operating frequency range 80
11.1.2 Channel numbering 80
11.2 PHY layer timing 81
11.2.1 Receive-to-transmit turnaround time 81
11.2.2 Transmit-to-receive turnaround time 82
11.2.3 Time between successive transmissions 82

12 Transmitter specifications 82
12.1 Transmit PSD mask 82
12.1.1 Transmit PSD 82
12.2 Transmit centre frequency tolerance 83
12.3 Symbol clock frequency tolerance 83
12.4 Clock synchronization 83
12.5 Transmit power control 83
12.6 Transmitter EVM 83
12.6.1 Type A 83
12.6.2 Type B 87

13 Receiver specification 87
13.1 Type A device 87
13.1.1 SCBT receiver sensitivity 87
13.1.2 OFDM receiver sensitivity 88
13.2 Type B device receiver sensitivity 88
13.3 Receiver CCA performance 89

14 Antenna training symbols and feedback methods 89
14.1 Antenna training sequence transmission 89
14.1.1 Training matrix in closed-loop mode 90
14.1.2 Tracking matrix 92
14.2 Antenna training feedback in closed-loop mode 92
14.2.1 Index feedback 92
14.2.2 Codebook based feedback 92
14.2.3 Quantised weights 95

15 MAC frame formats 95
15.1 Frame format conventions 95
15.1.1 Figures 95
15.1.2 Octet order 96
15.1.3 Encoding 96
15.2 General MAC frame format 96
15.2.1 Unaggregated MAC frame 96
15.2.2 Aggregated MAC frame 97
15.2.3 Frame control 98
15.2.4 DestAddr 99
15.2.5 SrcAddr 99
15.2.6 Sequence control 99
15.2.7 Access information 100
15.2.8 Frame payload 101
15.2.9 FCS 101
15.3 Beacon frames 102
15.4 Discovery frames 104
15.5 Control frames 105
15.5.1 Immediate acknowledgement (Imm-ACK) 106
15.5.2 Block acknowledgement (B-ACK) 107
15.5.3 Application-specific 108
15.5.4 B-Poll 108
15.5.5 B-Poll response frame 109
15.5.6 Antenna training/tracking control frames 109
15.6 Command frames 110

15.6.1 DRP reservation request 111
15.6.2 DRP reservation response 111
15.6.3 Channel selection 111
15.6.4 Link feedback 113
15.6.5 Probe 116
15.6.6 Pairwise temporal key (PTK) 117
15.6.7 Group temporal key (GTK) 118
15.6.8 Application-specific 119
15.6.9 Relay 119
15.6.10 Transmit switched diversity (TSD) request 119
15.6.11 Transmit switched diversity (TSD) set response 120
15.6.12 Transmit switched diversity (TSD) switch 120
15.6.13 Fast uplink channel allocation (FUCA) 121
15.7 Data frames 121
15.8 Aggregated MAC frames 122
15.8.1 Aggregated data frames 122
15.8.2 Aggregated tracking frames 122
15.9 Information elements 122
15.9.1 Application-specific IE (ASIE) 124
15.9.2 Application-specific probe IE 124
15.9.3 Antenna Capabilities IE (ACIE) 124
15.9.4 ATIE 125
15.9.5 ATTCIE 127
15.9.6 AFIE 128
15.9.7 Beacon period occupancy IE (BPOIE) 129
15.9.8 BP Switch IE 131
15.9.9 Channel bonding IE (CBOIE) 131
15.9.10 Channel change IE 132
15.9.11 Channel measurement IE 133
15.9.12 Distributed reservation protocol (DRP) IE 134
15.9.13 DRP availability IE 137
15.9.14 Hibernation anchor IE 137
15.9.15 Hibernation mode IE 137
15.9.16 Identification IE 138
15.9.17 Link feedback IE 139
15.9.18 MAC capabilities IE 140
15.9.19 Master key identifier (MKID) IE 141
15.9.20 Multicast address binding (MAB) IE 141
15.9.21 PHY capabilities IE 142
15.9.22 Probe IE 145
15.9.23 Relinquish request IE 145
15.9.24 Relay IE 146
15.9.25 Scan Timing IE 148
15.9.26 UEP information IE 149

16 MAC sublayer functional description 150
16.1 Frame processing 150
16.1.1 Frame addresses 150
16.1.2 Frame reception 151
16.1.3 Antenna training frame transaction 151
16.1.4 Frame transfer 151
16.1.5 Frame retry 152
16.1.6 Inter-frame space (IFS) 152
16.1.7 Duplicate detection 152
16.1.8 RTT/CTT use 152
16.1.9 MAC header fields 153
16.1.10 Information elements 154
16.2 Distributed contention access (DCA) 157
16.2.1 DCA medium availability 157
16.2.2 NAV 157
16.2.3 Medium status 158
16.2.4 Obtaining a TXOP 158

16.2.5 Using a TXOP 159
16.2.6 Invoking a backoff procedure 159
16.2.7 Decrementing a backoff counter 160
16.3 Device discovery 160
16.3.1 Power-up scan 161
16.3.2 Transmission and reception of discovery frames 162
16.4 Channel selection 164
16.4.1 Explicit channel selection 165
16.4.2 Implicit channel selection 166
16.5 Transmission and reception of beacons 166
16.5.1 Transmission and reception of Type A beacons 166
16.5.2 Transmission and reception of Type B beacon frames 167
16.5.3 Superframe 168
16.6 Distributed reservation protocol (DRP) 174
16.6.1 Reservation type 175
16.6.2 Reservation waveform 175
16.6.3 Medium access 175
16.6.4 DRP availability IE 176
16.6.5 DRP reservation negotiation 176
16.6.6 DRP reservation announcements 178
16.6.7 Resolution of DRP reservation conflicts 178
16.6.8 BPST realignment and existing DRP reservations 180
16.6.9 Modification and termination of existing DRP reservations 180
16.6.10 Retransmit procedures in DRP reservations 180
16.7 Coexistence and interoperability 181
16.7.1 Coexistence 181
16.7.2 Interoperability 181
16.8 Synchronization of devices 182
16.8.1 Clock accuracy 182
16.8.2 Synchronization for devices in hibernation mode 182
16.8.3 Guard times 182
16.9 Fragmentation and reassembly 184
16.10 Aggregation 184
16.11 Channel bonding 186
16.12 Acknowledgement policies 187
16.12.1 No-ACK 187
16.12.2 Immediate ACK 187
16.12.3 Block ACK 187
16.13 Probe 189
16.14 Multi-rate support 189
16.15 Transmit power control (TPC) 190
16.16 Power management mechanisms 190
16.16.1 Power management modes 190
16.16.2 Power state transitions at active mode 190
16.16.3 Hibernation mode operation 191
16.16.4 Hibernation anchor operation 192
16.17 ASIE operation 193
16.18 Antenna training and tracking 193
16.18.1 Announcement of antenna capabilities 193
16.18.2 Antenna training/tracking configuration 193
16.18.3 Iterative antenna training 194
16.18.4 Antenna tracking 195
16.19 Transmit switched diversity (TSD) operation 196
16.19.1 TSD initiating procedure 196
16.19.2 Antenna switching 196
16.20 MAC sublayer parameters 197

17 Security 198
17.1 Security mechanisms 198
17.1.1 Security operation 199
17.1.2 4-way handshake 199
17.1.3 Key transport 199

17.1.4 Freshness protection 199
17.1.5 Data encryption 199
17.1.6 Frame integrity protection 199
17.2 Security modes 200
17.2.1 Security mode 0 201
17.2.2 Security mode 1 201
17.2.3 Security mode 2 201
17.3 Temporal keys 202
17.3.1 Mutual authentication and PTK derivation 202
17.3.2 GTK exchange 203
17.3.3 Pseudo-random function (PRF) definition 204
17.3.4 PTK and KCK derivation 204
17.3.5 PTK MIC generation 205
17.3.6 Random number generation 205
17.4 Frame reception steps and replay prevention measures 206
17.4.1 Frame reception 206
17.4.2 Replay prevention 206
17.4.3 Implications on GTKs 207
17.5 AES-128 GCM inputs 207
17.5.1 Overview 207
17.5.2 Nonce 207
17.5.3 GCM blocks 208
17.6 Token authentication 209
17.6.1 Token issuance 209
17.6.2 Token revoke 210

18 HDMI PAL 210
18.1 Introduction 210
18.2 HDMI transmission 211
18.2.1 Identification of video vs. data 211
18.2.2 TMDS removal 211
18.2.3 Data type multiplexing 211
18.3 HDMI reception 213
18.3.1 TMDS encoding 213
18.3.2 Packet demultiplexing 213
18.4 PAL header format 217
18.4.1 Sub-packet header 218
18.5 PAL payload format 219
18.6 Block retransmission request 219
18.7 Type specific header fields 220
18.7.1 S-UEP 220
18.7.2 P-UEP 223
18.8 Video/audio format adaptation 224
18.8.1 Fast video format adaptation 224
18.8.2 Fast audio format adaptation 227
18.8.3 Control messages to support fast format adaptation 228
18.9 Fast uplink channel allocation (FUCA) 229
18.9.1 FUCA operation 230
18.9.2 The procedure of data exchange using FUCA 233

19 Out-of-band control channel 234
19.1 OOB operation 235
19.1.1 Ad hoc mode 235
19.1.2 Infrastructure mode 237
19.1.3 Other OOB functions 239
19.2 OOB frame format 240
19.2.1 General frame format 240
19.2.2 OOB-beacon 240
19.2.3 OOB-60GHz capability request 241
19.2.4 OOB-60GHz capability response 241
19.2.5 OOB-interference detection request 242
19.2.6 OOB-interference detection response 242

19.2.7 OOB-channel loss notification 242
19.2.8 OOB-block ACK 243
19.2.9 OOB-probe request 243
19.2.10 OOB-probe response 243
19.3 Convergence MAC sublayer parameters 244

20 Relay operation 244
20.1 Relay path setup 244
20.1.1 Identification of relay capabilites 244
20.1.2 Association with a relay device 244
20.1.3 Antenna training between the source and the destination 244
20.1.4 Antenna training between the source and the relay 244
20.1.5 Antenna training between the relay and the destination 245
20.1.6 Transition to data channel 245
20.2 Data transmission in relay operation 247
20.2.1 DRP reservation for relay operation in data channel 247
20.2.2 Usage of relay device 247
20.2.3 Frame transfer in relay operation 247
20.2.4 Frame reception in relay operation 248
20.2.5 Data exchange using relay device 248
20.2.6 Decision on path change 249
20.2.7 Path Change 249
20.2.8 Relay link feedback via relay device 250
20.2.9 Scan of idle path 251
20.2.10 Operation of relay device 251

Annex A (normative) MUX sublayer 253

Annex B (normative) MAC Policies 255

Annex C (informative) Higher Layer Synchronization Support 258

Annex D (informative) IP PAL 260

Annex E (informative) USB PAL 263

Annex F (informative) B-ACK buffer with fixed size elements 266

Bibliography 267