

# ISO/IEC 16504:2011-11 (E)

## Information technology - Telecommunications and information exchange between systems - MAC and PHY for operation in TV white space

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vii
Introduction .....		viii
1	Scope .....	1
2	Conformance .....	1
3	Normative references .....	1
4	Terms and definitions .....	1
5	Abbreviations and Acronyms .....	4
6	General description .....	7
6.1	Network components .....	7
6.2	Network formation .....	7
6.3	Protocol architecture .....	8
6.4	Addressing .....	9
6.5	PHY features .....	9
6.6	Overview of MAC service functionality .....	10
6.6.1	Logical groups .....	11
6.6.2	Control algorithms .....	11
6.6.3	Channel selection .....	11
6.6.4	The superframe .....	11
6.6.5	Beaconing .....	12
6.6.6	Medium access .....	13
6.6.7	Data communication between devices .....	13
6.6.8	MAC frame data rates .....	13
6.6.9	Security .....	13
6.6.10	Information discovery .....	14
6.6.11	Support for higher-layer timer synchronization .....	14
6.6.12	Protection of incumbent users .....	14
6.6.13	Self-coexistence .....	14
6.6.14	Rate adaptation .....	15
6.6.15	Power management .....	15
7	MAC common part sublayer .....	15
7.1	MAC Frame Format .....	15
7.1.1	Frame format conventions .....	16
7.1.2	General MAC frame format .....	16
7.1.3	Beacon frames .....	22
7.1.4	Control frames .....	24
7.1.5	Command frames .....	27
7.1.6	Data frames .....	35
7.1.7	Aggregated data frames .....	35
7.1.8	Information elements .....	35
7.2	Frame processing .....	63
7.2.1	Frame addresses .....	63
7.2.2	Frame reception .....	64
7.2.3	Frame transaction .....	64

7.2.4	Frame transfer .....	65
7.2.5	Frame retry .....	65
7.2.6	Inter-frame space (IFS) .....	65
7.2.7	Duplicate detection .....	66
7.2.8	RTS/CTS use .....	66
7.2.9	MAC header fields .....	67
7.2.10	Information elements .....	69
7.3	MAC Structure and Beaconing .....	73
7.3.1	Beacon Period .....	74
7.3.2	Beacon slot state .....	74
7.3.3	BP length .....	74
7.3.4	Beacon transmission and reception .....	75
7.3.5	Beacon collision detection .....	76
7.3.6	BP contraction .....	76
7.3.7	Merger of multiple beacon groups .....	77
7.3.8	Signalling window .....	79
7.4	Device Synchronization .....	80
7.4.1	Clock accuracy .....	80
7.4.2	Synchronization for devices in hibernation mode .....	80
7.4.3	Guard times .....	80
7.5	Data Transfer Period .....	82
7.5.1	Prioritized Contention Access (PCA) .....	83
7.5.2	Channel Reservation Access (CRA) .....	89
7.6	Fragmentation and Aggregation .....	96
7.6.1	Fragmentation and reassembly .....	96
7.6.2	Aggregation .....	97
7.7	ARQ, Multirate Support and Power Control .....	98
7.7.1	ARQ Policies .....	98
7.7.2	Multi-rate Support .....	100
7.7.3	Transmit Power Control .....	100
7.8	Dynamic Channel Selection .....	100
7.9	Power Management Mechanisms .....	101
7.9.1	Power management modes .....	101
7.9.2	Device power states .....	101
7.9.3	Power state transitions .....	101
7.9.4	Hibernation mode operation .....	103
7.9.5	Hibernation anchor operation .....	103
7.10	Probe .....	104
7.11	Protection of incumbents .....	104
7.11.1	Channel Measurement .....	104
7.11.2	Channel Classification .....	107
7.11.3	Channel Evacuation .....	108
7.12	Self-coexistence .....	109
7.12.1	Self-coexistence scenarios .....	109
7.12.2	Distributed self-coexistence mechanisms .....	109
7.12.3	Centralized self-coexistence mechanisms .....	110
7.13	Network Entry and Initialization .....	111
7.13.1	Initial Channel SCAN and Device Discovery .....	113
7.13.2	Master-Slave Association .....	114
7.13.3	Pair discovery .....	115
7.13.4	Create/join a beacon group .....	116
7.13.5	Pairing .....	116
7.13.6	Setup connections .....	117
7.14	MAC sublayer parameters .....	118
8	Security .....	120
8.1	Security mechanisms .....	120
8.1.1	Security operation .....	120
8.1.2	4-way handshake .....	121
8.1.3	Key transport .....	121
8.1.4	Freshness protection .....	121
8.1.5	Data encryption .....	121

8.1.6	Frame integrity protection .....	121
8.2	Security modes .....	121
8.2.1	Security mode 0 .....	123
8.2.2	Security mode 1 .....	123
8.2.3	Security mode 2 .....	123
8.3	Temporal keys .....	123
8.3.1	Mutual authentication and PTK derivation .....	124
8.3.2	GTK exchange .....	125
8.3.3	Pseudo-random function (PRF) definition .....	126
8.3.4	PTK and KCK derivation .....	127
8.3.5	PTK MIC generation .....	127
8.3.6	Random number generation .....	128
8.4	Frame reception steps and replay prevention measures .....	128
8.4.1	Frame reception .....	128
8.4.2	Replay prevention .....	129
8.4.3	Implications on GTKs .....	129
8.5	AES-128 CCM Inputs .....	129
8.5.1	Overview .....	129
8.5.2	Nonce .....	130
8.5.3	CCM blocks .....	130
9	PHY .....	132
9.1	Introduction .....	132
9.2	Symbol description .....	132
9.2.1	OFDM symbol description .....	132
9.2.2	Symbol parameters .....	134
9.3	PPDU .....	134
9.3.1	PLCP preamble .....	135
9.3.2	PLCP header .....	137
9.3.3	PSDU .....	142
9.4	Constellation mapping and modulation .....	148
9.4.1	Data modulation .....	148
9.4.2	Pilot modulation .....	150
9.5	OFDM modulation .....	150
9.5.1	Data subcarriers .....	151
9.5.2	Pilot subcarriers .....	151
9.5.3	Null subcarriers .....	153
9.5.4	Implementation of Fourier transform .....	153
9.6	General block diagram for the OFDM PHY .....	154
9.7	General requirements .....	154
9.7.1	Operating frequency range .....	154
9.7.2	Channel bandwidth and numbering .....	155
9.7.3	PHY layer timing .....	155
9.8	Transmitter requirements .....	155
9.8.1	Transmit center frequency tolerance .....	155
9.8.2	Symbol clock frequency tolerance .....	155
9.8.3	Clock synchronization .....	155
9.8.4	Transmitter constellation error .....	156
9.9	Receiver requirements .....	157
9.9.1	Receiver sensitivity .....	157
9.9.2	Maximum received signal level .....	158
9.9.3	Center frequency and symbol clock frequency tolerance .....	158
9.9.4	Link quality estimate .....	158
9.10	Control mechanisms .....	159
9.10.1	Device synchronization .....	159
9.10.2	Transmit power control .....	159
9.11	Multiple antennae (optional) .....	160
9.11.1	Multiple antennae normal preamble and burst preamble specification .....	160
9.11.2	Multiple antennae PLCP header specification .....	161
9.11.3	Pilot subcarriers for all multiple antennae modes .....	163
9.11.4	Frequency interleaved transmit diversity (FITD) .....	163
9.11.5	Alamouti space time block coding (STBC) .....	163

<b>9.11.6 Spatial multiplexing (SM) mode .....</b>	<b>164</b>
<b>Annex A (normative) MUX sublayer .....</b>	<b>165</b>
<b>Annex B (normative) OFDM parameters for 7 MHz and 8 MHz channel bandwidths .....</b>	<b>167</b>
<b>Annex C (normative) Data rates for 7 MHz and 8 MHz channel bandwidths .....</b>	<b>169</b>
<b>Annex D (normative) MAC policies .....</b>	<b>170</b>
<b>Annex E (informative) FFT-based pilot sensing algorithms .....</b>	<b>173</b>
<b>Annex F (informative) An example of TPC algorithm .....</b>	<b>175</b>
<b>Bibliography .....</b>	<b>178</b>