ISO/IEC 17417:2011-12 (E)

Information technology - Telecommunications and information exchange between systems - Short Distance Visible L ight Communication (SDVLC)

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms,definitions and abbreviations 2

5 Conventions and notations 6

6 General 6

7 Physical Layer 6

8 Transmitter and Receiver Block Diagram 7
8.1 Transmitter to Receiver Link 7
8.2 Data Encoding 7
8.2.1 8B10 Data Encoding 8
8.2.2 2B4B Data Encoding 8
8.3 Modulation 8
8.4 Bit Order 8

9 Frame Formats 8
9.1 Frame Structure overview 9
9.2 Frame Structure Detail 10
9.2.1 Start Indicator Structure 10
9.2.2 Control Header Structure 11
9.3 MAC PDU Structure 13
9.3.1 MAC Header 13
9.3.2 Payload 14
9.3.3 Payload CRC 15
9.4 Visible Frame 15
9.4.1 Visible Pattern 15
9.5 Cyclic Redundancy Check (CRC) 16

10 Connection Procedure 16

11 Association Operation Messages 17
11.1 Association Request (AS-REQ) 17
11.2 Association Response (AS-RSP) 18
11.3 Association Acknowledge (AS-ACK) 18
11.4 Disassociation Request (DAS-REQ) 19
11.5 Disassociation Response (DAS-RSP) 19
11.6 Disassociation Acknowledge (DAS-ACK) 20

12 Data Burst Modes Operation 20
12.1 Periodic Burst Mode 20

12.1.1 Burst Request Message (BR-REQ) 21
12.1.2 Burst Response Message (BR-RSP) 23
12.2 Aperiodic Burst Mode 24
12.2.1 Aperiodic Burst Request Message (ABR-REQ) 25
12.2.2 Aperiodic Burst Response Message (ABR-RSP) 26

13 Data Encoding Change 28
13.1 ENC-REQ (Data Encoding Change Request) 28
13.2 ENC-RSP (Data Encoding Change Response) 28