

ISO/IEC 18047-2:2012-01 (E)

Information technology - Radio frequency identification device conformance test methods - Part 2: Test methods for air interface communications below 135 kHz

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Symbols	2
3.3	Abbreviated terms	2
4.1	General	3
4.2	Default conditions applicable to the test methods	3
4.2.1	Test environment	3
4.2.2	Pre-conditioning	3
4.2.3	Default tolerance	3
4.2.4	Spurious inductance	3
4.2.5	Noise floor at test location	3
4.2.6	Total measurement uncertainty	3
4.3	Setup of test equipment for tag tests	4
4.3.1	Parameter definition	4
4.3.2	Test equipment configuration	4
4.4	Test methods for tags	11
4.4.1	Tag Orientation	11
4.5	Test procedure for tags	11
4.5.1	Calibrating null compensation	11
4.5.2	Minimum activating magnetic field strength in FDX mode	13
4.5.3	Minimal activating magnetic field strength in HDX mode	13
4.5.4	Level of tag response in FDX mode	14
4.5.5	Level of tag response in HDX mode	15
4.5.6	Tag waiting time for FDX mode	16
4.5.7	Tag waiting time for HDX mode	16
4.6	Equipment for interrogator tests	17
4.6.1	Tag Emulation Circuit	17
4.7	Methods for interrogator tests	17
4.7.1	Verification of reading	17
4.7.2	Tag Orientation	17
4.8	Test procedure for interrogator	18
4.8.1	Modulation index and waveform	18
4.8.2	Power generation for FDX (informative)	18
4.8.3	Power generation for HDX (informative)	19
4.8.4	Response detection for FDX	19
4.8.5	Response detection for HDX	19
Annex A (normative)	Design description of the tag emulation circuits	20
A.1	Reference air-cored antenna	20
A.2	FDX Tag Emulation Circuit	20
A.2.1	General	20

A.2.2	Set up trimming	22
A.3	The HDX Tag Emulation Circuit	22
A.3.1	General	22
A.3.2	Working principle of the HDX Tag Emulation Circuit	23
A.3.3	Set up and trimming procedure for the HDX emulation	23
Annex B (informative) Program for the evaluation of the spectrum		25
Bibliography		29