ISO/IEC 18000-61:2012-07 (E)

Information technology - Radio frequency identification for item management - Part 61: Parameters for air interface communications at 860 MHz to 960 MHz Type A

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Conformance 2
2.1 Claiming conformance 2
2.2 Interrogator conformance and obligations 2
2.3 Tag conformance and obligations 2

3 Normative references 3

4 Terms, definitions, symbols and abbreviated terms 3
4.1 Terms and definitions 3
4.2 Symbols 4
4.3 Abbreviated terms 4

5 Overview 5
5.1 Parameter tables 5

6 Type A 9
6.1 Physical layer and data coding 9
6.1.1 Interrogator power-up waveform 9
6.1.2 Interrogator power-down 10
6.1.3 Frequency hopping carrier rise and fall times 11
6.1.4 FM0 return link 12
6.1.5 PIE (Pulse interval encoding) forward link 15
6.2 Data elements 20
6.2.1 Unique identifier (Tag ID) 20
6.2.2 Sub-UID 20
6.2.3 Application family identifier 21
6.2.4 Data storage format identifier (DSFID) 21
6.3 Protocol elements 22
6.3.1 Tag memory organisation 22
6.3.2 Support of battery assisted passive (BAP) tags 22
6.3.3 Block lock status 22
6.3.4 Tag signature 23
6.4 Protocol description 23
6.4.1 Protocol concept 23
6.4.2 Command format 24
6.4.3 Command flags 25
6.4.4 Round size 26
6.4.5 Command code definition and structure 26
6.4.6 Command classes 26
6.4.7 Command codes and CRC 28
6.4.8 Response format 31
6.4.9 Tag states 33
6.4.10 Collision arbitration 34
6.4.11 General explanation of the collision arbitration mechanism 34
6.5 Timing specifications 36

6.5.1 Timing specifications general ... 36
6.5.2 Tag state storage ... 36
6.5.3 Forward link to return link handover ... 37
6.5.4 Return link to forward link handover ... 37
6.5.5 Acknowledgement time window ... 37
6.6 Command format examples ... 39
6.7 Mandatory commands ... 39
6.7.1 Mandatory commands general ... 39
6.7.2 Next_slot ... 39
6.7.3 Standby_round ... 41
6.7.4 Reset_to_ready ... 42
6.7.5 Init_round_all ... 43
6.8 Optional commands ... 45
6.8.1 Optional commands general ... 45
6.8.2 Init_round ... 46
6.8.3 Close_slot ... 47
6.8.4 New_round ... 48
6.8.5 Select (by SUID) ... 50
6.8.6 Read_blocks ... 51
6.8.7 Get_system_information ... 55
6.8.8 Begin_round ... 58
6.8.9 Write_single_block ... 60
6.8.10 Write_multiple_blocks ... 62
6.8.11 Lock_blocks ... 64
6.8.12 Write_AFI ... 66
6.8.13 Lock_AFI ... 68
6.8.14 Write_DSFID command ... 70
6.8.15 Lock_DSFID ... 72
6.8.16 Get_blocks_lock_status ... 74
6.8.17 Init_Fast_Slots ... 76
6.9 Custom commands ... 79
6.10 Proprietary commands ... 80

Annex A (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks ... 81

A.1 Example CRC-5 encoder/decoder ... 81
A.2 Example CRC-16 encoder/decoder ... 82

Bibliography ... 83