ISO/IEC 18000-62:2012-07 (E)

Information technology - Radio frequency identification for item management - Part 62: Parameters for air interface communications at 860 MHz to 960 MHz Type B

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Conformance 1
2.1 Claiming conformance 1
2.2 Interrogator conformance and obligations 2
2.3 Tag conformance and obligations 2

3 Normative references 3

4 Terms, definitions, symbols and abbreviated terms 3
4.1 Terms and definitions 3
4.2 Symbols 3
4.3 Abbreviated terms 4

5 Overview 5
5.1 Parameter tables 5

6 Type B 9
6.1 Physical layer and data coding 9
6.1.1 Interrogator power-up waveform 9
6.1.2 Interrogator power-down 9
6.1.3 Frequency hopping carrier rise and fall times 10
6.1.4 FM0 return link 11
6.1.5 Manchester forward link 14
6.1.6 Protocol concept 17
6.1.7 Command format 18
6.1.8 Response format 20
6.1.9 WAIT 20
6.1.10 Examples of a command packet 20
6.1.11 Communication sequences at packet level 21
6.2 Btree protocol and collision arbitration 22
6.2.1 Definition of data elements, bit and byte ordering 22
6.2.2 Tag memory organisation 23
6.2.3 Block security status 24
6.2.4 Overall protocol description, Btree protocol 24
6.2.5 Collision arbitration 29
6.2.6 Commands 31
6.2.7 Command types 31
6.2.8 Transmission errors 58

Annex A (informative) Calculation of 16-bit cyclic redundancy checks 59

A.1 Example CRC-16 encoder/decoder 59
A.2 Example CRC-16 calculations 60

Annex B (normative) Memory mapping 62

B.1 Unique identifier (normative) 62
B.1.1 Unique identifier general 62
B.1.2 Unique identifier format 62
B.1.3 Unique identifier according to ANSI 256 62
B.1.4 Remaining system memory 63

Annex C (informative) Tag memory map 67

C.1 Tag memory map 67

Bibliography 68