

ISO/IEC 18000-62:2012-07 (E)

Information technology - Radio frequency identification for item management - Part 62: Parameters for air interface communications at 860 MHz to 960 MHz Type B

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Conformance	1
2.1	Claiming conformance	1
2.2	Interrogator conformance and obligations	2
2.3	Tag conformance and obligations	2
3	Normative references	3
4	Terms, definitions, symbols and abbreviated terms	3
4.1	Terms and definitions	3
4.2	Symbols	3
4.3	Abbreviated terms	4
5	Overview	5
5.1	Parameter tables	5
6	Type B	9
6.1	Physical layer and data coding	9
6.1.1	Interrogator power-up waveform	9
6.1.2	Interrogator power-down	9
6.1.3	Frequency hopping carrier rise and fall times	10
6.1.4	FM0 return link	11
6.1.5	Manchester forward link	14
6.1.6	Protocol concept	17
6.1.7	Command format	18
6.1.8	Response format	20
6.1.9	WAIT	20
6.1.10	Examples of a command packet	20
6.1.11	Communication sequences at packet level	21
6.2	Btree protocol and collision arbitration	22
6.2.1	Definition of data elements, bit and byte ordering	22
6.2.2	Tag memory organisation	23
6.2.3	Block security status	24
6.2.4	Overall protocol description, Btree protocol	24
6.2.5	Collision arbitration	29
6.2.6	Commands	31
6.2.7	Command types	31
6.2.8	Transmission errors	58
Annex A (informative)	Calculation of 16-bit cyclic redundancy checks	59
A.1	Example CRC-16 encoder/decoder	59
A.2	Example CRC-16 calculations	60
Annex B (normative)	Memory mapping	62

B.1	Unique identifier (normative)	62
B.1.1	Unique identifier general	62
B.1.2	Unique identifier format	62
B.1.3	Unique identifier according to ANSI 256	62
B.1.4	Remaining system memory	63
Annex C (informative) Tag memory map		67
C.1	Tag memory map	67
Bibliography		68