

ISO/IEC 17982:2012-08 (E)

Information technology - Telecommunications and information exchange between systems - Close Capacitive Coupling Communication Physical Layer (CCCC PHY)

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms, definitions and acronyms	1
5	Conventions and notations	2
5.1	Representation of numbers	2
5.2	Names	2
6	General	2
7	Reference plate-electrode assembly	4
8	PHY parameters	5
8.1	Voltage conditions	5
8.2	Bit representation	6
8.2.1	Bit duration	6
8.2.2	Bit encoding	6
8.3	Transmission	6
8.4	DC balance of a P-PDU	6
8.5	Reception of a P-PDU	7
9	P-PDU	7
9.1	Structure	7
9.2	Space	7
9.3	Level adjust	7
9.4	Pre-amble and Sync	7
9.5	Attribute	8
9.6	TDS number	8
9.7	Sequence number	9
9.7.1	Initial and range	9
9.7.2	Acknowledgement	9
9.8	Payload	9
9.9	CRC	9
9.10	Post-amble	9
9.11	Null P-PDU	9
9.12	Data P-PDU	9
10	PHY Data Unit (P-DU)	9
11	Segmentation and Reassembly	10
12	TDS	10

13	LBT and synchronisation	11
13.1	LBT	11
13.2	Synchronisation	11
14	Association procedure	11
15	Communication	13
15.1	Full duplex communication	13
15.2	Broadcast communication	15
Annex A (normative) Tests		17