

ISO/IEC 17982:2012-08 (E)

Information technology - Telecommunications and information exchange between systems - Close Capacitive Coupling Communication Physical Layer (CCCC PHY)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 3 | Normative references | 1 |
| 4 | Terms, definitions and acronyms | 1 |
| 5 | Conventions and notations | 2 |
| 5.1 | Representation of numbers | 2 |
| 5.2 | Names | 2 |
| 6 | General | 2 |
| 7 | Reference plate-electrode assembly | 4 |
| 8 | PHY parameters | 5 |
| 8.1 | Voltage conditions | 5 |
| 8.2 | Bit representation | 6 |
| 8.2.1 | Bit duration | 6 |
| 8.2.2 | Bit encoding | 6 |
| 8.3 | Transmission | 6 |
| 8.4 | DC balance of a P-PDU | 6 |
| 8.5 | Reception of a P-PDU | 7 |
| 9 | P-PDU | 7 |
| 9.1 | Structure | 7 |
| 9.2 | Space | 7 |
| 9.3 | Level adjust | 7 |
| 9.4 | Pre-amble and Sync | 7 |
| 9.5 | Attribute | 8 |
| 9.6 | TDS number | 8 |
| 9.7 | Sequence number | 9 |
| 9.7.1 | Initial and range | 9 |
| 9.7.2 | Acknowledgement | 9 |
| 9.8 | Payload | 9 |
| 9.9 | CRC | 9 |
| 9.10 | Post-amble | 9 |
| 9.11 | Null P-PDU | 9 |
| 9.12 | Data P-PDU | 9 |
| 10 | PHY Data Unit (P-DU) | 9 |
| 11 | Segmentation and Reassembly | 10 |
| 12 | TDS | 10 |

| | | |
|--|--|-----------|
| 13 | LBT and synchronisation | 11 |
| 13.1 | LBT | 11 |
| 13.2 | Synchronisation | 11 |
| 14 | Association procedure | 11 |
| 15 | Communication | 13 |
| 15.1 | Full duplex communication | 13 |
| 15.2 | Broadcast communication | 15 |
| Annex A (normative) Tests | | 17 |