

# ISO/IEC 18000-63:2013-01 (E)

## Information technology - Radio frequency identification for item management - Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

<b>Contents</b>		<b>Page</b>
Foreword .....		ix
Introduction .....		x
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Conformance .....</b>	<b>1</b>
2.1	Interrogator conformance and obligations .....	2
2.2	Tag conformance and obligations .....	2
<b>3</b>	<b>Normative references .....</b>	<b>3</b>
<b>4</b>	<b>Terms and definitions, symbols and abbreviated terms .....</b>	<b>3</b>
4.1	Terms and definitions .....	3
<b>5</b>	<b>Symbols, abbreviated terms and notations .....</b>	<b>5</b>
5.1	Symbols .....	5
5.2	Abbreviated terms .....	6
5.3	Notation .....	8
<b>6</b>	<b>Type C .....</b>	<b>9</b>
6.1	Parameter tables .....	9
6.2	Protocol overview .....	14
6.2.1	Physical layer .....	14
6.2.2	Tag-identification layer .....	14
6.3	Command types and command structure .....	14
6.3.1	General .....	14
6.3.2	Mandatory .....	15
6.3.3	Optional .....	15
6.3.4	Custom .....	15
6.3.5	Proprietary .....	15
6.4	Description of operating procedure .....	15
6.4.1	Signalling .....	15
6.4.2	Tag selection, inventory, and access .....	30
<b>7</b>	<b>Battery Assisted Passive (BAP) Interrogator Talks First Type C systems (optional) .....</b>	<b>78</b>
7.1	Applicability .....	78
7.2	General overview, definitions, and requirements of BAP .....	78
7.3	Battery Assisted Passive inventoried flag and state machine behaviour modifications .....	80
7.3.1	Modification to ready state and power-down support for BAP Tags .....	80
7.3.2	Signal loss tolerance via timer (mandatory) .....	81
7.3.3	Modified persistence of BAP PIE inventory flags (optional) .....	83
7.4	Battery Assisted Passive PIE (optional) .....	85
7.4.1	Flex_Query command (optional) .....	85
7.4.2	BAP PIE detailed operation including optional Battery Saver Mode .....	86
7.5	Manchester mode Battery Assisted operation protocol extensions .....	92
7.5.1	Introduction .....	92
7.5.2	Physical layer .....	93
7.5.3	Manchester Activation .....	98
7.5.4	Commands summary .....	114
7.6	Extended Protocol Control and Battery Tag Capabilities Reporting and Setting .....	128

7.6.1	General .....	128
7.6.2	Extended Protocol Control definition .....	129
7.6.3	Battery Assisted Passive Tag Capability Reporting, Setting, and duty cycle/mode control (optional) .....	131
8	Sensor support .....	159
8.1	Applicability .....	159
8.2	Overview .....	159
8.3	Real Time Clock (RTC) .....	160
8.3.1	General .....	160
8.3.2	Setting the RTC .....	160
8.3.3	BroadcastSync command (optional, for Type C) .....	161
8.3.4	Time synchronisation .....	162
8.4	HandleSensor command (optional, for Type C) .....	163
8.5	Simple Sensor .....	164
8.5.1	Type C and Simple Sensor .....	164
8.6	Sensor Directory System and Full Function Sensors .....	166
8.6.1	Sensor Access - General Approach .....	166
Annex A (normative) Extensible bit vectors (EBV) .....		173
Annex B (normative) State-transition tables .....		174
B.1	Contents .....	174
B.2	State transition tables for passive .....	174
B.2.1	Present state: Ready .....	174
B.2.2	Present state: Arbitrate .....	175
B.2.3	Present state: Reply .....	176
B.2.4	Present state: Acknowledged .....	177
B.2.5	Present state: Open .....	178
B.2.6	Present state: Secured .....	179
B.2.7	Present state: Killed .....	180
B.3	State transition tables for BAP PIE .....	181
B.3.1	Present state: sleep .....	181
B.3.2	Present state: low power listen .....	181
B.3.3	Present state: listen or stateful listen .....	181
B.3.4	Present state: stateful sleep or stateful low power listen .....	181
B.3.5	Present state: battery ready .....	182
B.3.6	Present state: Arbitrate .....	182
B.3.7	Present state: Reply .....	183
B.3.8	Present state: Acknowledged .....	184
B.3.9	Present state: Open .....	185
B.3.10	Present state: Secured .....	187
B.3.11	Present state: Killed .....	189
B.4	State transition tables for BAP Manchester .....	189
B.4.1	Present state: Hibernate .....	189
B.4.2	Present state: Activation code check .....	190
B.4.3	Present state: Stateful Hibernate .....	190
B.4.4	Present state: Battery Ready .....	191
B.4.5	Present state: Arbitrate .....	193
B.4.6	Present state: Reply .....	195
B.4.7	Present state: Acknowledged .....	197
B.4.8	Present state: Open .....	199
B.4.9	Present state: Secured .....	201
B.4.10	Present state: Killed .....	204
Annex C (normative) Command-response tables .....		205
C.1	Contents .....	205
C.2	Command response tables for passive .....	205
C.2.1	Command response: Power-up .....	205
C.2.2	Command response: Query .....	205

C.2.3	Command response: QueryRep .....	206
C.2.4	Command response: QueryAdjust .....	206
C.2.5	Command response: ACK .....	207
C.2.6	Command response: NAK .....	207
C.2.7	Command response: Req_RN .....	207
C.2.8	Command response: Select .....	208
C.2.9	Command response: Read .....	208
C.2.10	Command response: Write .....	208
C.2.11	Command response: Kill .....	209
C.2.12	Command response: Lock .....	209
C.2.13	Command response: Access .....	210
C.2.14	Command response: BlockWrite .....	210
C.2.15	Command response: BlockErase .....	211
C.2.16	Command response: BlockPermalock .....	211
C.2.17	Command response: T2 timeout .....	212
C.2.18	Command response: Invalid command .....	212
C.3	Command response tables for BAP PIE .....	213
C.3.1	Command response: Flex_Query (optional for BAP PIE) .....	213
C.3.2	Command response: INACT_T or Selective Global Timeout .....	213
C.3.3	Command response: Global Timeout .....	214
C.3.4	Command response: HandleSensor .....	214
C.3.5	Command response: BroadcastSync .....	214
C.4	Command Response Tables for Manchester .....	215
C.4.1	Command response: Power-up .....	215
C.4.2	Command response: QueryRep .....	215
C.4.3	Command response: QueryAdjust .....	215
C.4.4	Command response: ACK .....	216
C.4.5	Command response: NAK .....	217
C.4.6	Command response: Req_RN .....	217
C.4.7	Command response: Select .....	217
C.4.8	Command response: Read .....	217
C.4.9	Command response: Write .....	217
C.4.10	Command response: Kill .....	217
C.4.11	Command response: Lock .....	217
C.4.12	Command response: Access .....	218
C.4.13	Command response: BlockWrite .....	218
C.4.14	Command response: BlockErase .....	218
C.4.15	Command response: BlockPermalock .....	218
C.4.16	Command response: T2 timeout .....	218
C.4.17	Command response: Long Activation .....	218
C.4.18	Command response: Short Activation .....	219
C.4.19	Command response: Query_BAT .....	220
C.4.20	Command response: Next .....	221
C.4.21	Command response: Deactivate_BAT .....	221
C.4.22	Command response: Broadcast ID .....	222
C.4.23	Command response: Multirate_Reset .....	223
C.4.24	Command response: HandleSensor .....	223
C.4.25	Command response: BroadcastSync .....	223
C.4.26	Command response: Session Flag timer timeout .....	224
C.4.27	Command response: INACT_T or Selective Global Timeout .....	224
C.4.28	Command response: Global Timeout .....	224
C.4.29	Command response: TA .....	225
C.4.30	Command response: OpRegister Read/Write .....	225
C.4.31	Command response: Invalid command .....	226
Annex D (informative) Example slot-count (Q) selection algorithm .....		227
D.1	Example algorithm an Interrogator might use to choose Q .....	227
Annex E (informative) Example of Tag inventory and access .....		228
E.1	Example inventory and access of a single Tag .....	228

<b>Annex F (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks .....</b>	<b>232</b>
<b>F.1 Example CRC-5 encoder/decoder .....</b>	<b>232</b>
<b>F.2 Example CRC-16 encoder/decoder .....</b>	<b>232</b>
<b>F.3 Example CRC-16 calculations .....</b>	<b>233</b>
<b>Annex G (normative) Dense- and Multiple-Interrogator channelised signalling .....</b>	<b>234</b>
<b>G.1 General .....</b>	<b>234</b>
<b>G.2 Overview of Dense-Interrogator channelised signalling (informative) .....</b>	<b>234</b>
<b>Annex H (informative) Interrogator-to-Tag link modulation .....</b>	<b>237</b>
<b>H.1 Baseband waveforms, modulated RF, and detected waveforms .....</b>	<b>237</b>
<b>Annex I (normative) Error codes .....</b>	<b>239</b>
<b>I.1 Tag error codes and their usage .....</b>	<b>239</b>
<b>Annex J (normative) Slot counter .....</b>	<b>241</b>
<b>J.1 Slot-counter operation .....</b>	<b>241</b>
<b>Annex K (informative) Example data-flow exchange .....</b>	<b>242</b>
<b>K.1 Overview of the data-flow exchange .....</b>	<b>242</b>
<b>K.2 Tag memory contents and lock-field values .....</b>	<b>242</b>
<b>K.3 Data-flow exchange and command sequence .....</b>	<b>243</b>
<b>Annex L (informative) Optional Tag features .....</b>	<b>244</b>
<b>L.1 General .....</b>	<b>244</b>
<b>L.2 Optional Tag passwords .....</b>	<b>244</b>
<b>L.2.1 Kill password .....</b>	<b>244</b>
<b>L.2.2 Access password .....</b>	<b>244</b>
<b>L.3 Optional Tag memory banks and memory-bank sizes .....</b>	<b>244</b>
<b>L.3.1 Reserved memory .....</b>	<b>244</b>
<b>L.3.2 Ull memory .....</b>	<b>244</b>
<b>L.3.3 TID memory .....</b>	<b>244</b>
<b>L.3.4 User memory .....</b>	<b>244</b>
<b>L.4 Optional Tag commands .....</b>	<b>245</b>
<b>L.5 Optional Tag error-code reporting format .....</b>	<b>245</b>
<b>L.6 Optional Tag backscatter modulation format .....</b>	<b>245</b>
<b>L.7 Optional Tag functionality .....</b>	<b>245</b>
<b>Annex M (informative) Battery Assisted Tag to Interrogator synchronization .....</b>	<b>246</b>
<b>M.1 Introduction .....</b>	<b>246</b>
<b>M.2 General concept .....</b>	<b>246</b>
<b>M.3 Tag to Interrogator synchronization .....</b>	<b>247</b>
<b>Annex N (normative) Simple Sensors Data Block .....</b>	<b>249</b>
<b>N.1 Simple sensor types .....</b>	<b>249</b>
<b>N.2 General bit-based rules .....</b>	<b>250</b>
<b>N.3 Temperature sensor with 14° C span .....</b>	<b>250</b>
<b>N.3.1 Monitored measurement span .....</b>	<b>250</b>
<b>N.3.2 Accuracy .....</b>	<b>251</b>
<b>N.3.3 Sampling regime .....</b>	<b>251</b>
<b>N.3.4 High in-range limit level .....</b>	<b>251</b>
<b>N.3.5 Low in-range limit level .....</b>	<b>252</b>

N.3.6	Monitor delay .....	252
N.3.7	High out-of-range alarm delay .....	253
N.3.8	Low out-of-range alarm delay .....	253
N.3.9	Alarms .....	254
N.4	Temperature sensor with 28° C span .....	255
N.4.1	Monitored measurement span .....	255
N.4.2	Accuracy .....	255
N.4.3	Sampling regime .....	255
N.4.4	High in-range limit .....	255
N.4.5	Low in-range limit .....	255
N.4.6	Monitor delay .....	256
N.4.7	High out-of-range alarm delay .....	256
N.4.8	Low out-of-range alarm delay .....	256
N.4.9	Alarms .....	256
N.5	Relative humidity .....	256
N.5.1	Monitored measurement span .....	256
N.5.2	Accuracy .....	256
N.5.3	Sampling regime .....	257
N.5.4	High in-range limit level .....	257
N.5.5	Low in-range limit level .....	257
N.5.6	Monitor delay .....	257
N.5.7	High out-of-range alarm delay .....	257
N.5.8	Low out-of-range alarm delay .....	257
N.5.9	Alarms .....	257
N.6	Impact .....	258
N.6.1	Monitored measurement span .....	258
N.6.2	Accuracy .....	258
N.6.3	Sampling regime .....	258
N.6.4	High in-range limit .....	258
N.6.5	Low in-range limit .....	258
N.6.6	Monitor delay .....	258
N.6.7	High out-of-range alarm delay .....	258
N.6.8	Low out-of-range alarm delay .....	259
N.6.9	Alarms .....	259
N.7	Tilt .....	259
N.7.1	Monitored measurement span .....	259
N.7.2	Accuracy .....	259
N.7.3	Sampling regime .....	259
N.7.4	High in-range limit .....	259
N.7.5	Low in-range limit .....	259
N.7.6	Monitor delay .....	259
N.7.7	High out-of-range alarm delay .....	260
N.7.8	Low out-of-range alarm delay .....	260
N.7.9	Alarms .....	260
<b>Annex O (normative) Record structures and commands for Ported Simple Sensors .....</b>		<b>261</b>
O.1	Record structure types .....	261
O.1.1	Simple sensor data block .....	261
O.1.2	Sensor characteristics record block .....	262
O.1.3	Manufacturer record block .....	262
O.1.4	Authorisation password record block .....	263
O.1.5	Calibration record block .....	263
O.1.6	Sample and configuration record block .....	265
O.1.7	Event record block .....	266
O.1.8	Time synchronisation record block .....	267
O.2	Ported Simple Sensor commands .....	267
O.2.1	Read-Simple-Sensor-Data-Block .....	267
O.2.2	Read-Manufacturer-Record .....	268
O.2.3	Write-Password .....	268
O.2.4	Read-Calibration-Record .....	269
O.2.5	Write-Sample-And-Configuration-Record .....	269

O.2.6	Initialise-Sensor-Monitoring .....	270
O.2.7	Read-Sample-And-Configuration-Record .....	271
O.2.8	Read-Event-Record .....	271
O.2.9	Write-UTC-Timestamp .....	272
O.2.10	Read-Time-Synchronisation-Record .....	273
O.2.11	Erase-Monitored-Data .....	274
O.2.12	Activate-Simple-Sensor .....	274
O.2.13	Deactivate-Simple-Sensor .....	275
<b>Annex P (informative) BAP PIE and Manchester mode tutorial guide .....</b>		<b>276</b>
P.1	Executive summary of Battery Assisted Passive RFID in this standard .....	276
P.2	Battery Assisted Passive fundamentals .....	278
P.2.1	Propagation physics and resulting relationship between Interrogator and Tag sensitivity .....	278
P.2.2	Tag receiver issues .....	280
P.3	BAP PIE .....	281
P.4	Manchester .....	281
P.5	Guidance on using Next vs. Deactivate_BAT (PIE and Manchester) .....	282
P.6	Reliable inventory status tracking .....	282
P.7	Environmental validation .....	283
P.7.1	INACT_T and (Selective) Global Timeout timer refresh .....	283
P.8	Fade delay tolerance via INACT_T and Global Timeout .....	284
P.9	Clocks and commanded data rates and BLFs .....	284
P.10	Tag Capabilities Reporting and Setting (TCRS) .....	285
P.11	BAP PIE persistence compliance .....	285
<b>Annex Q (informative) Manchester mode RF power control .....</b>		<b>286</b>
Q.1	General .....	286
Q.2	Power levelling description .....	286
Q.3	Power leveling algorithm .....	288
<b>Bibliography .....</b>		<b>291</b>