ISO/IEC 17568:2013-03 (E)

Information technology - Telecommunications and information exchange between systems - Close proximity electric induction wireless commu nications

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 1

5 Abbreviations and acronyms 2

6 Overview 3
6.1 Introduction 3

7 Transmit signal 4
7.1 Modulation scheme parameters 4
7.2 Transmitter functional block diagram 4
7.2.1 Supported Rate Settings and rate dependent parameters 5
7.2.2 Reed-Solomon encoder 6
7.2.3 Convolutional encoder 7
7.2.4 ECS 8
7.2.5 Spreader 9
7.2.6 Sync sequence 9
7.2.7 Scrambler 10
7.2.8 Scrambling sequence generator 11
7.2.9 Pi/2 shift BPSK mapper 12
7.2.10 Mathematical framework of the Up Converter and the Baseband Waveform Generator 13
7.2.11 Baseband waveform 13
7.3 Frame format 14
7.3.1 PPDU format 14
7.3.2 PHY Header format 15
7.4 Transmitter 17
7.4.1 Measurement points 17
7.4.2 Transmit frequency 17
7.4.3 Transmit clock rate requirement 17
7.4.4 Transmit Constellation Error (EVM) 17

8 Receiver 17
8.1 Measurement point 17
8.2 Reference sensitivity 17
8.3 Blocking 17

9 Electric Induction Field 18

10 CNL service definition 19
10.1 Overview of CNL services 19
10.1.1 Connection control service 19
10.1.2 Data service 19

10.1.3 Security service 19
10.2 CNL service access point 19
10.2.1 Initialize 22
10.2.2 Close 22
10.2.3 Connect and accept 22
10.2.4 Connection release 24
10.2.5 Power save 25
10.2.6 Data transfer 26
10.3 CPDU formats 27
10.3.1 Conventions 27
10.3.2 Acknowledgement (ACK) CPDU 28
10.3.3 CNL data CPDUs 32
10.3.4 Management CPDUs (Link control message) 34
10.4 CNL function description 42
10.4.1 Segmenting/Reassembling 42
10.4.2 Medium state sensing 43
10.4.3 CNL-Level acknowledgements 43
10.4.4 Interframe space (IFS) 48
10.4.5 Access procedure 49
10.4.6 Multirate support 51
10.4.7 UID filter 51
10.5 CNL state 51
10.5.1 Close state 52
10.5.2 Search state 52
10.5.3 Connection request state 53
10.5.4 Accept waiting state 53
10.5.5 Response waiting state 53
10.5.6 Responder response state 54
10.5.7 Initiator connected state 54
10.5.8 Responder connected state 54
10.5.9 Sub-states within the Initiator connected state or Responder connected state 55
10.6 Numerical parameters 57

Annex A (normative) UID Specification 59

A.1 UID Composition 59
A.1.1 Specifier ID 59
A.1.2 Reserved 59
A.1.3 Extension Identifier 59

Annex B (informative) Coupler 60

Annex C (informative) Coupler measurement 61

Annex D (informative) Reference Coupler 63

Annex E (informative) Sample Data Sequences 65

E.1 Reed-Solomon Encoder 65
E.2 Convolutional Encoder 65
E.3 PHY Header HCS 67
E.4 Common CNL Header HCS 67
E.5 Sub CNL Header HCS 67
E.6 Scrambling sequence generator 67

Annex F (informative) CNL frame exchange sequences 70

F.1 CNL frame exchange sequences 70
F.1.1 Connection setup procedure 70
F.1.2 CSDU exchange procedure 70
F.1.3 Connection sleep procedure 71
F.1.4 Connection wakeup procedure 72

F.1.5 Connection confirmation procedure 73
F.1.6 Connection release procedure 73

Annex G (informative) CNL service operation 74

G.1 Initialize operation 74
G.2 Close operation 74
G.3 Connect request 75
G.3.1 Connect request operation 75
G.3.2 Accept receive operation 75
G.3.3 Accept response operation 76
G.3.4 Connect release operation 76
G.3.5 Accept release operation 76
G.4 Connect accept 77
G.4.1 Request receive operation 77
G.4.2 Accept request operation 77
G.4.3 Accept acknowledge operation 78
G.4.4 Accept release operation 78
G.4.5 Connect release operation 79
G.4.6 Request crossover operation 79
G.4.7 Accept request operation 80
G.4.8 Accept release operation 80
G.5 Release 81
G.5.1 Release request receive operation 81
G.5.2 Release receive operation 81
G.6 Transfer data 82
G.6.1 Data send operation 82
G.6.2 Data receive operation 83
G.6.3 Resend timeout operation 84
G.6.4 Target wake operation 85
G.7 Power save 86
G.7.1 Power save request operation 86
G.7.2 Sleep receive operation 87
G.8 Wakeup 88
G.8.1 Wakeup request operation 88
G.8.2 Wakeup acknowledge operation 88
G.8.3 Wakeup receive operation 89
G.8.4 Data send request operation 89
G.8.5 Wakeup data send operation 89
G.8.6 Wakeup timeout operation 90
G.9 Probe 90
G.9.1 Probe send operation 91
G.10 Probe ACK receive operation 91
G.10.1 Probe receive operation 91
G.10.2 Probe timeout operation 92