

# ISO/IEC 17568:2013-03 (E)

## Information technology - Telecommunications and information exchange between systems - Close proximity electric induction wireless communications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vi
Introduction .....		vii
1	Scope .....	1
2	Conformance .....	1
3	Normative references .....	1
4	Terms and definitions .....	1
5	Abbreviations and acronyms .....	2
6	Overview .....	3
6.1	Introduction .....	3
7	Transmit signal .....	4
7.1	Modulation scheme parameters .....	4
7.2	Transmitter functional block diagram .....	4
7.2.1	Supported Rate Settings and rate dependent parameters .....	5
7.2.2	Reed-Solomon encoder .....	6
7.2.3	Convolutional encoder .....	7
7.2.4	ECS .....	8
7.2.5	Spreader .....	9
7.2.6	Sync sequence .....	9
7.2.7	Scrambler .....	10
7.2.8	Scrambling sequence generator .....	11
7.2.9	Pi/2 shift BPSK mapper .....	12
7.2.10	Mathematical framework of the Up Converter and the Baseband Waveform Generator .....	13
7.2.11	Baseband waveform .....	13
7.3	Frame format .....	14
7.3.1	PPDU format .....	14
7.3.2	PHY Header format .....	15
7.4	Transmitter .....	17
7.4.1	Measurement points .....	17
7.4.2	Transmit frequency .....	17
7.4.3	Transmit clock rate requirement .....	17
7.4.4	Transmit Constellation Error (EVM) .....	17
8	Receiver .....	17
8.1	Measurement point .....	17
8.2	Reference sensitivity .....	17
8.3	Blocking .....	17
9	Electric Induction Field .....	18
10	CNL service definition .....	19
10.1	Overview of CNL services .....	19
10.1.1	Connection control service .....	19
10.1.2	Data service .....	19

10.1.3	Security service .....	19
10.2	CNL service access point .....	19
10.2.1	Initialize .....	22
10.2.2	Close .....	22
10.2.3	Connect and accept .....	22
10.2.4	Connection release .....	24
10.2.5	Power save .....	25
10.2.6	Data transfer .....	26
10.3	CPDU formats .....	27
10.3.1	Conventions .....	27
10.3.2	Acknowledgement (ACK) CPDU .....	28
10.3.3	CNL data CPDUs .....	32
10.3.4	Management CPDUs (Link control message) .....	34
10.4	CNL function description .....	42
10.4.1	Segmenting/Reassembling .....	42
10.4.2	Medium state sensing .....	43
10.4.3	CNL-Level acknowledgements .....	43
10.4.4	Interframe space (IFS) .....	48
10.4.5	Access procedure .....	49
10.4.6	Multirate support .....	51
10.4.7	UID filter .....	51
10.5	CNL state .....	51
10.5.1	Close state .....	52
10.5.2	Search state .....	52
10.5.3	Connection request state .....	53
10.5.4	Accept waiting state .....	53
10.5.5	Response waiting state .....	53
10.5.6	Responder response state .....	54
10.5.7	Initiator connected state .....	54
10.5.8	Responder connected state .....	54
10.5.9	Sub-states within the Initiator connected state or Responder connected state .....	55
10.6	Numerical parameters .....	57
Annex A (normative) UID Specification .....		59
A.1	UID Composition .....	59
A.1.1	Specifier ID .....	59
A.1.2	Reserved .....	59
A.1.3	Extension Identifier .....	59
Annex B (informative) Coupler .....		60
Annex C (informative) Coupler measurement .....		61
Annex D (informative) Reference Coupler .....		63
Annex E (informative) Sample Data Sequences .....		65
E.1	Reed-Solomon Encoder .....	65
E.2	Convolutional Encoder .....	65
E.3	PHY Header HCS .....	67
E.4	Common CNL Header HCS .....	67
E.5	Sub CNL Header HCS .....	67
E.6	Scrambling sequence generator .....	67
Annex F (informative) CNL frame exchange sequences .....		70
F.1	CNL frame exchange sequences .....	70
F.1.1	Connection setup procedure .....	70
F.1.2	CSDU exchange procedure .....	70
F.1.3	Connection sleep procedure .....	71
F.1.4	Connection wakeup procedure .....	72

F.1.5	Connection confirmation procedure .....	73
F.1.6	Connection release procedure .....	73
<b>Annex G (informative) CNL service operation .....</b>		<b>74</b>
G.1	Initialize operation .....	74
G.2	Close operation .....	74
G.3	Connect request .....	75
G.3.1	Connect request operation .....	75
G.3.2	Accept receive operation .....	75
G.3.3	Accept response operation .....	76
G.3.4	Connect release operation .....	76
G.3.5	Accept release operation .....	76
G.4	Connect accept .....	77
G.4.1	Request receive operation .....	77
G.4.2	Accept request operation .....	77
G.4.3	Accept acknowledge operation .....	78
G.4.4	Accept release operation .....	78
G.4.5	Connect release operation .....	79
G.4.6	Request crossover operation .....	79
G.4.7	Accept request operation .....	80
G.4.8	Accept release operation .....	80
G.5	Release .....	81
G.5.1	Release request receive operation .....	81
G.5.2	Release receive operation .....	81
G.6	Transfer data .....	82
G.6.1	Data send operation .....	82
G.6.2	Data receive operation .....	83
G.6.3	Resend timeout operation .....	84
G.6.4	Target wake operation .....	85
G.7	Power save .....	86
G.7.1	Power save request operation .....	86
G.7.2	Sleep receive operation .....	87
G.8	Wakeup .....	88
G.8.1	Wakeup request operation .....	88
G.8.2	Wakeup acknowledge operation .....	88
G.8.3	Wakeup receive operation .....	89
G.8.4	Data send request operation .....	89
G.8.5	Wakeup data send operation .....	89
G.8.6	Wakeup timeout operation .....	90
G.9	Probe .....	90
G.9.1	Probe send operation .....	91
G.10	Probe ACK receive operation .....	91
G.10.1	Probe receive operation .....	91
G.10.2	Probe timeout operation .....	92