ISO/IEC 30190:2013-07 (E)

Information technology - Digitally recorded media for informatio n interchange and storage - 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk

Contents

Page

Foreword xi

Introduction xii

1 Scope 1

2 Conformance 2
2.1 Optical disk 2
2.2 Generating system 2
2.3 Receiving system 2
2.4 Compatibility statement 2

3 Normative references 2

4 Terms and definitions 3

5 Conventions and notations 7
5.1 Terminology: 7
5.1.1 Meaning of words 7
5.1.2 Levels of grouping 7
5.2 Representation of numbers 7
5.3 Integer calculus 8
5.4 Names 8

6 List of acronyms 9

7 General description of disk 11

8 General requirements 14
8.1 Environments 14
8.1.1 Test environment 14
8.1.2 Operating environment 14
8.1.3 Storage environment 15
8.1.4 Transportation 16
8.2 Safety requirements 16
8.3 Flammability 16

9 Reference drive 16
9.1 General 16
9.2 Measurement conditions 16
9.3 Optical system 17
9.4 Optical beam 18
9.5 HF read channel 18
9.6 Radial PP read channel 18
9.7 Disk Clamping 19
9.8 Rotation of disk and Measurement Velocity 19
9.9 Normalized servo transfer function 20
9.10 Measurement Velocities and Reference servos for axial tracking 20
9.10.1 General 20

9.10.2 Reference servo for axial tracking for 1x Measurement Velocity 21
9.10.3 Reference servo for axial tracking for 2x Measurement Velocity and 3x Measurement Velocity 22
9.11 Measurement Velocities and Reference servos for radial tracking 23
9.11.1 General 23
9.11.2 Reference servo for radial tracking for 1x Measurement Velocity 23
9.11.3 Reference servo foe radial tracking for 2x Measurement Velocity and 3x Measurement Velocity 24

10 Dimensional characteristics 25
10.1 General 25
10.2 Disk reference planes and reference axis 26
10.3 Overall dimensions 27
10.4 First transition Area 27
10.5 Protection ring 28
10.6 Clamping Zone 28
10.7 Second transition Area 28
10.8 Information Area 28
10.8.1 General 28
10.8.2 Subdivision of Information Zone on SL disks 29
10.8.3 Subdivision of Information Zone on DL disks 29
10.9 Rim Area 30

11 Mechanical characteristics 31
11.1 Mass 31
11.2 Moment of inertia 31
11.3 Dynamic imbalance 31
11.4 Axial runout 31
11.4.1 General 31
11.4.2 Residual axial tracking error for 1x Measurement Velocity 31
11.4.3 Residual axial tracking error for 2x Measurement Velocity 32
11.4.4 Residual axial tracking error for 3x Measurement Velocity 32
11.5 Radial runout 33
11.5.1 General 33
11.5.2 Residual radial tracking error for 1x Measurement Velocity on SL disks 33
11.5.3 Residual radial tracking error for 1x Measurement Velocity on DL disks 33
11.5.4 Residual radial tracking error for 2x Measurement Velocity on SL and DL disks 34
11.5.5 Residual radial tracking error for 3x Measurement Velocity on SL and DL disks 34
11.6 Durability of Cover Layer 34
11.6.1 Impact resistance of Cover Layer 34
11.6.2 Scratch resistance of Cover Layer 34
11.6.3 Repulsion of fingerprints by Cover Layer 35

12 Optical characteristics in Information Area 35
12.1 General 35
12.2 Refractive index of Transmission Stacks (TS) 35
12.3 Thickness of Transmission Stacks (TS) 35
12.3.1 Thickness of Transmission Stack of SL disks 35
12.3.2 Thickness of Transmission Stacks of DL disks 35
12.4 Reflectivity 37
12.4.1 Reflectivity of Recording Layer of SL disks 37
12.4.2 Reflectivity of Recording Layers of DL disks 37
12.5 Birefringence 37
12.6 Angular deviation 38

13 Data Format 39
13.1 General 39
13.2 Data Frame 41
13.3 Error-Detection Code (EDC) 41
13.4 Scrambled Data Frame 42
13.5 Data Block 43
13.6 LDC Block 44

13.7 LDC code words 44
13.8 LDC Cluster 45
13.8.1 General 45
13.8.2 First interleaving step 45
13.8.3 Second interleaving step 45
13.9 Addressing and Control Data 47
13.9.1 General 47
13.9.2 Address Units 47
13.9.3 User-Control Data 50
13.9.4 Byte/Bit assignment for User-Control Data 50
13.10 Access Block 52
13.11 BIS Block 52
13.12 BIS code words 53
13.13 BIS Cluster 53
13.14 ECC Cluster 58
13.15 Recording Frames 59
13.16 Physical Cluster 59
13.17 17PP modulation for Recordable data 60
13.17.1 General 60
13.17.2 Bit conversion rules 60
13.17.3 dc-control procedure 61
13.17.4 Frame Sync 61
13.18 Modulation and NRZI conversion 62

14 Physical Data Allocating and Linking 63
14.1 General 63
14.2 Recording-Unit Block (RUB) 63
14.2.1 General 63
14.2.2 Data Run-in 64
14.2.3 Data Run-out 65
14.2.4 Guard_3 field 66
14.3 Locating data relative to wobble addresses 66

15 Track format 67
15.1 General 67
15.2 Track shape 67
15.3 Track path 68
15.4 Track Pitch 69
15.4.1 Track Pitch in BCA Zone 69
15.4.2 Track Pitch in Embossed HFM Area 69
15.4.3 Track Pitch in Recordable Area(s) 69
15.4.4 Track Pitch between Embossed HFM Area and Recordable Area 69
15.5 Track layout of HFM Groove 69
15.5.1 General 69
15.5.2 Data Format 70
15.5.3 Addressing and Control Data 71
15.5.4 Recording Frames 75
15.6 Track layout of Wobbled Groove(s) 77
15.6.1 General 77
15.6.2 Modulation of wobbles 77
15.6.3 Wobble polarity 79
15.7 ADIP information 79
15.7.1 General 79
15.7.2 ADIP-Unit Types 79
15.7.3 ADIP word structure 80
15.7.4 ADIP data structure 82
15.7.5 ADIP error correction 84
15.8 Disk Information in ADIP Aux Frame 86
15.8.1 General 86
15.8.2 Error protection for Disk-Information Aux Frames 86
15.8.3 Disk-Information data structure 87

16 General description of Information Zone 127
16.1 General 127
16.2 Format of Information Zone on Single-Layer disk 127
16.3 Format of Information Zone on Dual-Layer disk 127

17 Layout of Recordable Area of Information Zone 127

18 Inner Zone 131
18.1 General 131
18.2 Permanent Information & Control data (PIC) Zone 133
18.2.1 General 133
18.2.2 Content of PIC Zone 133
18.2.3 Emergency Brake 135
18.3 Recordable Area of Inner Zone 0 136
18.3.1 Protection-Zone 2 136
18.3.2 INFO 2 / Reserved 8 137
18.3.3 INFO 2 / Reserved 7 137
18.3.4 INFO 2 / Reserved 6 137
18.3.5 INFO 2 / Reserved 5 137
18.3.6 INFO 2 / PAC 2 137
18.3.7 INFO 2 / DMA 2 137
18.3.8 INFO 2 / Control Data 2 137
18.3.9 INFO 2 / Buffer 2 137
18.3.10 OPC 0 / Test Zone 137
18.3.11 Usage of OPC Areas 137
18.3.12 OPC 0 / OPC 0 Buffer 139
18.3.13 TDMA 0 139
18.3.14 INFO 1 / Pre-write Area 139
18.3.15 INFO 1 / Drive Area 139
18.3.16 INFO 1 / DMA 1 140
18.3.17 INFO 1 / Control Data 1 140
18.3.18 INFO 1 / PAC 1 140
18.4 Recordable Area of Inner Zone 1 141
18.4.1 Buffer 141
18.4.2 OPC 1 141
18.4.3 Buffer 141
18.4.4 INFO 2 / Reserved 8 141
18.4.5 INFO 2 / Reserved 7 141
18.4.6 INFO 2 / Reserved 6 141
18.4.7 INFO 2 / Reserved 5 141
18.4.8 INFO 2 / PAC 2 141
18.4.9 INFO 2 / DMA 2 141
18.4.10 INFO 2 / Control Data 2 141
18.4.11 INFO 2 / Buffer 2 142
18.4.12 TDMA 1 142
18.4.13 Reserved 142
18.4.14 INFO 1 / Pre-write Area 142
18.4.15 INFO 1 / Drive Area 142
18.4.16 INFO 1 / DMA 1 142
18.4.17 INFO 1 / Control Data 1 142
18.4.18 INFO 1 / PAC 1 142

19 Data Zone 142

20 Outer Zone(s) 143
20.1 General 143
20.2 Recordable Area of Outer Zone(s) 143
20.2.1 INFO 3 / Buffer 4 143
20.2.2 INFO 3 / DMA 3 143
20.2.3 INFO 3 / Control Data 3 144
20.2.4 Angular buffer 144
20.2.5 INFO 4 / DMA 4 144

20.2.6 INFO 4 / Control Data 4 144
20.2.7 INFO 4 / Buffer 6 144
20.2.8 DCZ 0 / Test Zone and DCZ 1 / Test Zone 144
20.2.9 Usage of DCZ Area 144
20.2.10 Protection-Zone 3 146

21 Physical-Access Control Clusters 147
21.1 General 147
21.2 Layout of PAC Zones 147
21.3 General structure of PAC Clusters 148
21.4 IS1 and IS2 PAC Clusters 151

22 Disk Management 152
22.1 General 152
22.2 Recording Management 152
22.2.1 Sequential-Recording Mode (SRM) 152
22.2.2 Recording User Data in SRR 152
22.2.3 SRR status 153
22.2.4 Closing SRR 153
22.3 Temporary Disk-Management Areas (TDMA) 153
22.3.1 General 153
22.3.2 TDMA Access indicators 153
22.4 Disk-Management Structure (DMS) 154
22.4.1 General 154
22.4.2 Temporary Disk-Management Structure (TDMS) 154
22.4.3 TDMS in Sequential-Recording Mode 155
22.4.4 Temporary Disk-Definition Structure (TDDS) 155
22.4.5 Temporary Defect List (TDFL) 160
22.4.6 Sequential-Recording Range Information (SRRI) 161
22.5 Unrecorded (blank) disk structure 163
22.5.1 General 163
22.5.2 Pre-recorded Areas on Unrecorded disk 163
22.5.3 Pre-recorded BCA 165
22.5.4 Pre-recorded INFO 2 / Reserved 5, Reserved 8 and Pre-recorded INFO 1 / Pre-write Area 165
22.5.5 Pre-recorded INFO 1 / PAC 1 and Pre-recorded INFO 2 / PAC 2 165
22.5.6 OPC 0 / Test Zone and OPC 1 / Test Zone 165
22.5.7 TDMA 0 165
22.5.8 Initialization of disk 166
22.6 Recorded (Closed) disk structure 166
22.6.1 General 166
22.6.2 DMA Zones 166
22.6.3 Disk-Management Structures (DMS) 167

23 Assignment of Logical-Sector Numbers (LSNs) 169

24 Characteristics of Grooved Areas 170

25 Method of testing for Grooved Area 171
25.1 General 171
25.2 Environment 171
25.3 Reference drive 171
25.3.1 General 171
25.3.2 Read power 171
25.3.3 Read channels 171
25.3.4 Tracking requirements 171
25.3.5 Scanning velocities 171
25.4 Definition of signals 172

26 Signals from HFM Groove 174
26.1 Push-Pull polarity 174
26.2 Push-Pull signal 174
26.3 Wobble signal 174

26.4 Jitter of HFM signal 174

27 Signals from Wobbled Groove(s) 175
27.1 Phase depth 175
27.2 Push-Pull signal 175
27.3 Wobble signal 175
27.3.1 General 175
27.3.2 Measurement of NWS 176
27.3.3 Measurement of wobble CNR 176
27.3.4 Measurement of harmonic distortion of wobble 176
27.4 HFM and Wobbled Groove transition requirements 176

28 Characteristics of Recording Layer 177

29 Method of testing for Recording Layer 178
29.1 General 178
29.2 Environment 178
29.3 Reference drive 178
29.3.1 General 178
29.3.2 Read power 178
29.3.3 Read channels 178
29.3.4 Tracking requirements 178
29.3.5 Scanning velocities 178
29.4 Write conditions 179
29.4.1 Write-pulse waveform 179
29.4.2 Write powers 180
29.4.3 Write conditions for jitter measurement 180
29.5 Definition of signals 180

30 Signals from Recorded Areas 181
30.1 HF signals 181
30.2 Modulated amplitude 181
30.3 Reflectivity-Modulation product 182
30.4 Asymmetry 182
30.5 Jitter 182
30.6 Read stability 183

31 Local defects 184

32 Characteristics of User Data 184

33 Method of testing for User Data 185
33.1 General 185
33.2 Environment 185
33.3 Reference drive 185
33.3.1 General 185
33.3.2 Read power 185
33.3.3 Read channels 185
33.3.4 Error correction 185
33.3.5 Tracking requirements 185
33.3.6 Scanning velocities 185
33.4 Definition of signals 186

34 Minimum quality of recorded information 187
34.1 Symbol Error Rate 187
34.2 Maximum burst errors 187
34.3 User-written Data 187

35 BCA 188

Annex A (normative) Thickness of Transmission Stacks in case of multiple layers 189

A.1 General 189
A.2 Refractive Index ni of all layers in Cover and Spacer Layers 189
A.3 Thickness variation of Transmission Stack 189
A.4 Example of thickness calculation for SL 189

Annex B (normative) Measurement of reflectivity 190

B.1 General 190
B.2 Calibration method 190
B.3 Measuring method 191

Annex C (normative) Measurement of scratch resistance of Cover Layer 192

C.1 General 192
C.2 Taber Abrasion test 192

Annex D (normative) Measurement of repulsion of grime by Cover Layer 194

D.1 General 194
D.2 Specifications of stamp 194
D.3 Preparation of ink 195
D.4 Preparation of ink pad 195
D.5 Using ink pad and stamp 196

Annex E (normative) Measurement of wobble amplitude 197

E.1 Measurement methods 197
E.2 Calibration of filters 201

Annex F (normative) Write-pulse waveform for testing 202

F.1 General write-pulse waveform 202
F.2 N-1 write strategy 203
F.3 N/2 write strategy 206
F.4 Castle write strategy 209
F.5 Definition of pulse widths and rise and fall times 213

Annex G (normative) Optimum Power Control(OPC) procedure for media 214

G.1 General 214
G.2 Mathematical model for modulation versus power function 214
G.3 Procedure for determination of OPC parameters for media 216
G.4 Procedure to determine Beta value 216

Annex H (normative) HF signal pre-processing for jitter measurements 218

H.1 General 218
H.2 General implementation of equalizer 218
H.3 Conventional Equalizer circuit 219
H.4 Limit Equalizer circuit 220
H.5 Specifications of supporting circuits 221
H.5.1 Amplifiers and filters 221
H.5.2 Open-loop transfer function for PLL 222
H.5.3 Slicer 223
H.6 Condition for measurement 223
H.7 Jitter measurement 224

Annex I (normative) Measurement procedure 225

I.1 General 225
I.2 Initial adjustments of Reference drive 225
I.3 Jitter measurement 225

I.4 Modulated amplitude measurements 226
I.5 Measurements of Resolution I2pp / I8pp and I3pp / I8pp 226
I.5.1 Method for measuring I2pp and I8pp 226
I.5.2 I3pp / I8pp, I8pp / I8H and asymmetry measurement procedure 227
I.6 Tracking-error signal measurements (PPnorm measurement procedure) 228
I.7 Residual error of axial tracking measurement procedure 229
I.8 Residual error of radial tracking measurement procedure 230
I.9 Random SER measurement 231

Annex J (informative) Measurement of birefringence 232

J.1 Principle of measurement 232
J.2 Measurements conditions 232
J.3 Example of measurement procedure 233
J.4 Interchangeability of measuring results 233

Annex K (informative) Measurement of thickness of Cover Layer and Spacer Layer 234

K.1 Focusing method 234
K.2 Interferometer method 235

Annex L (informative) Measurement of impact resistance of Cover Layer 237

L.1 General 237
L.2 Recommendation for drives 237
L.3 Measurements of impact resistance of Cover Layer 237

Annex M (informative) Groove deviation and wobble amplitude 239

M.1 Relation between normalized wobble signal and wobble amplitude 239
M.2 Tolerance of normalized wobble signal 239

Bibliography 241