

ISO/IEC 24730-61:2013-08 (E)

Information technology - Real time locating systems (RTLS) - Part 61: Low rate pulse repetition frequency Ultra Wide Band (UWB) air interface

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Symbols (and abbreviated terms)	2
4	General description	3
4.1	Introduction	3
4.3	Architecture	4
4.4	Functional overview	5
4.4.1	Data transfer from tag to infrastructure reader	5
4.4.2	Frame structure	5
4.4.3	Data verification	5
4.4.4	Overview of UWB options	6
5	PHY specification	6
5.1	General requirements and definitions	6
5.2	Modulation and data rates	6
5.3	LRP UWB PHY channel numbering	7
5.4	LRP UWB PHY symbol structure	7
5.4.1	Base mode OOK PHY symbol structure	8
5.4.2	Extended mode OOK PHY symbol structure	8
5.4.3	Long range mode PPM PHY symbol structure	10
5.4.4	LRP UWB SHR	11
5.4.5	LRP UWB PHY header (PHR)	12
5.4.6	LRP UWB data field	14
5.4.7	LRP UWB location enhancing information postamble	14
5.4.8	LRP UWB transmitter specification	15
5.4.9	LRP UWB reader specification	16
6	Tag management layer	16
6.1	Overview	17
6.2	Frame control	17
6.2.1	Frame type	17
6.2.2	Long frame control	17
6.2.3	Destination address mode	18
6.2.4	Source address mode	18
6.3	Sequence number	18
6.4	Tag ID (EUI-64)	18
6.5	Encoding header	18
6.6.1	Allocation class	19
6.6.2	Manufacturer ID	20
6.6.3	Tag ID	20
6.7	Temperature sensor data	20
6.8	Optional extended ID	20

6.8.1	Ex-ID source	20
6.8.2	Ex-ID length	20
6.8.3	ExID	21
6.9	Optional extended data	21
6.10	Frame check sequence	21
Bibliography		33