

ISO/IEC 24730-62:2013-09 (E)

Information technology - Real time locating systems (RTLS) - Part 62: High rate pulse repetition frequency Ultra Wide Band (UWB) air interface

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Abbreviated terms	3
4	Overview	4
4.1	Components	4
4.2	Not covered by the standard	5
4.3	System	5
4.4	Document structure	5
5	Physical (PHY) layer specification	5
5.1	General	5
5.2	Default operating mode for a HRP UWB tag	6
5.3	PPDU format	7
5.3.1	PPDU encoding process	7
5.3.2	Symbol structure	9
5.3.3	PSDU timing parameters	10
5.3.4	Preamble timing parameters	12
5.3.5	SHR preamble	13
5.3.6	PHY header (PHR)	16
5.3.7	Data field	18
5.4	UWB PHY modulation	19
5.4.1	Modulation mathematical framework	19
5.4.2	Spreading	19
5.4.3	Forward error correction (FEC)	21
5.5	UWB PHY RF requirements	23
5.5.1	Operating frequency bands	23
5.5.2	Channel assignments	23
5.5.3	Transmitter specification	23
5.6	Timestamps and time units	26
5.6.1	Time units	26
5.6.2	Antenna delays	26
6	Basic message format	26
6.1	Message structure and processing rules	26
6.1.1	Time of arrival / Time of sending	27
6.2	Frame Check Sequence (FCS)	27
7	One-way communication - blink message	28
7.1.1	Sub-fields of the blink frame with ISO ID	29
7.2	Encoding of blink frames with IEEE EUI-64 tag ID	31
7.2.1	Sub-fields of the blink frame with IEEE ID	31

8	Two-way communication - data messages	35
8.1	Data Messages	35
8.1.1	Data frame sub-fields	35
8.2	Operation of two-way communication	36
8.2.1	The mechanics of two-way Communication	37
8.2.2	Activity Control	38
8.2.3	Read Tag Capabilities	39
8.2.4	Read Tag Configuration	40
8.2.5	Set Tag Configuration	42
8.2.6	Perform two-way ranging	43
	Bibliography	57