ISO/IEC 24730-62:2013-09 (E)

Information technology - Real time locating systems (RTLS) - Part 62: High rate pulse repetition frequenc y Ultra Wide Band (UWB) air interface

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, and abbreviated terms 2
3.1 Terms and definitions 2
3.2 Abbreviated terms 3

4 Overview 4
4.1 Components 4
4.2 Not covered by the standard 5
4.3 System 5
4.4 Document structure 5

5 Physical (PHY) layer specification 5
5.1 General 5
5.2 Default operating mode for a HRP UWB tag 6
5.3 PPDU format 7
5.3.1 PPDU encoding process 7
5.3.2 Symbol structure 9
5.3.3 PSDU timing parameters 10
5.3.4 Preamble timing parameters 12
5.3.5 SHR preamble 13
5.3.6 PHY header (PHR) 16
5.3.7 Data field 18
5.4 UWB PHY modulation 19
5.4.1 Modulation mathematical framework 19
5.4.2 Spreading 19
5.4.3 Forward error correction (FEC) 21
5.5 UWB PHY RF requirements 23
5.5.1 Operating frequency bands 23
5.5.2 Channel assignments 23
5.5.3 Transmitter specification 23
5.6 Timestamps and time units 26
5.6.1 Time units 26
5.6.2 Antenna delays 26

6 Basic message format 26
6.1 Message structure and processing rules 26
6.1.1 Time of arrival / Time of sending 27
6.2 Frame Check Sequence (FCS) 27

7 One-way communication - blink message 28
7.1.1 Sub-fields of the blink frame with ISO ID 29
7.2 Encoding of blink frames with IEEE EUI-64 tag ID 31
7.2.1 Sub-fields of the blink frame with IEEE ID 31

8 Two-way communication - data messages 35
8.1 Data Messages 35
8.1.1 Data frame sub-fields 35
8.2 Operation of two-way communication 36
8.2.1 The mechanics of two-way Communication 37
8.2.2 Activity Control 38
8.2.3 Read Tag Capabilities 39
8.2.4 Read Tag Configuration 40
8.2.5 Set Tag Configuration 42
8.2.6 Perform two-way ranging 43

Bibliography 57