ISO/IEC/IEEE 8802-1AS:2014-02 (E)

Information technology - Te lecommunications and information exchange between systems - Local and metropolitan area networks - Part 1AS: Timing and synchronization for time-sensitive applications in bridged local area networks

Contents

Page

1. Overview ... 1
   1.1 Scope ... 1
   1.2 Purpose ... 2

2. Normative references ... 3

3. Definitions ... 5

4. Acronyms and abbreviations ... 9

5. Conformance ... 11
   5.1 Requirements terminology ... 11
   5.2 Protocol Implementation Conformance Statement (PICS) ... 11
   5.3 Time-aware Bridge and end station requirements ... 11
   5.4 MAC-specific timing and synchronization methods for IEEE 802.3 full-duplex links ... 12
   5.5 MAC-specific timing and synchronization methods for IEEE Std 802.11-2007 ... 12
   5.6 MAC-specific timing and synchronization methods for IEEE 802.3 EPON ... 12
   5.7 MAC-specific timing and synchronization methods for coordinated shared network (CSN) ... 13

6. Conventions ... 15
   6.1 General ... 15
   6.2 Service specification method and notation ... 15
   6.3 Data types and on-the-wire formats ... 15

7. Time synchronization model for a bridged local area network ... 19
   7.1 General ... 19
   7.2 Architecture of a time-aware bridged local area network ... 19
   7.3 Time synchronization ... 21
   7.4 Time-aware system architecture ... 24
   7.5 Differences between gPTP and PTP ... 25

8. IEEE 802.1AS concepts and terminology ... 27
   8.1 gPTP domain ... 27
   8.2 Timescale ... 27
   8.3 Communication path asymmetry ... 28
   8.4 Messages ... 29
   8.5 Ports ... 30
   8.6 Time-aware system characterization ... 32

9. Application interfaces ... 37
   9.1 Overview of the interfaces ... 37
   9.2 ClockSourceTime interface ... 38
   9.3 ClockTargetEventCapture interface ... 38
   9.4 ClockTargetTriggerGenerate interface ... 39
   9.5 ClockTargetClockGenerator interface ... 40
   9.6 ClockTargetPhaseDiscontinuity interface ... 41

10. Media-independent layer specification 43
10.1 Overview 43
10.2 Time-synchronization state machines 44
10.3 Best master clock selection and announce interval setting state machines 67
10.4 Message attributes 85
10.5 Message formats 87
10.6 Protocol timing characterization 95

11. Media-dependent layer specification for full-duplex, point-to-point links 99
11.1 Overview 99
11.2 State machines for MD entity specific to full-duplex, point-to-point links 105
11.3 Message attributes 122
11.4 Message formats 124
11.5 Protocol timing characterization 131

12. Media-dependent layer specification for IEEE 802.11 links 133
12.1 Overview 133
12.2 Messages 135
12.3 Determination of asCapable 135
12.4 State machines 136
12.5 Format of VendorSpecific information element 143
12.6 Synchronization message interval 144

13. Media-dependent layer specification for interface to IEEE 802.3 Ethernet passive optical network link 145
13.1 Overview 145
13.2 Message attributes 149
13.3 Message format 149
13.4 Determination of asCapable 151
13.5 Layering for IEEE 802.3 EPON links 151
13.6 Service interface definitions 152
13.7 MD entity global variables 154
13.8 State machines 154
13.9 Message transmission intervals 158

14. Timing and synchronization management 159
14.1 General 159
14.2 Default Parameter Data Set 159
14.3 Current Parameter Data Set 161
14.4 Parent Parameter Data Set 164
14.5 Time Properties Parameter Data Set 165
14.6 Port Parameter Data Set 166
14.7 Port Parameter Statistics 170
14.8 Acceptable Master Table Parameter Data Set 173

15. Managed object definitions 175
15.1 Internet Standard Management Framework 175
15.2 Structure of the MIB 175
15.3 Security considerations 175
15.4 Textual conventions defined in this MIB 179
15.5 IEEE 802.1AS MIB module 179

Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma 231
A.1 Introduction 231
A.2 Abbreviations and special symbols 231
A.3 Instructions for completing the PICS proforma 232
A.4 PICS proforma for IEEE Std 802.1AS-2011 233
A.5 Major capabilities 235
A.6 Media access control methods 236
A.7 Minimal time-aware system 236
A.8 Signalling 237
A.9 Best master clock 238
A.10 Grandmaster-capable system 239
A.11 Media-independent master 240
A.12 Media-dependent, full-duplex, point-to-point link 241
A.13 Media-dependent IEEE 802.11 link 243
A.14 Media-dependent IEEE 802.3 EPON link 243
A.15 Media-dependent CSN link 244
A.16 Media-dependent MoCA link 244
A.17 Media-dependent ITU-T G.hn link 244

Annex B (normative) Performance requirements 245
B.1 LocalClock requirements 245
B.2 Time-aware system requirements 249
B.3 End-to-end time-synchronization performance 250
B.4 End-to-end jitter and wander performance 250

Annex C (informative) Time-scales and epochs 253
C.1 Overview 253
C.2 TAI and UTC 253
C.3 NTP and GPS 254
C.4 Time-scale conversions 255
C.5 Time zones and GMT 256

Annex D (normative) State diagram notation 257

Annex E (normative) Media-dependent layer specification for CSN Network 259
E.1 Overview 259
E.2 Coordinated Shared Network characteristics 259
E.3 Layering for CSN links 260
E.4 Path delay measurement over a CSN backbone 262
E.5 Synchronization messages 265
E.6 Specific CSN requirements 268
E.7 Grandmaster capability 269
E.8 CSN clock and node requirements 269

Annex F (informative) PTP profile included in this standard 271
F.1 Identification 271
F.2 PTP attribute values 271
F.3 PTP options 271
F.4 LocalClock and time-aware system performance requirements 272

Annex G (informative) Bibliography 273

Annex H (informative) IEEE list of participants 274

List of figures

Figure 7-1—Time-aware network example 20
Figure 7-2—Time-aware network of Figure 7-1 after an access network link failure 21
Figure 7-3— Example delay measurement 22
Figure 7-4—Time-aware system model 24
Figure 8-1—Propagation asymmetry 28
Figure 8-2—Definition of message timestamp point, reference plane, timestamp measurement plane, and latency constants 30
Figure 9-1—Application interfaces 37
Figure 10-1—Model for media-independent layer of time-aware system 44
Figure 10-2—Time-synchronization state machines—overview and interrelationships 46
Figure 10-3—SiteSyncSync state machine 56
Figure 10-4—PortSyncSyncReceive state machine 58
Figure 10-5—ClockMasterSyncSend state machine 60
Figure 10-6—ClockMasterSyncOffset state machine 61
Figure 10-7—ClockMasterSyncReceive state machine 63
Figure 10-8—PortSyncSyncSend state machine 65
Figure 10-9—ClockSlaveSync state machine 67
Figure 10-10—Example master/slave hierarchy of time-aware systems 69
Figure 10-11—Best master clock selection state machines—overview and interrelationships 74
Figure 10-12—PortAnnounceReceive state machine 79
Figure 10-13—PortAnnounceInformation state machine 80
Figure 10-14—PortRoleSelection state machine 83
Figure 10-15—PortAnnounceTransmit state machine 84
Figure 10-16—AnnounceIntervalSetting state machine 85
Figure 11-1—Propagation delay measurement using peer delay mechanism 100
Figure 11-2—Transport of time-synchronization information 102
Figure 11-3—Model for time-aware system with full-duplex, point-to-point links 105
Figure 11-4—Detail of MD entity time-synchronization state machines for full-duplex, point-to-point links 106
Figure 11-5—Peer delay mechanism state machines—overview and interrelationships 106
Figure 11-6—MDSyncReceiveSM state machine 111
Figure 11-7—MDSyncSendSM state machine 114
Figure 11-8—MDPdelayReq state machine 118
Figure 11-9—MDPdelayResp state machine 120
Figure 11-10—LinkDelaySyncIntervalSetting state machine 121
Figure 12-1—Timing measurement procedure for IEEE 802.11 links 134
Figure 12-2—Media-dependent and lower entities in stations with IEEE 802.11 links 135
Figure 12-3—Master state machine 137
Figure 12-4—Slave state machine 141
Figure 12-5—Format of VendorSpecific information element when Type = 0 143
Figure 13-1—IEEE 802.3 EPON time-synchronization interfaces 148
Figure 13-2—IEEE 802.3 EPON interface model 152
Figure 13-3—State machine for IEEE 802.3 EPON requester 156
Figure 13-4—State machine for IEEE 802.3 EPON responder 157
Figure B.1—Wander generation (TDEV) requirement for LocalClock entity 247
Figure B.2—ADEV limit corresponding to wander generation requirement of Figure B.1 248
Figure B.3—PTPDEV limit corresponding to wander generation requirement of Figure B.1 249
Figure B.4—MTIE masks met for maximum endpoint filter bandwidths of Table B.4 251
Figure E.1—Example of CSN backbone in an AVB LAN 260
Figure E.2—Media-dependent and lower entities in CSN nodes 261
Figure E.3—Path types over CSN as IEEE 802.1AS backbone 262
Figure E.4—Propagation delay and residence time over a CSN Backbone 262
Figure E.5—CSN node-to-node path delay measurement 263
Figure E.6—IEEE 802.1AS Sync Message Propagation over the CSN backbone 265

List of tables

Table 6-1—Primitive data types 15
Table 8-1—Illustration of formation of clockIdentity from EUI-48 31
Table 8-2—Default values for priority1, for the respective media 33
Table 8-3—timeSource enumeration 36
Table 10-1—Port role definitions 68
Table 10-2—Destination address for Announce and Signaling messages 86
Table 10-3—Ethertype for Announce and Signaling messages 86
Table 10-4—PTP message header 88
Table 10-5—Values for messageType field 88
Table 10-6—Values of flag bits 89
Table 10-7—Announce message fields 90
Table 10-8—Path trace TLV 91
Table 10-9—Signaling message fields 92
Table 10-10—Message interval request TLV 93
Table 10-11—Interpretation of special values of linkDelayInterval 94
Table 10-12—Interpretation of special values of timeSyncInterval 94
Table 10-14—Definitions of bits of flags field of message interval request TLV 95
Table 10-13—Interpretation of special values of announceInterval 95
Table 11-1—Destination address for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages 123
Table 11-2—Ethertype for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages 123
Table 11-4—Values of flag bits 125
Table 11-3—Values for messageType field 125
Table 11-6—References for sequenceId value exceptions 126
Table 11-7—Value of control field 126
Table 11-5—Value of correction field 126
Table 11-8—Sync message fields 127
Table 11-9—Follow_Up message fields 127
Table 11-10—Follow_Up information TLV 128
Table 11-11—Pdelay_Req message fields 129
Table 11-12—Pdelay_Resp message fields 130
Table 11-13—Pdelay_Resp_Follow_Up message fields 130
Table 12-1—Parameters of MLME-TIMINGMSMT.request 139
Table 12-2—Parameters of MLME-TIMINGMSMST.confirm 140
Table 12-3—Parameters of MLME-TIMINGMSMT.indication 143
Table 12-4—Values of the Type field in the VendorSpecific information element 144
Table 13-1—TIMESYNC message fields 150
Table 14-1—Default Parameter Data Set Table 162
Table 14-2—Current Parameter Data Set Table 163
Table 14-3—Parent Parameter Data Set Table 165
Table 14-4—Time Properties Parameter Data Set Table 166
Table 14-5—portRole enumeration 167
Table 14-6—Port Parameter Data Set Table 170
Table 14-7—Port Parameter Statistics Table 173
Table 14-8—Acceptable Master Table Parameter Data Set Table 174
Table 15-1—IEEE8021-AS MIB structure and object cross reference 177
Table B.1—Wander generation TDEV requirement for LocalClock entity 246
Table B.2—ADEV limit corresponding to wander generation requirement of Table B.1 247
Table B.3—PTPDEV limit corresponding to wander generation requirement of Table B.1 248
Table B.4—Maximum endpoint filter bandwidths needed to meet respective MTIE masks and peak-to-peak jitter limits 250
Table B.5—Breakpoints for Mask 1 251
Table B.6—Breakpoints for Mask 2 251
Table B.7—Breakpoints for Mask 3 251
Table C.1—Time-scale parameters 253
Table C.2—Time-scale conversions 255
Table D.1—State machine symbols 258
Table E.1—CSN TLV 267
Table E.2—Definitions and option selections per link technology 268