

ISO/IEC/IEEE 8802-1AS:2014-02 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Part 1AS: Timing and synchronization for time-sensitive applications in bridged local area networks

| Contents | Page |
|---|------|
| 1. Overview..... | 1 |
| 1.1 Scope..... | 1 |
| 1.2 Purpose..... | 2 |
| 2. Normative references..... | 3 |
| 3. Definitions..... | 5 |
| 4. Acronyms and abbreviations..... | 9 |
| 5. Conformance..... | 11 |
| 5.1 Requirements terminology..... | 11 |
| 5.2 Protocol Implementation Conformance Statement (PICS)..... | 11 |
| 5.3 Time-aware Bridge and end station requirements..... | 11 |
| 5.4 MAC-specific timing and synchronization methods for IEEE 802.3 full-duplex links..... | 12 |
| 5.5 MAC-specific timing and synchronization methods for IEEE Std 802.11-2007..... | 12 |
| 5.6 MAC-specific timing and synchronization methods for IEEE 802.3 EPON..... | 12 |
| 5.7 MAC-specific timing and synchronization methods for coordinated shared network (CSN)..... | 13 |
| 6. Conventions..... | 15 |
| 6.1 General..... | 15 |
| 6.2 Service specification method and notation..... | 15 |
| 6.3 Data types and on-the-wire formats..... | 15 |
| 7. Time synchronization model for a bridged local area network..... | 19 |
| 7.1 General..... | 19 |
| 7.2 Architecture of a time-aware bridged local area network..... | 19 |
| 7.3 Time synchronization..... | 21 |
| 7.4 Time-aware system architecture..... | 24 |
| 7.5 Differences between gPTP and PTP..... | 25 |
| 8. IEEE 802.1AS concepts and terminology..... | 27 |
| 8.1 gPTP domain..... | 27 |
| 8.2 Timescale..... | 27 |
| 8.3 Communication path asymmetry..... | 28 |
| 8.4 Messages..... | 29 |
| 8.5 Ports..... | 30 |
| 8.6 Time-aware system characterization..... | 32 |
| 9. Application interfaces..... | 37 |
| 9.1 Overview of the interfaces..... | 37 |
| 9.2 ClockSourceTime interface..... | 38 |
| 9.3 ClockTargetEventCapture interface..... | 38 |
| 9.4 ClockTargetTriggerGenerate interface..... | 39 |
| 9.5 ClockTargetClockGenerator interface..... | 40 |
| 9.6 ClockTargetPhaseDiscontinuity interface..... | 41 |

| | | |
|-----|---|-----|
| 10. | Media-independent layer specification | 43 |
| | 10.1 Overview | 43 |
| | 10.2 Time-synchronization state machines | 44 |
| | 10.3 Best master clock selection and announce interval setting state machines | 67 |
| | 10.4 Message attributes | 85 |
| | 10.5 Message formats | 87 |
| | 10.6 Protocol timing characterization | 95 |
| 11. | Media-dependent layer specification for full-duplex, point-to-point links | 99 |
| | 11.1 Overview | 99 |
| | 11.2 State machines for MD entity specific to full-duplex, point-to-point links | 105 |
| | 11.3 Message attributes | 122 |
| | 11.4 Message formats | 124 |
| | 11.5 Protocol timing characterization | 131 |
| 12. | Media-dependent layer specification for IEEE 802.11 links | 133 |
| | 12.1 Overview | 133 |
| | 12.2 Messages | 135 |
| | 12.3 Determination of asCapable | 135 |
| | 12.4 State machines | 136 |
| | 12.5 Format of VendorSpecific information element | 143 |
| | 12.6 Synchronization message interval | 144 |
| 13. | Media-dependent layer specification for interface to IEEE 802.3 Ethernet passive optical network link | 145 |
| | 13.1 Overview | 145 |
| | 13.2 Message attributes | 149 |
| | 13.3 Message format | 149 |
| | 13.4 Determination of asCapable | 151 |
| | 13.5 Layering for IEEE 802.3 EPON links | 151 |
| | 13.6 Service interface definitions | 152 |
| | 13.7 MD entity global variables | 154 |
| | 13.8 State machines | 154 |
| | 13.9 Message transmission intervals | 158 |
| 14. | Timing and synchronization management | 159 |
| | 14.1 General | 159 |
| | 14.2 Default Parameter Data Set | 159 |
| | 14.3 Current Parameter Data Set | 161 |
| | 14.4 Parent Parameter Data Set | 164 |
| | 14.5 Time Properties Parameter Data Set | 165 |
| | 14.6 Port Parameter Data Set | 166 |
| | 14.7 Port Parameter Statistics | 170 |
| | 14.8 Acceptable Master Table Parameter Data Set | 173 |
| 15. | Managed object definitions | 175 |
| | 15.1 Internet Standard Management Framework | 175 |
| | 15.2 Structure of the MIB | 175 |
| | 15.3 Security considerations | 175 |
| | 15.4 Textual conventions defined in this MIB | 179 |
| | 15.5 IEEE 802.1AS MIB module | 179 |

| | |
|---|---------|
| Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma | 231 |
| A.1 Introduction..... | 231 |
| A.2 Abbreviations and special symbols..... | 231 |
| A.3 Instructions for completing the PICS proforma..... | 232 |
| A.4 PICS proforma for IEEE Std 802.1AS-2011 | 233 |
| A.5 Major capabilities | 235 |
| A.6 Media access control methods | 236 |
| A.7 Minimal time-aware system..... | 236 |
| A.8 Signalling..... | 237 |
| A.9 Best master clock | 238 |
| A.10 Grandmaster-capable system | 239 |
| A.11 Media-independent master | 240 |
| A.12 Media-dependent, full-duplex, point-to-point link..... | 241 |
| A.13 Media-dependent IEEE 802.11 link..... | 243 |
| A.14 Media-dependent IEEE 802.3 EPON link | 243 |
| A.15 Media-dependent CSN link..... | 244 |
| A.16 Media-dependent MoCA link | 244 |
| A.17 Media-dependent ITU-T G.hn link | 244 |
| Annex B (normative) Performance requirements..... | 245 |
| B.1 LocalClock requirements..... | 245 |
| B.2 Time-aware system requirements | 249 |
| B.3 End-to-end time-synchronization performance | 250 |
| B.4 End-to-end jitter and wander performance | 250 |
| Annex C (informative) Time-scales and epochs..... | 253 |
| C.1 Overview..... | 253 |
| C.2 TAI and UTC..... | 253 |
| C.3 NTP and GPS..... | 254 |
| C.4 Time-scale conversions..... | 255 |
| C.5 Time zones and GMT | 256 |
| Annex D (normative) State diagram notation..... | 257 |
| Annex E (normative) Media-dependent layer specification for CSN Network..... | 259 |
| E.1 Overview..... | 259 |
| E.2 Coordinated Shared Network characteristics..... | 259 |
| E.3 Layering for CSN links..... | 260 |
| E.4 Path delay measurement over a CSN backbone | 262 |
| E.5 Synchronization messages | 265 |
| E.6 Specific CSN requirements..... | 268 |
| E.7 Grandmaster capability | 269 |
| E.8 CSN clock and node requirements..... | 269 |
| Annex F (informative) PTP profile included in this standard | 271 |
| F.1 Identification..... | 271 |
| F.2 PTP attribute values | 271 |
| F.3 PTP options..... | 271 |
| F.4 LocalClock and time-aware system performance requirements..... | 272 |
| Annex G (informative) Bibliography | 273 |
| Annex J (informative) IEEE Std 802.1AS-2011 CPU | 276 |

List of figures

| | |
|--|-----|
| Figure 7-1—Time-aware network example..... | 20 |
| Figure 7-2—Time-aware network of Figure 7-1 after an access network link failure | 21 |
| Figure 7-3— Example delay measurement | 22 |
| Figure 7-4—Time-aware system model | 24 |
| Figure 8-1—Propagation asymmetry..... | 28 |
| Figure 8-2—Definition of message timestamp point, reference plane, timestamp measurement plane, and latency constants | 30 |
| Figure 9-1—Application interfaces | 37 |
| Figure 10-1—Model for media-independent layer of time-aware system..... | 44 |
| Figure 10-2—Time-synchronization state machines—overview and interrelationships..... | 46 |
| Figure 10-3—SiteSyncSync state machine..... | 56 |
| Figure 10-4—PortSyncSyncReceive state machine | 58 |
| Figure 10-5—ClockMasterSyncSend state machine | 60 |
| Figure 10-6—ClockMasterSyncOffset state machine | 61 |
| Figure 10-7—ClockMasterSyncReceive state machine | 63 |
| Figure 10-8—PortSyncSyncSend state machine | 65 |
| Figure 10-9—ClockSlaveSync state machine | 67 |
| Figure 10-10—Example master/slave hierarchy of time-aware systems | 69 |
| Figure 10-11—Best master clock selection state machines—overview and interrelationships | 74 |
| Figure 10-12—PortAnnounceReceive state machine..... | 79 |
| Figure 10-13—PortAnnounceInformation state machine..... | 80 |
| Figure 10-14—PortRoleSelection state machine..... | 83 |
| Figure 10-15—PortAnnounceTransmit state machine | 84 |
| Figure 10-16—AnnounceIntervalSetting state machine..... | 85 |
| Figure 11-1—Propagation delay measurement using peer delay mechanism | 100 |
| Figure 11-2—Transport of time-synchronization information..... | 102 |
| Figure 11-3—Model for time-aware system with full-duplex, point-to-point links..... | 105 |
| Figure 11-4—Detail of MD entity time-synchronization state machines for full-duplex, point-to-point links | 106 |
| Figure 11-5—Peer delay mechanism state machines—overview and interrelationships..... | 106 |
| Figure 11-6—MDSyncReceiveSM state machine..... | 111 |
| Figure 11-7—MDSyncSendSM state machine..... | 114 |
| Figure 11-8—MDPdelayReq state machine | 118 |
| Figure 11-9—MDPdelayResp state machine | 120 |
| Figure 11-10—LinkDelaySyncIntervalSetting state machine..... | 121 |
| Figure 12-1—Timing measurement procedure for IEEE 802.11 links | 134 |
| Figure 12-2—Media-dependent and lower entities in stations with IEEE 802.11 links | 135 |
| Figure 12-3—Master state machine..... | 137 |
| Figure 12-4—Slave state machine | 141 |
| Figure 12-5—Format of VendorSpecific information element when Type = 0 | 143 |
| Figure 13-1—IEEE 802.3 EPON time-synchronization interfaces | 148 |
| Figure 13-2—IEEE 802.3 EPON interface model..... | 152 |
| Figure 13-3—State machine for IEEE 802.3 EPON requester..... | 156 |
| Figure 13-4—State machine for IEEE 802.3 EPON responder..... | 157 |
| Figure B.1—Wander generation (TDEV) requirement for LocalClock entity..... | 247 |
| Figure B.2—ADEV limit corresponding to wander generation requirement of Figure B.1 | 248 |
| Figure B.3—PTPDEV limit corresponding to wander generation requirement of Figure B.1 | 249 |
| Figure B.4—MTIE masks met for maximum endpoint filter bandwidths of Table B.4 | 251 |
| Figure E.1—Example of CSN backbone in an AVB LAN | 260 |
| Figure E.2—Media-dependent and lower entities in CSN nodes | 261 |
| Figure E.3—Path types over CSN as IEEE 802.1AS backbone..... | 262 |
| Figure E.4—Propagation delay and residence time over a CSN Backbone | 262 |
| Figure E.5—CSN node-to-node path delay measurement..... | 263 |
| Figure E.6—IEEE 802.1AS Sync Message Propagation over the CSN backbone | 265 |

List of tables

| | |
|---|-----|
| Table 6-1—Primitive data types | 15 |
| Table 8-1—Illustration of formation of clockIdentity from EUI-48 | 31 |
| Table 8-2—Default values for priority1, for the respective media | 33 |
| Table 8-3—timeSource enumeration | 36 |
| Table 10-1—Port role definitions | 68 |
| Table 10-2—Destination address for Announce and Signaling messages | 86 |
| Table 10-3—Ethertype for Announce and Signaling messages | 86 |
| Table 10-4—PTP message header | 88 |
| Table 10-5—Values for messageType field | 88 |
| Table 10-6—Values of flag bits | 89 |
| Table 10-7—Announce message fields | 90 |
| Table 10-8—Path trace TLV | 91 |
| Table 10-9—Signaling message fields | 92 |
| Table 10-10—Message interval request TLV | 93 |
| Table 10-11—Interpretation of special values of linkDelayInterval | 94 |
| Table 10-12—Interpretation of special values of timeSyncInterval | 94 |
| Table 10-14—Definitions of bits of flags field of message interval request TLV | 95 |
| Table 10-13—Interpretation of special values of announceInterval | 95 |
| Table 11-1—Destination address for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages | 123 |
| Table 11-2—Ethertype for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages | 123 |
| Table 11-4—Values of flag bits | 125 |
| Table 11-3—Values for messageType field | 125 |
| Table 11-6—References for sequenceId value exceptions | 126 |
| Table 11-7—Value of control field | 126 |
| Table 11-5—Value of correction field | 126 |
| Table 11-8—Sync message fields | 127 |
| Table 11-9—Follow_Up message fields | 127 |
| Table 11-10—Follow_Up information TLV | 128 |
| Table 11-11—Pdelay_Req message fields | 129 |
| Table 11-12—Pdelay_Resp message fields | 130 |
| Table 11-13—Pdelay_Resp_Follow_Up message fields | 130 |
| Table 12-1—Parameters of MLME-TIMINGMSMT.request | 139 |
| Table 12-2—Parameters of MLME-TIMINGMSMST.confirm | 140 |
| Table 12-3—Parameters of MLME-TIMINGMSMT.indication | 143 |
| Table 12-4—Values of the Type field in the VendorSpecific information element | 144 |
| Table 13-1—TIMESYNC message fields | 150 |
| Table 14-1—Default Parameter Data Set Table | 162 |
| Table 14-2—Current Parameter Data Set Table | 163 |
| Table 14-3—Parent Parameter Data Set Table | 165 |
| Table 14-4—Time Properties Parameter Data Set Table | 166 |
| Table 14-5—portRole enumeration | 167 |
| Table 14-6—Port Parameter Data Set Table | 170 |
| Table 14-7—Port Parameter Statistics Table | 173 |
| Table 14-8—Acceptable Master Table Parameter Data Set Table | 174 |
| Table 15-1—IEEE8021-AS MIB structure and object cross reference | 177 |
| Table B.1—Wander generation TDEV requirement for LocalClock entity | 246 |
| Table B.2—ADEV limit corresponding to wander generation requirement of Table B.1 | 247 |
| Table B.3—PTPDEV limit corresponding to wander generation requirement of Table B.1 | 248 |
| Table B.4—Maximum endpoint filter bandwidths needed to meet respective MTIE masks and peak-to-peak jitter limits | 250 |
| Table B.5—Breakpoints for Mask 1 | 251 |
| Table B.6—Breakpoints for Mask 2 | 251 |
| Table B.7—Breakpoints for Mask 3 | 251 |
| Table C.1—Time-scale parameters | 253 |
| Table C.2—Time-scale conversions | 255 |
| Table D.1—State machine symbols | 258 |
| Table E.1—CSN TLV | 267 |
| Table E.2—Definitions and option selections per link technology | 268 |