ISO/IEC 24771:2014-08 (E)

Information technology - Telecommunications and information exchange between systems - MAC/PHY standard for ad hoc wireless network to support QoS in an industrial work environment

Contents

Page

1 Scope 1
2 Normative references 1
3 Terms and definitions, and abbreviations 2
3.1 Terms and definitions 2
3.2 List of Abbreviations 3
4 Overview 7
4.1 Characteristics 7
4.1.1 Ad-hoc network 7
4.1.2 Quality of Service 7
4.1.3 Binary CDMA technology 7
4.2 Components of network 7
4.2.1 Station 8
4.2.2 Resources 8
4.3 Functional overview 8
4.3.1 Network synchronization 9
4.3.2 Data transmission 9
4.3.3 Security 10
4.3.4 Power management 11
4.3.5 Master handover 11
4.4 Summary of operations 11
4.4.1 Broadcasting during the beacon period 11
4.4.2 Random access during the contention period 11
4.4.3 Exclusive access during the allocation period 11
4.5 Summary of states 12
4.5.1 Establishing the network 12
4.5.2 Associating with the network 12
4.5.3 Security membership and key establishment 12
4.5.4 Data transfer 12
4.5.5 Master handover 12
4.5.6 Disassociating from the network 13
4.5.7 Terminating the network 13
5 Inter-layer interfaces 14
5.1 Summary 14
5.2 General format of management primitives 14
5.2.1 MLME-GET.request and PLME-GET.request 15
5.2.2 MLME-GET.confirm and PLME-GET.confirm 16
5.2.3 MLME-SET.request and PLME-SET.request 16
5.2.4 MLME-SET.confirm and PLME-SET.confirm 16
5.3 MLME SAP 17
5.3.1 Reset 18
5.3.2 Scan 19
5.3.3 Startup of network 21
5.3.4 Synchronization 22
5.3.5 Association 24
5.3.6 Disassociation 27

5.3.7 Key request 29
5.3.8 Key distribution 31
5.3.9 Security management 34
5.3.10 Master handover 38
5.3.11 Data request 40
5.3.12 Network node data probe 42
5.3.13 Strean creation, modification, termination 44
5.3.14 Channel state 48
5.3.15 Remote scan 50
5.3.16 Network parameter modification 53
5.3.17 Adjustment of power 55
5.3.18 Power saving 56
5.4 MAC management 58
5.4.1 MAC PIB master group 58
5.4.2 MAC PIB attributes group 59
5.4.3 MAC PIB authentication group 59
5.4.4 MAC PIB association group 59
5.4.5 MAC PIB network security group 60
5.5 MAC SAP 60
5.5.1 MAC-ASYNC-DATA.request 61
5.5.2 MAC-ASYNC-DATA.confirm 62
5.5.3 MAC-ASYNC-DATA.indication 62
5.5.4 MAC-ISOCH-DATA.request 63
5.5.5 MAC-ISOCH-DATA.confirm 63
5.5.6 MAC-ISOCH-DATA.indication 64
5.6 PHY specification 64
5.6.1 PD-SAP 64
5.6.2 PLME-SAP 74
5.6.3 Physical layer enumerated description 79

6 Mac frame format 81
6.1 Overview 81
6.2 General format of MAC frames 81
6.2.1 Frame header 82
6.2.2 Frame body 85
6.3 Frame formats 86
6.3.1 Beacon 86
6.3.2 Acknowledgement 88
6.3.3 Command 89
6.3.4 Data (stream or non-stream) 90
6.3.5 RTS (Request To Send) 90
6.3.6 CTS (Clear To Send) 91
6.4 Information block 91
6.4.1 Station UID 92
6.4.2 Station name 92
6.4.3 Station type 92
6.4.4 Network synchronization 92
6.4.5 Capabilities 93
6.4.6 Maximum supported time slot 93
6.4.7 Maximum transmit power 94
6.4.8 Resource allocation 94
6.4.9 New master notification 95
6.4.10 Sleep state notification 95
6.4.11 Vendor specific 95
6.5 Command block 95
6.5.1 Network management 97
6.5.2 Stream management 99
6.5.3 Power management 103
6.5.4 Key management 104
6.5.5 Security management 105
6.5.6 Vendor specific 105
6.5.7 Other 106

7 MAC feature description 110
7.1 Network formation and association 110
7.1.1 Channel scanning 110
7.1.2 Network ID 111
7.1.3 Association 111
7.1.4 Disassociation 111
7.1.5 Master handover 112
7.2 Media access 112
7.2.1 Code assignment 112
7.2.2 Inter-frame space 112
7.2.3 Access during the contention period 113
7.2.4 Access during the allocation period 113
7.3 Synchronization 114
7.3.1 Superframe synchronization 114
7.3.2 Beacon generation 115
7.3.3 Beacon reception 115
7.3.4 Synchronization 115
7.4 Resource allocation 115
7.4.1 Transmission of synchronous data 115
7.4.2 Asynchronous data transmission 117
7.5 Fragmentation and defragmentation 117
7.6 Acknowledgement and retransmission 118
7.6.1 No acknowledgement 118
7.6.2 Immediate acknowledgement 118
7.6.3 Delayed acknowledgement 118
7.6.4 Implicit acknowledgement 118
7.6.5 Retransmission 118
7.7 Power saving 119
7.7.1 Saving power in a connected state 119
7.7.2 Sleep state 119
7.8 Dynamic channel management 119
7.8.1 Channel state probe 119
7.8.2 Remote Channel state probe 119
7.8.3 Frequency channel change 120
7.9 MAC parameters 120

8 Security 121
8.1 Security mechanisms 121
8.1.1 Security membership and key establishment 121
8.1.2 Key transport 121
8.1.3 Data encryption 121
8.1.4 Data integrity 121
8.1.5 Beacon integrity protection 122
8.1.6 Command integrity protection 122
8.1.7 Freshness protection 122
8.2 Security modes 122
8.2.1 Security mode 0 122
8.2.2 Security mode 1 122
8.2.3 Security mode 2 123
8.3 Security Support 123
8.3.1 Changes in the network group data key 123
8.3.2 Joining a secure network 123
8.3.3 Secure frame generation 124
8.3.4 Secure frame reception 124
8.3.5 Retransmission detect 125
8.3.6 Key selection 125
8.4 Key management protocol 128
8.4.1 Key distribution protocol 128
8.4.2 Key request protocol 130
8.5 CCM mode 131
8.5.1 Overview 131

8.5.2 Nonce 131
8.5.3 Inputs 132

9 General specifications 135
9.1 General requirements 135
9.1.1 Operating frequency range 135
9.1.2 PHY layer timing 136
9.1.3 Receive-to-transmit turnaround time 137
9.1.4 Transmit-to-receive turnaround time 137
9.1.5 Channel switch time 137
9.1.6 Maximum frame size 137
9.2 PHY Protocol Data Unit (PDU) format 137
9.2.1 General format 137
9.2.2 Preamble 138
9.2.3 PHY Header 139
9.2.4 PHY payload 140
9.3 Modulation and coding 141
9.3.1 Spreading code 141
9.3.2 QPSK modulation 142
9.3.3 Constant envelope coding 142
9.3.4 Modulation methods for PHY PDU 145
9.3.5 Data rate 146
9.3.6 QPSK Modulation and constellation 146
9.4 PHY layer constants and PHY PIB attribute 147
9.5 Transmitter specification 147
9.5.1 Error vector magnitude (EVM) definition 147
9.5.2 EVM calculated values 148
9.5.3 Transmitter power spectrum mask 148
9.5.4 Signal waveform filter 149
9.5.5 Error tolerance for carrier frequency 149
9.5.6 Transmitter data rate 149
9.5.7 Synchronization 149
9.5.8 Transmitter response time 150
9.5.9 RF carrier suppression 150
9.5.10 Transmit power 150
9.6 Receiver specifications 150
9.6.1 Error rate criteria 150
9.6.2 Receiver sensitivity 151
9.6.3 Maximum input power 151
9.6.4 Receiver Energy detection (ED) 151
9.6.5 Clear channel assessment (CCA) 151
9.6.6 Received CCA performance 151
9.6.7 Received Signal Strength Index 151
9.6.8 Link Quality Index (LQI) 152

Annex A (informative) Example scheduler and admission control 153

A.1 Scheduling algorithm 153
A.2 Admission control Algorithm 154

List of Figures FIGURE 1- NETWORK 8

FIGURE 2 - SUPERFRAME 9

FIGURE 3 - PROTOCOL STACK CONFIGURATION 14

FIGURE 4 - TRANSMISSION ORDER 81

FIGURE 5 - FORMAT OF MAC FRAME 82

FIGURE 6 - NON-SECURE MAC FRAME BODY FORMAT 82

FIGURE 7 - SECURE MAC FRAME BODY FORMAT 82
FIGURE 8 - FORMAT OF FRAME CONTROL FIELDS 82
FIGURE 9 - FORMAT OF STREAM ID FIELD 84
FIGURE 10 - NON-SECURE BEACON FRAME FORMAT 86
FIGURE 11 - SECURE BEACON FRAME FORMAT 87
FIGURE 12 - IMMEDIATE ACKNOWLEDGEMENT FRAME FORMAT 88
FIGURE 13 - DELAYED ACKNOWLEDGEMENT FRAME PAYLOAD FORMAT 89
FIGURE 14 - FORMAT OF RECORD FOR STREAM-M 89
FIGURE 15 - NON-SECURE COMMAND FRAME FORMAT 89
FIGURE 16 - COMMAND BLOCK FORMAT 90
FIGURE 17 - FORMAT OF SECURE COMMAND FRAME 90
FIGURE 18 - NON-SECURE DATA FRAME FORMAT 90
FIGURE 19 - SECURE DATA FRAME FORMAT 90
FIGURE 20 - RTS FRAME FORMAT 91
FIGURE 21 - CTS FRAME FORMAT 91
FIGURE 22 - INFORMATION BLOCK FORMAT 92
FIGURE 23 - STATION UID INFORMATION BLOCK FORMAT 92
FIGURE 24 - STATION NAME INFORMATION BLOCK FORMAT 92
FIGURE 25 - STATION TYPE INFORMATION BLOCK FORMAT 92
FIGURE 26 - NETWORK SYNCHRONIZATION INFORMATION BLOCK FORMAT 92
FIGURE 27 - CAPABILITY INFORMATION BLOCK FORMAT 93
FIGURE 28 - CAPABILITY FIELD FORMAT 93
FIGURE 29 - MAXIMUM SUPPORT TIMESLOT INFORMATION BLOCK FORMAT 93
FIGURE 30 - MAXIMUM TRANSMIT POWER INFORMATION BLOCK FORMAT 94
FIGURE 31 - RESOURCE ALLOCATION INFORMATION BLOCK FORMAT 94
FIGURE 32 - RESOURCE ALLOCATION BLOCK FORMAT 94
FIGURE 33 - NEW MASTER NOTIFICATION INFORMATION BLOCK FORMAT 95
FIGURE 34 - SLEEP STATE NOTIFICATION INFORMATION BLOCK FORMAT 95
FIGURE 35 - VENDOR SPECIFIC INFORMATION ELEMENT FORMAT 95
FIGURE 36 - COMMAND BLOCK FORMAT 96
FIGURE 37 -ASSOCIATE REQUEST COMMAND BLOCK FORMAT 97

FIGURE 38 -ASSOCIATION RESPONSE COMMAND BLOCK FORMAT 97

FIGURE 39 - DISASSOCIATION REQUEST PAYLOAD FORMAT 98

FIGURE 40 - MASTER HANDOVER COMMAND BLOCK FORMAT 99

FIGURE 41 - RESOURCE ALLOCATION REQUEST COMMAND BLOCK FORMAT 100

FIGURE 42 - RESOURCE ALLOCATION REQUEST RECORD FORMAT 100

FIGURE 43 - RESOURCE ALLOCATION RESPONSE COMMAND BLOCK FORMAT 100

FIGURE 44 - RESOURCE ALLOCATION MODIFICATION COMMAND BLOCK FORMAT 101

FIGURE 45 - RESOURCE ALLOCATION MODIFICATION REQUEST RECORD FORMAT 101

FIGURE 46 - RESOURCE ALLOCATION TERMINATION COMMAND BLOCK FORMAT 102

FIGURE 47 - DELAYED ACKNOWLEDGEMENT RESYNCHRONIZATION COMMAND BLOCK FORMAT 102

FIGURE 48 - DELAYED ACKNOWLEDGEMENT RESYNCHRONIZATION COMMAND RECORD FORMAT 102

FIGURE 49 - SLEEP STATE REQUEST COMMAND BLOCK FORMAT 103

FIGURE 50 - SLEEP STATE RESPONSE COMMAND BLOCK FORMAT 103

FIGURE 51 -ACTIVATION INDICATION COMMAND BLOCK FORMAT 104

FIGURE 52 - TRANSMIT POWER ADJUSTMENT COMMAND BLOCK FORMAT 104

FIGURE 53 - KEY REQUEST COMMAND FORMAT 104

FIGURE 54 - REQUEST KEY RESPONSE COMMAND FORMAT 104

FIGURE 55 - REQUEST KEY RESPONSE COMMAND FORMAT 105

FIGURE 56 - REQUEST KEY RESPONSE COMMAND FORMAT 105

FIGURE 57 - VENDOR SPECIFIC SECURITY INFORMATION FORMAT 105

FIGURE 58 - VENDOR SPECIFIC INFORMATION ELEMENT FORMAT 106

FIGURE 59 - STATION INFORMATION REQUEST COMMAND BLOCK FORMAT 106

FIGURE 60 - STATION INFORMATION RESPONSE COMMAND BLOCK FORMAT 106

FIGURE 61 - STATION INFORMATION BLOCK FORMAT 106

FIGURE 62 - DATA QUERY COMMAND BLOCK FORMAT 107

FIGURE 63 - CHANNEL STATE REQUEST COMMAND BLOCK FORMAT 107

FIGURE 64 - CHANNEL STATE RESPONSE COMMAND BLOCK FORMAT 107

FIGURE 65 - REMOTE CHANNEL SCAN REQUEST COMMAND BLOCK FORMAT 108

FIGURE 66 - REMOTE CHANNEL SCAN RESPONSE COMMAND BLOCK FORMAT 108

FIGURE 67 - CHANNEL INFORMATION BLOCK FORMAT 108

FIGURE 68 -APPLICATION SPECIFIC COMMAND FORMAT 109
FIGURE 69 -ASSOCIATION PROCESS 111
FIGURE 70 - INTER-FRAME SPACE IN THE ALLOCATED TIME SLOTS 114
FIGURE 71 - SUPERFRAME SYNCHRONIZATION 114
FIGURE 72 - STREAM CONNECTION PROCESS FOR SYNCHRONIZED DATA TRANSMISSION 116
FIGURE 73 - MESSAGE FLOW OF KEY DISTRIBUTION BETWEEN THE MASTER AND A STATION .129
FIGURE 74 - MESSAGE FLOW OF THE KEY DISTRIBUTION BETWEEN STATIONS 130
FIGURE 75 - MESSAGE FLOW OF KEY REQUEST BETWEEN A STATION AND A KEY ORIGINATOR 131
FIGURE 76 - CCM NONCE FORMAT 132
FIGURE 77 - SECURE BEACON FRAME FORMAT 132
FIGURE 78 - FORMAT OF SECURE COMMAND FRAME 132
FIGURE 79 - SECURE DATA FRAME FORMAT 133
FIGURE 80 - CCM INTEGRITY CODE GENERATION BLOCK 133
FIGURE 81 - INTEGRITY BLOCK B_0 133
FIGURE 82 - INTEGRITY BLOCK B_1 133
FIGURE 83 - INTEGRITY BLOCK B_2, ..., B_N134
FIGURE 84 - DATA ENCRYPTION BLOCK 134
FIGURE 85 - ENCRYPTION BLOCK 134
FIGURE 86 - OPERATING FREQUENCY CHANNELS AT 2.42.4835GHZ AND 5.7255.825GHZ 135
FIGURE 87 - PHY PROTOCOL DATA UNIT (PDU) FORMAT 137
FIGURE 88 - PREAMBLE FORMAT 138
FIGURE 89 - PHY HEADER 139
FIGURE 90 - LFSR GENERATING THE (15,10) SHORTENED HAMMING CODE 139
FIGURE 91 - LFSR CIRCUIT GENERATING THE HEC 140
FIGURE 92 - SCRAMBLER BLOCK DIAGRAM 141
FIGURE 93 - QPSK MODULATION 142
FIGURE 94 - RATE1 BLOCK DIAGRAM 143
FIGURE 95 - RATE2 BLOCK DIAGRAM 143
FIGURE 96 - RATE3 BLOCK DIAGRAM 144
FIGURE 97 - RATE4 BLOCK DIAGRAM 145
FIGURE 98 - PREAMBLE MODULATION 145

FIGURE 99 - HEADER MODULATION 145

FIGURE 100 - PAYLOAD MODULATION 146

FIGURE 101 - SIGNAL CONSTELLATION- OF QPSK 146

FIGURE 102 - ERROR VECTOR CALCULATION 148

FIGURE 103 - TRANSMIT POWER SPECTRUM MASK 149

FIGURE 104 - TRANSMITTER RF RESPONSE TIME 150

List of Tables TABLE 1 - GENERAL MANAGEMENT PRIMITIVE OVERVIEW 15

TABLE 2 - MLME/PLME GENERAL MANAGEMENT PRIMITIVE PARAMETERS 15

TABLE 3 - MLME PRIMITIVE SUMMARY 17

TABLE 4 - MLME-RESET PRIMITIVE PARAMETERS 18

TABLE 5 - MLME-SCAN PRIMITIVE PARAMETERS 19

TABLE 6 - PICONETDESCRIPTION ELEMENTS 19

TABLE 7 - MLME-START PRIMITIVE PARAMETERS 21

TABLE 8 - MLME-SYNCH PRIMITIVE PARAMETERS 22

TABLE 9 - MLME-ASSOCIATE.PRIMITIVE PARAMETERS 24

TABLE 10 - MLME-DISASSOCIATE PRIMITIVE PARAMETERS 27

TABLE 11 - MLME-REQUEST-KEY PRIMITIVE PARAMETERS 29

TABLE 12 - MLME-DISTRIBUTE-KEY PRIMITIVE PARAMETERS 31

TABLE 13 - MLME-MEMBERSHIP-UPDATE PRIMITIVE PARAMETERS 34

TABLE 14 - MLME-SECURITY-ERROR PRIMITIVE PARAMETERS 34

TABLE 15 - MLME-SECURITY-MESSAGE PRIMITIVE PARAMETERS 35

TABLE 16 - MLME-MASTER-HANDOVER PRIMITIVE PARAMETERS 38

TABLE 17 - MLME-MASTER-INFO PRIMITIVE PARAMETERS 40

TABLE 18 - MLME-PROBE PRIMITIVE PARAMETERS 42

TABLE 19 - MLME-CREATE-STREAM, MLME-MODIFY-STREAM, MLME-TERMINATE-STREAM PRIMITIVE PARAMETERS 44

TABLE 20 - MLME-CHANNEL-STATUS PRIMITIVE PARAMETERS 48

TABLE 21 - MLME-REMOTE-SCAN PRIMITIVE PARAMETERS 50

TABLE 22 - REMOTEPICONETDESCRIPTION ELEMENTS 51

TABLE 23 - MLME-NETWORK-PARM-CHANGE PRIMITIVE PARAMETERS 53

TABLE 24 - MLME-TX-POWER-CHANGE PRIMITIVE PARAMETERS 55

TABLE 25 - MLME-SLEEP PRIMITIVE PARAMETERS 56
TABLE 26 - MAC PIB MASTER GROUP PARAMETERS 58
TABLE 27 - MAC PIB ATTRIBUTE GROUP PARAMETERS 59
TABLE 28 - MAC PIB AUTHENTICATION GROUP PARAMETERS 59
TABLE 29 - MAC PIB ASSOCIATION GROUP PARAMETERS 60
TABLE 30 - MAC PIB NETWORK SECURITY GROUP PARAMETERS 60
TABLE 31 - MAC SAP PRIMITIVE SUMMARY 61
TABLE 32 - MAC-ASYNC-DATAAND MAC-ISOCH-DATAPRIMITIVE PARAMETERS 61
TABLE 33 - PD-SAP PRIMITIVES 64
TABLE 34 - PD-SAP PARAMETERS 65
TABLE 35 - PLME-SAP PRIMITIVES 74
TABLE 36 - PLME-SAP PRIMITIVE PARAMETERS 74
TABLE 37 - PHYSICAL LAYER ENUMERATED VALUES 79
TABLE 38 - FRAME TYPES 83
TABLE 39 - USAGE CODES BY FRAME TYPE 86
TABLE 40 - BEACON FRAME BODY 87
TABLE 41 - SETTING THE CONTROL FIELD OF THE NON-SECURE BEACON FRAME 87
TABLE 42 - SETTING THE CONTROL FIELD OF THE SECURE BEACON FRAME 88
TABLE 43 - SETTING THE CONTROL FIELD OF THE BEACON FRAME 88
TABLE 44 - INFORMATION BLOCKS 91
TABLE 45 - COMMAND TYPES 96
TABLE 46 - ORDER OF PREFERENCE WHEN COMPARING CAPABILITY 99
TABLE 47 - MAC LAYER PARAMETERS 120
TABLE 48 - KEY SELELCTION 125
TABLE 49 - CENTER FREQUENCIES OF CHANNELS AT 2.4GHZ AND 5.8GHZ 136
TABLE 50 - PHY LAYER TIMING PARAMETERS AT 2.4GHZ AND 5.8GHZ 136
TABLE 51 - INTERFRAME SPACE PARAMETER 136
TABLE 52 - CAZAC SEQUENCE 138
TABLE 53 - FORWARD ERROR CORRECTION 139
TABLE 54 - CONSTANT ENVELOPE CODING 140
TABLE 55 - DATA RATE ACCORDING TO MODULATION TYPE 146

TABLE 56 - PHY LAYER CONSTANTS 147

TABLE 57 - PIB CHARACTERISTICS GROUP PARAMETERS 147

TABLE 58 - TRANSMIT PSD LIMITS 149

TABLE 59 - TRANSMIT POWER 150