ISO/IEC 9834-8:2014-08 (E)

Information technology - Procedures for the operation of object identifier registration authorities - Part 8: Generation of universally unique identifiers (UUIDs) and their use in object identifiers

Contents

Page

1 Scope 1
2 Normative references 1
2.1 Identical Recommendations | International Standards 1
2.2 Other normative references 1
3 Terms and definitions 2
3.1 ASN.1 notation 2
3.2 Registration authorities 2
3.3 Network terms 2
3.4 Additional definitions 2
4 Abbreviations 3
5 Notation 3
6 UUID structure and representation 3
6.1 UUID field structure 3
6.2 Binary representation 4
6.3 Representation as a single integer value 4
6.4 Hexadecimal representation 4
6.5 Formal syntax of the hexadecimal representation 4
7 Use of a UUID as the primary integer value and Unicode label of a Joint UUID arc 5
8 Use of a UUID to form a URN 5
9 Rules for comparison and ordering of UUIDs 5
10 Validation 6
11 Variant bits 6
12 Use of UUID fields and transmission byte order 6
12.1 General 6
12.2 Version 7
12.3 Time 7
12.4 Clock sequence 8
12.5 Node 8
13 Setting the fields of a time-based UUID 9
14 Setting the fields of a name-based UUID 9
15 Setting the fields of a random-number-based UUID 10
Annex A – Algorithms for the efficient generation of time-based UUIDs 11
A.1 Basic algorithm 11
A.2 Reading stable storage 11
A.3 System clock resolution 11
A.4 Writing stable storage 12
A.5 Sharing state across processes 12

Annex B – Properties of name-based UUIDs 13
Annex C – Generation of random numbers in a system 14
Annex D – Sample implementation 15
D.1 Files provided 15
D.2 The `copyrt.h` file 15
D.3 The `uuid.h` file 15
D.4 The `uuid.c` file 16
D.5 The `sysdep.h` file 19
D.6 The `sysdep.c` file 19
D.7 The `utest.c` file 21
D.8 Sample output of `utest` 21
D.9 Some name space IDs 22
Bibliography 23