ISO/IEC 18000-4:2015-02 (E)

Information technology - Radio frequency identification for item management - Part 4 : Parameters for air interface communications at 2,45 GHz

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 3

5.1 Protocols 5
5.2 Frequency 5
5.2.1 Interface definitions 5
5.3 Tag identification number 6
5.4 Potential interference 6

6 MODE 1: Passive backscatter RFID system 6
6.1 MODE 1: General 6
6.2 Physical layer and data coding 7
6.2.1 Interrogator power-up waveform 7
6.2.2 Interrogator power-down 8
6.2.3 Frequency hopping carrier rise and fall times 9
6.2.4 Forward link 9
6.2.5 FM0 return link 11
6.2.6 Cyclic redundancy check (CRC) 12
6.2.7 Protocol concept 13
6.2.8 Command format 14
6.2.9 Response format 15
6.2.10 WAIT 15
6.2.11 Communication sequences at packet level 16
6.3 Protocol and collision arbitration 17
6.3.1 Definition of data elements, bit and byte ordering 17
6.3.2 Tag memory organisation 18
6.3.3 Block security status 18
6.3.4 Overall protocol description 19
6.3.5 Collision arbitration 23
6.3.6 Commands 24
6.3.7 Transmission errors 43

7 MODE 2: Long range high data rate RFID system 43
7.1 MODE 2: General 43
7.2 Modulation and coding 43
7.2.1 Forward link (only for R/W-tag) 43
7.2.2 Return link for notification (for both types of the tag) 44
7.2.3 Return link for communication (only for R/W-tag) 44
7.3 General system description 45
7.4 Frame structure 46
7.4.1 Hierarchical structure 46
7.4.2 Logical channels 47

7.4.3 Physical channels 53
7.5 Channel coding and sequences 68
7.5.1 Synchronisation and CRC patterns 68
7.6 Command set for the command slot channel: CS-CH (only for R/W-tag) 68
7.6.1 Command types 68
7.6.2 Command set 69
7.6.3 Command codes 70

8 MODE 3: Active RFID ITF network 72
8.1 General 72
8.2 Operational Requirements 72
8.3 Network Physical Layer Description 73
8.4 Network Description 73
8.4.1 General 73
8.4.2 Network Topology 73
8.5 Star Topology 76
8.5.1 General 76
8.5.2 Star Topology Data Flow 76
8.6 Trunk Topology 76
8.6.1 Trunk Coordinator Requirements 76
8.6.2 Data Flow in a Trunk Topology 77
8.7 Peer-to-Peer Topology 77
8.8 Mesh Topology 78
8.8.1 Establishing a Mesh Network 78
8.9 Message Types 81
8.9.1 Network Discovery Beacon (NDB) 83
8.9.2 Network Status Message (NSM) 87
8.9.3 Acknowledgement Message 91
8.9.4 Command Message 94
8.9.5 Data Message 95
8.9.6 Mesh Request 96
8.9.7 Mesh Data 97
8.10 Network Discovery 97
8.10.1 Methods of Network Discovery 98
8.10.2 Transmitting Network Discovery Beacons 98
8.10.3 Connectionless Network 99
8.10.4 Associated Network Connection (ANC) 100
8.11 Link Encryption Methods 102

9 Table of characteristic differences between the modes specified in this part of ISO/ IEC 18000 103

Annex A (informative) Mode 1: Memory Map 104

Annex B (informative) Mode 1: CRC 110

Annex C (normative) Mode 2: Memory Map 113

Annex D (informative) Mode 2: CRC 115

Bibliography 117