ISO/IEC 29157:2015-07 (E)

Information technology - Telecommunications and information excha nge between systems - PHY/MAC specifications for short-range wireless low-rate applications in the ISM band

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Abbreviated terms 2

5 Overview 3

6 Interlayer service specification 5
6.1 Overview 6
6.2 General format of management primitives 6
6.2.1 MLME-GET.request and PLME-GET.request 7
6.2.2 MLME-GET.confirm and PLME-GET.confirm 7
6.2.3 MLME-SET.request and PLME-SET.request 8
6.2.4 MLME-SET.confirm and MLME-SET.confirm 8
6.3 MLME-SAP 9
6.3.1 MLME-GET.request 10
6.3.2 MLME-GET.confirm 10
6.3.3 MLME-MASTER-START.request 10
6.3.4 MLME-MASTER-START.confirm 11
6.3.5 MLME-RESET.request 11
6.3.6 MLME-RESET.confirm 12
6.3.7 MLME-SCAN.request 12
6.3.8 MLME-SCAN.confirm 13
6.3.9 MLME-SET.request 13
6.3.10 MLME-SET.confirm 14
6.4 MAC-SAP 14
6.4.1 MAC-DATA.request 15
6.4.2 MAC-DATA.confirm 15
6.4.3 MAC-DATA.indication 16
6.5 PLME-SAP 16
6.5.1 PLME-GET.request 17
6.5.2 PLME-GET.confirm 17
6.5.3 PLME-SET.request 18
6.5.4 PLME-SET.confirm 18
6.5.5 PLME-RESET.request 19
6.5.6 PLME-RESET.confirm 19
6.6 PD-SAP 20
6.6.1 PD-DATA.request 20
6.6.2 PD-DATA.confirm 21
6.6.3 PD-DATA.indication 21

7 MAC PDU format 22

7.1 MPDU of beacon frame (BF) 22
7.1.1 Open flag (OF, 2 bits) 22
7.1.2 MAC version (6 bits) 23
7.1.3 Address mode (ADDM, 2 bits) 23
7.1.4 PHY version (6 bits) 23
7.1.5 Frame type (8 bits) 23
7.1.6 Superframe mode control (SFMC, 2 bits) 23
7.1.7 Upper layer frame size (ULPS, 6 bits) 24
7.1.8 Source MAC address (64 bits) 24
7.1.9 Superframe counter (SFC, 4 bits) 24
7.1.10 Middleframe counter (FC, 4 bits) 24

7.1.11 Hopping sequence (32 bits) 24
7.1.12 Beacon frequency table (BFT, 16 bytes) 24
7.1.13 Upper layer data (16 bytes) 24
7.1.14 TCRC16 (16 bits), MCRC16 (16 bits) 24
7.2 MPDU of fast beacon frame (FBF) 24
7.2.1 Open flag (OF, 2 bits) 24
7.2.2 MAC version (6 bits) 25
7.2.3 Address mode (ADDM, 2 bits) 25
7.2.4 PHY version (6 bits) 25
7.2.5 Frame type (8 bits) 25
7.2.6 Superframe mode control (SFMC, 2 bits) 25
7.2.7 Upper layer frame size (ULPS, 6 bits) 26
7.2.8 Source MAC address (64 bits) 26
7.2.9 Superframe counter (SFC, 4 bits) 26
7.2.10 Middleframe counter (SC, 4 bits) 26
7.2.11 Hopping sequence (32 bits) 26
7.2.12 Beacon frequency table (BFT, 16 bytes) 26
7.2.13 Upper layer data (16 Bytes) 26
7.2.14 TCRC16 (16 bits), MCRC16 (16 bits) 26
7.3 MPDU of request control frame (RCF) 26
7.3.1 Open flag (OF, 2 bits) 26
7.3.2 MAC version (6 bits) 26
7.3.3 Address mode (ADDM, 2 bits) 27
7.3.4 PHY version (6 bits) 27
7.3.5 Frame type (8 bits) 27
7.3.6 Upper layer frame size (ULPS, 6 bits) 27
7.3.7 Source MAC address (64 bits) 27
7.3.8 Destination MAC address (64 bits) 27
7.3.9 Upper layer data 28
7.3.10 TCRC16 (16 bits), MCRC16 (16 bits) 28
7.4 MPDU of master control frame (MCF) 28
7.4.1 Open flag (OF, 2 bits) 28
7.4.2 MAC version (6 bits) 28
7.4.3 Address mode (ADDM, 2 bits) 28
7.4.4 PHY version (6 bits) 28
7.4.5 Frame type (8 bits) 28
7.4.6 Upper layer frame size (ULPS, 6 bits) 28
7.4.7 Source MAC address (64 bits) 28
7.4.8 Destination MAC address (64 bits) 29
7.4.9 Upper layer data 29
7.4.10 TCRC16 (16 bits), MCRC16 (16 bits) 29
7.5 MPDU of RCF acknowledge control frame (RACF) 29
7.6 MPDU of MCF acknowledge control frame (MACF) 29
7.7 MPDU of payload frame (PF) 30
7.7.1 Open flag (OF, 2 bits) 30
7.7.2 MAC version (6 bits) 30
7.7.3 Address mode (ADDM, 2 bits) 30
7.7.4 PHY version (6 bits) 30
7.7.5 Frame type (8 bits) 30
7.7.6 Upper layer frame size (ULPS, 6 bits) 30

7.7.7 Source MAC address (64 bits) 30
7.7.8 Destination MAC address (64 bits) 30
7.7.9 Upper layer data 30
7.7.10 TCRC16 (16 bits), MCRC16 (16 bits) 30

8 MAC functional description 31
8.1 General description 31
8.2 System state diagram 32
8.3 Protocol structure 34
8.3.1 Middleframe structure 35
8.3.2 Superframe structure 35
8.4 Frequency operation 37
8.4.1 Frequency hopping control 37
8.4.2 Frame frequency mapping 37
8.4.3 Frequency diversity and time diversity 38
8.4.4 Orthogonal frequency offset 38
8.4.5 Frequency selection 38

9 PHY specification 41
9.1 General requirements 41
9.1.1 Operating frequency range 41
9.1.2 Frequency assignment 41
9.1.3 Frequency synthesizer stabilisation time 41
9.1.4 Frequency synthesizer turn off time 41
9.2 PHY protocol data unit (PPDU) format 42
9.2.1 Lock time 42
9.2.2 Preamble 42
9.2.3 Header (48 bits) 43
9.2.4 Message 43
9.2.5 EoF delimiter 43
9.3 Modulation and codes 43
9.3.1 Modulation 43
9.3.2 Codes 44
9.4 Transmitter specification 45
9.4.1 Pulse shaping filter 45
9.4.2 Transmitter power spectrum mask 45

Annex A (informative) Pico-net Light-weight Architecture Security (PLAS) 46