

ISO/IEC 29157:2015-07 (E)

Information technology - Telecommunications and information exchange between systems - PHY/MAC specifications for short-range wireless low-rate applications in the ISM band

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	2
5	Overview	3
6	Interlayer service specification	5
6.1	Overview	6
6.2	General format of management primitives	6
6.2.1	MLME-GET.request and PLME-GET.request	7
6.2.2	MLME-GET.confirm and PLME-GET.confirm	7
6.2.3	MLME-SET.request and PLME-SET.request	8
6.2.4	MLME-SET.confirm and MLME-SET.confirm	8
6.3	MLME-SAP	9
6.3.1	MLME-GET.request	10
6.3.2	MLME-GET.confirm	10
6.3.3	MLME-MASTER-START.request	10
6.3.4	MLME-MASTER-START.confirm	11
6.3.5	MLME-RESET.request	11
6.3.6	MLME-RESET.confirm	12
6.3.7	MLME-SCAN.request	12
6.3.8	MLME-SCAN.confirm	13
6.3.9	MLME-SET.request	13
6.3.10	MLME-SET.confirm	14
6.4	MAC-SAP	14
6.4.1	MAC-DATA.request	15
6.4.2	MAC-DATA.confirm	15
6.4.3	MAC-DATA.indication	16
6.5	PLME-SAP	16
6.5.1	PLME-GET.request	17
6.5.2	PLME-GET.confirm	17
6.5.3	PLME-SET.request	18
6.5.4	PLME-SET.confirm	18
6.5.5	PLME-RESET.request	19
6.5.6	PLME-RESET.confirm	19
6.6	PD-SAP	20
6.6.1	PD-DATA.request	20
6.6.2	PD-DATA.confirm	21
6.6.3	PD-DATA.indication	21
7	MAC PDU format	22

7.1	MPDU of beacon frame (BF)	22
7.1.1	Open flag (OF, 2 bits)	22
7.1.2	MAC version (6 bits)	23
7.1.3	Address mode (ADDM, 2 bits)	23
7.1.4	PHY version (6 bits)	23
7.1.5	Frame type (8 bits)	23
7.1.6	Superframe mode control (SFMC, 2 bits)	23
7.1.7	Upper layer frame size (ULPS, 6 bits)	24
7.1.8	Source MAC address (64 bits)	24
7.1.9	Superframe counter (SFC, 4 bits)	24
7.1.10	Middleframe counter (FC, 4 bits)	24
7.1.11	Hopping sequence (32 bits)	24
7.1.12	Beacon frequency table (BFT, 16 bytes)	24
7.1.13	Upper layer data (16 bytes)	24
7.1.14	TCRC16 (16 bits), MCRC16 (16 bits)	24
7.2	MPDU of fast beacon frame (FBF)	24
7.2.1	Open flag (OF, 2 bits)	24
7.2.2	MAC version (6 bits)	25
7.2.3	Address mode (ADDM, 2 bits)	25
7.2.4	PHY version (6 bits)	25
7.2.5	Frame type (8 bits)	25
7.2.6	Superframe mode control (SFMC, 2 bits)	25
7.2.7	Upper layer frame size (ULPS, 6 bits)	26
7.2.8	Source MAC address (64 bits)	26
7.2.9	Superframe counter (SFC, 4 bits)	26
7.2.10	Middleframe counter (SC, 4 bits)	26
7.2.11	Hopping sequence (32 bits)	26
7.2.12	Beacon frequency table (BFT, 16 bytes)	26
7.2.13	Upper layer data (16 Bytes)	26
7.2.14	TCRC16 (16 bits), MCRC16 (16 bits)	26
7.3	MPDU of request control frame (RCF)	26
7.3.1	Open flag (OF, 2 bits)	26
7.3.2	MAC version (6 bits)	26
7.3.3	Address mode (ADDM, 2 bits)	27
7.3.4	PHY version (6 bits)	27
7.3.5	Frame type (8 bits)	27
7.3.6	Upper layer frame size (ULPS, 6 bits)	27
7.3.7	Source MAC address (64 bits)	27
7.3.8	Destination MAC address (64 bits)	27
7.3.9	Upper layer data	28
7.3.10	TCRC16 (16 bits), MCRC16 (16 bits)	28
7.4	MPDU of master control frame (MCF)	28
7.4.1	Open flag (OF, 2 bits)	28
7.4.2	MAC version (6 bits)	28
7.4.3	Address mode (ADDM, 2 bits)	28
7.4.4	PHY version (6 bits)	28
7.4.5	Frame type (8 bits)	28
7.4.6	Upper layer frame size (ULPS, 6 bits)	28
7.4.7	Source MAC address (64 bits)	28
7.4.8	Destination MAC address (64 bits)	29
7.4.9	Upper layer data	29
7.4.10	TCRC16 (16 bits), MCRC16 (16 bits)	29
7.5	MPDU of RCF acknowledge control frame (RACF)	29
7.6	MPDU of MCF acknowledge control frame (MACF)	29
7.7	MPDU of payload frame (PF)	30
7.7.1	Open flag (OF, 2 bits)	30
7.7.2	MAC version (6 bits)	30
7.7.3	Address mode (ADDM, 2 bits)	30
7.7.4	PHY version (6 bits)	30
7.7.5	Frame type (8 bits)	30
7.7.6	Upper layer frame size (ULPS, 6 bits)	30

7.7.7	Source MAC address (64 bits)	30
7.7.8	Destination MAC address (64 bits)	30
7.7.9	Upper layer data	30
7.7.10	TCRC16 (16 bits), MCRC16 (16 bits)	30
8	MAC functional description	31
8.1	General description	31
8.2	System state diagram	32
8.3	Protocol structure	34
8.3.1	Middleframe structure	35
8.3.2	Superframe structure	35
8.4	Frequency operation	37
8.4.1	Frequency hopping control	37
8.4.2	Frame frequency mapping	37
8.4.3	Frequency diversity and time diversity	38
8.4.4	Orthogonal frequency offset	38
8.4.5	Frequency selection	38
9	PHY specification	41
9.1	General requirements	41
9.1.1	Operating frequency range	41
9.1.2	Frequency assignment	41
9.1.3	Frequency synthesizer stabilisation time	41
9.1.4	Frequency synthesizer turn off time	41
9.2	PHY protocol data unit (PPDU) format	42
9.2.1	Lock time	42
9.2.2	Preamble	42
9.2.3	Header (48 bits)	43
9.2.4	Message	43
9.2.5	EoF delimiter	43
9.3	Modulation and codes	43
9.3.1	Modulation	43
9.3.2	Codes	44
9.4	Transmitter specification	45
9.4.1	Pulse shaping filter	45
9.4.2	Transmitter power spectrum mask	45
Annex A (informative) Pico-net Light-weight Architecture Security (PLAS)		46