

# ISO/IEC 29157:2015-07 (E)

Information technology - Telecommunications and information exchange between systems - PHY/MAC specifications for short-range wireless low-rate applications in the ISM band

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vi
Introduction .....		vii
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Abbreviated terms .....</b>	<b>2</b>
<b>5</b>	<b>Overview .....</b>	<b>3</b>
<b>6</b>	<b>Interlayer service specification .....</b>	<b>5</b>
6.1	Overview .....	6
6.2	General format of management primitives .....	6
6.2.1	MLME-GET.request and PLME-GET.request .....	7
6.2.2	MLME-GET.confirm and PLME-GET.confirm .....	7
6.2.3	MLME-SET.request and PLME-SET.request .....	8
6.2.4	MLME-SET.confirm and MLME-SET.confirm .....	8
6.3	MLME-SAP .....	9
6.3.1	MLME-GET.request .....	10
6.3.2	MLME-GET.confirm .....	10
6.3.3	MLME-MASTER-START.request .....	10
6.3.4	MLME-MASTER-START.confirm .....	11
6.3.5	MLME-RESET.request .....	11
6.3.6	MLME-RESET.confirm .....	12
6.3.7	MLME-SCAN.request .....	12
6.3.8	MLME-SCAN.confirm .....	13
6.3.9	MLME-SET.request .....	13
6.3.10	MLME-SET.confirm .....	14
6.4	MAC-SAP .....	14
6.4.1	MAC-DATA.request .....	15
6.4.2	MAC-DATA.confirm .....	15
6.4.3	MAC-DATA.indication .....	16
6.5	PLME-SAP .....	16
6.5.1	PLME-GET.request .....	17
6.5.2	PLME-GET.confirm .....	17
6.5.3	PLME-SET.request .....	18
6.5.4	PLME-SET.confirm .....	18
6.5.5	PLME-RESET.request .....	19
6.5.6	PLME-RESET.confirm .....	19
6.6	PD-SAP .....	20
6.6.1	PD-DATA.request .....	20
6.6.2	PD-DATA.confirm .....	21
6.6.3	PD-DATA.indication .....	21
<b>7</b>	<b>MAC PDU format .....</b>	<b>22</b>

7.1	MPDU of beacon frame (BF)	22
7.1.1	Open flag (OF, 2 bits)	22
7.1.2	MAC version (6 bits)	23
7.1.3	Address mode (ADDM, 2 bits)	23
7.1.4	PHY version (6 bits)	23
7.1.5	Frame type (8 bits)	23
7.1.6	Superframe mode control (SFMC, 2 bits)	23
7.1.7	Upper layer frame size (ULPS, 6 bits)	24
7.1.8	Source MAC address (64 bits)	24
7.1.9	Superframe counter (SFC, 4 bits)	24
7.1.10	Middleframe counter (FC, 4 bits)	24
7.1.11	Hopping sequence (32 bits)	24
7.1.12	Beacon frequency table (BFT, 16 bytes)	24
7.1.13	Upper layer data (16 bytes)	24
7.1.14	TCRC16 (16 bits), MCRC16 (16 bits)	24
7.2	MPDU of fast beacon frame (FBF)	24
7.2.1	Open flag (OF, 2 bits)	24
7.2.2	MAC version (6 bits)	25
7.2.3	Address mode (ADDM, 2 bits)	25
7.2.4	PHY version (6 bits)	25
7.2.5	Frame type (8 bits)	25
7.2.6	Superframe mode control (SFMC, 2 bits)	25
7.2.7	Upper layer frame size (ULPS, 6 bits)	26
7.2.8	Source MAC address (64 bits)	26
7.2.9	Superframe counter (SFC, 4 bits)	26
7.2.10	Middleframe counter (SC, 4 bits)	26
7.2.11	Hopping sequence (32 bits)	26
7.2.12	Beacon frequency table (BFT, 16 bytes)	26
7.2.13	Upper layer data (16 Bytes)	26
7.2.14	TCRC16 (16 bits), MCRC16 (16 bits)	26
7.3	MPDU of request control frame (RCF)	26
7.3.1	Open flag (OF, 2 bits)	26
7.3.2	MAC version (6 bits)	26
7.3.3	Address mode (ADDM, 2 bits)	27
7.3.4	PHY version (6 bits)	27
7.3.5	Frame type (8 bits)	27
7.3.6	Upper layer frame size (ULPS, 6 bits)	27
7.3.7	Source MAC address (64 bits)	27
7.3.8	Destination MAC address (64 bits)	27
7.3.9	Upper layer data	28
7.3.10	TCRC16 (16 bits), MCRC16 (16 bits)	28
7.4	MPDU of master control frame (MCF)	28
7.4.1	Open flag (OF, 2 bits)	28
7.4.2	MAC version (6 bits)	28
7.4.3	Address mode (ADDM, 2 bits)	28
7.4.4	PHY version (6 bits)	28
7.4.5	Frame type (8 bits)	28
7.4.6	Upper layer frame size (ULPS, 6 bits)	28
7.4.7	Source MAC address (64 bits)	28
7.4.8	Destination MAC address (64 bits)	29
7.4.9	Upper layer data	29
7.4.10	TCRC16 (16 bits), MCRC16 (16 bits)	29
7.5	MPDU of RCF acknowledge control frame (RACF)	29
7.6	MPDU of MCF acknowledge control frame (MACF)	29
7.7	MPDU of payload frame (PF)	30
7.7.1	Open flag (OF, 2 bits)	30
7.7.2	MAC version (6 bits)	30
7.7.3	Address mode (ADDM, 2 bits)	30
7.7.4	PHY version (6 bits)	30
7.7.5	Frame type (8 bits)	30
7.7.6	Upper layer frame size (ULPS, 6 bits)	30

7.7.7	Source MAC address (64 bits) .....	30
7.7.8	Destination MAC address (64 bits) .....	30
7.7.9	Upper layer data .....	30
7.7.10	TCRC16 (16 bits), MCRC16 (16 bits) .....	30
<b>8</b>	<b>MAC functional description .....</b>	<b>31</b>
8.1	General description .....	31
8.2	System state diagram .....	32
8.3	Protocol structure .....	34
8.3.1	Middleframe structure .....	35
8.3.2	Superframe structure .....	35
8.4	Frequency operation .....	37
8.4.1	Frequency hopping control .....	37
8.4.2	Frame frequency mapping .....	37
8.4.3	Frequency diversity and time diversity .....	38
8.4.4	Orthogonal frequency offset .....	38
8.4.5	Frequency selection .....	38
<b>9</b>	<b>PHY specification .....</b>	<b>41</b>
9.1	General requirements .....	41
9.1.1	Operating frequency range .....	41
9.1.2	Frequency assignment .....	41
9.1.3	Frequency synthesizer stabilisation time .....	41
9.1.4	Frequency synthesizer turn off time .....	41
9.2	PHY protocol data unit (PPDU) format .....	42
9.2.1	Lock time .....	42
9.2.2	Preamble .....	42
9.2.3	Header (48 bits) .....	43
9.2.4	Message .....	43
9.2.5	EoF delimiter .....	43
9.3	Modulation and codes .....	43
9.3.1	Modulation .....	43
9.3.2	Codes .....	44
9.4	Transmitter specification .....	45
9.4.1	Pulse shaping filter .....	45
9.4.2	Transmitter power spectrum mask .....	45
<b>Annex A (informative) Pico-net Light-weight Architecture Security (PLAS) .....</b>		<b>46</b>