

ISO/IEC TR 23009-3:2015-10 (E)

Information technology - Dynamic adaptive streaming over HTTP (DASH) - Part 3: Implementation guidelines

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, and abbreviated terms | 1 |
| 4 | General | 2 |
| 4.1 | System overview | 2 |
| 4.2 | Normative parts | 2 |
| 4.3 | Main design principles | 3 |
| 4.3.1 | Common timeline | 3 |
| 4.3.2 | Data model | 3 |
| 4.3.3 | Segments | 4 |
| 4.3.4 | Segment types | 5 |
| 4.3.5 | Segment addressing schemes | 5 |
| 4.3.6 | Stream access points | 6 |
| 4.3.7 | Remote elements | 6 |
| 4.3.8 | Events | 7 |
| 4.3.9 | General-purpose descriptors | 7 |
| 4.4 | Background on DASH profile concept | 8 |
| 4.5 | Dynamic aspects | 8 |
| 5 | Guidelines for content generation | 10 |
| 5.1 | General guidelines | 10 |
| 5.1.1 | Video content generation | 10 |
| 5.1.2 | Audio content generation | 12 |
| 5.1.3 | Content preparation for live streaming | 14 |
| 5.1.4 | Guidelines for generation of segment file names | 14 |
| 5.2 | Guidelines for ISO-BMFF content generation | 17 |
| 5.2.1 | On-demand streaming | 17 |
| 5.2.2 | Live streaming | 21 |
| 5.2.3 | Enabling trick modes | 23 |
| 5.2.4 | Support for SubRepresentations | 24 |
| 5.2.5 | Enabling delivery format to storage file format conversion | 26 |
| 5.3 | Guidelines for MPEG-2 TS content generation | 30 |
| 5.3.1 | General recommendations | 30 |
| 5.3.2 | Live streaming | 31 |
| 5.3.3 | On demand streaming | 32 |
| 5.4 | Guidelines for Advertisement Insertion | 33 |
| 5.4.1 | Use cases | 33 |
| 5.4.2 | Architectures and workflows | 34 |
| 5.4.3 | App-driven ad insertion | 36 |
| 5.5 | DASH MPD and Segment-based Live Service Offering | 37 |
| 5.5.1 | Preliminaries | 37 |
| 5.5.2 | Service Offering Requirements and Guidelines | 38 |
| 5.5.3 | Client requirements and guidelines | 41 |
| 5.6 | Guidelines for low latency live service | 43 |

| | | |
|--------|--|----|
| 5.6.1 | Use case | 43 |
| 5.6.2 | General Approach: Chunked transfer | 43 |
| 5.6.3 | MPD generation | 43 |
| 6 | Client implementation guidelines | 44 |
| 6.1 | General | 44 |
| 6.2 | Client architecture overview | 44 |
| 6.3 | Example of client operation | 45 |
| 6.4 | Timing model for live streaming | 45 |
| 6.4.1 | General | 45 |
| 6.4.2 | MPD information | 45 |
| 6.4.3 | MPD times | 46 |
| 6.4.4 | Context derivation | 46 |
| 6.4.5 | Derivation of MPD times | 47 |
| 6.4.6 | Addressing methods | 47 |
| 6.4.7 | Scheduling playout | 48 |
| 6.4.8 | Validity of MPD | 48 |
| 6.5 | MPD retrieval | 48 |
| 6.6 | Segment list generation | 49 |
| 6.6.1 | General | 49 |
| 6.6.2 | Template-based generation of segment list | 50 |
| 6.6.3 | Playlist-based generation of segment list | 51 |
| 6.6.4 | Media segment list restrictions | 51 |
| 6.7 | Rate adaptation | 52 |
| 6.8 | Seeking | 53 |
| 6.9 | Support for trick modes | 53 |
| 6.10 | Stream switching | 54 |
| 6.11 | Client support for dependent representations | 54 |
| 6.11.1 | General | 54 |
| 6.11.2 | Client trick-mode support using SubRepresentations | 55 |
| 6.12 | Events | 55 |
| 6.12.1 | General processing | 56 |
| 6.12.2 | Inband events | 56 |
| 7 | Extending DASH | 56 |
| 7.1 | Extension of MPD Schema in external namespace | 56 |
| 7.1.1 | General | 56 |
| 7.1.2 | Example | 56 |
| | Bibliography | 58 |