

# ISO/IEC/IEEE 8802-1Q:2016-03 (E)

## Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 1Q: Bridges and bridged networks

---

### Contents

- 1. Overview ..... 1
  - 1.1 Scope ..... 2
  - 1.2 Purpose ..... 2
  - 1.3 Introduction ..... 2
- 2. Normative references ..... 9
- 3. Definitions ..... 12
- 4. Abbreviations ..... 32
- 5. Conformance ..... 37
  - 5.1 Requirements terminology ..... 37
  - 5.2 Conformant components and equipment ..... 37
  - 5.3 Protocol Implementation Conformance Statement (PICS) ..... 38
  - 5.4 VLAN Bridge component requirements ..... 38
    - 5.4.1 VLAN Bridge component options ..... 39
    - 5.4.2 Multiple VLAN Registration Protocol (MVRP) requirements ..... 43
    - 5.4.3 VLAN Bridge requirements for congestion notification ..... 44
    - 5.4.4 Multiple Stream Registration Protocol (MSRP) requirements ..... 44
    - 5.4.5 Shortest Path Bridging (SPB) operation (optional) ..... 45
  - 5.5 C-VLAN component conformance ..... 46
    - 5.5.1 C-VLAN component options ..... 46
  - 5.6 S-VLAN component conformance ..... 46
    - 5.6.1 S-VLAN component options ..... 47
    - 5.6.2 S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE) ..... 47
      - 5.6.3 S-VLAN component requirements for PBB-TE IPS ..... 47
      - 5.6.4 S-VLAN component requirements for ECMP with flow filtering ..... 48
  - 5.7 I-component conformance ..... 48
    - 5.7.1 I-component options ..... 48
  - 5.8 B-component conformance ..... 48
    - 5.8.1 B-component options ..... 49
    - 5.8.2 B-component requirements for PBB-TE ..... 49
    - 5.8.3 B-component requirements for PBB-TE IPS ..... 49
    - 5.8.4 B-component requirements for ECMP with flow filtering ..... 50
  - 5.9 C-VLAN Bridge conformance ..... 50
    - 5.9.1 C-VLAN Bridge options ..... 50
  - 5.10 Provider Bridge conformance ..... 50
    - 5.10.1 S-VLAN Bridge conformance ..... 50
    - 5.10.2 Provider Edge Bridge conformance ..... 51
  - 5.11 System requirements for Priority-based Flow Control (PFC) ..... 51
  - 5.12 Backbone Edge Bridge (BEB) conformance ..... 51
    - 5.12.1 BEB requirements for PBB-TE ..... 52
  - 5.13 MAC Bridge component requirements ..... 52
    - 5.13.1 MAC Bridge component options ..... 52
  - 5.14 MAC Bridge conformance ..... 53
    - 5.14.1 MAC Bridge options ..... 53
  - 5.15 TPMR component conformance ..... 53
    - 5.15.1 TPMR component options ..... 53

|        |  |    |
|--------|--|----|
| 5.16   | TPMR conformance.....  | 54 |
| 5.16.1 | TPMR options .....   | 54 |
| 5.17   | T-component conformance.....   | 54 |
| 5.17.1 | T-component options .....  | 54 |
| 5.18   | End station requirements for MMRP, MVRP, and MSRP .....                            | 54 |
| 5.18.1 | MMRP requirements and options .....  | 55 |
| 5.18.2 | MVRP requirements and options .....  | 55 |
| 5.18.3 | MSRP requirements and options .....  | 56 |
| 5.19   | VLAN-aware end station requirements for CFM .....                                  | 56 |
| 5.20   | End station requirements—FQSS.....   | 57 |
| 5.21   | End station requirements for congestion notification .....                         | 57 |
| 5.22   | MAC-specific bridging methods.....   | 58 |
| 5.23   | EVB Bridge requirements.....   | 58 |
| 5.24   | EVB station requirements.....  | 59 |
| 5.24.1 | Edge relay (ER) requirements .....   | 59 |
| 6.     | Support of the MAC Service.....  | 61 |
| 6.1    | Basic architectural concepts and terms .....                                       | 62 |
| 6.2    | Provision of the MAC Service.....  | 62 |
| 6.2.1  | Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ..... | 63 |
| 6.3    | Support of the MAC Service.....  | 63 |
| 6.4    | Preservation of the MAC Service .....  | 64 |
| 6.5    | Quality of service (QoS) maintenance.....  | 64 |
| 6.5.1  | Service availability .....   | 64 |
| 6.5.2  | Frame loss .....   | 65 |
| 6.5.3  | Frame misordering .....  | 65 |
| 6.5.4  | Frame duplication .....  | 66 |
| 6.5.5  | Transit delay .....  | 67 |
| 6.5.6  | Frame lifetime .....   | 68 |
| 6.5.7  | Undetected frame error rate .....  | 68 |
| 6.5.8  | Maximum Service Data Unit Size .....   | 68 |
| 6.5.9  | Priority .....   | 68 |
| 6.5.10 | Throughput .....   | 69 |
| 6.6    | Internal Sublayer Service (ISS) .....  | 70 |
| 6.6.1  | Control primitives and parameters .....  | 70 |
| 6.7    | Support of the ISS by specific MAC procedures.....                                 | 70 |
| 6.7.1  | Support of the ISS by IEEE Std 802.3 (Ethernet) .....                              | 70 |
| 6.8    | Enhanced Internal Sublayer Service (EISS) .....                                    | 70 |
| 6.8.1  | Service primitives .....   | 71 |
| 6.8.2  | Status parameters .....  | 72 |
| 6.8.3  | Point-to-point parameters .....  | 72 |
| 6.8.4  | Control primitives and parameters .....  | 72 |
| 6.9    | Support of the EISS .....  | 72 |
| 6.9.1  | Data indications .....   | 74 |
| 6.9.2  | Data requests .....  | 75 |
| 6.9.3  | Priority Code Point encoding .....   | 75 |
| 6.9.4  | Regenerating priority .....  | 77 |
| 6.10   | Support of the ISS/EISS by PIPs .....  | 78 |
| 6.10.1 | Data indications .....   | 80 |
| 6.10.2 | Data requests .....  | 81 |
| 6.10.3 | Priority Code Point encoding .....   | 81 |
| 6.11   | Support of the EISS by CBPs .....  | 82 |
| 6.11.1 | Data indications .....   | 83 |

|        |  |     |
|--------|--|-----|
| 6.11.2 | Data requests .....                                      | 84  |
| 6.11.3 | Priority Code Point decoding .....                       | 85  |
| 6.11.4 | Regenerating priority .....                              | 85  |
| 6.12   | Protocol VLAN classification.....                        | 85  |
| 6.12.1 | Protocol Templates .....                                 | 87  |
| 6.12.2 | Protocol Group Identifiers .....                         | 87  |
| 6.12.3 | Protocol Group Database .....                            | 87  |
| 6.13   | Support of the ISS for attachment to a PBN .....         | 88  |
| 6.13.1 | Data requests .....                                      | 89  |
| 6.13.2 | Data indications .....                                   | 90  |
| 6.14   | Support of the ISS within a system.....                  | 90  |
| 6.15   | Support of the ISS by additional technologies.....       | 90  |
| 6.16   | Filtering services in Bridged Networks .....             | 91  |
| 6.16.1 | Purpose(s) of filtering service provision .....          | 91  |
| 6.16.2 | Goals of filtering service provision .....               | 91  |
| 6.16.3 | Users of filtering services .....                        | 91  |
| 6.16.4 | Basis of service .....                                   | 92  |
| 6.16.5 | Categories of service .....                              | 92  |
| 6.16.6 | Service configuration .....                              | 92  |
| 6.16.7 | Service definition for Extended Filtering Services ..... | 93  |
| 6.17   | EISS Multiplex Entity.....                               | 94  |
| 6.18   | Backbone Service Instance Multiplex Entity.....          | 95  |
| 6.18.1 | Demultiplexing direction .....                           | 96  |
| 6.18.2 | Multiplexing direction .....                             | 97  |
| 6.18.3 | Priority Code Point encoding .....                       | 98  |
| 6.18.4 | Status parameters .....                                  | 98  |
| 6.19   | TESI Multiplex Entity .....                              | 98  |
| 6.20   | Support of the ISS with signaled priority .....          | 99  |
| 6.20.1 | Data indications .....                                   | 100 |
| 6.20.2 | Data requests .....                                      | 100 |
| 6.21   | Infrastructure Segment Multiplex Entity .....            | 100 |
| 7.     | Principles of Virtual Bridged Network operation.....     | 102 |
| 7.1    | Network overview.....                                    | 102 |
| 7.2    | Use of VLANs .....                                       | 103 |
| 7.3    | Active topology.....                                     | 103 |
| 7.4    | VLAN topology .....                                      | 104 |
| 7.5    | Locating end stations .....                              | 105 |
| 7.6    | Ingress, forwarding, and egress rules.....               | 105 |
| 8.     | Principles of Bridge operation .....                     | 107 |
| 8.1    | Bridge operation.....                                    | 107 |
| 8.1.1  | Relay .....  | 107 |
| 8.1.2  | Filtering and relaying information .....                 | 108 |
| 8.1.3  | Duplicate frame prevention .....                         | 108 |
| 8.1.4  | Traffic segregation .....                                | 108 |
| 8.1.5  | Traffic reduction .....                                  | 109 |
| 8.1.6  | Traffic expediting .....                                 | 109 |
| 8.1.7  | Conversion of frame formats .....                        | 109 |
| 8.2    | Bridge architecture.....                                 | 110 |
| 8.3    | Model of operation.....                                  | 112 |
| 8.4    | Active topologies, learning, and forwarding.....         | 115 |
| 8.5    | Bridge Port Transmit and Receive.....                    | 117 |

|         |   |     |
|---------|---|-----|
| 8.5.1   | Bridge Port connectivity .....  | 117 |
| 8.5.2   | TPMR Port connectivity .....  | 118 |
| 8.5.3   | Support of Higher Layer Entities .....                                | 118 |
| 8.6     | The Forwarding Process .....  | 119 |
| 8.6.1   | Active topology enforcement .....                                     | 120 |
| 8.6.2   | Ingress filtering .....   | 121 |
| 8.6.3   | Frame filtering .....   | 121 |
| 8.6.4   | Egress filtering .....  | 124 |
| 8.6.5   | Flow classification and metering .....                                | 124 |
| 8.6.6   | Queuing frames .....  | 125 |
| 8.6.7   | Queue management .....  | 126 |
| 8.6.8   | Transmission selection .....  | 127 |
| 8.7     | The Learning Process.....   | 129 |
| 8.7.1   | Default filtering utility criteria .....                              | 130 |
| 8.7.2   | Enhanced filtering utility criteria .....                             | 130 |
| 8.7.3   | Ageing of Dynamic Filtering Entries .....                             | 130 |
| 8.8     | The Filtering Database (FDB) .....                                    | 131 |
| 8.8.1   | Static Filtering Entries .....  | 134 |
| 8.8.2   | Static VLAN Registration Entries .....                                | 135 |
| 8.8.3   | Dynamic Filtering Entries .....                                       | 136 |
| 8.8.4   | MAC Address Registration Entries .....                                | 136 |
| 8.8.5   | Dynamic VLAN Registration Entries .....                               | 137 |
| 8.8.6   | Default Group filtering behavior .....                                | 137 |
| 8.8.7   | Dynamic Reservation Entries .....                                     | 139 |
| 8.8.8   | Allocation of VIDs to FIDs .....                                      | 139 |
| 8.8.9   | Querying the FDB .....  | 140 |
| 8.8.10  | Determination of the member set for a VID .....                       | 143 |
| 8.8.11  | Permanent Database .....  | 144 |
| 8.8.12  | Connection_Identifier .....   | 144 |
| 8.9     | MST, SPB, and ESP configuration information.....                      | 144 |
| 8.9.1   | MST Configuration Table .....   | 145 |
| 8.9.2   | MST configuration identification .....                                | 146 |
| 8.9.3   | FID to MSTI Allocation Table .....                                    | 146 |
| 8.9.4   | SPT Configuration Identification .....                                | 146 |
| 8.10    | Spanning Tree Protocol Entity.....                                    | 147 |
| 8.11    | MRP entities .....  | 147 |
| 8.12    | Bridge Management Entity.....   | 147 |
| 8.13    | Addressing .....  | 148 |
| 8.13.1  | End stations .....  | 148 |
| 8.13.2  | Bridge Ports .....  | 148 |
| 8.13.3  | Use of LLC by Spanning Tree Protocol Entities .....                   | 148 |
| 8.13.4  | Reserved MAC addresses .....  | 149 |
| 8.13.5  | Group MAC addresses for spanning tree entity .....                    | 149 |
| 8.13.6  | Group MAC addresses for MRP Applications .....                        | 151 |
| 8.13.7  | Bridge Management Entities .....                                      | 151 |
| 8.13.8  | Unique identification of a Bridge .....                               | 152 |
| 8.13.9  | Points of attachment and connectivity for Higher Layer Entities ..... | 152 |
| 8.13.10 | VLAN attachment and connectivity for Higher Layer Entities .....      | 155 |
| 8.13.11 | CFM entities .....  | 156 |
| 9.      | Tagged frame format.....  | 158 |
| 9.1     | Purpose of tagging .....  | 158 |
| 9.2     | Representation and encoding of tag fields .....                       | 158 |

|         |   |     |
|---------|---|-----|
| 9.3     | Tag format.....   | 159 |
| 9.4     | TPID formats .....  | 159 |
| 9.5     | Tag Protocol identification .....   | 159 |
| 9.6     | VLAN Tag Control Information (TCI).....   | 160 |
| 9.7     | Backbone Service Instance Tag Control Information (I-TAG TCI).....                      | 161 |
| 10.     | Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP)..... | 163 |
| 10.1    | MRP overview .....  | 163 |
| 10.2    | MRP architecture .....  | 166 |
| 10.3    | MRP Attribute Propagation (MAP).....  | 167 |
| 10.3.1  | MAP Context .....   | 168 |
| 10.4    | Requirements to be met by MRP .....   | 169 |
| 10.5    | Requirements for interoperability between MRP Participants .....                        | 170 |
| 10.6    | Protocol operation.....   | 171 |
| 10.7    | Protocol specification.....   | 175 |
| 10.7.1  | Notational conventions and abbreviations .....  | 176 |
| 10.7.2  | Registrar Administrative Controls .....   | 178 |
| 10.7.3  | Applicant Administrative Controls .....   | 178 |
| 10.7.4  | Protocol timers .....   | 178 |
| 10.7.5  | Protocol event definitions .....  | 179 |
| 10.7.6  | Protocol Action definitions .....   | 182 |
| 10.7.7  | Applicant state machine .....   | 184 |
| 10.7.8  | Registrar state machine .....   | 185 |
| 10.7.9  | LeaveAll state machine .....  | 185 |
| 10.7.10 | PeriodicTransmission state machine .....  | 186 |
| 10.7.11 | Timer values .....  | 186 |
| 10.7.12 | Operational reporting and statistics .....  | 187 |
| 10.7.13 | Interoperability considerations .....   | 187 |
| 10.8    | Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs).....       | 188 |
| 10.8.1  | Structure .....   | 188 |
| 10.8.2  | Encoding of MRPDU parameters .....  | 190 |
| 10.8.3  | Packing and parsing MRPDUs .....  | 193 |
| 10.9    | Multiple MAC Registration Protocol (MMRP)—Purpose.....                                  | 195 |
| 10.10   | Model of operation.....   | 196 |
| 10.10.1 | Propagation of Group Membership information .....                                       | 197 |
| 10.10.2 | Propagation of Group service requirement information .....                              | 198 |
| 10.10.3 | Source pruning .....  | 198 |
| 10.10.4 | Use of Group service requirement registration by end stations .....                     | 198 |
| 10.11   | Default Group filtering behavior and MMRP propagation.....                              | 198 |
| 10.12   | Definition of the MMRP application.....   | 200 |
| 10.12.1 | Definition of MRP elements .....  | 200 |
| 10.12.2 | Provision and support of Extended Filtering Services .....                              | 202 |
| 10.12.3 | Use of “new” declaration capability .....   | 204 |
| 10.12.4 | Attribute value support requirements .....  | 204 |
| 10.12.5 | Registrar Administrative Controls .....   | 205 |
| 11.     | VLAN topology management.....   | 206 |
| 11.1    | Static and dynamic VLAN configuration .....   | 206 |
| 11.2    | Multiple VLAN Registration Protocol (MVRP).....   | 207 |
| 11.2.1  | MVRP overview .....   | 207 |
| 11.2.2  | VLAN registration service definition .....  | 209 |
| 11.2.3  | Definition of the MVRP application .....  | 210 |
| 11.2.4  | VID translation table .....   | 213 |

|         |  |     |
|---------|--|-----|
| 9.3     | Tag format.....  | 159 |
| 9.4     | TPID formats .....   | 159 |
| 9.5     | Tag Protocol identification .....  | 159 |
| 9.6     | VLAN Tag Control Information (TCI).....  | 160 |
| 9.7     | Backbone Service Instance Tag Control Information (I-TAG TCI).....                       | 161 |
| 10.     | Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP) ..... | 163 |
| 10.1    | MRP overview .....   | 163 |
| 10.2    | MRP architecture .....   | 166 |
| 10.3    | MRP Attribute Propagation (MAP).....   | 167 |
| 10.3.1  | MAP Context .....  | 168 |
| 10.4    | Requirements to be met by MRP .....  | 169 |
| 10.5    | Requirements for interoperability between MRP Participants .....                         | 170 |
| 10.6    | Protocol operation.....  | 171 |
| 10.7    | Protocol specification.....  | 175 |
| 10.7.1  | Notational conventions and abbreviations .....   | 176 |
| 10.7.2  | Registrar Administrative Controls .....  | 178 |
| 10.7.3  | Applicant Administrative Controls .....  | 178 |
| 10.7.4  | Protocol timers .....  | 178 |
| 10.7.5  | Protocol event definitions .....   | 179 |
| 10.7.6  | Protocol Action definitions .....  | 182 |
| 10.7.7  | Applicant state machine .....  | 184 |
| 10.7.8  | Registrar state machine .....  | 185 |
| 10.7.9  | LeaveAll state machine .....   | 185 |
| 10.7.10 | PeriodicTransmission state machine .....   | 186 |
| 10.7.11 | Timer values .....   | 186 |
| 10.7.12 | Operational reporting and statistics .....   | 187 |
| 10.7.13 | Interoperability considerations .....  | 187 |
| 10.8    | Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs).....        | 188 |
| 10.8.1  | Structure .....  | 188 |
| 10.8.2  | Encoding of MRPDU parameters .....   | 190 |
| 10.8.3  | Packing and parsing MRPDUs .....   | 193 |
| 10.9    | Multiple MAC Registration Protocol (MMRP)—Purpose .....                                  | 195 |
| 10.10   | Model of operation.....  | 196 |
| 10.10.1 | Propagation of Group Membership information .....  | 197 |
| 10.10.2 | Propagation of Group service requirement information .....                               | 198 |
| 10.10.3 | Source pruning .....   | 198 |
| 10.10.4 | Use of Group service requirement registration by end stations .....                      | 198 |
| 10.11   | Default Group filtering behavior and MMRP propagation.....                               | 198 |
| 10.12   | Definition of the MMRP application .....   | 200 |
| 10.12.1 | Definition of MRP elements .....   | 200 |
| 10.12.2 | Provision and support of Extended Filtering Services .....                               | 202 |
| 10.12.3 | Use of “new” declaration capability .....  | 204 |
| 10.12.4 | Attribute value support requirements .....   | 204 |
| 10.12.5 | Registrar Administrative Controls .....  | 205 |
| 11.     | VLAN topology management.....  | 206 |
| 11.1    | Static and dynamic VLAN configuration .....  | 206 |
| 11.2    | Multiple VLAN Registration Protocol (MVRP).....  | 207 |
| 11.2.1  | MVRP overview .....  | 207 |
| 11.2.2  | VLAN registration service definition .....   | 209 |
| 11.2.3  | Definition of the MVRP application .....   | 210 |
| 11.2.4  | VID translation table .....  | 213 |

|         |  |     |
|---------|--|-----|
| 11.2.5  | Use of “new” declaration capability .....                        | 213 |
| 11.2.6  | New-Only Participant and Registrar Administrative Controls ..... | 213 |
| 11.2.7  | Attribute value support requirements .....                       | 213 |
| 12.     | Bridge management .....  | 214 |
| 12.1    | Management functions.....  | 214 |
| 12.1.1  | Configuration Management .....                                   | 214 |
| 12.1.2  | Fault Management .....   | 215 |
| 12.1.3  | Performance Management .....                                     | 215 |
| 12.1.4  | Security Management .....  | 215 |
| 12.1.5  | Accounting Management .....                                      | 215 |
| 12.2    | VLAN Bridge objects .....  | 215 |
| 12.3    | Data types.....  | 216 |
| 12.4    | Bridge Management Entity .....                                   | 217 |
| 12.4.1  | Bridge Configuration .....                                       | 217 |
| 12.4.2  | Port configuration .....   | 220 |
| 12.5    | MAC entities.....  | 222 |
| 12.5.1  | ISS Port Number table managed object (optional) .....            | 222 |
| 12.6    | Forwarding process.....  | 222 |
| 12.6.1  | The Port Counters .....  | 223 |
| 12.6.2  | Priority handling .....  | 223 |
| 12.6.3  | Traffic Class Table .....  | 231 |
| 12.7    | Filtering Database (FDB).....                                    | 232 |
| 12.7.1  | The Filtering Database object .....                              | 232 |
| 12.7.2  | A Static Filtering Entry object .....                            | 233 |
| 12.7.3  | A Dynamic Filtering Entry object .....                           | 234 |
| 12.7.4  | A MAC Address Registration Entry object .....                    | 234 |
| 12.7.5  | A VLAN Registration Entry object .....                           | 234 |
| 12.7.6  | Permanent Database object .....                                  | 234 |
| 12.7.7  | General FDB operations .....                                     | 235 |
| 12.8    | Bridge Protocol Entity .....                                     | 237 |
| 12.8.1  | The Protocol Entity .....  | 237 |
| 12.8.2  | Bridge Port .....  | 240 |
| 12.9    | MRP Entities.....  | 244 |
| 12.9.1  | The MRP Timer object .....                                       | 244 |
| 12.9.2  | The MRP Attribute Type object .....                              | 245 |
| 12.9.3  | Periodic state machine objects .....                             | 246 |
| 12.10   | Bridge VLAN managed objects.....                                 | 247 |
| 12.10.1 | Bridge VLAN Configuration managed object .....                   | 247 |
| 12.10.2 | VLAN Configuration managed object .....                          | 252 |
| 12.10.3 | The VID to FID allocation managed object .....                   | 254 |
| 12.11   | MMRP entities.....   | 256 |
| 12.11.1 | MMRP Configuration managed object .....                          | 256 |
| 12.12   | MST configuration entities .....                                 | 258 |
| 12.12.1 | The MSTI List .....  | 258 |
| 12.12.2 | The FID to MSTID Allocation Table .....                          | 259 |
| 12.12.3 | The MST Configuration Table .....                                | 260 |
| 12.13   | Provider Bridge management .....                                 | 262 |
| 12.13.1 | Provider Bridge Port Type managed object .....                   | 263 |
| 12.13.2 | Customer Edge Port Configuration managed object .....            | 264 |
| 12.13.3 | Remote Customer Access Port Configuration managed object .....   | 267 |
| 12.14   | CFM entities .....   | 269 |
| 12.14.1 | Maintenance Domain list managed object .....                     | 270 |

|         |  |     |
|---------|--|-----|
| 12.14.2 | CFM Stack managed object .....                             | 272 |
| 12.14.3 | Default MD Level managed object .....                      | 272 |
| 12.14.4 | Configuration Error List managed object .....              | 274 |
| 12.14.5 | Maintenance Domain managed object .....                    | 274 |
| 12.14.6 | Maintenance Association managed object .....               | 277 |
| 12.14.7 | Maintenance association Endpoint managed object .....      | 279 |
| 12.15   | Backbone Core Bridge (BCB) management.....                 | 286 |
| 12.16   | Backbone Edge Bridge (BEB) management.....                 | 286 |
| 12.16.1 | BEB configuration managed object .....                     | 288 |
| 12.16.2 | BEB/PB/VLAN Bridge Port configuration managed object ..... | 291 |
| 12.16.3 | VIP configuration managed object .....                     | 292 |
| 12.16.4 | PIP configuration managed object .....                     | 293 |
| 12.16.5 | CBP Configuration managed object .....                     | 300 |
| 12.17   | DDCFM entities.....  | 302 |
| 12.17.1 | DDCFM Stack managed object .....                           | 303 |
| 12.17.2 | Reflection Responder managed object .....                  | 303 |
| 12.17.3 | RFM Receiver managed object .....                          | 307 |
| 12.17.4 | Decapsulator Responder managed object .....                | 308 |
| 12.17.5 | SFM Originator managed object .....                        | 310 |
| 12.18   | PBB-TE Protection Switching managed objects .....          | 313 |
| 12.18.1 | TE protection group list managed object .....              | 313 |
| 12.18.2 | TE protection group managed object .....                   | 314 |
| 12.19   | TPMR managed objects.....                                  | 316 |
| 12.19.1 | TPMR management entity .....                               | 317 |
| 12.19.2 | MAC and PHY entities .....                                 | 319 |
| 12.19.3 | Forwarding Process .....                                   | 319 |
| 12.19.4 | MAC Status Propagation Entity (MSPE) .....                 | 324 |
| 12.20   | Management entities for FQTSS .....                        | 326 |
| 12.20.1 | The Bandwidth Availability Parameter Table .....           | 326 |
| 12.20.2 | The Transmission Selection Algorithm Table .....           | 327 |
| 12.20.3 | The Priority Regeneration Override Table .....             | 327 |
| 12.21   | Congestion Notification managed objects .....              | 327 |
| 12.21.1 | CN component managed object .....                          | 328 |
| 12.21.2 | CN component priority managed object .....                 | 328 |
| 12.21.3 | CN Port priority managed object .....                      | 329 |
| 12.21.4 | Congestion Point managed object .....                      | 330 |
| 12.21.5 | Reaction Point port priority managed object .....          | 331 |
| 12.21.6 | Reaction Point group managed object .....                  | 331 |
| 12.22   | Stream Reservation Protocol (SRP) entities .....           | 332 |
| 12.22.1 | SRP Bridge Base Table .....                                | 332 |
| 12.22.2 | SRP Bridge Port Table .....                                | 332 |
| 12.22.3 | SRP Latency Parameter Table .....                          | 333 |
| 12.22.4 | SRP Stream Table .....                                     | 333 |
| 12.22.5 | SRP Reservations Table .....                               | 333 |
| 12.23   | Priority-based Flow Control objects .....                  | 334 |
| 12.24   | 1:1 PBB-TE IPS managed objects .....                       | 335 |
| 12.24.1 | IPG list managed object .....                              | 335 |
| 12.24.2 | IPG managed object .....                                   | 336 |
| 12.25   | Shortest Path Bridging managed objects .....               | 339 |
| 12.25.1 | The SPB System managed object .....                        | 340 |
| 12.25.2 | The SPB MTID Static managed object .....                   | 342 |
| 12.25.3 | The SPB Topology Instance Dynamic managed object .....     | 343 |
| 12.25.4 | The SPB ECT Static Entry managed object .....              | 344 |
| 12.25.5 | The SPB ECT Dynamic Entry managed object .....             | 345 |

|          |  |     |
|----------|--|-----|
| 12.25.6  | The SPB Adjacency Static Entry managed object .....    | 346 |
| 12.25.7  | The SPB Adjacency Dynamic Entry managed object .....   | 347 |
| 12.25.8  | The SPBM BSI Static Entry managed object .....         | 348 |
| 12.25.9  | The SPB Topology Node Table managed object .....       | 349 |
| 12.25.10 | The SPB Topology ECT Table managed object .....        | 350 |
| 12.25.11 | The SPB Topology Edge Table managed object .....       | 351 |
| 12.25.12 | The SPBM Topology Service Table managed object .....   | 352 |
| 12.25.13 | The SPBV Topology Service Table managed object .....   | 353 |
| 12.25.14 | The ECMP ECT Static Entry managed object .....         | 354 |
| 12.26    | Edge Virtual Bridging (EVB) management.....            | 355 |
| 12.26.1  | EVB system base table .....                            | 358 |
| 12.26.2  | SBP table entry .....                                  | 360 |
| 12.26.3  | VSI table entry .....                                  | 361 |
| 12.26.4  | S-channel configuration and management .....           | 363 |
| 12.26.5  | ER management .....                                    | 366 |
| 12.27    | Edge Control Protocol (ECP) management.....            | 367 |
| 12.27.1  | ECP table entry .....                                  | 367 |
| 13.      | Spanning tree protocols.....                           | 368 |
| 13.1     | Protocol design requirements.....                      | 369 |
| 13.2     | Protocol support requirements.....                     | 370 |
| 13.2.1   | MSTP support requirements .....                        | 370 |
| 13.2.2   | SPB support requirements .....                         | 370 |
| 13.3     | Protocol design goals.....                             | 371 |
| 13.4     | RSTP overview.....                                     | 371 |
| 13.4.1   | Computation of the active topology .....               | 372 |
| 13.4.2   | Example topologies .....                               | 373 |
| 13.5     | MSTP overview.....                                     | 376 |
| 13.5.1   | Example topologies .....                               | 377 |
| 13.5.2   | Relationship of MSTP to RSTP .....                     | 380 |
| 13.5.3   | Modeling an MST or SPT Region as a single Bridge ..... | 380 |
| 13.6     | SPB overview.....                                      | 381 |
| 13.7     | Compatibility and interoperability.....                | 382 |
| 13.7.1   | Designated Port selection .....                        | 382 |
| 13.7.2   | Force Protocol Version .....                           | 382 |
| 13.8     | MST Configuration Identifier (MCID).....               | 383 |
| 13.9     | Spanning tree priority vectors.....                    | 384 |
| 13.10    | CIST Priority Vector calculations.....                 | 386 |
| 13.11    | MST Priority Vector calculations.....                  | 388 |
| 13.12    | Port Role assignments.....                             | 390 |
| 13.13    | Stable connectivity.....                               | 391 |
| 13.14    | Communicating spanning tree information .....          | 392 |
| 13.15    | Changing spanning tree information.....                | 393 |
| 13.16    | Changing Port States with RSTP or MSTP.....            | 394 |
| 13.16.1  | Subtree connectivity and priority vectors .....        | 395 |
| 13.16.2  | Root Port transition to Forwarding .....               | 395 |
| 13.16.3  | Designated Port transition to Forwarding .....         | 395 |
| 13.16.4  | Master Port transition to Forwarding .....             | 397 |
| 13.17    | Changing Port States with SPB .....                    | 399 |
| 13.17.1  | Agreement Digest .....                                 | 402 |
| 13.18    | Managing spanning tree topologies.....                 | 402 |
| 13.19    | Updating learned station location information .....    | 403 |
| 13.20    | Managing reconfiguration.....                          | 405 |

|          |  |     |
|----------|--|-----|
| 13.21    | Partial and disputed connectivity .....    | 406 |
| 13.22    | In-service upgrades .....                  | 406 |
| 13.23    | Fragile Bridges.....                       | 408 |
| 13.24    | Spanning tree protocol state machines..... | 408 |
| 13.25    | State machine timers .....                 | 410 |
| 13.25.1  | edgeDelayWhile .....                       | 411 |
| 13.25.2  | fdWhile .....                              | 411 |
| 13.25.3  | helloWhen .....                            | 411 |
| 13.25.4  | mdelayWhile .....                          | 411 |
| 13.25.5  | rbWhile .....                              | 411 |
| 13.25.6  | rcvdInfoWhile .....                        | 411 |
| 13.25.7  | rrWhile .....                              | 412 |
| 13.25.8  | tcDetected .....                           | 412 |
| 13.25.9  | tcWhile .....                              | 412 |
| 13.25.10 | pseudoInfoHelloWhen .....                  | 412 |
| 13.26    | Per Bridge variables.....                  | 412 |
| 13.26.1  | agreementDigest .....                      | 413 |
| 13.26.2  | BridgeIdentifier .....                     | 413 |
| 13.26.3  | BridgePriority .....                       | 413 |
| 13.26.4  | BridgeTimes .....                          | 413 |
| 13.26.5  | ForceProtocolVersion .....                 | 414 |
| 13.26.6  | MigrateTime .....                          | 414 |
| 13.26.7  | MstConfigId .....                          | 414 |
| 13.26.8  | AuxMstConfigId .....                       | 414 |
| 13.26.9  | rootPortId .....                           | 414 |
| 13.26.10 | rootPriority .....                         | 414 |
| 13.26.11 | rootTimes .....                            | 414 |
| 13.26.12 | TxHoldCount .....                          | 414 |
| 13.27    | Per port variables .....                   | 414 |
| 13.27.1  | AdminEdge .....                            | 417 |
| 13.27.2  | ageingTime .....                           | 417 |
| 13.27.3  | agree .....                                | 417 |
| 13.27.4  | agreed .....                               | 417 |
| 13.27.5  | agreedAbove .....                          | 417 |
| 13.27.6  | agreedDigest .....                         | 417 |
| 13.27.7  | agreedDigestValid .....                    | 417 |
| 13.27.8  | agreeDigest .....                          | 417 |
| 13.27.9  | agreeDigestValid .....                     | 417 |
| 13.27.10 | agreedMisorder .....                       | 418 |
| 13.27.11 | agreedN .....                              | 418 |
| 13.27.12 | agreedND .....                             | 418 |
| 13.27.13 | agreedPriority .....                       | 418 |
| 13.27.14 | agreedTopology .....                       | 418 |
| 13.27.15 | agreementOutstanding .....                 | 418 |
| 13.27.16 | agreeN .....                               | 418 |
| 13.27.17 | agreeND .....                              | 418 |
| 13.27.18 | AutoEdge .....                             | 418 |
| 13.27.19 | AutoIsolate .....                          | 419 |
| 13.27.20 | designatedPriority .....                   | 419 |
| 13.27.21 | designatedTimes .....                      | 419 |
| 13.27.22 | disputed .....                             | 419 |
| 13.27.23 | enableBPDUrx .....                         | 419 |
| 13.27.24 | enableBPDUtx .....                         | 419 |
| 13.27.25 | ExternalPortPathCost .....                 | 419 |

|          |   |     |
|----------|---|-----|
| 13.27.26 | isL2gp                                  | 419 |
| 13.27.27 | isolate                                 | 420 |
| 13.27.28 | fdbFlush                                | 420 |
| 13.27.29 | forward                                 | 420 |
| 13.27.30 | forwarding                              | 420 |
| 13.27.31 | infoInternal                            | 420 |
| 13.27.32 | infoIs                                  | 420 |
| 13.27.33 | InternalPortPathCost                    | 420 |
| 13.27.34 | learn                                   | 421 |
| 13.27.35 | learning                                | 421 |
| 13.27.36 | master                                  | 421 |
| 13.27.37 | mastered                                | 421 |
| 13.27.38 | mcheck                                  | 421 |
| 13.27.39 | msgPriority                             | 421 |
| 13.27.40 | msgTimes                                | 421 |
| 13.27.41 | neighbourPriority                       | 422 |
| 13.27.42 | newInfo                                 | 422 |
| 13.27.43 | newInfoMsti                             | 422 |
| 13.27.44 | operEdge                                | 422 |
| 13.27.45 | portEnabled                             | 422 |
| 13.27.46 | portId                                  | 422 |
| 13.27.47 | portPriority                            | 422 |
| 13.27.48 | portTimes                               | 423 |
| 13.27.49 | proposed                                | 423 |
| 13.27.50 | proposing                               | 423 |
| 13.27.51 | pseudoRootId                            | 423 |
| 13.27.52 | rcvdBPDU                                | 423 |
| 13.27.53 | rcvdInfo                                | 423 |
| 13.27.54 | rcvdInternal                            | 423 |
| 13.27.55 | rcvdMsg                                 | 423 |
| 13.27.56 | rcvdRSTP                                | 423 |
| 13.27.57 | rcvdSTP                                 | 423 |
| 13.27.58 | rcvdTc                                  | 423 |
| 13.27.59 | rcvdTcAck                               | 423 |
| 13.27.60 | rcvdTcn                                 | 424 |
| 13.27.61 | reRoot                                  | 424 |
| 13.27.62 | reselect                                | 424 |
| 13.27.63 | restrictedDomainRole                    | 424 |
| 13.27.64 | restrictedRole                          | 424 |
| 13.27.65 | restrictedTcn                           | 424 |
| 13.27.66 | role                                    | 424 |
| 13.27.67 | selected                                | 424 |
| 13.27.68 | selectedRole                            | 424 |
| 13.27.69 | sendRSTP                                | 425 |
| 13.27.70 | sync                                    | 425 |
| 13.27.71 | synced                                  | 425 |
| 13.27.72 | tcAck                                   | 425 |
| 13.27.73 | tcProp                                  | 425 |
| 13.27.74 | tick                                    | 425 |
| 13.27.75 | txCount                                 | 425 |
| 13.27.76 | updtInfo                                | 425 |
| 13.28    | State machine conditions and parameters | 425 |
| 13.28.1  | allSptAgree                             | 426 |
| 13.28.2  | allSynced                               | 426 |

|          |                                       |     |
|----------|---------------------------------------|-----|
| 13.28.3  | allTransmitReady                      | 426 |
| 13.28.4  | BestAgreementPriority                 | 426 |
| 13.28.5  | cist                                  | 426 |
| 13.28.6  | cistRootPort                          | 426 |
| 13.28.7  | cistDesignatedPort                    | 427 |
| 13.28.8  | EdgeDelay                             | 427 |
| 13.28.9  | forwardDelay                          | 427 |
| 13.28.10 | FwdDelay                              | 427 |
| 13.28.11 | HelloTime                             | 427 |
| 13.28.12 | MaxAge                                | 427 |
| 13.28.13 | msti                                  | 427 |
| 13.28.14 | mstiDesignatedOrTCpropagatingRootPort | 427 |
| 13.28.15 | mstiMasterPort                        | 427 |
| 13.28.16 | operPointToPoint                      | 427 |
| 13.28.17 | rcvdAnyMsg                            | 427 |
| 13.28.18 | rcvdCistMsg                           | 427 |
| 13.28.19 | rcvdMstiMsg                           | 428 |
| 13.28.20 | reRooted                              | 428 |
| 13.28.21 | rstpVersion                           | 428 |
| 13.28.22 | spt                                   | 428 |
| 13.28.23 | stpVersion                            | 428 |
| 13.28.24 | updtCistInfo                          | 428 |
| 13.28.25 | updtMstiInfo                          | 428 |
| 13.29    | State machine procedures              | 428 |
| 13.29.1  | betterorsameInfo(newInfoIs)           | 429 |
| 13.29.2  | clearAllRcvdMsgs()                    | 429 |
| 13.29.3  | clearReselectTree()                   | 429 |
| 13.29.4  | disableForwarding()                   | 430 |
| 13.29.5  | disableLearning()                     | 430 |
| 13.29.6  | enableForwarding()                    | 430 |
| 13.29.7  | enableLearning()                      | 430 |
| 13.29.8  | fromSameRegion()                      | 430 |
| 13.29.9  | newTcDetected()                       | 430 |
| 13.29.10 | newTcWhile()                          | 430 |
| 13.29.11 | pseudoRcvMsgs()                       | 431 |
| 13.29.12 | rcvInfo()                             | 431 |
| 13.29.13 | rcvMsgs()                             | 432 |
| 13.29.14 | rcvAgreements()                       | 432 |
| 13.29.15 | recordAgreement()                     | 432 |
| 13.29.16 | recordDispute()                       | 433 |
| 13.29.17 | recordMastered()                      | 433 |
| 13.29.18 | recordPriority()                      | 433 |
| 13.29.19 | recordProposal()                      | 433 |
| 13.29.20 | recordTimes()                         | 433 |
| 13.29.21 | setReRootTree()                       | 434 |
| 13.29.22 | setSelectedTree()                     | 434 |
| 13.29.23 | setSyncTree()                         | 434 |
| 13.29.24 | setTcFlags()                          | 434 |
| 13.29.25 | setTcPropTree()                       | 434 |
| 13.29.26 | syncMaster()                          | 434 |
| 13.29.27 | txConfig()                            | 434 |
| 13.29.28 | txRstp()                              | 435 |
| 13.29.29 | txTcn()                               | 435 |
| 13.29.30 | updtAgreement()                       | 435 |

|          |   |     |
|----------|---|-----|
| 13.29.31 | updtBPDUVersion()   | 436 |
| 13.29.32 | updtDigest()  | 436 |
| 13.29.33 | updtRcvdInfoWhile()   | 437 |
| 13.29.34 | updtRolesTree()   | 438 |
| 13.29.35 | uptRolesDisabledTree()  | 439 |
| 13.30    | The Port Timers state machine                                       | 440 |
| 13.31    | Port Receive state machine  | 440 |
| 13.32    | Port Protocol Migration state machine                               | 441 |
| 13.33    | Bridge Detection state machine                                      | 441 |
| 13.34    | Port Transmit state machine   | 442 |
| 13.35    | Port Information state machine                                      | 443 |
| 13.36    | Port Role Selection state machine                                   | 444 |
| 13.37    | Port Role Transitions state machine                                 | 444 |
| 13.38    | Port State Transition state machine                                 | 449 |
| 13.38.1  | Port State transitions for the CIST and MSTIs                       | 450 |
| 13.38.2  | Port State transitions for SPTs                                     | 450 |
| 13.39    | Topology Change state machine                                       | 451 |
| 13.40    | Layer 2 Gateway Port Receive state machine                          | 452 |
| 13.41    | CEP spanning tree operation   | 452 |
| 13.41.1  | PEP operPointToPointMAC and operEdge                                | 452 |
| 13.41.2  | updtRolesTree()   | 453 |
| 13.41.3  | setReRootTree(), setSyncTree(), setTcPropTree()                     | 453 |
| 13.41.4  | allSynced, reRooted   | 453 |
| 13.41.5  | Configuration parameters  | 453 |
| 13.42    | Virtual Instance Port (VIP) spanning tree operation                 | 454 |
| 14.      | Encoding of Bridge Protocol Data Units (BPDUs)                      | 455 |
| 14.1     | BPDUs Structure   | 455 |
| 14.1.1   | Transmission and representation of octets                           | 455 |
| 14.1.2   | Common BPDU fields  | 457 |
| 14.2     | Encoding of parameter types   | 457 |
| 14.2.1   | Encoding of Protocol Identifiers                                    | 457 |
| 14.2.2   | Encoding of Protocol Version Identifiers                            | 457 |
| 14.2.3   | Encoding of BPDU types  | 457 |
| 14.2.4   | Encoding of flags   | 457 |
| 14.2.5   | Encoding of Bridge Identifiers                                      | 457 |
| 14.2.6   | Encoding of External Root Path Cost and Internal Root Path Cost     | 458 |
| 14.2.7   | Encoding of Port Identifiers  | 458 |
| 14.2.8   | Encoding of Timer Values  | 459 |
| 14.2.9   | Encoding of Port Role values  | 459 |
| 14.2.10  | Encoding of Length Values   | 459 |
| 14.2.11  | Encoding of Hop Counts  | 459 |
| 14.3     | Transmission of BPDUs   | 459 |
| 14.4     | Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs | 460 |
| 14.4.1   | MSTI Configuration Messages   | 461 |
| 14.5     | Validation of received BPDUs  | 462 |
| 14.6     | Validation and interoperability                                     | 463 |
| 15.      | Support of the MAC Service by PBNs                                  | 465 |
| 15.1     | Service transparency  | 465 |
| 15.2     | Customer service interfaces   | 466 |
| 15.3     | Port-based service interface  | 466 |
| 15.4     | C-tagged service interface  | 467 |

|         |   |     |
|---------|---|-----|
| 15.5    | S-tagged service interface .....                                      | 468 |
| 15.6    | Remote customer service interfaces (RCSIs) .....                      | 469 |
| 15.7    | Service instance segregation .....                                    | 472 |
| 15.8    | Service instance selection and identification .....                   | 472 |
| 15.9    | Service priority selection .....                                      | 473 |
| 15.10   | Service access protection .....                                       | 474 |
| 16.     | Principles of Provider Bridged Network (PBN) operation .....          | 475 |
| 16.1    | PBN overview .....  | 475 |
| 16.2    | Provider Bridged Network (PBN) .....                                  | 476 |
| 16.3    | Service instance connectivity .....                                   | 479 |
| 16.4    | Service provider learning of customer end station addresses .....     | 480 |
| 16.5    | Detection of connectivity loops through attached networks .....       | 480 |
| 16.6    | Network management .....  | 481 |
| 17.     | Management Information Base (MIB) .....                               | 482 |
| 17.1    | Internet Standard Management Framework .....                          | 482 |
| 17.2    | Structure of the MIB .....  | 482 |
| 17.2.1  | Structure of the IEEE8021-TC-MIB .....                                | 483 |
| 17.2.2  | Structure of the IEEE8021-BRIDGE-MIB .....                            | 485 |
| 17.2.3  | Structure of the IEEE8021-SPANNING-TREE MIB .....                     | 490 |
| 17.2.4  | Structure of the IEEE8021-Q-BRIDGE-MIB .....                          | 492 |
| 17.2.5  | Structure of the IEEE8021-PB-MIB .....                                | 499 |
| 17.2.6  | Structure of the IEEE8021-MSTP-MIB .....                              | 500 |
| 17.2.7  | Structure of the IEEE8021-CFM-MIB .....                               | 503 |
| 17.2.8  | Structure of the IEEE8021-PBB-MIB .....                               | 509 |
| 17.2.9  | Structure of the IEEE8021-DDCFM-MIBs .....                            | 512 |
| 17.2.10 | Structure of the IEEE8021-PBBTE-MIB .....                             | 514 |
| 17.2.11 | Structure of the TPMR MIB .....                                       | 517 |
| 17.2.12 | Structure of the IEEE8021-FQTSS-MIB .....                             | 519 |
| 17.2.13 | Structure of the Congestion Notification MIB .....                    | 520 |
| 17.2.14 | Structure of the IEEE8021-SRP-MIB .....                               | 522 |
| 17.2.15 | Structure of the MVRP extension MIB .....                             | 524 |
| 17.2.16 | Structure of the MIRP MIB .....                                       | 524 |
| 17.2.17 | Structure of the PFC MIB .....  | 525 |
| 17.2.18 | Structure of the IEEE80221-TEIPS MIB .....                            | 525 |
| 17.2.19 | Structure of the IEEE8021-SPB-MIB .....                               | 527 |
| 17.2.20 | Structure of the IEEE8021-EVB-MIB .....                               | 531 |
| 17.2.21 | Structure of the IEEE8021-ECMP-MIB .....                              | 534 |
| 17.3    | Relationship to other MIBs .....                                      | 535 |
| 17.3.1  | Relationship of the IEEE8021-TC-MIB to other MIB modules .....        | 535 |
| 17.3.2  | Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules .....    | 536 |
| 17.3.3  | Relationship of the IEEE8021-RSTP MIB to other MIB modules .....      | 538 |
| 17.3.4  | Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules .....  | 538 |
| 17.3.5  | Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules ..... | 540 |
| 17.3.6  | Relationship of the IEEE8021-MSTP-MIB to other MIB modules .....      | 540 |
| 17.3.7  | Relationship of the IEEE8021-CFM-MIB to other MIB modules .....       | 540 |
| 17.3.8  | Relationship of the IEEE8021-PBB-MIB to other MIB modules .....       | 541 |
| 17.3.9  | Relationship of the IEEE8021-DDCFM to other MIB modules .....         | 543 |
| 17.3.10 | Relationship of the IEEE8021-PBBTE-MIB to other MIB modules .....     | 543 |
| 17.3.11 | Relationship of the TPMR MIB to other MIB modules .....               | 543 |
| 17.3.12 | Relationship of the IEEE8021-FQTSS-MIB to other MIB modules .....     | 544 |
| 17.3.13 | Relationship of the IEEE802-CN-MIB to other MIB modules .....         | 544 |

|         |   |     |
|---------|---|-----|
| 17.3.14 | Relationship of the IEEE8021-SRP-MIB to other MIB modules .....         | 544 |
| 17.3.15 | Relationship of the IEEE8021-MVRPX-MIB to other MIB modules .....       | 544 |
| 17.3.16 | Relationship of the IEEE8021-MIRP-MIB to other MIB modules .....        | 545 |
| 17.3.17 | Relationship of the PFC MIB to other MIB modules .....                  | 545 |
| 17.3.18 | Relationship of the IEEE8021-TEIPS-MIB to other MIB modules .....       | 545 |
| 17.3.19 | Relationship of the of the IEEE8021-SPB-MIB to other MIB modules .....  | 545 |
| 17.3.20 | Relationship of the IEEE8021-EVB-MIB to other MIB modules .....         | 545 |
| 17.3.21 | Relationship of the of the IEEE8021-ECMP-MIB to other MIB modules ..... | 545 |
| 17.4    | Security considerations .....   | 546 |
| 17.4.1  | Security considerations of the IEEE8021-TC-MIB .....                    | 546 |
| 17.4.2  | Security considerations of the IEEE8021-BRIDGE-MIB .....                | 546 |
| 17.4.3  | Security considerations of the IEEE8021-SPANNING-TREE MIB .....         | 547 |
| 17.4.4  | Security considerations of the IEEE8021-Q-BRIDGE-MIB .....              | 548 |
| 17.4.5  | Security considerations of the IEEE8021-PB-MIB .....                    | 549 |
| 17.4.6  | Security considerations of the IEEE8021-MSTP-MIB .....                  | 549 |
| 17.4.7  | Security considerations of the IEEE8021-CFM-MIB .....                   | 549 |
| 17.4.8  | Security considerations of the IEEE8021-PBB-MIB .....                   | 552 |
| 17.4.9  | Security considerations of the IEEE8021-DDCFM-MIB .....                 | 552 |
| 17.4.10 | Security considerations of the IEEE8021-PBBTE-MIB .....                 | 553 |
| 17.4.11 | Security considerations of the TPMR MIB .....                           | 554 |
| 17.4.12 | Security considerations of the IEEE8021-FQTSS-MIB .....                 | 554 |
| 17.4.13 | Security considerations of the Congestion Notification MIB .....        | 555 |
| 17.4.14 | Security considerations of the IEEE8021-SRP-MIB .....                   | 556 |
| 17.4.15 | Security considerations of the IEEE8021-MVRPX-MIB .....                 | 557 |
| 17.4.16 | Security considerations of the IEEE8021-MIRP-MIB .....                  | 557 |
| 17.4.17 | Security considerations for the PFC MIB .....                           | 558 |
| 17.4.18 | Security considerations of the IEEE8021-TEIPS-MIB .....                 | 558 |
| 17.4.19 | Security considerations of the IEEE8021-SPB-MIB .....                   | 558 |
| 17.4.20 | Security considerations of the IEEE8021-EVB-MIB .....                   | 559 |
| 17.4.21 | Security considerations of the IEEE8021-ECMP-MIB .....                  | 560 |
| 17.5    | Dynamic component and Port creation .....                               | 561 |
| 17.5.1  | Overview of the dynamically created Bridge entities .....               | 561 |
| 17.5.2  | Component creation .....  | 562 |
| 17.5.3  | Port creation .....   | 563 |
| 17.6    | MIB operations for service interface configuration .....                | 573 |
| 17.6.1  | Provisioning PBN service interfaces .....                               | 573 |
| 17.6.2  | Provisioning Backbone Bridged Network service interfaces .....          | 576 |
| 17.7    | MIB modules, .....  | 582 |
| 17.7.1  | Definitions for the IEEE8021-TC-MIB module .....                        | 582 |
| 17.7.2  | Definitions for the IEEE8021-BRIDGE-MIB module .....                    | 593 |
| 17.7.3  | Definitions for the IEEE8021-SPANNING-TREE-MIB module .....             | 633 |
| 17.7.4  | Definitions for the IEEE8021-Q-BRIDGE-MIB module .....                  | 651 |
| 17.7.5  | Definitions for the IEEE8021-PB-MIB module .....                        | 697 |
| 17.7.6  | Definitions for the IEEE8021-MSTP-MIB module .....                      | 715 |
| 17.7.7  | Definitions for the CFM MIB modules .....                               | 744 |
| 17.7.8  | Definitions for the IEEE8021-PBB-MIB module .....                       | 826 |
| 17.7.9  | Definitions for the IEEE8021-DDCFM-MIB module .....                     | 849 |
| 17.7.10 | Definitions for the IEEE8021-PBBTE-MIB module .....                     | 867 |
| 17.7.11 | Definitions for the IEEE8021-TPMR-MIB module .....                      | 884 |
| 17.7.12 | Definitions for the IEEE8021-FQTSS-MIB module .....                     | 898 |
| 17.7.13 | Definitions for the IEEE8021-CN-MIB module .....                        | 909 |
| 17.7.14 | Definitions for the IEEE8021-SRP-MIB module .....                       | 945 |
| 17.7.15 | Definitions for the IEEE8021-MVRPX-MIB module .....                     | 961 |
| 17.7.16 | Definitions for the IEEE8021-MIRP-MIB module .....                      | 966 |

|         |   |      |
|---------|---|------|
| 17.7.17 | Definitions for the IEEE8021-PFC-MIB module .....           | 972  |
| 17.7.18 | Definitions for the IEEE8021-TEIPS-V2-MIB module .....      | 976  |
| 17.7.19 | Definitions for the IEEE8021-SPB-MIB module .....           | 990  |
| 17.7.20 | Definitions for the IEEE8021-EVB-MIB module .....           | 1027 |
| 17.7.21 | Definitions for the IEEE8021-ECMP-MIB module .....          | 1056 |
| 18.     | Principles of Connectivity Fault Management operation ..... | 1064 |
| 18.1    | Maintenance Domains and DoSAPs .....                        | 1065 |
| 18.2    | Service instances and MAs .....                             | 1067 |
| 18.3    | Maintenance Domain Levels .....                             | 1068 |
| 19.     | CFM entity operation .....                                  | 1072 |
| 19.1    | Maintenance Points .....                                    | 1072 |
| 19.2    | MA Endpoints (MEPs) .....                                   | 1073 |
| 19.2.1  | MEP identification .....                                    | 1073 |
| 19.2.2  | MEP functions .....   | 1074 |
| 19.2.3  | MEP architecture .....                                      | 1074 |
| 19.2.4  | MP Type Demultiplexer .....                                 | 1076 |
| 19.2.5  | MP Multiplexer .....  | 1076 |
| 19.2.6  | MP Level Demultiplexer .....                                | 1076 |
| 19.2.7  | MP OpCode Demultiplexer .....                               | 1076 |
| 19.2.8  | MEP Continuity Check Receiver .....                         | 1077 |
| 19.2.9  | MEP Continuity Check Initiator .....                        | 1077 |
| 19.2.10 | MP Loopback Responder .....                                 | 1078 |
| 19.2.11 | MEP Loopback Initiator .....                                | 1078 |
| 19.2.12 | MEP Linktrace Initiator .....                               | 1078 |
| 19.2.13 | MEP LTI SAP .....   | 1078 |
| 19.2.14 | MEP Linktrace SAP .....                                     | 1078 |
| 19.2.15 | MEP CCM Database .....                                      | 1078 |
| 19.2.16 | MEP Fault Notification Generator .....                      | 1078 |
| 19.2.17 | MEP Decapsulator Responder (DR) .....                       | 1079 |
| 19.2.18 | MEP RFM Receiver .....                                      | 1079 |
| 19.3    | MIP Half Function .....                                     | 1079 |
| 19.3.1  | MHF identification .....                                    | 1079 |
| 19.3.2  | MHF functions .....   | 1079 |
| 19.3.3  | MHF architecture .....                                      | 1080 |
| 19.3.4  | MHF Level Demultiplexer .....                               | 1080 |
| 19.3.5  | MHF Type Demultiplexer .....                                | 1080 |
| 19.3.6  | MHF OpCode Demultiplexer .....                              | 1080 |
| 19.3.7  | MHF Multiplexer .....                                       | 1080 |
| 19.3.8  | MHF Loopback Responder .....                                | 1080 |
| 19.3.9  | MHF Continuity Check Receiver .....                         | 1081 |
| 19.3.10 | MIP CCM Database .....                                      | 1081 |
| 19.3.11 | MHF Linktrace SAP .....                                     | 1082 |
| 19.3.12 | MHF DR .....  | 1082 |
| 19.3.13 | MHF RFM Receiver .....                                      | 1082 |
| 19.4    | MP addressing .....   | 1082 |
| 19.5    | Linktrace Output Multiplexer (LOM) .....                    | 1083 |
| 19.6    | Linktrace Responder .....                                   | 1083 |
| 20.     | CFM protocols .....   | 1085 |
| 20.1    | Continuity Check protocol .....                             | 1086 |

|         |  |      |
|---------|--|------|
| 20.1.1  | MAC status reporting in the CCM .....              | 1088 |
| 20.1.2  | Defects and Fault Alarms .....                     | 1088 |
| 20.1.3  | CCM reception .....                                | 1089 |
| 20.2    | Loopback protocol .....                            | 1089 |
| 20.2.1  | LBM transmission .....                             | 1090 |
| 20.2.2  | LBM reception and LBR transmission .....           | 1090 |
| 20.2.3  | LBR reception .....                                | 1091 |
| 20.3    | Linktrace protocol .....                           | 1091 |
| 20.3.1  | LTM origination .....                              | 1092 |
| 20.3.2  | LTM reception, forwarding, and replying .....      | 1093 |
| 20.3.3  | LTR reception .....                                | 1094 |
| 20.4    | CFM state machines .....                           | 1095 |
| 20.5    | CFM state machine timers .....                     | 1095 |
| 20.5.1  | LTFwhile .....                                     | 1097 |
| 20.5.2  | CCIwhile .....                                     | 1097 |
| 20.5.3  | errorCCMwhile .....                                | 1097 |
| 20.5.4  | xconCCMwhile .....                                 | 1097 |
| 20.5.5  | LBIwhile .....                                     | 1097 |
| 20.5.6  | FNGwhile .....                                     | 1097 |
| 20.5.7  | mmCCMwhile .....                                   | 1097 |
| 20.5.8  | mmLocwhile .....                                   | 1097 |
| 20.5.9  | mmFNGwhile .....                                   | 1097 |
| 20.5.10 | rMEPwhile .....                                    | 1097 |
| 20.6    | CFM procedures .....                               | 1098 |
| 20.6.1  | CCMtime() .....                                    | 1098 |
| 20.7    | Maintenance Domain variable .....                  | 1098 |
| 20.7.1  | mdLevel .....                                      | 1098 |
| 20.8    | MA variables .....                                 | 1098 |
| 20.8.1  | CCMinterval .....                                  | 1098 |
| 20.9    | MEP variables .....                                | 1098 |
| 20.9.1  | MEPactive .....                                    | 1099 |
| 20.9.2  | enableRmepDefect .....                             | 1099 |
| 20.9.3  | MAdefectIndication .....                           | 1100 |
| 20.9.4  | allRMEPsDead .....                                 | 1100 |
| 20.9.5  | lowestAlarmPri .....                               | 1100 |
| 20.9.6  | presentRDI .....                                   | 1100 |
| 20.9.7  | MEPprimaryVID .....                                | 1100 |
| 20.9.8  | presentTraffic .....                               | 1100 |
| 20.9.9  | presentmmLoc .....                                 | 1100 |
| 20.9.10 | ISpresentTraffic .....                             | 1101 |
| 20.9.11 | ISpresentmmLoc .....                               | 1101 |
| 20.9.12 | EpMEP .....  | 1101 |
| 20.10   | MEP Continuity Check Initiator variables .....     | 1101 |
| 20.10.1 | CCIenabled .....                                   | 1101 |
| 20.10.2 | CCIsentCCMs .....                                  | 1101 |
| 20.10.3 | MACstatusChanged .....                             | 1101 |
| 20.10.4 | Npaths .....                                       | 1101 |
| 20.10.5 | flowHash[ ] .....                                  | 1102 |
| 20.10.6 | pathN .....  | 1102 |
| 20.10.7 | CCMcnt .....                                       | 1102 |
| 20.11   | MEP Continuity Check Initiator procedures .....    | 1102 |
| 20.11.1 | xmitCCM() .....                                    | 1102 |
| 20.12   | MEP Continuity Check Initiator state machine ..... | 1103 |
| 20.13   | MHF Continuity Check Receiver variables .....      | 1103 |

|          |   |      |
|----------|---|------|
| 20.13.1  | MHFrecvdCCM .....                                 | 1104 |
| 20.13.2  | MHFCCMPDU .....                                   | 1104 |
| 20.14    | MHF Continuity Check Receiver procedures .....    | 1104 |
| 20.14.1  | MHFprocessCCM() .....                             | 1104 |
| 20.15    | MHF Continuity Check Receiver state machine ..... | 1104 |
| 20.16    | MEP Continuity Check Receiver variables .....     | 1104 |
| 20.16.1  | CCMreceivedEqual .....                            | 1105 |
| 20.16.2  | CCMequalPDU .....                                 | 1105 |
| 20.16.3  | CCMreceivedLow .....                              | 1105 |
| 20.16.4  | CCMlowPDU .....                                   | 1105 |
| 20.16.5  | recvdMacAddress .....                             | 1105 |
| 20.16.6  | recvdRDI .....                                    | 1105 |
| 20.16.7  | recvdInterval .....                               | 1105 |
| 20.16.8  | recvdPortState .....                              | 1106 |
| 20.16.9  | recvdInterfaceStatus .....                        | 1106 |
| 20.16.10 | recvdSenderId .....                               | 1106 |
| 20.16.11 | recvdFrame .....                                  | 1106 |
| 20.16.12 | CCMsequenceErrors .....                           | 1106 |
| 20.16.13 | rcvdTrafficBit .....                              | 1106 |
| 20.17    | MEP Continuity Check Receiver procedures .....    | 1106 |
| 20.17.1  | MEPprocessEqualCCM() .....                        | 1106 |
| 20.17.2  | MEPprocessLowCCM() .....                          | 1107 |
| 20.18    | MEP Continuity Check Receiver state machine ..... | 1107 |
| 20.19    | Remote MEP variables .....                        | 1108 |
| 20.19.1  | rMEPCCMdefect .....                               | 1108 |
| 20.19.2  | rMEPlastRDI and rMEPlastRDI[i] .....              | 1108 |
| 20.19.3  | rMEPlastPortState .....                           | 1109 |
| 20.19.4  | rMEPlastInterfaceStatus .....                     | 1109 |
| 20.19.5  | rMEPlastSenderId .....                            | 1109 |
| 20.19.6  | rCCMreceived .....                                | 1109 |
| 20.19.7  | rMEPmacAddress .....                              | 1109 |
| 20.19.8  | rMEPportStatusDefect .....                        | 1109 |
| 20.19.9  | rMEPinterfaceStatusDefect .....                   | 1109 |
| 20.19.10 | lastPathN .....                                   | 1109 |
| 20.20    | Remote MEP state machine .....                    | 1110 |
| 20.21    | Remote MEP Error variables .....                  | 1110 |
| 20.21.1  | errorCCMreceived .....                            | 1111 |
| 20.21.2  | errorCCMlastFailure .....                         | 1111 |
| 20.21.3  | errorCCMdefect .....                              | 1111 |
| 20.22    | Remote MEP Error state machine .....              | 1111 |
| 20.23    | MEP Cross Connect variables .....                 | 1111 |
| 20.23.1  | xconCCMreceived .....                             | 1112 |
| 20.23.2  | xconCCMlastFailure .....                          | 1112 |
| 20.23.3  | xconCCMdefect .....                               | 1112 |
| 20.24    | MEP Cross Connect state machine .....             | 1112 |
| 20.25    | MEP Mismatch variables .....                      | 1113 |
| 20.25.1  | mmCCMreceived .....                               | 1113 |
| 20.25.2  | mmCCMdefect .....                                 | 1113 |
| 20.25.3  | mmCCMTime .....                                   | 1113 |
| 20.25.4  | disableLocdefect .....                            | 1113 |
| 20.25.5  | mmLocdefect .....                                 | 1113 |
| 20.26    | MEP Mismatch state machines .....                 | 1114 |
| 20.27    | MP Loopback Responder variables .....             | 1115 |
| 20.27.1  | LBMreceived .....                                 | 1115 |

|         |   |      |
|---------|---|------|
| 20.27.2 | LBMPDU .....  | 1115 |
| 20.28   | MP Loopback Responder procedures .....                        | 1115 |
| 20.28.1 | ProcessLBM() .....  | 1115 |
| 20.28.2 | xmitLBR() .....   | 1116 |
| 20.29   | MP Loopback Responder state machine .....                     | 1116 |
| 20.30   | MEP Loopback Initiator variables .....                        | 1117 |
| 20.30.1 | LBMstoSend .....  | 1117 |
| 20.30.2 | nextLBMtransID .....  | 1117 |
| 20.30.3 | expectedLBRtransID .....                                      | 1117 |
| 20.30.4 | LBIactive .....   | 1117 |
| 20.30.5 | xmitReady .....   | 1117 |
| 20.30.6 | LBRreceived .....   | 1117 |
| 20.30.7 | LBRPDU .....  | 1117 |
| 20.31   | MEP Loopback Initiator transmit procedures .....              | 1118 |
| 20.31.1 | xmitLBM() .....   | 1118 |
| 20.32   | MEP Loopback Initiator transmit state machine .....           | 1119 |
| 20.33   | MEP Loopback Initiator receive procedures .....               | 1119 |
| 20.33.1 | ProcessLBR() .....  | 1119 |
| 20.34   | MEP Loopback Initiator receive state machine .....            | 1120 |
| 20.35   | MEP Fault Notification Generator variables .....              | 1120 |
| 20.35.1 | fngPriority .....   | 1120 |
| 20.35.2 | fngDefect .....   | 1121 |
| 20.35.3 | fngAlarmTime .....  | 1121 |
| 20.35.4 | fngResetTime .....  | 1121 |
| 20.35.5 | someRMEPCCMdefect .....                                       | 1121 |
| 20.35.6 | someMACstatusDefect .....                                     | 1121 |
| 20.35.7 | someRDId defect .....   | 1121 |
| 20.35.8 | highestDefectPri .....  | 1121 |
| 20.35.9 | highestDefect .....   | 1121 |
| 20.36   | MEP Fault Notification Generator procedures .....             | 1122 |
| 20.36.1 | xmitFaultAlarm() .....  | 1122 |
| 20.37   | MEP Fault Notification Generator state machine .....          | 1122 |
| 20.38   | MEP Mismatch Fault Notification Generator variables .....     | 1123 |
| 20.38.1 | mfngAllowed .....   | 1123 |
| 20.38.2 | mmdefectIndication .....                                      | 1123 |
| 20.38.3 | mfngAlarmTime .....   | 1123 |
| 20.38.4 | mfngResetTime .....   | 1123 |
| 20.39   | MEP Mismatch Fault Notification Generator procedures .....    | 1123 |
| 20.39.1 | xmitFaultAlarm() .....  | 1123 |
| 20.40   | MEP Mismatch Fault Notification Generator state machine ..... | 1124 |
| 20.41   | MEP Linktrace Initiator variables .....                       | 1124 |
| 20.41.1 | nextLTMtransID .....  | 1124 |
| 20.41.2 | lrmReplyList .....  | 1125 |
| 20.42   | MEP Linktrace Initiator procedures .....                      | 1126 |
| 20.42.1 | xmitLTM() .....   | 1127 |
| 20.43   | MEP Linktrace Initiator receive variables .....               | 1127 |
| 20.43.1 | LTRreceived .....   | 1127 |
| 20.43.2 | LTRPDU .....  | 1128 |
| 20.44   | MEP Linktrace Initiator receive procedures .....              | 1128 |
| 20.44.1 | ProcessLTR() .....  | 1128 |
| 20.45   | MEP Linktrace Initiator receive state machine .....           | 1128 |
| 20.46   | Linktrace Responder variables .....                           | 1129 |
| 20.46.1 | nPendingLTRs .....  | 1129 |
| 20.46.2 | LTMreceived .....   | 1129 |

|         |   |      |
|---------|---|------|
| 20.46.3 | LTMPDU .....                                      | 1129 |
| 20.47   | LTM Receiver procedures .....                     | 1129 |
| 20.47.1 | ProcessLTM() .....                                | 1129 |
| 20.47.2 | clearPendingLTRs() .....                          | 1133 |
| 20.47.3 | ForwardLTM() .....                                | 1134 |
| 20.47.4 | enqueLTR() .....                                  | 1134 |
| 20.48   | LTM Receiver state machine .....                  | 1136 |
| 20.49   | LTR Transmitter procedure .....                   | 1136 |
| 20.49.1 | xmitOldestLTR() .....                             | 1136 |
| 20.50   | LTR Transmitter state machine .....               | 1136 |
| 20.51   | CFM PDU validation and versioning .....           | 1137 |
| 20.51.1 | Goals of CFM PDU versioning .....                 | 1137 |
| 20.51.2 | PDU transmission .....                            | 1137 |
| 20.51.3 | PDU validation .....                              | 1138 |
| 20.51.4 | Validation pass .....                             | 1138 |
| 20.51.5 | Execution pass .....                              | 1139 |
| 20.51.6 | Future extensions .....                           | 1140 |
| 20.52   | PDU identification .....                          | 1140 |
| 20.53   | Use of transaction IDs and sequence numbers ..... | 1141 |
| 21.     | Encoding of CFM PDUs .....                        | 1142 |
| 21.1    | Structure, representation, and encoding .....     | 1142 |
| 21.2    | CFM encapsulation .....                           | 1142 |
| 21.3    | CFM request and indication parameters .....       | 1143 |
| 21.3.1  | destination_address parameter .....               | 1143 |
| 21.3.2  | source_address parameter .....                    | 1143 |
| 21.4    | Common CFM Header .....                           | 1144 |
| 21.4.1  | MD Level .....                                    | 1144 |
| 21.4.2  | Version .....                                     | 1144 |
| 21.4.3  | OpCode .....                                      | 1144 |
| 21.4.4  | Flags .....                                       | 1145 |
| 21.4.5  | First TLV Offset .....                            | 1145 |
| 21.5    | TLV format .....                                  | 1145 |
| 21.5.1  | General format for CFM TLVs .....                 | 1145 |
| 21.5.2  | Organization-Specific TLV .....                   | 1146 |
| 21.5.3  | Sender ID TLV .....                               | 1147 |
| 21.5.4  | Port Status TLV .....                             | 1149 |
| 21.5.5  | Interface Status TLV .....                        | 1149 |
| 21.5.6  | Data TLV .....                                    | 1150 |
| 21.5.7  | End TLV .....                                     | 1150 |
| 21.6    | CCM format .....                                  | 1151 |
| 21.6.1  | Flags .....                                       | 1151 |
| 21.6.2  | First TLV Offset .....                            | 1152 |
| 21.6.3  | Sequence Number .....                             | 1152 |
| 21.6.4  | Maintenance association Endpoint Identifier ..... | 1153 |
| 21.6.5  | Maintenance Association Identifier .....          | 1153 |
| 21.6.6  | Defined by ITU-T Y.1731 (02/2008) .....           | 1155 |
| 21.6.7  | Optional CCM TLVs .....                           | 1155 |
| 21.7    | LBM and LBR formats .....                         | 1156 |
| 21.7.1  | Flags .....                                       | 1156 |
| 21.7.2  | First TLV Offset .....                            | 1156 |
| 21.7.3  | Loopback Transaction Identifier .....             | 1156 |
| 21.7.4  | Additional LBM/LBR TLVs .....                     | 1156 |

|        |  |      |
|--------|--|------|
| 21.7.5 | PBB-TE MIP TLV .....   | 1157 |
| 21.8   | LTM format .....   | 1158 |
| 21.8.1 | Flags .....  | 1158 |
| 21.8.2 | First TLV Offset .....   | 1158 |
| 21.8.3 | LTM Transaction Identifier .....   | 1158 |
| 21.8.4 | LTM TTL .....  | 1159 |
| 21.8.5 | Original MAC Address .....   | 1159 |
| 21.8.6 | Target MAC Address .....   | 1159 |
| 21.8.7 | Additional LTM TLVs .....  | 1159 |
| 21.8.8 | LTM Egress Identifier TLV .....  | 1159 |
| 21.9   | LTR format .....   | 1160 |
| 21.9.1 | Flags .....  | 1160 |
| 21.9.2 | First TLV Offset .....   | 1161 |
| 21.9.3 | LTR Transaction Identifier .....   | 1161 |
| 21.9.4 | Reply TTL .....  | 1161 |
| 21.9.5 | Relay Action .....   | 1161 |
| 21.9.6 | Additional LTR TLVs .....  | 1161 |
| 21.9.7 | LTR Egress Identifier TLV .....  | 1162 |
| 21.9.8 | Reply Ingress TLV .....  | 1162 |
| 21.9.9 | Reply Egress TLV .....   | 1163 |
| 22.    | CFM in systems .....   | 1166 |
| 22.1   | CFM shims in Bridges .....   | 1166 |
| 22.1.1 | Preliminary positioning of MPs .....   | 1166 |
| 22.1.2 | CFM and the Forwarding Process .....   | 1167 |
| 22.1.3 | Up/Down separation of MPs .....  | 1169 |
| 22.1.4 | Service instances over multiple Bridges .....  | 1171 |
| 22.1.5 | Multiple VID service instances .....   | 1173 |
| 22.1.6 | Untagged CFM PDUs .....  | 1173 |
| 22.1.7 | MPs and non-VLAN aware Bridges .....   | 1173 |
| 22.1.8 | MPs and other standards .....  | 1174 |
| 22.1.9 | CFM and IEEE 802.3-2012 Clause 57 OAM .....  | 1176 |
| 22.2   | Maintenance Entity creation .....  | 1176 |
| 22.2.1 | Creating Maintenance Domains and MAs .....   | 1177 |
| 22.2.2 | Creating MEPs .....  | 1177 |
| 22.2.3 | Creating MIPs .....  | 1179 |
| 22.2.4 | CFM configuration errors .....   | 1180 |
| 22.3   | MPs, Ports, and MD Level assignment.....   | 1181 |
| 22.4   | Stations and CFM .....   | 1181 |
| 22.5   | Scalability of CFM.....  | 1182 |
| 22.6   | CFM in Provider Bridges.....   | 1183 |
| 22.6.1 | MPs and C-VLAN components .....  | 1183 |
| 22.6.2 | Maintenance C-VLAN on a Port-based service interface .....                           | 1184 |
| 22.6.3 | Maintenance C-VLAN on a C-tagged service interface .....                             | 1185 |
| 22.6.4 | MPs and Port-mapping S-VLAN components .....   | 1185 |
| 22.7   | Management Port MEPs and CFM in the enterprise environment.....                      | 1187 |
| 22.8   | Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q .... | 1188 |
| 23.    | MAC status propagation .....   | 1190 |
| 23.1   | Model of operation.....  | 1191 |
| 23.1.1 | MAC Status Shim (MSS) .....  | 1192 |
| 23.1.2 | Relationship of CFM to the MSS .....   | 1193 |
| 23.2   | MAC Status Protocol (MSP) overview.....  | 1193 |

|         |   |      |
|---------|---|------|
| 23.3    | MSP state machines .....  | 1198 |
| 23.4    | State machine timers .....  | 1199 |
| 23.4.1  | linkNotifyWhen .....  | 1199 |
| 23.4.2  | linkNotifyWhile .....   | 1199 |
| 23.4.3  | macNotifyWhile .....  | 1199 |
| 23.4.4  | macRecoverWhile .....   | 1199 |
| 23.5    | MSP performance parameters .....                                  | 1199 |
| 23.5.1  | LinkNotify .....  | 1200 |
| 23.5.2  | LinkNotifyWait .....  | 1200 |
| 23.5.3  | LinkNotifyRetry .....   | 1200 |
| 23.5.4  | MACNotify .....   | 1200 |
| 23.5.5  | MACNotifyTime .....   | 1200 |
| 23.5.6  | MACRecoverTime .....  | 1200 |
| 23.6    | State machine variables.....                                      | 1200 |
| 23.6.1  | BEGIN .....   | 1200 |
| 23.6.2  | addConfirmed .....  | 1200 |
| 23.6.3  | disableMAC .....  | 1200 |
| 23.6.4  | disabledMAC .....   | 1200 |
| 23.6.5  | disableMSS .....  | 1201 |
| 23.6.6  | lossConfirmed .....   | 1201 |
| 23.6.7  | macOperational .....  | 1201 |
| 23.6.8  | mssOperational .....  | 1201 |
| 23.6.9  | prop .....  | 1201 |
| 23.6.10 | rxAck .....   | 1201 |
| 23.6.11 | rxAdd .....   | 1201 |
| 23.6.12 | rxAddConfirm .....  | 1201 |
| 23.6.13 | rxLoss .....  | 1201 |
| 23.6.14 | rxLossConfirm .....   | 1201 |
| 23.6.15 | txAck .....   | 1201 |
| 23.6.16 | txAdd .....   | 1201 |
| 23.6.17 | txAddConfirm .....  | 1202 |
| 23.6.18 | txLoss .....  | 1202 |
| 23.6.19 | txLossConfirm .....   | 1202 |
| 23.7    | State machine procedures .....                                    | 1202 |
| 23.8    | Status Transition state machine (STM).....                        | 1202 |
| 23.9    | Status Notification state machine (SNM) .....                     | 1203 |
| 23.10   | Receive Process .....   | 1203 |
| 23.11   | Transmit Process.....   | 1203 |
| 23.12   | Management of MSP .....   | 1203 |
| 23.13   | MSPDU transmission, addressing, and protocol identification ..... | 1204 |
| 23.13.1 | Destination MAC Address .....                                     | 1204 |
| 23.13.2 | Source MAC Address .....  | 1204 |
| 23.13.3 | Priority .....  | 1205 |
| 23.13.4 | EtherType use and encoding .....                                  | 1205 |
| 23.14   | Representation and encoding of octets .....                       | 1205 |
| 23.15   | MSPDU structure.....  | 1205 |
| 23.15.1 | Protocol Version .....  | 1206 |
| 23.15.2 | Packet Type .....   | 1206 |
| 23.16   | Validation of received MSPDUs .....                               | 1206 |
| 23.17   | Other MSP participants.....                                       | 1206 |
| 24.     | Bridge performance .....  | 1207 |
| 24.1    | Guaranteed Port Filtering Rate .....                              | 1207 |

|         |  |      |
|---------|--|------|
| 24.2    | Guaranteed Bridge Relaying Rate .....                                  | 1207 |
| 24.3    | RSTP performance requirements .....                                    | 1207 |
| 25.     | Support of the MAC Service by PBBNs.....                               | 1209 |
| 25.1    | Service transparency .....   | 1211 |
| 25.2    | Customer service interface.....  | 1211 |
| 25.3    | Port-based service interface .....                                     | 1212 |
| 25.4    | S-tagged service interface .....                                       | 1213 |
| 25.5    | I-tagged service interface.....  | 1215 |
| 25.6    | Service instance segregation .....                                     | 1217 |
| 25.7    | Service instance selection and identification .....                    | 1217 |
| 25.8    | Service priority and drop eligibility selection.....                   | 1218 |
| 25.9    | Service access protection .....  | 1218 |
| 25.9.1  | Class II redundant LANs access protection .....                        | 1220 |
| 25.9.2  | Class III simple redundant LANs and nodes access protection .....      | 1221 |
| 25.10   | Support of the MAC Service by a PBB-TE Region .....                    | 1222 |
| 25.10.1 | Provisioning TESIS .....   | 1223 |
| 25.10.2 | ESP forwarding behavior .....  | 1224 |
| 25.11   | Transparent service interface .....                                    | 1225 |
| 26.     | Principles of Provider Backbone Bridged Network (PBBN) operation ..... | 1227 |
| 26.1    | PBBN overview .....  | 1227 |
| 26.2    | PBBN example.....  | 1228 |
| 26.3    | B-VLAN connectivity.....   | 1230 |
| 26.4    | Backbone addressing .....  | 1231 |
| 26.4.1  | Learning individual backbone addresses at a PIP .....                  | 1232 |
| 26.4.2  | Translating backbone destination addresses at a CBP .....              | 1232 |
| 26.4.3  | Backbone addressing considerations for CFM MPs .....                   | 1233 |
| 26.5    | Detection of connectivity loops through attached networks.....         | 1233 |
| 26.6    | Scaling of PBBs .....  | 1233 |
| 26.6.1  | Hierarchal PBBNs .....   | 1234 |
| 26.6.2  | Peer PBBNs .....   | 1234 |
| 26.7    | Network management .....   | 1234 |
| 26.8    | CFM in PBBs.....   | 1235 |
| 26.8.1  | CFM over Port-based and S-tagged service interfaces .....              | 1240 |
| 26.8.2  | CFM over I-tagged Service Interfaces .....                             | 1241 |
| 26.8.3  | CFM over hierarchal E-NNI .....  | 1241 |
| 26.8.4  | CFM over peer E-NNI .....  | 1241 |
| 26.9    | CFM in a PBB-TE Region.....  | 1242 |
| 26.9.1  | Addressing PBB-TE MEPs .....   | 1242 |
| 26.9.2  | TESI identification .....  | 1243 |
| 26.9.3  | PBB-TE MEP placement in a Bridge Port .....                            | 1243 |
| 26.9.4  | PBB-TE MIP placement in a Bridge Port .....                            | 1243 |
| 26.9.5  | TESI Maintenance Domains .....   | 1243 |
| 26.9.6  | PBB-TE enhancements of the CFM protocols .....                         | 1244 |
| 26.9.7  | Addressing Infrastructure Segment MEPs .....                           | 1246 |
| 26.9.8  | Infrastructure Segment identification .....                            | 1246 |
| 26.9.9  | Infrastructure Segment MEP placement in a Bridge Port .....            | 1247 |
| 26.9.10 | Infrastructure Segment Maintenance Domains .....                       | 1247 |
| 26.9.11 | IPS extensions to Continuity Check operation .....                     | 1247 |
| 26.10   | Protection switching for point-to-point TESIS.....                     | 1249 |
| 26.10.1 | Introduction .....   | 1249 |
| 26.10.2 | 1:1 point-to-point TESI protection switching .....                     | 1250 |

|         |  |      |
|---------|--|------|
| 26.10.3 | Protection Switching state machines .....                | 1253 |
| 26.11   | IPS in PBB-TE Region .....                               | 1258 |
| 26.11.1 | Infrastructure Segment monitoring .....                  | 1259 |
| 26.11.2 | 1:1 IPS .....  | 1260 |
| 26.11.3 | IPS Control entity .....                                 | 1263 |
| 26.11.4 | 1:1 IPS state machines .....                             | 1264 |
| 26.11.5 | M:1 IPS .....  | 1264 |
| 26.12   | Mismatch defect.....                                     | 1270 |
| 26.13   | Signaling VLAN registrations among I-components .....    | 1271 |
| 27.     | Shortest Path Bridging (SPB) .....                       | 1272 |
| 27.1    | Protocol design requirements.....                        | 1274 |
| 27.2    | Protocol support.....                                    | 1275 |
| 27.3    | Protocol design goals .....                              | 1276 |
| 27.4    | ISIS-SPB VLAN configuration .....                        | 1276 |
| 27.4.1  | SPT Region and ISIS-SPB adjacency determination .....    | 1278 |
| 27.5    | ISIS-SPB information .....                               | 1279 |
| 27.6    | Calculating CIST connectivity.....                       | 1280 |
| 27.7    | Connectivity between regions in the same domain.....     | 1281 |
| 27.8    | Calculating SPT connectivity .....                       | 1281 |
| 27.8.1  | ISIS-SPB overload .....                                  | 1282 |
| 27.9    | Loop prevention .....                                    | 1282 |
| 27.10   | SPVID and SPSsourceID allocation.....                    | 1283 |
| 27.11   | Allocation of VIDs to FIDs.....                          | 1284 |
| 27.12   | SPBV SPVID translation .....                             | 1285 |
| 27.13   | VLAN topology management.....                            | 1285 |
| 27.14   | Individual addresses and SPBM .....                      | 1286 |
| 27.14.1 | Loop mitigation .....                                    | 1287 |
| 27.14.2 | Loop prevention .....                                    | 1287 |
| 27.15   | SPBM group addressing .....                              | 1288 |
| 27.16   | Backbone service instance topology management .....      | 1289 |
| 27.17   | Equal cost shortest paths, ECTs, and load spreading..... | 1290 |
| 27.18   | Connectivity Fault Management for SPBM .....             | 1290 |
| 27.18.1 | SPBM MA types .....                                      | 1291 |
| 27.18.2 | SPBM MEP placement in a Bridge Port .....                | 1291 |
| 27.18.3 | SPBM MIP placement in a Bridge Port .....                | 1291 |
| 27.18.4 | SPBM modifications of the CFM protocols .....            | 1292 |
| 27.19   | Using SPBV and SPBM modes .....                          | 1293 |
| 27.19.1 | Shortest Path Bridging—VID .....                         | 1293 |
| 27.19.2 | Shortest Path Bridging—MAC .....                         | 1295 |
| 27.20   | Security considerations .....                            | 1297 |
| 28.     | ISIS-SPB Link State Protocol.....                        | 1298 |
| 28.1    | ISIS-SPB control plane MAC.....                          | 1298 |
| 28.2    | Formation and maintenance of ISIS-SPB adjacencies.....   | 1299 |
| 28.3    | Loop prevention .....                                    | 1300 |
| 28.4    | The Agreement Digest .....                               | 1300 |
| 28.4.1  | Agreement Digest Format Identifier .....                 | 1301 |
| 28.4.2  | Agreement Digest Format Capabilities .....               | 1301 |
| 28.4.3  | Agreement Digest Convention Identifier .....             | 1301 |
| 28.4.4  | Agreement Digest Convention Capabilities .....           | 1302 |
| 28.4.5  | Agreement Digest Edge Count .....                        | 1302 |
| 28.4.6  | The Computed Topology Digest .....                       | 1302 |

|          |   |      |
|----------|---|------|
| 28.5     | Symmetric shortest path tie breaking.....                             | 1303 |
| 28.6     | Symmetric ECT framework.....  | 1304 |
| 28.7     | Symmetric ECT .....   | 1305 |
| 28.8     | ECT Algorithm details.....  | 1306 |
| 28.9     | ECT Migration.....  | 1307 |
| 28.9.1   | Use of a new ECT Algorithm in SPBV .....                              | 1308 |
| 28.9.2   | Use of a new ECT Algorithm in SPBM .....                              | 1308 |
| 28.10    | MAC address registration .....  | 1309 |
| 28.11    | Circuit IDs and Port Identifiers.....                                 | 1309 |
| 28.12    | ISIS-SPB TLVs.....  | 1310 |
| 28.12.1  | MT-Capability TLV .....   | 1310 |
| 28.12.2  | SPB MCID sub-TLV .....  | 1311 |
| 28.12.3  | SPB Digest sub-TLV .....  | 1311 |
| 28.12.4  | SPB Base VLAN-Identifiers sub-TLV .....                               | 1312 |
| 28.12.5  | SPB Instance sub-TLV .....  | 1313 |
| 28.12.6  | SPB Instance Opaque ECT Algorithm sub-TLV .....                       | 1315 |
| 28.12.7  | SPB Link Metric sub-TLV .....   | 1316 |
| 28.12.8  | SPB Adjacency Opaque ECT Algorithm sub-TLV .....                      | 1317 |
| 28.12.9  | SPBV MAC address sub-TLV .....  | 1317 |
| 28.12.10 | SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV ..... | 1319 |
| 29.      | DDCFM operations and protocols.....                                   | 1322 |
| 29.1     | Principles of DDCFM operation.....                                    | 1322 |
| 29.1.1   | Data-driven and data-dependent faults (DDFs) .....                    | 1322 |
| 29.1.2   | Basic principle to diagnose and isolate DDFs .....                    | 1322 |
| 29.2     | DDCFM Entity operation .....  | 1325 |
| 29.2.1   | DDCFM implementation .....  | 1325 |
| 29.2.2   | FPT RR .....  | 1326 |
| 29.2.3   | RR-related parameters .....   | 1327 |
| 29.2.4   | Reflection Target and RFM Receiver .....                              | 1328 |
| 29.2.5   | RPT-related parameters .....  | 1328 |
| 29.2.6   | Decapsulator Responder (DR) .....                                     | 1329 |
| 29.2.7   | SFM Originator .....  | 1330 |
| 29.3     | DDCFM protocols.....  | 1330 |
| 29.3.1   | RR variables .....  | 1330 |
| 29.3.2   | RR Filter procedures .....  | 1332 |
| 29.3.3   | RR Encapsulation procedures .....                                     | 1333 |
| 29.3.4   | RR Transmit procedure .....   | 1334 |
| 29.3.5   | RR-related state machines .....                                       | 1335 |
| 29.3.6   | RFM Receiver variables .....  | 1337 |
| 29.3.7   | RFM Receiver procedure .....  | 1337 |
| 29.3.8   | DR variables .....  | 1338 |
| 29.3.9   | DR procedures .....   | 1339 |
| 29.3.10  | Decapsulator Responder state machine .....                            | 1340 |
| 29.4     | Encoding of DDCFM PDUs.....   | 1340 |
| 29.4.1   | RFM and SFM Header .....  | 1340 |
| 29.4.2   | RFM format .....  | 1341 |
| 29.4.3   | SFM format .....  | 1342 |
| 30.      | Principles of congestion notification .....                           | 1344 |
| 30.1     | Congestion notification design requirements .....                     | 1344 |
| 30.2     | Quantized Congestion Notification protocol (QCN) .....                | 1346 |
| 30.2.1   | The CP algorithm .....  | 1347 |

|         |   |      |
|---------|---|------|
| 30.2.2  | Basic RP algorithm .....                            | 1348 |
| 30.2.3  | RP algorithm with timer .....                       | 1349 |
| 30.3    | Congestion Controlled Flow (CCF) .....              | 1350 |
| 30.4    | Congestion Notification Priority Value (CNPV) ..... | 1351 |
| 30.5    | Congestion Notification tag (CN-TAG) .....          | 1351 |
| 30.6    | Congestion Notification Domain (CND) .....          | 1351 |
| 30.7    | Multicast data .....                                | 1352 |
| 30.8    | Congestion notification and additional tags .....   | 1352 |
| 31.     | Congestion notification entity operation .....      | 1354 |
| 31.1    | Congestion aware Bridge Forwarding Process .....    | 1354 |
| 31.1.1  | Congestion Point (CP) .....                         | 1355 |
| 31.1.2  | CP ingress multiplexer .....                        | 1355 |
| 31.2    | Congestion aware end station functions .....        | 1355 |
| 31.2.1  | Output flow segregation .....                       | 1356 |
| 31.2.2  | Per-CNPV station function .....                     | 1357 |
| 31.2.3  | Flow Select Database .....                          | 1359 |
| 31.2.4  | Flow multiplexer .....                              | 1359 |
| 31.2.5  | CNM demultiplexer .....                             | 1359 |
| 31.2.6  | Input flow segregation .....                        | 1359 |
| 31.2.7  | End station input queue .....                       | 1360 |
| 31.2.8  | Reception selection .....                           | 1360 |
| 32.     | Congestion notification protocol .....              | 1361 |
| 32.1    | CND operations .....                                | 1361 |
| 32.1.1  | CND defense .....                                   | 1361 |
| 32.1.2  | Automatic CND recognition .....                     | 1363 |
| 32.1.3  | Variables controlling CND defense .....             | 1363 |
| 32.2    | CN component variables .....                        | 1364 |
| 32.2.1  | cngMasterEnable .....                               | 1365 |
| 32.2.2  | cngCnmTransmitPriority .....                        | 1365 |
| 32.2.3  | cngDiscardedFrames .....                            | 1365 |
| 32.2.4  | cngErroredPortList .....                            | 1365 |
| 32.3    | Congestion notification per-CNPV variables .....    | 1365 |
| 32.3.1  | cncpDefModeChoice .....                             | 1365 |
| 32.3.2  | cncpAlternatePriority .....                         | 1366 |
| 32.3.3  | cncpAutoAltPri .....                                | 1366 |
| 32.3.4  | cncpAdminDefenseMode .....                          | 1366 |
| 32.3.5  | cncpCreation .....                                  | 1366 |
| 32.3.6  | cncpLdpInstanceChoice .....                         | 1366 |
| 32.3.7  | cncpLdpInstanceSelector .....                       | 1366 |
| 32.4    | CND defense per-Port per-CNPV variables .....       | 1367 |
| 32.4.1  | cnpdDefModeChoice .....                             | 1367 |
| 32.4.2  | cnpdAdminDefenseMode .....                          | 1367 |
| 32.4.3  | cnpdAutoDefenseMode .....                           | 1368 |
| 32.4.4  | cnpdLdpInstanceChoice .....                         | 1368 |
| 32.4.5  | cnpdLdpInstanceSelector .....                       | 1368 |
| 32.4.6  | cnpdAlternatePriority .....                         | 1368 |
| 32.4.7  | cnpdXmitCnpvCapable .....                           | 1368 |
| 32.4.8  | cnpdXmitReady .....                                 | 1368 |
| 32.4.9  | cncpDoesEdge .....                                  | 1369 |
| 32.4.10 | cnpdAcceptsCnTag .....                              | 1369 |
| 32.4.11 | cnpdRcvdCnpv .....                                  | 1369 |

|          |  |      |
|----------|--|------|
| 32.4.12  | cnpdRcvdReady .....                    | 1369 |
| 32.4.13  | cnpdIsAdminDefMode .....               | 1369 |
| 32.4.14  | cnpdDefenseMode .....                  | 1370 |
| 32.5     | CND defense procedures .....           | 1370 |
| 32.5.1   | DisableCnpvRemapping() .....           | 1370 |
| 32.5.2   | TurnOnCnDefenses() .....               | 1370 |
| 32.5.3   | TurnOffCnDefenses() .....              | 1370 |
| 32.6     | CND defense state machine .....        | 1370 |
| 32.7     | Congestion notification protocol ..... | 1371 |
| 32.8     | CP variables .....                     | 1372 |
| 32.8.1   | cpMacAddress .....                     | 1373 |
| 32.8.2   | cpId .....                             | 1373 |
| 32.8.3   | cpQSp .....                            | 1373 |
| 32.8.4   | cpQLen .....                           | 1373 |
| 32.8.5   | cpQLenOld .....                        | 1373 |
| 32.8.6   | cpW .....                              | 1373 |
| 32.8.7   | cpQOffset .....                        | 1373 |
| 32.8.8   | cpQDelta .....                         | 1373 |
| 32.8.9   | cpFb .....                             | 1373 |
| 32.8.10  | cpEnqued .....                         | 1374 |
| 32.8.11  | cpSampleBase .....                     | 1374 |
| 32.8.12  | cpDiscardedFrames .....                | 1374 |
| 32.8.13  | cpTransmittedFrames .....              | 1374 |
| 32.8.14  | cpTransmittedCnms .....                | 1374 |
| 32.8.15  | cpMinHeaderOctets .....                | 1374 |
| 32.9     | CP procedures .....                    | 1374 |
| 32.9.1   | Random .....                           | 1374 |
| 32.9.2   | NewCpSampleBase() .....                | 1374 |
| 32.9.3   | EM_UNITDATA.request (parameters) ..... | 1375 |
| 32.9.4   | GenerateCnmPdu() .....                 | 1375 |
| 32.10    | RP per-Port per-CNPV variables .....   | 1376 |
| 32.10.1  | rpppMaxRps .....                       | 1376 |
| 32.10.2  | rpppCreatedRps .....                   | 1376 |
| 32.10.3  | rpppRpCentiseconds .....               | 1377 |
| 32.11    | RP group variables .....               | 1377 |
| 32.11.1  | rpgEnable .....                        | 1377 |
| 32.11.2  | rpgTimeReset .....                     | 1377 |
| 32.11.3  | rpgByteReset .....                     | 1377 |
| 32.11.4  | rpgThreshold .....                     | 1378 |
| 32.11.5  | rpgMaxRate .....                       | 1378 |
| 32.11.6  | rpgAiRate .....                        | 1378 |
| 32.11.7  | rpgHaiRate .....                       | 1378 |
| 32.11.8  | rpgGd .....                            | 1378 |
| 32.11.9  | rpgMinDecFac .....                     | 1378 |
| 32.11.10 | rpgMinRate .....                       | 1378 |
| 32.12    | RP timer .....                         | 1378 |
| 32.12.1  | RpWhile .....                          | 1379 |
| 32.13    | RP variables .....                     | 1379 |
| 32.13.1  | rpEnabled .....                        | 1379 |
| 32.13.2  | rpByteCount .....                      | 1379 |
| 32.13.3  | rpByteStage .....                      | 1379 |
| 32.13.4  | rpTimeStage .....                      | 1379 |
| 32.13.5  | rpTargetRate .....                     | 1379 |
| 32.13.6  | rpCurrentRate .....                    | 1380 |

|         |   |      |
|---------|---|------|
| 32.13.7 | rpFreeze .....  | 1380 |
| 32.13.8 | rpLimiterRate .....   | 1380 |
| 32.13.9 | rpFb .....  | 1380 |
| 32.14   | RP procedures .....   | 1380 |
| 32.14.1 | ResetCnm .....  | 1380 |
| 32.14.2 | TestRpTerminate .....   | 1381 |
| 32.14.3 | TransmitDataFrame .....   | 1381 |
| 32.14.4 | ReceiveCnm .....  | 1381 |
| 32.14.5 | ProcessCnm .....  | 1382 |
| 32.14.6 | AdjustRates .....   | 1382 |
| 32.15   | RP rate control state machine .....   | 1382 |
| 32.16   | Congestion notification and encapsulation interworking function .....       | 1384 |
| 33.     | Encoding of congestion notification PDUs .....                              | 1386 |
| 33.1    | Structure, representation, and encoding .....                               | 1386 |
| 33.2    | CN-TAG format .....   | 1386 |
| 33.2.1  | Flow Identifier .....   | 1387 |
| 33.3    | Congestion Notification Message (CNM) .....                                 | 1387 |
| 33.4    | Congestion Notification Message PDU format .....                            | 1388 |
| 33.4.1  | Version .....   | 1388 |
| 33.4.2  | ReservedV .....   | 1388 |
| 33.4.3  | Quantized Feedback .....  | 1389 |
| 33.4.4  | Congestion Point Identifier .....   | 1389 |
| 33.4.5  | cnmQOffset .....  | 1389 |
| 33.4.6  | cnmQDelta .....   | 1389 |
| 33.4.7  | Encapsulated priority .....   | 1389 |
| 33.4.8  | Encapsulated destination MAC address .....                                  | 1389 |
| 33.4.9  | Encapsulated MSDU length .....  | 1389 |
| 33.4.10 | Encapsulated MSDU .....   | 1389 |
| 33.4.11 | CNM Validation .....  | 1390 |
| 34.     | Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)..... | 1391 |
| 34.1    | Overview.....   | 1391 |
| 34.2    | Detection of SRP domains.....   | 1391 |
| 34.3    | The bandwidth availability parameters.....                                  | 1392 |
| 34.3.1  | Relationships among bandwidth availability parameters .....                 | 1392 |
| 34.3.2  | Bandwidth availability parameter management .....                           | 1393 |
| 34.4    | Deriving actual bandwidth requirements from the size of the MSDU .....      | 1393 |
| 34.5    | Mapping priorities to traffic classes for time-sensitive streams .....      | 1394 |
| 34.6    | End station behavior .....  | 1396 |
| 34.6.1  | Talker behavior .....   | 1396 |
| 34.6.2  | Listener behavior .....   | 1397 |
| 35.     | Stream Reservation Protocol (SRP).....                                      | 1398 |
| 35.1    | Multiple Stream Registration Protocol (MSRP).....                           | 1399 |
| 35.1.1  | MSRP and Shared Media .....   | 1400 |
| 35.1.2  | Behavior of end stations .....  | 1400 |
| 35.1.3  | Behavior of Bridges .....   | 1402 |
| 35.1.4  | SRP domains and status parameters .....                                     | 1402 |
| 35.2    | Definition of the MSRP application .....                                    | 1402 |
| 35.2.1  | Definition of internal state variables .....                                | 1403 |
| 35.2.2  | Definition of MRP elements .....  | 1405 |

|        |   |      |
|--------|---|------|
| 35.2.3 | Provision and support of Stream registration service .....    | 1415 |
| 35.2.4 | MSRP Attribute Propagation .....                              | 1419 |
| 35.2.5 | Operational reporting and statistics .....                    | 1424 |
| 35.2.6 | Encoding .....  | 1424 |
| 35.2.7 | Attribute value support requirements .....                    | 1425 |
| 36.    | Priority-based Flow Control (PFC) .....                       | 1426 |
| 36.1   | PFC operation .....   | 1426 |
| 36.1.1 | Overview .....  | 1426 |
| 36.1.2 | PFC primitives .....  | 1427 |
| 36.1.3 | Detailed specification of PFC operation .....                 | 1428 |
| 36.2   | PFC aware system queue functions .....                        | 1429 |
| 36.2.1 | PFC Initiator .....   | 1430 |
| 36.2.2 | PFC Receiver .....  | 1430 |
| 37.    | Enhanced Transmission Selection (ETS).....                    | 1432 |
| 37.1   | Overview.....   | 1432 |
| 37.1.1 | Relationship to other transmission selection algorithms ..... | 1432 |
| 37.2   | ETS configuration parameters .....                            | 1432 |
| 37.3   | ETS algorithm.....  | 1432 |
| 37.4   | Legacy configuration .....                                    | 1433 |
| 38.    | Data Center Bridging eXchange protocol (DCBX).....            | 1434 |
| 38.1   | Overview.....   | 1434 |
| 38.2   | Goals .....   | 1434 |
| 38.3   | Types of DCBX attributes .....                                | 1434 |
| 38.3.1 | Informational attributes .....                                | 1434 |
| 38.4   | DCBX and LLDP.....  | 1434 |
| 38.4.1 | Asymmetric attribute passing .....                            | 1435 |
| 38.4.2 | Symmetric attribute passing .....                             | 1436 |
| 39.    | Multiple I-SID Registration Protocol (MIRP) .....             | 1438 |
| 39.1   | MIRP overview .....   | 1438 |
| 39.1.1 | Behavior of I-components .....                                | 1440 |
| 39.1.2 | Behavior of B-components .....                                | 1440 |
| 39.2   | Definition of the MIRP application .....                      | 1440 |
| 39.2.1 | Definition of MRP elements .....                              | 1440 |
| 39.2.2 | Alternate MIRP model for B-components .....                   | 1443 |
| 39.2.3 | Use of “new” declaration capability .....                     | 1445 |
| 39.2.4 | Attribute value support requirements .....                    | 1445 |
| 39.2.5 | MRP Message filtering .....                                   | 1445 |
| 40.    | Edge Virtual Bridging (EVB) .....                             | 1446 |
| 40.1   | EVB architecture without S-channels.....                      | 1447 |
| 40.2   | EVB architecture with S-channels.....                         | 1448 |
| 40.3   | Asymmetric EVB architecture without S-channels .....          | 1450 |
| 40.4   | EVB status parameters .....                                   | 1450 |
| 40.4.1 | EVBMode = Not supported .....                                 | 1452 |
| 40.4.2 | EVBMode = EVB Bridge .....                                    | 1452 |
| 40.4.3 | EVBMode = EVB station .....                                   | 1452 |

|         |  |      |
|---------|--|------|
| 41.     | VSI Discovery and Configuration Protocol (VDP)               | 1453 |
| 41.1    | VSI manager ID TLV definition                                | 1453 |
| 41.1.1  | TLV type   | 1453 |
| 41.1.2  | TLV information string length                                | 1453 |
| 41.1.3  | VSI Manager ID   | 1454 |
| 41.2    | VDP association TLV definitions                              | 1454 |
| 41.2.1  | TLV type   | 1454 |
| 41.2.2  | TLV information string length                                | 1455 |
| 41.2.3  | Status   | 1455 |
| 41.2.4  | VSI Type ID (VTID)   | 1456 |
| 41.2.5  | VSI Type Version   | 1456 |
| 41.2.6  | VSIID format   | 1456 |
| 41.2.7  | VSIID  | 1456 |
| 41.2.8  | Filter Info format   | 1457 |
| 41.2.9  | Filter Info field  | 1457 |
| 41.2.10 | VDP TLV type and Status semantics                            | 1459 |
| 41.3    | Organizationally defined TLV definitions                     | 1460 |
| 41.3.1  | TLV type   | 1461 |
| 41.3.2  | TLV information string length                                | 1461 |
| 41.3.3  | Organizationally unique identifier (OUI) or Company ID (CID) | 1461 |
| 41.3.4  | Organizationally defined information                         | 1461 |
| 41.4    | Validation rules for VDP TLVs                                | 1461 |
| 41.5    | VDP state machines   | 1461 |
| 41.5.1  | State machine conventions                                    | 1461 |
| 41.5.2  | Bridge VDP state machine                                     | 1462 |
| 41.5.3  | Station VDP state machine                                    | 1463 |
| 41.5.4  | VDP state machine timers                                     | 1464 |
| 41.5.5  | VDP state machine variables and parameters                   | 1464 |
| 41.5.6  | Command-Response TLV field references in state machines      | 1467 |
| 41.5.7  | VDP state machine procedures                                 | 1467 |
| 42.     | S-Channel Discovery and Configuration Protocol (CDCP)        | 1469 |
| 42.1    | CDCP discovery and configuration                             | 1469 |
| 42.2    | CDCP state machine overview                                  | 1469 |
| 42.3    | CDCP configuration state machine                             | 1470 |
| 42.4    | CDCP configuration variables                                 | 1471 |
| 42.4.1  | AdminChnCap  | 1471 |
| 42.4.2  | AdminRole  | 1472 |
| 42.4.3  | AdminSVIDWants   | 1472 |
| 42.4.4  | LastLocalSVIDPool  | 1472 |
| 42.4.5  | LastRemoteSVIDList   | 1472 |
| 42.4.6  | LastSVIDWants  | 1472 |
| 42.4.7  | LocalSVIDPool  | 1472 |
| 42.4.8  | OperChnCap   | 1472 |
| 42.4.9  | OperRole   | 1472 |
| 42.4.10 | OperSVIDList   | 1473 |
| 42.4.11 | RemoteChnCap   | 1473 |
| 42.4.12 | RemoteRole   | 1473 |
| 42.4.13 | RemoteSVIDList   | 1473 |
| 42.4.14 | schState   | 1473 |
| 42.5    | CDCP configuration procedures                                | 1473 |
| 42.5.1  | SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList)      | 1473 |
| 42.5.2  | RxSVIDConfig (OperSVIDList, LastRemoteSVIDList)              | 1474 |

|        |  |      |
|--------|--|------|
| 42.5.3 | TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool, RemoteSVIDList, OperSVIDList) ..... | 1474 |
| 43.    | Edge Control Protocol (ECP) .....  | 1475 |
| 43.1   | ECP operation .....  | 1475 |
| 43.2   | Edge Control Sublayer Service (ECSS) .....   | 1476 |
| 43.3   | ECP state machines .....   | 1476 |
| 43.3.1 | State machine conventions .....  | 1476 |
| 43.3.2 | Overview .....   | 1476 |
| 43.3.3 | Edge Control Protocol Data Unit (ECPDU) .....  | 1477 |
| 43.3.4 | ECP transmit state machine .....   | 1478 |
| 43.3.5 | ECP receive state machine .....  | 1479 |
| 43.3.6 | ECP state machine timers .....   | 1479 |
| 43.3.7 | ECP state machine variables and parameters .....   | 1480 |
| 43.3.8 | ECP state machine procedures .....   | 1481 |
| 44.    | Equal Cost Multiple Paths (ECMP).....  | 1482 |
| 44.1   | SPBM ECMP .....  | 1482 |
| 44.1.1 | ECMP Operation .....   | 1482 |
| 44.1.2 | ECMP ECT Algorithm .....   | 1483 |
| 44.1.3 | Loop prevention for ECMP .....   | 1485 |
| 44.2   | Support for Flow Filtering .....   | 1485 |
| 44.2.1 | Flow filtering tag (F-TAG) .....   | 1486 |
| 44.2.2 | F-TAG processing .....   | 1487 |
| 44.2.3 | Forwarding process extension for flow filtering .....  | 1488 |
| 44.2.4 | TTL Loop mitigation .....  | 1489 |
| 44.2.5 | CFM for ECMP with flow filtering .....   | 1489 |
| 44.2.6 | Operation with selective support for flow filtering .....                                      | 1491 |
|        | Annex A (normative) PICS proforma—Bridge implementations .....                                 | 1492 |
|        | Annex B (normative) PICS proforma—End station implementations .....                            | 1553 |
|        | Annex C (normative) Designated MSRP Node (DMN) Implementations .....                           | 1567 |
|        | Annex D (normative) IEEE 802.1 Organizationally Specific TLVs .....                            | 1584 |
|        | Annex E (normative) Notational conventions used in state diagrams .....                        | 1692 |
|        | Annex F (informative) Shared and Independent VLAN Learning (SVL and IVL) .....                 | 1694 |
|        | Annex G (informative) MAC method-dependent aspects of VLAN support.....                        | 1703 |
|        | Annex H (informative) Interoperability considerations.....                                     | 1705 |
|        | Annex I (informative) Priority and drop precedence .....                                       | 1711 |
|        | Annex J (informative) CFM protocol design and use.....   | 1719 |
|        | Annex K (informative) TPMR use cases .....   | 1727 |
|        | Annex L (informative) Operation of the credit-based shaper algorithm .....                     | 1732 |

|   |      |
|---|------|
| Annex M (normative) Support for PFC in link layers without MAC Control.....       | 1749 |
| Annex N (informative) Buffer requirements for PFC.....                            | 1750 |
| Annex O (informative) Preserving the integrity of FCS fields in MAC Bridges ..... | 1755 |
| Annex P (informative) Frame duplication and misordering.....                      | 1762 |
| Annex Q (informative) Bibliography.....   | 1765 |

## Figures

|  |     |
|--|-----|
| Figure 6-1—Internal organization of the MAC sublayer .....                               | 61  |
| Figure 6-2—Provider Instance Ports (PIPs) .....  | 79  |
| Figure 6-3—B-Component CBP .....   | 82  |
| Figure 6-4—Example of operation of Port-and-Protocol-based classification .....          | 86  |
| Figure 6-5—Service access priority selection .....                                       | 88  |
| Figure 6-6—Two back-to-back EISS Multiplex Entities .....                                | 94  |
| Figure 6-7—Two back-to-back Backbone Service Instance Multiplex Entities .....           | 95  |
| Figure 6-8—Backbone Service Instance Multiplex Entities with example CFM shims .....     | 95  |
| Figure 6-9—Two back-to-back Up and Down TESI Multiplex Entities .....                    | 98  |
| Figure 6-10—Supporting the ISS with signaled priority .....                              | 99  |
| Figure 6-11—Two back-to-back Up and Down Infrastructure Segment Multiplex Entities ..... | 100 |
| Figure 7-1—VLAN Bridging overview .....  | 103 |
| Figure 8-1—A Bridged Network .....   | 108 |
| Figure 8-2—VLAN Bridge architecture .....  | 110 |
| Figure 8-3—MAC Bridge architecture .....   | 111 |
| Figure 8-4—Relaying MAC frames .....   | 113 |
| Figure 8-5—Observation of network traffic .....  | 113 |
| Figure 8-6—Operation of Spanning Tree Protocol Entity .....                              | 113 |
| Figure 8-7—Operation of MRP .....  | 114 |
| Figure 8-8—Management Port transmission and reception .....                              | 114 |
| Figure 8-8—Infrastructure Segment MEP placement in a PNP .....                           | 115 |
| Figure 8-9—Bridge Port Transmit and Receive .....  | 117 |
| Figure 8-10—TPMR Port Transmit and Receive .....   | 118 |
| Figure 8-11—Forwarding Process functions .....   | 119 |
| Figure 8-12—Logical points of attachment of the Higher Layer and Relay Entities .....    | 152 |
| Figure 8-13—Effect of control information on the forwarding path .....                   | 153 |
| Figure 8-14—Per-Port points of attachment .....  | 153 |
| Figure 8-15—Single point of attachment—relay permitted .....                             | 154 |
| Figure 8-16—Single point of attachment—relay not permitted .....                         | 154 |
| Figure 8-17—Effect of Port State .....   | 155 |
| Figure 8-18—Controlled and Uncontrolled Port connectivity .....                          | 155 |
| Figure 8-19—Ingress/egress control information in the forwarding path .....              | 156 |
| Figure 9-1—VLAN TCI format .....   | 160 |
| Figure 9-2—I-TAG TCI format .....  | 161 |
| Figure 10-1—Example—Attribute value propagation from one station .....                   | 164 |
| Figure 10-2—Example—Attribute value propagation from two stations .....                  | 165 |
| Figure 10-3—Example—Registrations as pointers to the sources of declarations .....       | 165 |
| Figure 10-4—MRP architecture .....   | 167 |
| Figure 10-5—Format of the major components of an MRPDU .....                             | 190 |
| Figure 10-6—Operation of MMRP for a single VLAN Context .....                            | 196 |
| Figure 10-7—Example Directed Graph .....   | 197 |
| Figure 10-8—Example of MMRP propagation in a VLAN Context .....                          | 199 |
| Figure 11-1—Operation of MVRP .....  | 208 |
| Figure 12-1—Relationships among CFM managed objects .....                                | 270 |
| Figure 12-2—Relationship among BEB managed objects .....                                 | 287 |
| Figure 12-3—SPB managed objects (MOs) .....  | 339 |
| Figure 12-4—Relationships among EVB Bridge managed objects .....                         | 355 |
| Figure 12-5—Relationship among EVB station managed objects .....                         | 356 |
| Figure 13-1—Diagrammatic conventions for spanning tree topologies .....                  | 373 |
| Figure 13-2—Physical topology and active topology .....                                  | 374 |
| Figure 13-3—Port Roles and Port States .....   | 374 |

|  |      |
|--|------|
| Figure 13-4—A Backup Port .....  | 375  |
| Figure 13-5—“Ring Backbone” example .....  | 375  |
| Figure 13-6—An MST Bridge network .....  | 377  |
| Figure 13-7—CIST Priority Vectors, Port Roles, and MST Regions .....                 | 378  |
| Figure 13-8—MSTI Active Topology in Region 2 .....                                   | 379  |
| Figure 13-9—CIST and MSTI active topologies in Region 1 of the example network ..... | 392  |
| Figure 13-10—Agreements and Proposals .....  | 396  |
| Figure 13-11—CIST and MSTI Active Topologies in Region 2 of Figure 13-6 .....        | 397  |
| Figure 13-12—Enhanced Agreements .....   | 398  |
| Figure 13-13—Spanning tree protocol state machines—overview and relationships .....  | 409  |
| Figure 13-14—MSTP overview notation .....  | 410  |
| Figure 13-15—Port Timers state machine .....   | 440  |
| Figure 13-16—Port Receive state machine .....  | 440  |
| Figure 13-17—Port Protocol Migration state machine .....                             | 441  |
| Figure 13-18—Bridge Detection state machine .....                                    | 441  |
| Figure 13-19—Port Transmit state machine .....                                       | 442  |
| Figure 13-20—Port Information state machine .....                                    | 443  |
| Figure 13-21—Port Role Selection state machine .....                                 | 444  |
| Figure 13-22—Disabled Port role transitions .....                                    | 445  |
| Figure 13-23—Port Role Transitions state machine—MasterPort .....                    | 446  |
| Figure 13-24—Port Role Transitions state machine—RootPort .....                      | 447  |
| Figure 13-25—Port Role Transitions state machine—DesignatedPort .....                | 448  |
| Figure 13-26—Port Role Transitions state machine—AlternatePort and BackupPort .....  | 449  |
| Figure 13-27—Port State Transition state machine .....                               | 449  |
| Figure 13-28—Topology Change state machine .....                                     | 451  |
| Figure 13-29—L2 Gateway Port Receive state machine .....                             | 452  |
| Figure 14-1—RST, MST, SPT, and STP Configuration BPDU format .....                   | 456  |
| Figure 14-2—STP TCN BPDU format .....  | 456  |
| Figure 14-3—MSTI Configuration Message parameters and format .....                   | 462  |
| Figure 15-1—Internal organization of the MAC sublayer in a PBN .....                 | 465  |
| Figure 15-2—Port-based service interface to a PBN .....                              | 466  |
| Figure 15-3—Port-based service interface to a PBN .....                              | 467  |
| Figure 15-4—C-tagged service interface to a PBN .....                                | 467  |
| Figure 15-5—C-tagged service interface to a PBN .....                                | 467  |
| Figure 15-6—Customer Edge Ports (CEPs) .....   | 468  |
| Figure 15-7—S-tagged service interface to a PBN .....                                | 468  |
| Figure 15-8—S-tagged interface to a PBN .....  | 469  |
| Figure 15-9—RCSIs to a PBN .....   | 469  |
| Figure 15-10—Remote Customer Access Ports (RCAPs) .....                              | 470  |
| Figure 15-11—C-tagged RCSI to a PBN .....  | 471  |
| Figure 15-12—Port-based RCSI to a PBN .....  | 471  |
| Figure 15-13—Provider Network Port (PNP) interface .....                             | 472  |
| Figure 16-1—PBN with interface examples .....  | 476  |
| Figure 16-2—Examples of remote customer service access via a second PBN .....        | 478  |
| Figure 16-3—Access service separation and “Hairpin Switching” .....                  | 479  |
| Figure 17-1—C-VLAN component internal LAN managed system .....                       | 538  |
| Figure 17-2—I/B-component internal LAN managed system .....                          | 542  |
| Figure 18-1—One Maintenance Domain: operator’s view .....                            | 1066 |
| Figure 18-2—One service instance: operator’s view .....                              | 1067 |
| Figure 18-3—One service instance: customer’s view .....                              | 1067 |
| Figure 18-4—MEP and MIP Symbols .....  | 1068 |
| Figure 18-5—MAs: one service instance in a provider network .....                    | 1069 |
| Figure 18-6—MAs: Expansion of Figure 18-5 .....                                      | 1070 |
| Figure 18-7—MEPs, MIPs, and MD Levels .....  | 1071 |

|   |      |
|---|------|
| Figure 19-1—CFM Protocol shims .....  | 1072 |
| Figure 19-2—MA Endpoint (MEP) .....   | 1075 |
| Figure 19-3—MIP Half Function (MHF) .....                                     | 1081 |
| Figure 19-4—LOM shim .....  | 1083 |
| Figure 19-5—LOM architecture .....  | 1083 |
| Figure 20-1—MEP state machines—overview and relationships .....               | 1096 |
| Figure 20-2—MEP Continuity Check Initiator state machine .....                | 1103 |
| Figure 20-3—MHF Continuity Check Receiver state machine .....                 | 1104 |
| Figure 20-4—MEP Continuity Check Receiver state machine .....                 | 1108 |
| Figure 20-5—Remote MEP state machine .....                                    | 1110 |
| Figure 20-6—Remote MEP Error state machine .....                              | 1111 |
| Figure 20-7—MEP Cross Connect state machine .....                             | 1112 |
| Figure 20-8—MEP Traffic Field Mismatch state machine .....                    | 1114 |
| Figure 20-9—MEP Local Mismatch state machine .....                            | 1114 |
| Figure 20-10—MP Loopback Responder state machine .....                        | 1116 |
| Figure 20-11—MEP Loopback Initiator transmit state machine .....              | 1119 |
| Figure 20-12—MEP Loopback Initiator receive state machine .....               | 1120 |
| Figure 20-13—MEP Fault Notification Generator state machine .....             | 1122 |
| Figure 20-14—MEP Mismatch Fault Notification Generator state machine .....    | 1124 |
| Figure 20-15—MEP Linktrace Initiator receive state machine .....              | 1128 |
| Figure 20-16—Linktrace Responder, MEPs, MHFs, and LOMs .....                  | 1130 |
| Figure 20-17—LTM Receiver state machine .....                                 | 1136 |
| Figure 20-18—LTR Transmitter state machine .....                              | 1137 |
| Figure 22-1—MEPs and MIPs distinguished by VID (incomplete picture) .....     | 1167 |
| Figure 22-2—Alternate view of Forwarding process .....                        | 1168 |
| Figure 22-3—Combining per-VLAN MPs into two shims .....                       | 1169 |
| Figure 22-4—More complete picture of MP placement in a Bridge Port .....      | 1170 |
| Figure 22-5—Service instance spanning two Bridges protected by Up MPs .....   | 1172 |
| Figure 22-6—Service instance spanning two Bridges protected by Down MPs ..... | 1172 |
| Figure 22-7—MP placement in a non-VLAN aware Bridge Port .....                | 1174 |
| Figure 22-8—MP placement relative to other standards .....                    | 1175 |
| Figure 22-9—Creating MEPs and MIPs .....                                      | 1178 |
| Figure 22-10—CFM in a Provider Edge Bridge C-tagged service interface .....   | 1184 |
| Figure 22-11—CFM in a Provider Edge Bridge C-tagged RCSI .....                | 1186 |
| Figure 22-12—Up MEPs in a Management Port .....                               | 1187 |
| Figure 22-13—CFM in the enterprise environment .....                          | 1188 |
| Figure 22-14—CFM on a Bridge that implements IEEE Std 802.1Q-2005 .....       | 1189 |
| Figure 23-1—TPMR connecting two Bridge Ports .....                            | 1190 |
| Figure 23-2—TPMR chain connecting Bridge Ports .....                          | 1190 |
| Figure 23-3—MSSs and the MSPE .....   | 1192 |
| Figure 23-4—Adding connectivity .....   | 1194 |
| Figure 23-5—Losing connectivity .....   | 1195 |
| Figure 23-6—TPMR recovery .....   | 1196 |
| Figure 23-7—Notification from one end of the link to the other .....          | 1197 |
| Figure 23-8—Immediate MAC status notification at the end of a link .....      | 1197 |
| Figure 23-9—MSPE state machine overview .....                                 | 1198 |
| Figure 23-10—Status Transition state machine (STM) .....                      | 1202 |
| Figure 23-11—Status Notification state machine (SNM) .....                    | 1203 |
| Figure 23-12—MSPDU structure .....  | 1205 |
| Figure 25-1—Internal organization of the MAC sublayer in a PBBN .....         | 1209 |
| Figure 25-2—PBB terminology .....   | 1210 |
| Figure 25-3—Customer service interface types .....                            | 1211 |
| Figure 25-4—Port-based service interface .....                                | 1212 |
| Figure 25-5—Port-based interface equipment .....                              | 1213 |

|  |      |
|--|------|
| Figure 25-6—Encapsulated service frames at ISS .....                                 | 1214 |
| Figure 25-7—S-tagged service interface .....   | 1214 |
| Figure 25-8—S-tagged service interface equipment .....                               | 1215 |
| Figure 25-9—I-tagged service interface .....   | 1216 |
| Figure 25-10—I-tagged service interface equipment .....                              | 1216 |
| Figure 25-11—S-tagged and Port-based service interface access classifications .....  | 1219 |
| Figure 25-12—I-tagged service interface access protection classifications .....      | 1220 |
| Figure 25-13—Internal organization of the MAC sublayer in a PBB-TE Region .....      | 1222 |
| Figure 25-14—PBB-TE Region .....   | 1224 |
| Figure 25-15—Transparent service interface .....                                     | 1226 |
| Figure 25-16—Transparent service interface equipment .....                           | 1226 |
| Figure 26-1—PBBN example .....   | 1228 |
| Figure 26-2—CFM shim model .....   | 1235 |
| Figure 26-3—CFM example applied to a Port-based and S-tagged service interface ..... | 1236 |
| Figure 26-4—CFM example applied to an I-tagged Service Interface .....               | 1237 |
| Figure 26-5—CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc .....          | 1238 |
| Figure 26-6—CFM example applied to a peer E-NNI, CBP-PIP .....                       | 1239 |
| Figure 26-7—Independent ESPs using the same ESP-DAs and ESP-VIDs .....               | 1243 |
| Figure 26-8—PBB-TE MEP placement in a CBP .....                                      | 1244 |
| Figure 26-9—Independent Infrastructure Segments distinguished by SMP-SA .....        | 1247 |
| Figure 26-10—Infrastructure Segment MEP placement in a PNP .....                     | 1248 |
| Figure 26-11—Protection switching architecture .....                                 | 1249 |
| Figure 26-12—PBB-TE point-to-point protection switching .....                        | 1251 |
| Figure 26-13—Mapping data traffic to the protection entity .....                     | 1252 |
| Figure 26-14—Relationships of the Protection switching state machines—overview ..... | 1253 |
| Figure 26-15—Hold-off state machine .....  | 1257 |
| Figure 26-16—Clear Manual Switch state machine .....                                 | 1257 |
| Figure 26-17—Service Mapping state machine .....                                     | 1258 |
| Figure 26-18—Segment terminology and properties .....                                | 1259 |
| Figure 26-19—Infrastructure Segment monitoring .....                                 | 1260 |
| Figure 26-20—Working Segment and Protection Segment .....                            | 1260 |
| Figure 26-21—Nested IPGs .....   | 1261 |
| Figure 26-22—IPS Control entity .....  | 1263 |
| Figure 26-23—M:1 IPS .....   | 1265 |
| Figure 26-24—M:1 IPS state machines .....  | 1266 |
| Figure 26-25—M:1 Hold-off state machine .....  | 1269 |
| Figure 26-26—Protection Segment Selection state machine .....                        | 1270 |
| Figure 27-1—Configuring VLAN support in an SPT Region (example) .....                | 1277 |
| Figure 27-2—SPBM group MAC address—general format .....                              | 1288 |
| Figure 27-3—SPBM group MAC addresses—source rooted SPT .....                         | 1289 |
| Figure 27-4—SPBM group MAC addresses—shared tree .....                               | 1289 |
| Figure 27-5—SPBM MEP placement in a CBP .....  | 1292 |
| Figure 27-6—SPBV campus network example .....  | 1294 |
| Figure 27-7—SPT Bridge Network using SPBM example .....                              | 1296 |
| Figure 28-1—Agreement Digest field format .....                                      | 1301 |
| Figure 28-2—MT-Capability TLV .....  | 1310 |
| Figure 28-3—SPB MCID sub-TLV .....   | 1311 |
| Figure 28-4—SPB Digest sub-TLV .....   | 1311 |
| Figure 28-5—SPB Base VLAN-Identifiers sub-TLV .....                                  | 1312 |
| Figure 28-6—SPB Instance sub-TLV .....   | 1313 |
| Figure 28-7—SPB Instance Opaque ECT-ALGORITHM sub-TLV .....                          | 1315 |
| Figure 28-8—ECMP ECT-ALGORITHM sub-TLV .....   | 1316 |
| Figure 28-9—SPB Link Metric sub-TLV .....  | 1316 |
| Figure 28-10—SPB Adjacency Opaque ECT-ALGORITHM sub-TLV .....                        | 1317 |

|  |      |
|--|------|
| Figure 28-11—SPBV MAC Address sub-TLV .....  | 1318 |
| Figure 28-12—SPBM Service Identifier and Unicast Address sub-TLV .....                   | 1319 |
| Figure 29-1—Forward path test (FPT) .....  | 1323 |
| Figure 29-2—Return path test (RPT) .....   | 1324 |
| Figure 29-3—Combination of FPT and RPT .....   | 1325 |
| Figure 29-4—Detailed functions of RR .....   | 1326 |
| Figure 29-5—RFM Receiver on an non-MP .....  | 1329 |
| Figure 29-6—Return Path DR .....   | 1330 |
| Figure 29-7—RR Filter state machine .....  | 1335 |
| Figure 29-8—RR Encapsulation state machine .....   | 1336 |
| Figure 29-9—RR Transmit state machine .....  | 1336 |
| Figure 29-10—RFM Receiver state machine .....  | 1338 |
| Figure 29-11—Decapsulator Responder state machine .....                                  | 1340 |
| Figure 30-1—Congestion detection in QCN CP .....   | 1347 |
| Figure 30-2—Sampling (reflection) probability in QCN CP as a function of  Fb  .....      | 1347 |
| Figure 30-3—QCN RP operation .....   | 1348 |
| Figure 30-4—Byte Counter and Timer interaction with Rate Limiter .....                   | 1350 |
| Figure 30-5—CP–RP peering in VLAN Bridged Network .....                                  | 1352 |
| Figure 30-6—CP–RP peering in PBBN .....  | 1353 |
| Figure 31-1—CPs and congestion aware queues in a Bridge .....                            | 1354 |
| Figure 31-2—Congestion aware queue functions in an end station .....                     | 1356 |
| Figure 31-3—Per-CNPV station function .....  | 1358 |
| Figure 32-1—CND defense state machine .....  | 1371 |
| Figure 32-2—RP rate control state machine .....  | 1383 |
| Figure 32-3—CP–RP peering in any hierarchical Bridged Network .....                      | 1384 |
| Figure 34-1—Queuing model for a Talker station .....                                     | 1396 |
| Figure 35-1—Operation of MSRP .....  | 1399 |
| Figure 35-2—Format of the components of the reservation FirstValue fields .....          | 1409 |
| Figure 35-3—Format of the components of the Domain FirstValue .....                      | 1414 |
| Figure 36-1—PFC peering .....  | 1426 |
| Figure 36-2—PFC Receiver state diagram for priority n .....                              | 1428 |
| Figure 36-3—PFC aware system queue functions .....                                       | 1430 |
| Figure 36-4—PFC aware system queue functions with Link Aggregation .....                 | 1431 |
| Figure 38-1—DCBX Asymmetric State Machine .....  | 1436 |
| Figure 38-2—Symmetric State Machine .....  | 1437 |
| Figure 39-1—Operation of MIRP in an I-component .....                                    | 1439 |
| Figure 39-2—Operation of MIRP in a B-component .....                                     | 1439 |
| Figure 39-3—Alternate model for MIRP in a B-component .....                              | 1444 |
| Figure 40-1—EVB architecture overview .....  | 1446 |
| Figure 40-2—EVB architecture without S-channels .....                                    | 1448 |
| Figure 40-3—EVB architecture with S-channel .....  | 1448 |
| Figure 40-4—EVB components and internal LANs with S-channels .....                       | 1449 |
| Figure 40-5—EVB architecture without S-channels, with EVB Bridge S-VLAN component .....  | 1451 |
| Figure 40-6—EVB architecture without S-channels, with EVB station S-VLAN component ..... | 1451 |
| Figure 41-1—VSI manager ID TLV .....   | 1453 |
| Figure 41-2—VDP association TLV .....  | 1454 |
| Figure 41-3—VID Filter Info format .....   | 1458 |
| Figure 41-4—MAC/VID filter format .....  | 1458 |
| Figure 41-5—GroupID/VID filter format .....  | 1459 |
| Figure 41-6—GroupID/MAC/VID filter format .....  | 1459 |
| Figure 41-7—Organizationally defined TLV .....   | 1461 |
| Figure 41-8—Bridge VDP state machine .....   | 1462 |
| Figure 41-9—Station VDP state machine .....  | 1463 |
| Figure 42-1—CDCP state machine—Station role .....  | 1470 |

|   |      |
|---|------|
| Figure 42-2—CDCP state machine—Bridge role .....  | 1471 |
| Figure 43-1—Example ECP exchange .....  | 1475 |
| Figure 43-2—ECPDU structure .....   | 1477 |
| Figure 43-3—ECP transmit state machine .....  | 1478 |
| Figure 43-4—ECP receive state machine .....   | 1479 |
| Figure 44-1—Flow Filtering TCI format .....   | 1486 |
| Figure 44-2—SPBM VID MEP and ECMP path MEP placement in a CBP .....                             | 1490 |
| Figure C-1—CSN backbone .....   | 1567 |
| Figure C-2—Bridge’s CSN model for bandwidth reservation .....                                   | 1568 |
| Figure C-3—Talker MSRPDU flow .....   | 1569 |
| Figure C-4—Listener MSRPDU flow .....   | 1569 |
| Figure C-5—IEEE DMN Device Attribute IE .....   | 1571 |
| Figure C-6—DMN Confirmation Transaction .....   | 1573 |
| Figure C-7—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA downstream Port) .....   | 1576 |
| Figure C-8—Bandwidth reservation—bridge model for IEEE 802.11 BSS (STA upstream Port) .....     | 1576 |
| Figure C-9—Bandwidth reservation—bridge model for IEEE 802.11 BSS (direct link setup) .....     | 1577 |
| Figure C-10—MSRP/IEEE 802.11 query flows .....  | 1577 |
| Figure C-11—MSRP/802.11 Talker STA to Listener STA reservation flows .....                      | 1578 |
| Figure C-12—MSRP/802.11 “Bridged” Listener to Talker STA reservation flows .....                | 1579 |
| Figure C-13—MSRP/802.11 Listener STA to “Bridged” Talker reservation flows .....                | 1579 |
| Figure D-1—Port VLAN ID TLV format .....  | 1585 |
| Figure D-2—Port And Protocol VLAN ID TLV format .....   | 1585 |
| Figure D-3—VLAN Name TLV format .....   | 1586 |
| Figure D-4—Protocol Identity TLV format .....   | 1587 |
| Figure D-5—VID Usage Digest TLV format .....  | 1588 |
| Figure D-6—Management VID TLV format .....  | 1588 |
| Figure D-7—Link Aggregation TLV format .....  | 1589 |
| Figure D-8—Congestion Notification TLV format .....   | 1590 |
| Figure D-9—ETS Configuration TLV format .....   | 1591 |
| Figure D-10—ETS Recommendation TLV format .....   | 1593 |
| Figure D-11—Priority-based Flow Control Configuration TLV format .....                          | 1594 |
| Figure D-12—Application Priority TLV format .....   | 1595 |
| Figure D-13—EVB TLV format .....  | 1597 |
| Figure D-14—CDCP TLV structure .....  | 1600 |
| Figure F-1—Connecting independent VLANs—1 .....   | 1695 |
| Figure F-2—Connecting independent VLANs—2 .....   | 1696 |
| Figure F-3—Duplicate MAC addresses .....  | 1696 |
| Figure F-4—Asymmetric VID use: “multi-netted server” .....                                      | 1697 |
| Figure F-5—Asymmetric VLAN use: “Rooted-Multipoint” .....                                       | 1699 |
| Figure F-6—Rooted-Multipoint with tagged interfaces .....                                       | 1700 |
| Figure F-7—SPBV VLAN Shared Learning and VID Translation .....                                  | 1701 |
| Figure G-1—Example of IEEE 802.3 MAC frame format .....   | 1703 |
| Figure H-1—Static filtering inconsistency .....   | 1707 |
| Figure H-2—Interoperability with MAC Bridges: example 1 .....                                   | 1708 |
| Figure H-3—Interoperability with MAC Bridges: example 2 .....                                   | 1709 |
| Figure H-4—Interoperability between Port-based and Port-and-Protocol-based classification ..... | 1710 |
| Figure J-1—Up MPs in a CFM Port .....   | 1724 |
| Figure K-1—TPMR as UNI demarcation device .....   | 1727 |
| Figure K-2—TPMRs with aggregated links .....  | 1728 |
| Figure K-3—Multiple TPMRs .....   | 1728 |
| Figure K-4—Recovery at the end of a chain .....   | 1729 |
| Figure K-5—Near simultaneous recoveries .....   | 1730 |
| Figure K-6—Near simultaneous failure and recovery .....   | 1730 |
| Figure K-7—Loss with quick recovery .....   | 1731 |

|   |      |
|---|------|
| Figure L-1—Credit-based shaper operation—no conflicting traffic ..... | 1734 |
| Figure L-2—Credit-based shaper operation—conflicting traffic .....    | 1735 |
| Figure L-3—Credit-based shaper operation—burst traffic .....          | 1736 |
| Figure L-4—Interference and latency .....                             | 1740 |
| Figure L-5—Burst behavior and credit .....                            | 1740 |
| Figure L-6—Fan-in scenario .....                                      | 1744 |
| Figure L-7—Permanent delay scenario .....                             | 1745 |
| Figure L-8—Building up buffer occupancy—1 .....                       | 1746 |
| Figure L-9—Building up buffer occupancy—2 .....                       | 1746 |
| Figure L-10—Building up buffer occupancy—3 .....                      | 1747 |
| Figure L-11—Building up buffer occupancy—4 .....                      | 1747 |
| Figure M-1—PFC PDU format .....                                       | 1749 |
| Figure N-1—PFC delays .....   | 1750 |
| Figure N-2—Delay model .....  | 1751 |
| Figure N-3—Worst-case delay .....                                     | 1752 |
| Figure O-1—Converting a CRC to an FCS .....                           | 1757 |
| Figure O-2—Detection Lossless Circuit .....                           | 1757 |
| Figure O-3—Field change adjustment .....                              | 1759 |
| Figure O-4—Field insertion adjustment .....                           | 1760 |
| Figure P-1—Frame duplication scenario .....                           | 1763 |
| Figure P-2—Frame misordering scenario .....                           | 1764 |

## Tables

|   |     |
|---|-----|
| Table 6-1—Bridge transit delay .....  | 68  |
| Table 6-2—Priority Code Point encoding .....  | 76  |
| Table 6-3—Priority Code Point decoding .....  | 76  |
| Table 6-4—Priority regeneration .....   | 77  |
| Table 6-5—Default SRP domain boundary port priority regeneration override values .....  | 78  |
| Table 6-6—Service Access Priority .....   | 89  |
| Table 6-7—Encapsulated Addresses EtherType .....  | 96  |
| Table 8-1—C-VLAN and MAC Bridge component Reserved addresses .....  | 122 |
| Table 8-2—S-VLAN component Reserved addresses .....   | 123 |
| Table 8-3—TPMR component Reserved addresses .....   | 123 |
| Table 8-4—Recommended priority to traffic class mappings .....  | 126 |
| Table 8-5—Transmission selection algorithm identifiers .....  | 128 |
| Table 8-6—Ageing time parameter value .....   | 131 |
| Table 8-7—Combining Static and Dynamic Filtering Entries for an individual MAC address .....  | 140 |
| Table 8-8—Combining Static Filtering Entry and MAC Address Registration Entry for<br>“All Group Addresses” and “All Unregistered Group Addresses” ..... | 141 |
| Table 8-9—Forwarding or Filtering for specific group MAC addresses .....  | 142 |
| Table 8-10—Forwarding or Filtering with Dynamic Reservation Entries .....   | 143 |
| Table 8-11—Determination of whether a Port is in a VID’s member set .....   | 144 |
| Table 8-12—Standard LLC address assignment .....  | 148 |
| Table 8-13—ISIS-SPB reserved addresses .....  | 150 |
| Table 8-14—ISIS-SPB Recommended Address Usage .....   | 151 |
| Table 8-15—CCM group destination MAC addresses .....  | 157 |
| Table 8-16—LTM group destination MAC addresses .....  | 157 |
| Table 9-1—IEEE 802.1Q EtherType allocations .....   | 160 |
| Table 9-2—Reserved VID values .....   | 160 |
| Table 9-3—Reserved I-SID values .....   | 162 |
| Table 10-1—MRP application addresses .....  | 170 |
| Table 10-2—MRP EtherType values .....   | 171 |
| Table 10-3—Applicant state table .....  | 184 |
| Table 10-4—Registrar state table .....  | 185 |
| Table 10-6—PeriodicTransmission state table .....   | 186 |
| Table 10-5—LeaveAll state table .....   | 186 |
| Table 10-7—MRP timer parameter values .....   | 187 |
| Table 12-1—Component table entry managed object .....   | 220 |
| Table 12-2—Port table entry .....   | 221 |
| Table 12-3—ISS Port Number table entry .....  | 222 |
| Table 12-4—Bandwidth Availability Parameter Table row elements .....  | 326 |
| Table 12-5—Transmission Selection Algorithm Table row elements .....  | 327 |
| Table 12-6—Priority Regeneration Override Table row elements .....  | 327 |
| Table 12-7—CN component managed object row elements .....   | 328 |
| Table 12-8—CN component priority managed object row elements .....  | 329 |
| Table 12-10—Congestion Point managed object row elements .....  | 330 |
| Table 12-9—CN Port priority managed object row elements .....   | 330 |
| Table 12-11—Reaction Point port priority managed object row elements .....  | 331 |
| Table 12-12—Reaction Point group managed object row elements .....  | 331 |
| Table 12-13—SRP Bridge Base Table row elements .....  | 332 |
| Table 12-14—SRP Bridge Port Table row elements .....  | 332 |
| Table 12-15—SRP Latency Parameter Table row elements .....  | 333 |
| Table 12-16—SRP Stream Table row elements .....   | 333 |
| Table 12-17—SRP Reservations Table row elements .....   | 334 |

|  |     |
|--|-----|
| Table 12-15—Priority-based Flow Control objects .....  | 334 |
| Table 12-17—EVB system base table .....  | 358 |
| Table 12-18—EVB system parameter defaults .....  | 360 |
| Table 12-20—VSI table entry .....  | 361 |
| Table 12-19—SBP table entry .....  | 361 |
| Table 12-21—VSI MAC/VLAN table entry .....   | 363 |
| Table 12-22—UAP table entry .....  | 364 |
| Table 12-23—UAP table entry parameters .....   | 364 |
| Table 12-24—S-channel interface table entry .....  | 365 |
| Table 12-25—URP table entry .....  | 366 |
| Table 12-26—ECP table entry .....  | 367 |
| Table 13-1—Configuration Digest Signature Key .....  | 383 |
| Table 13-2—Sample Configuration Digest Signature Keys .....  | 384 |
| Table 13-3—Bridge and Port Priority values .....   | 402 |
| Table 13-4—Port Path Cost values .....   | 403 |
| Table 13-5—Timer and related parameter values .....  | 411 |
| Table 17-1—Structure of the MIB modules .....  | 482 |
| Table 17-2—IEEE8021-TC-MIB Structure .....   | 484 |
| Table 17-3—IEEE8021-BRIDGE-MIB structure and<br>relationship to IETF RFC 4188 and this standard .....        | 485 |
| Table 17-4—IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB .....  | 490 |
| Table 17-5—IEEE8021-SPANNING-TREE MIB structure and relationship to<br>IETF RFC 4318 and this standard ..... | 490 |
| Table 17-6—Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB .....                                     | 492 |
| Table 17-7—IEEE8021-QBRIDGE MIB structure and<br>relationship to IETF RFC 4363 and this standard .....       | 493 |
| Table 17-8—Clause 12 management not in IEEE8021-Q-BRIDGE-MIB .....   | 498 |
| Table 17-9—IEEE8021-PB-MIB structure and relationship to this standard .....                                 | 499 |
| Table 17-10—IEEE8021-MSTP-MIB structure and relationship to this standard .....                              | 501 |
| Table 17-11—IEEE8021-CFM-MIB correspondence between variables, managed objects,<br>and MIB objects .....     | 503 |
| Table 17-12—IEEE8021-CFM-V2-MIB correspondence between variables, managed objects,<br>and MIB objects .....  | 507 |
| Table 17-13—IEEE8021-PBB-MIB structure and relationship to this standard .....                               | 509 |
| Table 17-14—IEEE8021-DDCFM-MIB structure and relationship<br>to this standard .....                          | 512 |
| Table 17-15—IEEE8021-PBBTE-MIB Structure and relationship to this standard .....                             | 514 |
| Table 17-16—Example of ieee8021PbbTeTeSiEspTable .....   | 516 |
| Table 17-17—IEEE8021-TPMR-MIB Structure and relationship to this standard .....                              | 517 |
| Table 17-18—FQTSS MIB structure and object cross reference .....   | 519 |
| Table 17-19—Variables, managed object tables, and MIB objects .....  | 520 |
| Table 17-20—SRP MIB structure and object cross reference .....   | 522 |
| Table 17-21—IEEE8021-MVRPX-MIB structure and relationship to this standard .....                             | 524 |
| Table 17-22—IEEE8021-MIRP-MIB structure and relationship to this standard .....                              | 524 |
| Table 17-23—Variables, managed object tables, and MIB objects .....  | 525 |
| Table 17-24—IEEE8021-TE IPS MIB Structure and relationship to this standard .....                            | 525 |
| Table 17-25—IEEE8021-SPB-MIB structure and relationship to this standard .....                               | 527 |
| Table 17-26—EVB MIB structure and object cross reference .....   | 531 |
| Table 17-27—IEEE8021-ECMP-MIB structure and relationship to this standard .....                              | 534 |
| Table 17-28—PBB-TE required MIB compliances .....  | 543 |
| Table 17-30—Sensitive managed objects: variables in dot1agCfmMdTable .....                                   | 551 |
| Table 17-29—Sensitive managed objects: tables and notifications .....  | 551 |
| Table 17-32—Sensitive managed objects (of DDCFM) for read .....  | 553 |
| Table 17-31—Sensitive managed objects (of DDCFM): tables and notifications .....                             | 553 |

|  |      |
|--|------|
| Table 17-33—Sensitive managed objects (of EVB): tables and notifications .....                           | 560  |
| Table 17-34—Sensitive managed objects (of EVB) for read .....  | 560  |
| Table 17-35—Provider Bridge service interface parameters .....   | 574  |
| Table 17-36—PBB service interface parameters .....   | 577  |
| Table 19-1—Actions taken by MP OpCode Demultiplexers .....   | 1077 |
| Table 19-2—SAP use for LTMs and LTRs .....   | 1084 |
| Table 20-1—Fault Alarm defects and priorities .....  | 1089 |
| Table 20-2—Deriving enableRmepDefect and Port Status TLV in a Bridge .....                               | 1099 |
| Table 21-1—CFM PDU Encapsulation: Length/Type Media .....  | 1143 |
| Table 21-2—CFM PDU Encapsulation: LLC Media .....  | 1143 |
| Table 21-3—Common CFM Header format .....  | 1144 |
| Table 21-4—OpCode Field range assignments .....  | 1144 |
| Table 21-5—TLV format .....  | 1145 |
| Table 21-6—Type Field values .....   | 1146 |
| Table 21-8—Sender ID TLV format .....  | 1147 |
| Table 21-7—Organization-Specific TLV format .....  | 1147 |
| Table 21-9—Port Status TLV format .....  | 1149 |
| Table 21-10—Port Status TLV values .....   | 1149 |
| Table 21-11—Interface Status TLV format .....  | 1149 |
| Table 21-13—Data TLV format .....  | 1150 |
| Table 21-14—End TLV format .....   | 1150 |
| Table 21-12—Interface Status TLV values .....  | 1150 |
| Table 21-15—CCM format .....   | 1151 |
| Table 21-16—CCM Interval field encoding .....  | 1152 |
| Table 21-17—CCM Maintenance Association Identifier field format: Maintenance Domain present ....         | 1153 |
| Table 21-18—CCM Maintenance Association Identifier field format: Maintenance Domain not<br>present ..... | 1153 |
| Table 21-19—Maintenance Domain Name Format .....   | 1154 |
| Table 21-20—Short MA Name Format .....   | 1154 |
| Table 21-21—LBM and LBR formats .....  | 1156 |
| Table 21-22—PBB-TE MIP TLV format .....  | 1157 |
| Table 21-23—LTM format .....   | 1158 |
| Table 21-24—LTM Flags field .....  | 1158 |
| Table 21-26—LTR format .....   | 1160 |
| Table 21-27—LTR Flags field .....  | 1160 |
| Table 21-25—LTM Egress Identifier TLV format .....   | 1160 |
| Table 21-28—Relay Action field values .....  | 1161 |
| Table 21-29—LTR Egress Identifier TLV format .....   | 1162 |
| Table 21-30—Reply Ingress TLV format .....   | 1162 |
| Table 21-31—Ingress Action field values .....  | 1163 |
| Table 21-33—Egress Action field values .....   | 1164 |
| Table 21-32—Reply Egress TLV format .....  | 1164 |
| Table 22-1—MEP creation .....  | 1178 |
| Table 22-2—MIP creation .....  | 1179 |
| Table 22-3—Bandwidth required for CCMs for 1 MA .....  | 1182 |
| Table 22-4—Bandwidth required for CCMs for 1000 MAs .....  | 1183 |
| Table 23-1—Time sequence diagram symbols .....   | 1193 |
| Table 23-2—MSP performance parameters .....  | 1199 |
| Table 23-3—MSP EtherType assignment .....  | 1205 |
| Table 23-4—MSP Packet Types .....  | 1206 |
| Table 24-1—Transmission and reception delays .....   | 1208 |
| Table 26-1—Backbone Service Instance Group address OUI .....   | 1231 |
| Table 26-8—Protection Requests Hierarchy .....   | 1254 |
| Table 27-1—Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example) .....                | 1277 |

|  |      |
|--|------|
| Table 28-1—Bridge Priority Masking .....   | 1306 |
| Table 29-1—RFM format .....  | 1341 |
| Table 29-2—SFM format .....  | 1342 |
| Table 32-1—LLDP instance selection managed object overrides .....                      | 1364 |
| Table 32-2—CND defense mode selection managed object overrides .....                   | 1364 |
| Table 32-3—Determining cnpdIsAdminDefMode and cnpdDefenseMode .....                    | 1370 |
| Table 32-4—Correspondence of QCN and CCF message fields .....                          | 1372 |
| Table 32-5—NewCpSampleBase() return value as a function of cpFb .....                  | 1375 |
| Table 33-3—CNM Encapsulation: Length/Type Media .....                                  | 1387 |
| Table 33-1—CN-TAG Encapsulation: Length/Type Media .....                               | 1387 |
| Table 33-2—CN-TAG Encapsulation: LLC Media .....                                       | 1387 |
| Table 33-5—Congestion Notification Message PDU .....                                   | 1388 |
| Table 33-4—CNM Encapsulation: LLC Media .....  | 1388 |
| Table 34-1—Recommended priority to traffic class mappings for SR classes A and B ..... | 1395 |
| Table 34-2—Recommended priority to traffic class mappings for SR class B only .....    | 1395 |
| Table 35-1—AttributeType Values .....  | 1405 |
| Table 35-2—AttributeLength Values .....  | 1406 |
| Table 35-4—MSRP FirstValue NumberOfValues example .....                                | 1407 |
| Table 35-3—FourPackedEvent Values .....  | 1407 |
| Table 35-5—TSPEC components examples .....   | 1411 |
| Table 35-6—Reservation Failure Codes .....   | 1413 |
| Table 35-7—SR class ID .....   | 1414 |
| Table 35-8—Summary of Talker primitives .....  | 1416 |
| Table 35-9—Summary of Listener primitives .....  | 1416 |
| Table 35-11—Incoming Listener attribute propagation per port .....                     | 1421 |
| Table 35-10—Talker attribute propagation per port .....                                | 1421 |
| Table 35-12—Updating Dynamic Reservation Entries .....                                 | 1422 |
| Table 35-14—Listener Declaration Type Summation .....                                  | 1423 |
| Table 35-13—Updating operIdleSlope(N) .....  | 1423 |
| Table 41-1—VDP TLV types .....   | 1454 |
| Table 41-2—Flag values in VDP requests .....   | 1455 |
| Table 41-3—Error types in VDP responses .....  | 1455 |
| Table 41-5—VSIID format values .....   | 1456 |
| Table 41-4—Flag values in VDP responses .....  | 1456 |
| Table 41-6—Filter Info format values .....   | 1457 |
| Table 43-1—ECP subtypes .....  | 1477 |
| Table 44-1—ECMP ECT-ALGORITHM values .....   | 1485 |
| Table 44-2—F-TAG EtherType .....   | 1486 |
| Table C-1—SRP to MoCA PQoS Transaction mapping .....                                   | 1574 |
| Table C-2—SRP TSpec to MoCA TSPEC mapping .....  | 1575 |
| Table C-3—SRP StreamID to MoCA PQoS Flow transaction mapping .....                     | 1575 |
| Table C-4—SRP to MLME QoS Services mapping .....                                       | 1581 |
| Table C-5—EDCA-AC for AV Streams .....   | 1582 |
| Table C-6—HCCA for AV Streams .....  | 1583 |
| Table D-1—IEEE 802.1 Organizationally Specific TLVs specified in this standard .....   | 1584 |
| Table D-2—Port and protocol capability/status .....                                    | 1586 |
| Table D-3—Link Aggregation capability/status .....                                     | 1589 |
| Table D-4—Priority assignment table .....  | 1591 |
| Table D-5—Traffic class bandwidth assignment table .....                               | 1592 |
| Table D-6—TSA Assignment Table .....   | 1592 |
| Table D-7—PFC Enable bit vector .....  | 1595 |
| Table D-8—Application Priority Table .....   | 1596 |
| Table D-9—Sel field values .....   | 1596 |
| Table D-10—RRSAT flag values and meanings .....  | 1598 |

|  |      |
|--|------|
| Table D-11—EVB Mode values .....   | 1599 |
| Table D-12—IEEE 802.1 extension MIB object group conformance requirements .....          | 1607 |
| Table D-13—IEEE 802.1/LLDP extension MIB object cross reference .....                    | 1608 |
| Table E-1—State machine symbols .....  | 1693 |
| Table I-1—Traffic type to traffic class mapping .....                                    | 1712 |
| Table I-2—Traffic type acronyms .....  | 1714 |
| Table I-3—Defining traffic types .....   | 1715 |
| Table I-5—Defining traffic types—Credit-based shaper support of SR classes A and B ..... | 1716 |
| Table I-4—Defining traffic types—Credit-based shaper support of SR class B only .....    | 1716 |
| Table I-6—Priority Code Point encoding .....   | 1718 |
| Table I-7—Priority Code Point decoding .....   | 1718 |
| Table J-1—Provider MD Level allocation .....   | 1720 |
| Table J-2—IEEE / ITU-T terminology differences .....                                     | 1720 |
| Table N-1—IEEE 802.3 Interface Delays .....  | 1753 |