ISO/IEC 30190:2016-06 (E)

Information technology - Digitally recorded media fo r information interchange and storage - 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk

Contents

Page

1 Scope 1

2 Conformance 2
2.1 Optical disk 2
2.2 Generating system 2
2.3 Receiving system 2
2.4 Compatibility statement 2

3 Normative references 2

4 Terms and definitions 3

5 Conventions and notations 7
5.1 Terminology: 7
5.1.1 Meaning of words 7
5.1.2 Levels of grouping 7
5.2 Representation of numbers 7
5.3 Integer calculus 8
5.4 Names 8

6 List of acronyms 9

7 General description of disk 11

8 General requirements 14
8.1 Environments 14
8.1.1 Test environment 14
8.1.2 Operating environment 14
8.1.3 Storage environment 15
8.1.4 Transportation 16
8.2 Safety requirements 16
8.3 Flammability 16

9 Reference drive 16
9.1 General 16
9.2 Measurement conditions 16
9.3 Optical system 17
9.4 Optical beam 18
9.5 HF read channel 18
9.6 Radial PP read channel 18
9.7 Disk Clamping 19
9.8 Rotation of disk and Measurement Velocity 19
9.9 Normalized servo transfer function 20
9.10 Measurement Velocities and Reference servos for axial tracking 20
9.10.1 General 20
9.10.2 Reference servo for axial tracking for 1x Measurement Velocity 21
9.10.3 Reference servo for axial tracking for 2x Measurement Velocity and 3x Measurement Velocity 22
9.11 Measurement Velocities and Reference servos for radial tracking 23

9.11.1 General ... 23
9.11.2 Reference servo for radial tracking for 1x Measurement Velocity ... 23
9.11.3 Reference servo for radial tracking for 2x Measurement Velocity and 3x Measurement Velocity ... 24

10 Dimensional characteristics ... 25
10.1 General ... 25
10.2 Disk reference planes and reference axis ... 25
10.3 Overall dimensions ... 27
10.4 First transition Area ... 27
10.5 Protection ring ... 28
10.6 Clamping Zone ... 28
10.7 Second transition Area ... 28
10.8 Information Area ... 28
10.8.1 General ... 28
10.8.2 Subdivision of Information Zone on SL disks ... 29
10.8.3 Subdivision of Information Zone on DL disks ... 29
10.9 Rim Area ... 30

11 Mechanical characteristics ... 31
11.1 Mass ... 31
11.2 Moment of inertia ... 31
11.3 Dynamic imbalance ... 31
11.4 Axial runout ... 31
11.4.1 General ... 31
11.4.2 Residual axial tracking error for 1x Measurement Velocity ... 31
11.4.3 Residual axial tracking error for 2x Measurement Velocity ... 32
11.4.4 Residual axial tracking error for 3x Measurement Velocity ... 32
11.5 Radial runout ... 33
11.5.1 General ... 33
11.5.2 Residual radial tracking error for 1x Measurement Velocity on SL disks ... 33
11.5.3 Residual radial tracking error for 1x Measurement Velocity on DL disks ... 33
11.5.4 Residual radial tracking error for 2x Measurement Velocity on SL and DL disks ... 34
11.5.5 Residual radial tracking error for 3x Measurement Velocity on SL and DL disks ... 34
11.6 Durability of Cover Layer ... 34
11.6.1 Impact resistance of Cover Layer ... 34
11.6.2 Scratch resistance of Cover Layer ... 34
11.6.3 Repulsion of fingerprints by Cover Layer ... 35

12 Optical characteristics in Information Area ... 35
12.1 General ... 35
12.2 Refractive index of Transmission Stacks (TS) ... 35
12.3 Thickness of Transmission Stacks (TS) ... 35
12.3.1 Thickness of Transmission Stack of SL disks ... 35
12.3.2 Thickness of Transmission Stacks of DL disks ... 35
12.4 Reflectivity ... 37
12.4.1 Reflectivity of Recording Layer of SL disks ... 37
12.4.2 Reflectivity of Recording Layers of DL disks ... 37
12.5 Birefringence ... 37
12.6 Angular deviation ... 38

13 Data Format ... 39
13.1 General ... 39
13.2 Data Frame ... 41
13.3 Error-Detection Code (EDC) ... 41
13.4 Scrambled Data Frame ... 42
13.5 Data Block ... 43
13.6 LDC Block ... 44
13.7 LDC code-words ... 44
13.8 LDC Cluster ... 45
13.8.1 General ... 45
13.8.2 First interleaving step ... 45

13.8.3 Second interleaving step 45
13.9 Addressing and Control Data 47
13.9.1 General 47
13.9.2 Address Units 47
13.9.3 User-Control Data 50
13.9.4 Byte/Bit assignment for User-Control Data 50
13.10 Access Block 52
13.11 BIS Block 52
13.12 BIS code-words 53
13.13 BIS Cluster 53
13.14 ECC Cluster 58
13.15 Recording Frames 59
13.16 Physical Cluster 59
13.17 17PP modulation for Recordable data 60
13.17.1 General 60
13.17.2 Bit conversion rules 60
13.17.3 dc-control procedure 61
13.17.4 Frame Sync 61
13.18 Modulation and NRZI conversion 62

14 Physical Data Allocating and Linking 63
14.1 General 63
14.2 Recording-Unit Block (RUB) 63
14.2.1 General 63
14.2.2 Data Run-in 64
14.2.3 Data Run-out 65
14.2.4 Guard_3 field 66
14.3 Locating data relative to wobble addresses 66

15 Track format 67
15.1 General 67
15.2 Track shape 67
15.3 Track path 68
15.4 Track Pitch 69
15.4.1 Track Pitch in BCA Zone 69
15.4.2 Track Pitch in Embossed HFM Area 69
15.4.3 Track Pitch in Recordable Area(s) 69
15.4.4 Track Pitch between Embossed HFM Area and Recordable Area 69
15.5 Track layout of HFM Groove 69
15.5.1 General 69
15.5.2 Data Format 70
15.5.3 Addressing and Control Data 71
15.5.4 Recording Frames 75
15.6 Track layout of Wobbled Groove(s) 77
15.6.1 General 77
15.6.2 Modulation of wobbles 77
15.6.3 Wobble polarity 79
15.7 ADIP information 79
15.7.1 General 79
15.7.2 ADIP-Unit Types 79
15.7.3 ADIP word structure 80
15.7.4 ADIP data structure 82
15.7.5 ADIP error correction 84
15.8 Disk Information in ADIP Aux Frame 86
15.8.1 General 86
15.8.2 Error protection for Disk-Information Aux Frames 86
15.8.3 Disk-Information data structure 87

16 General description of Information Zone 127
16.1 General 127
16.2 Format of Information Zone on Single-Layer disk 127
16.3 Format of Information Zone on Dual-Layer disk 127

17 Layout of Recordable Area of Information Zone 127

18 Inner Zone 131
18.1 General 131
18.2 Permanent Information & Control data (PIC) Zone 133
18.2.1 General 133
18.2.2 Content of PIC Zone 133
18.2.3 Emergency Brake 135
18.3 Recordable Area of Inner Zone 0 136
18.3.1 Protection-Zone 2 136
18.3.2 INFO 2 / Reserved 8 137
18.3.3 INFO 2 / Reserved 7 137
18.3.4 INFO 2 / Reserved 6 137
18.3.5 INFO 2 / Reserved 5 137
18.3.6 INFO 2 / PAC 2 137
18.3.7 INFO 2 / DMA 2 137
18.3.8 INFO 2 / Control Data 2 137
18.3.9 INFO 2 / Buffer 2 137
18.3.10 OPC 0 / Test Zone 137
18.3.11 Usage of OPC Areas 138
18.3.12 OPC 0 / OPC 0 Buffer 139
18.3.13 TDMA 0 139
18.3.14 INFO 1 / Pre-write Area 139
18.3.15 INFO 1 / Drive Area 139
18.3.16 INFO 1 / DMA 1 141
18.3.17 INFO 1 / Control Data 1 141
18.3.18 INFO 1 / PAC 1 141
18.4 Recordable Area of Inner Zone 1 142
18.4.1 Buffer 142
18.4.2 OPC 1 142
18.4.3 Buffer 142
18.4.4 INFO 2 / Reserved 8 142
18.4.5 INFO 2 / Reserved 7 142
18.4.6 INFO 2 / Reserved 6 142
18.4.7 INFO 2 / Reserved 5 142
18.4.8 INFO 2 / PAC 2 142
18.4.9 INFO 2 / DMA 2 142
18.4.10 INFO 2 / Control Data 2 142
18.4.11 INFO 2 / Buffer 2 143
18.4.12 TDMA 1 143
18.4.13 Reserved 143
18.4.14 INFO 1 / Pre-write Area 143
18.4.15 INFO 1 / Drive Area 143
18.4.16 INFO 1 / DMA 1 143
18.4.17 INFO 1 / Control Data 1 143
18.4.18 INFO 1 / PAC 1 143

19 Data Zone 143

20 Outer Zone(s) 144
20.1 General 144
20.2 Recordable Area of Outer Zone(s) 144
20.2.1 INFO 3 / Buffer 4 144
20.2.2 INFO 3 / DMA 3 144
20.2.3 INFO 3 / Control Data 3 145
20.2.4 Angular buffer 145
20.2.5 INFO 4 / DMA 4 145
20.2.6 INFO 4 / Control Data 4 145
20.2.7 INFO 4 / Buffer 6 145
20.2.8 DCZ 0 / Test Zone and DCZ 1 / Test Zone 145
20.2.9 Usage of DCZ Area 145

20.2.10 Protection-Zone 3 147

21 Physical-Access Control Clusters 148
21.1 General 148
21.2 Layout of PAC Zones 148
21.3 General structure of PAC Clusters 149
21.4 IS1 and IS2 PAC Clusters 152

22 Disk Management 153
22.1 General 153
22.2 Recording Management 153
22.2.1 Sequential-Recording Mode (SRM) 153
22.2.2 Recording User Data in SRR 153
22.2.3 SRR status 154
22.2.4 Closing SRR 154
22.3 Temporary Disk-Management Areas (TDMA) 154
22.3.1 General 154
22.3.2 TDMA Access indicators 154
22.4 Disk-Management Structure (DMS) 155
22.4.1 General 155
22.4.2 Temporary Disk-Management Structure (TDMS) 155
22.4.3 TDMS in Sequential-Recording Mode 156
22.4.4 Temporary Disk-Definition Structure (TDDS) 156
22.4.5 Temporary Defect List (TDFL) 160
22.4.6 Sequential-Recording Range Information (SRRI) 162
22.5 Unrecorded (blank) disk structure 164
22.5.1 General 164
22.5.2 Pre-recorded Areas on Unrecorded disk 164
22.5.3 Pre-recorded BCA 165
22.5.4 Pre-recorded INFO 2 / Reserved 5, Reserved 8 and Pre-recorded INFO 1 / Pre-write Area 165
22.5.5 Pre-recorded INFO 1 / PAC 1 and Pre-recorded INFO 2 / PAC 2 165
22.5.6 OPC 0 / Test Zone and OPC 1 / Test Zone 165
22.5.7 TDMA 0 166
22.5.8 Initialization of disk 166
22.6 Recorded (Closed) disk structure 166
22.6.1 General 166
22.6.2 DMA Zones 166
22.6.3 Disk-Management Structures (DMS) 167

23 Assignment of Logical-Sector Numbers (LSNs) 169

24 Characteristics of Grooved Areas 170

25 Method of testing for Grooved Area 171
25.1 General 171
25.2 Environment 171
25.3 Reference drive 171
25.3.1 General 171
25.3.2 Read power 171
25.3.3 Read channels 171
25.3.4 Tracking requirements 171
25.3.5 Scanning velocities 171
25.4 Definition of signals 172

26 Signals from HFM Groove 174
26.1 Push-Pull polarity 174
26.2 Push-Pull signal 174
26.3 Wobble signal 174
26.4 Jitter of HFM signal 174

27 Signals from Wobbled Groove(s) 175
27.1 Phase depth 175

27.2 Push-Pull signal 175
27.3 Wobble signal 175
27.3.1 General 175
27.3.2 Measurement of NWS 176
27.3.3 Measurement of wobble CNR 176
27.3.4 Measurement of harmonic distortion of wobble 176
27.4 HFM and Wobbled Groove transition requirements 176

28 Characteristics of Recording Layer 177

29 Method of testing for Recording Layer 178
29.1 General 178
29.2 Environment 178
29.3 Reference drive 178
29.3.1 General 178
29.3.2 Read power 178
29.3.3 Read channels 178
29.3.4 Tracking requirements 178
29.3.5 Scanning velocities 178
29.4 Write conditions 179
29.4.1 Write-pulse waveform 179
29.4.2 Write powers 180
29.4.3 Write conditions for jitter measurement 180
29.5 Definition of signals 180

30 Signals from Recorded Areas 182
30.1 HF signals 182
30.2 Modulated amplitude 182
30.3 Reflectivity-Modulation product 183
30.4 Asymmetry 183
30.5 Jitter 183
30.6 Read stability 184

31 Local defects 185

32 Characteristics of User Data 185

33 Method of testing for User Data 186
33.1 General 186
33.2 Environment 186
33.3 Reference drive 186
33.3.1 General 186
33.3.2 Read power 186
33.3.3 Read channels 186
33.3.4 Error correction 186
33.3.5 Tracking requirements 186
33.3.6 Scanning velocities 186
33.4 Definition of signals 187

34 Minimum quality of recorded information 188
34.1 Symbol Error Rate 188
34.2 Maximum burst errors 188
34.3 User-written Data 188

35 BCA 189

Annex A (normative) Thickness of Transmission Stacks in case of multiple layers 190

A.1 General 190
A.2 Refractive Index ni of all layers in Cover and Spacer Layers 190
A.3 Thickness variation of Transmission Stack 190
A.4 Example of thickness calculation for SL 190

Annex B (normative) Measurement of reflectivity 191

B.1 General 191
B.2 Calibration method 191
B.3 Measuring method 192

Annex C (normative) Measurement of scratch resistance of Cover Layer 194

C.1 General 194
C.2 Taber Abrasion test 194

Annex D (normative) Measurement of repulsion of grime by Cover Layer 196

D.1 General 196
D.2 Specifications of stamp 196
D.3 Preparation of ink 197
D.4 Preparation of ink pad 197
D.5 Using ink pad and stamp 198

Annex E (normative) Measurement of wobble amplitude 199

E.1 Measurement methods 199
E.2 Calibration of filters 203

Annex F (normative) Write-pulse waveform for testing 204

F.1 General write-pulse waveform 204
F.2 N-1 write strategy 205
F.3 N/2 write strategy 208
F.4 Castle write strategy 211
F.5 Definition of pulse widths and rise and fall times 215

Annex G (normative) Optimum Power Control(OPC) procedure for disk 216

G.1 General 216
G.2 Mathematical model for modulation versus power function 216
G.3 Procedure for determination of OPC parameters for disk 218
G.4 Procedure to determine Beta value 218

Annex H (normative) HF signal pre-processing for jitter measurements 220

H.1 General 220
H.2 General implementation of equalizer 220
H.3 Conventional Equalizer circuit 221
H.4 Limit Equalizer circuit 222
H.5 Specifications of supporting circuits 223
H.5.1 Amplifiers and filters 223
H.5.2 Open-loop transfer function for PLL 224
H.5.3 Slicer 225
H.6 Condition for measurement 225
H.7 Jitter measurement 226

Annex I (normative) Measurement procedure 227

I.1 General 227
I.2 Initial adjustments of Reference drive 227
I.3 Jitter measurement 227
I.4 Modulated amplitude measurements 228
I.5 Measurements of Resolution I2pp / I8pp and I3pp / I8pp 228
I.5.1 Method for measuring I2pp and I8pp 228
I.5.2 I3pp / I8pp, I8pp / I8H and asymmetry measurement procedure 229

I.6 Tracking-error signal measurements (PPnorm measurement procedure) 230
I.7 Residual error of axial tracking measurement procedure 231
I.8 Residual error of radial tracking measurement procedure 232
I.9 Random SER measurement 233

Annex J (informative) Measurement of birefringence 234

J.1 Principle of measurement 234
J.2 Measurements conditions 234
J.3 Example of measurement procedure 235
J.4 Interchangeability of measuring results 235

Annex K (informative) Measurement of thickness of Cover Layer and Spacer Layer 236

K.1 Focusing method 236
K.2 Interferometer method 237

Annex L (informative) Measurement of impact resistance of Cover Layer 239

L.1 General 239
L.2 Recommendation for drives 239
L.3 Measurements of impact resistance of Cover Layer 239

Annex M (informative) Groove deviation and wobble amplitude 241

M.1 Relation between normalized wobble signal and wobble amplitude 241
M.2 Tolerance of normalized wobble signal 241