ISO/IEC/IEEE 8802-1BR:2016-10 (E)

Information technology - Telecommunications and inform ation exchange between systems - Local and metropolitan area networks - Specific requirements - Part 1BR: Virtual bridged local area networks - Bridge port extension

Contents

Page

1. Overview ... 1

1.1 Scope ... 1
1.2 Purpose ... 2

2. Normative references ... 3

3. Definitions ... 4

4. Acronyms and abbreviations ... 6

5. Conformance ... 7

5.1 Terminology ... 7
5.2 Protocol Implementation Conformance Statement (PICS) ... 7
5.3 Bridge Port Extender Conformance ... 7
5.4 Controlling Bridge Conformance ... 8

6. Principles of Bridge Port Extension ... 10

6.1 Bridge Port Extension Overview ... 10
6.2 Extended Bridge ... 11
6.3 Base and aggregating Bridge Port Extenders ... 13
6.4 Bridge Port Extender operation ... 14
6.5 Bridge Port Extender architecture ... 16
6.6 Bridge Port Extender Model of operation ... 17
6.7 Bridge Port Extender Frame Reception ... 19
6.8 Bridge Port Extender Transmit and Receive ... 19
6.9 Bridge Port Extender tag handler ... 20
6.10 Bridge Port Extender Internal Sublayer Service ... 21
6.11 Bridge Port Extender Forwarding Process ... 25
6.12 Bridge Port Extender Filtering Database ... 29
6.13 Determination of the Upstream Port ... 29
6.14 Upstream Port Addressing ... 30
6.15 Bridge Port Extender Initialization ... 30
6.16 Support of Congestion Points ... 31

7. Tagged frame format ... 32

7.1 Representation and encoding of tag fields ... 32
7.2 Tag format ... 32
7.3 Tag Protocol Identifier (TPID) formats ... 32
7.4 Tag Protocol Identification ... 32
7.5 E-TAG Control Information ... 32

8. Support of Bridge Port Extension by C-VLAN components ... 35

8.1 Use of Tags ... 36
8.2 Bridge Port Extension Port Types ... 36
8.3 Internal Bridge Port Extender Cascade Ports ... 37
8.4 Bridge Port Extender Upstream Ports ... 39

8.5 External Extended Ports 39
8.6 External Bridge Port Extender Cascade Ports 40
8.7 Traffic isolation 41
8.8 Support of Port Extension by a C-VLAN component MAC Relay 41
8.9 Remote replication 42
8.10 Support of Remote Replication by a Controlling Bridge 43
8.11 Assignment of E-CIDs 44
8.12 Support of Congestion Notification 45

9. Port Extender Control and Status Protocol 46

9.1 Port Selection and Addressing 46
9.2 PE CSP State Machines 46
9.3 Protocol Errors 52
9.4 PE CSP PDUs 52
9.5 Basic TLV format 52
9.6 Command TLV 54
9.7 Flow Control 56
9.8 Messages 56
9.9 Additional TLVs 61

10. Bridge management 72

10.1 Data types 72
10.2 Bridge Port Extension Entries 72

11. Management Information Base (MIB) 75

11.1 Structure of the IEEE8021-PE MIB 75
11.2 Relationship to other MIBs 76
11.3 Security considerations 76
11.4 Definition of the IEEE8021-PE MIB Module 78

Annex A (normative) PICS proforma 89

Annex B (normative) IEEE 802.1 Organizationally Specific TLVs 105

Annex C (informative) Utilizing VDP with Port Extension 114

Annex D (informative) Extended Bridge Initialization 116

Annex E (informative) Bibliography 121

Figures

Figure 6-1—Extended Bridge 10
Figure 6-2—Aggregating and base Bridge Port Extenders 14
Figure 6-3—External Bridge Port Extender architecture 16
Figure 6-4—Internal Bridge Port Extender architecture 17
Figure 6-5—Relaying MAC frames in an External Bridge Port Extender 18
Figure 6-6—Operation of Bridge Port Extender Control and Status Protocol Agent 18
Figure 6-7—Port connectivity 20
Figure 6-8—Bridge Port Extender Forwarding Process functions 26
Figure 7-1—E-TAG TCI format 32
Figure 8-1—Internal organization of the MAC sublayer in an Extended Bridge 35
Figure 8-2—Extended Bridge Interconnection 37
Figure 8-3—Cascaded Bridge Port Extenders 40
Figure 8-4—Extended Bridge traffic isolation 41
Figure 9-1—PE CSP Receive PDU state machine 47
Figure 9-2—PE CSP Transmit PDU state machine 47
Figure 9-3—PE CSP Local Request state machine 48
Figure 9-4—PE CSP Remote Request state machine 48
Figure 9-5—Basic TLV format 52
Figure 9-6—Command TLV 54
Figure 9-7—Resource Limit Capability TLV 61
Figure 9-1—Port Parameters TLV 63
Figure 9-8—Port Array TLV 64
Figure 9-9—Port Entry 64
Figure 9-10—VID Array TLV 65
Figure 9-11—VID Entry 65
Figure 9-12—Port Status TLV 66
Figure 9-13—Statistics TLV 66
Figure 9-14—Object Name TLV 67
Figure 9-15—Object Value TLV 67
Figure 9-16—CN Parameters TLV 70
Figure 9-17—Basic format for Organizationally Specific TLVs 71
Figure B.1—Port Extension TLV format 105
Figure C.1—Relationship of Port Extension and EVB 114
Figure C.2—Port Extension and EVB combined architecture 115
Figure D.1—Attachment of a physical Bridge Port Extender 117
Figure D.2—Attachment of a downstream Bridge Port Extender 118
Figure D.3—Example Initialization Message Flow 120

Tables

Table 6-1—Bridge Port Extender Initialization 31
Table 6-2—Bridge Port Extender Port Initialization 31
Table 7-1—E-TAG EtherType allocation 32
Table 8-1—Bridge Port Extender parameter settings 38
Table 9-1—Port Extender Control and Status Protocol—Time out Values 52
Table 9-2—TLV type values 53
Table 9-3—Completion Codes 54
Table 9-4—Message Types 55
Table 9-5—Priority Code Point Selection Encoding 64
Table 9-6—Action Values 65
Table 9-8—Statistics TLV contents 66
Table 9-7—Action Values 66
Table 9-9—Reference 67
Table 9-10—Get Objects Value Error Codes 68
Table 9-11—Set Object Value Error Codes 68
Table 9-12—CN Parameter Fields 70
Table 10-1—Port Extension Port Table row elements 73
Table 10-3—Port Extension Upstream Port ETS Table row elements 74
Table 10-2—Port Extension Remote Replication Table row elements 74
Table 11-1—PE MIB structure and object cross reference 75
Table B.1—IEEE 802.1 Organizationally Specific TLVs 105
Table B.2—IEEE 802.1/LLDP extension MIB object cross reference 106