

ISO/IEC 23008-1:2017-08 (E)

Information technology - High efficiency coding and media delivery in heterogeneous environments - Part 1: MPEG media transport (MMT)

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	4
4	Conventions	6
5	Overview	6
6	MMT data model	9
6.1	General	9
6.2	Package	10
6.3	Asset	10
6.4	Media processing unit (MPU)	11
6.5	Asset delivery characteristics	12
6.5.1	General	12
6.5.2	ADC descriptors	12
6.5.3	Syntax	13
6.5.4	Semantics	14
6.6	Bundle delivery characteristics	15
6.6.1	General	15
6.6.2	BDC descriptors	15
6.6.3	Syntax	15
6.6.4	Semantics	16
7	ISOBMFF-based MPU	17
7.1	General	17
7.2	MPU brand definition	18
7.3	MPU box	19
7.3.1	Definition	19
7.3.2	Syntax	20
7.3.3	Semantics	20
8	MMT hint track	21
8.1	General	21
8.2	Sample description format	21
8.2.1	Definition	21
8.2.2	Syntax	21
8.2.3	Semantics	21
8.3	Sample format	22
8.3.1	Definition	22
8.3.2	Syntax	22
8.3.3	Semantics	22

9	Packetized delivery of Package	23
9.1	General	23
9.2	MMT protocol	24
9.2.1	General	24
9.2.2	Structure of an MMTP packet	25
9.2.3	Semantics	26
9.2.4	MMTP session description information	29
9.3	MMTP payload	29
9.3.1	General	29
9.3.2	MPU mode	30
9.3.3	Generic file delivery mode	32
9.3.4	Signalling message mode	37
9.4	MMTP operation	38
9.4.1	General	38
9.4.2	Delivering MPUs	38
9.4.3	Delivering generic objects	40
9.4.4	Header compression for MMTP packet	43
10	Signalling	45
10.1	General	45
10.2	Signalling message format	46
10.2.1	General	46
10.2.2	Syntax	47
10.2.3	Semantics	47
10.3	Signalling messages for Package consumption	47
10.3.1	General	47
10.3.2	PA message	48
10.3.3	MPI message	49
10.3.4	MPT message	51
10.3.5	CRI message	51
10.3.6	DCI message	52
10.3.7	PA table	53
10.3.8	MPI table	54
10.3.9	MP table	57
10.3.10	CRI table	60
10.3.11	DCI table	61
10.3.12	SSWR message	63
10.3.13	LS message	64
10.3.14	LR message	65
10.3.15	SI table	66
10.4	Signalling messages for Package delivery	70
10.4.1	General	70
10.4.2	Hypothetical receiver buffer model (HRBM) message	71
10.4.3	Measurement configuration (MC) message	72
10.4.4	ARQ configuration (AC) message	74
10.4.5	ARQ feedback (AF) message	75
10.4.6	Reception quality feedback (RQF) message	78
10.4.7	NAM feedback (NAMF) message	80
10.4.8	Low delay consumption (LDC) message	82
10.4.9	HRBM removal message	83
10.4.10	ADC message	84
10.5	Descriptors	87
10.5.1	CRI descriptor	87
10.5.2	MPU timestamp descriptor	88
10.5.3	Dependency descriptor	89
10.5.4	GFDT descriptor	90
10.5.5	SI descriptor	92
10.6	Syntax element groups	93
10.6.1	MMT_general_location_info	93
10.6.2	asset_id	96
10.6.3	Identifier mapping	96

10.6.4	mime_type	98
10.7	ID and tags values	98
11	Hypothetical receiver buffer model (HRBM)	100
11.1	General	100
11.2	FEC decoding buffer	101
11.3	De-jitter buffer	101
11.4	MMTP packet decapsulation buffer	102
11.5	Usage of HRBM	102
11.6	Estimation of end-to-end delay and buffer requirement	102
11.7	HRBM signalling	103
12	Cross layer interface (CLI)	103
12.1	General	103
12.2	Cross layer information	103
12.2.1	General	103
12.2.2	Top-down QoS information	103
12.2.3	Bottom-up QoS information	103
12.2.4	Network abstraction for media (NAM)	104
12.2.5	Syntax	104
12.2.6	Semantics	105
Annex A	(informative) Jitter calculation in MMTP	106
Annex B	(normative) XML syntax and MIME type for signalling message	107
Annex C	(normative) AL-FEC framework for MMT	114
Annex D	(informative) QoS management model for MMT	139
Annex E	(informative) Operation of downloadable DRM and CAS	141
Annex F	(informative) DASH segment over MMTP	142
Annex G	(normative) Scheme of MMT URI	145
Bibliography	146