ISO/IEC/IEEE 8802-1Q AMD 1:2017-07 (E)

Path control and reservation

Contents

Page

1. Overview ... 2
   1.3 Introduction ... 2
2. Normative references ... 3
3. Definitions ... 4
4. Abbreviations ... 6
5. Conformance ... 7
   5.4.6 Path Control and Reservation (PCR) (optional) ... 7
7. Principles of Virtual Bridged Network operation ... 8
   7.1 Network overview ... 8
   7.3 Active topology ... 8
8. Principles of Bridge operation ... 10
   8.4 Active topologies, learning, and forwarding ... 10
   8.6.1 Active topology enforcement ... 10
   8.8.9 Querying the FDB ... 10
   8.9.3 ID to MSTI Allocation Table ... 11
12. Bridge management ... 12
   12.25 Shortest Path Bridging managed objects ... 12
   12.25.4 The SPB ECT Static Entry managed object ... 13
   12.28 Path Control and Reservation (PCR) management ... 13
   12.28.1 The PCR ECT Static Entry managed object ... 14
   12.28.2 The PCR Topology ECT Table managed object ... 16
17. Management Information Base (MIB) ... 18
   17.2 Structure of the MIB ... 18
   17.2.19 Structure of the IEEE8021-SPB-MIB ... 18
   17.3 Relationship to other MIBs ... 19
   17.3.22 Relationship of the PCR MIB to other MIB modules ... 19
   17.4 Security considerations ... 19
   17.4.22 Security considerations of the PCR MIB ... 19
   17.7 MIB modules ... 19
   17.7.19 Definitions for the IEEE8021-SPB-MIB module ... 19
27. Shortest Path Bridging (SPB) ... 64
   27.1 Protocol design requirements ... 64
   27.4 ISIS-SPB VLAN configuration ... 64
28. ISIS-SPB Link State Protocol ... 66
   28.6 Symmetric ECT framework ... 66
   28.7 Symmetric ECT ... 66
   28.8 Symmetric ECT Algorithm details ... 66

28.12.4 SPB Base VLAN-Identifiers sub-TLV 67
28.12.5 SPB Instance sub-TLV 67
28.12.10 SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV 67

45. Path Control and Reservation (PCR) 68

45.1 Explicit trees 68
45.1.1 Tree structures 72
45.1.2 Explicit ECT Algorithms 73
45.1.3 ISIS-PCR VLAN configuration 75
45.1.4 Use of VIDs for strict explicit trees 79
45.1.5 MAC addresses and ISIS-PCR 80
45.1.6 Filtering Database entries for explicit trees 80
45.1.7 ISIS-PCR support 81
45.1.8 Attributes for path computation 81
45.1.9 Topology sub-TLV 83
45.1.10 Hop sub-TLV 86
45.1.11 Administrative Group sub-TLV 89
45.1.12 Bandwidth Constraint sub-TLV 89
45.2 Reservation 90
45.2.1 Bandwidth Assignment sub-TLV 90
45.2.2 Timestamp sub-TLV 92
45.2.3 Precedence ordering 92
45.3 Redundancy 92
45.3.1 Loop-free alternates for unicast data flows 93
45.3.2 Static redundant trees 93
45.3.3 Maximally Redundant Trees (MRTs) 94
45.3.4 MRTs with centralized GADAG computation 97

Annex A (normative) PICS proforma—Bridge implementations 101

Annex Q (informative) Bibliography 105

Figures

Figure 7-1 VLAN Bridging overview 8
Figure 12-3 SPB managed objects (MOs) 12
Figure 27-1 Configuring VLAN support in an SPT Region (example) 65
Figure 45-1 An SPT Region controlled by a single PCE 69
Figure 45-2 An SPT Region controlled by multiple PCEs 70
Figure 45-3 The use of the SPB Instance sub-TLV for MRT 78
Figure 45-4 Shared Risk Link Group (SRLG) TLV 82
Figure 45-5 Topology sub-TLV 83
Figure 45-6 A strict tree and its descriptor Topology sub-TLV 84
Figure 45-7 Topology sub-TLV of a loose tree 85
Figure 45-8 Hop sub-TLV 86
Figure 45-9 Administrative Group sub-TLV 89
Figure 45-10 Bandwidth Constraint sub-TLV 90
Figure 45-11 Bandwidth Assignment sub-TLV 91
Figure 45-12 Timestamp sub-TLV 92
Figure 45-13 A GADAG and its descriptor Topology sub-TLV 98
Figure 45-14 MRT-Blue and MRT-Red for MRT Root 55 98
Figure 45-15 A GADAG for a topology with multiple blocks 99

Tables

Table 17-1 Structure of the MIB modules 18
Table 17-25 IEEE8021-SPB-MIB structure and relationship to this standard 18
Table 45-1 ECT-ALGORITHM values for explicit trees 73
Table 45-2 Bridge Priority Masking for the LT and LTS ECT Algorithms 74
Table 45-3 Hop sub-TLV flags 87