

ISO/IEC/IEEE 8802-15-4:2018-03 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-4: Wireless medium access control (MAC) and physical layer (PHY) specifications for low-rate wireless personal area networks (WPANs)

Contents

- 1. Overview 35
 - 1.1 Scope 35
 - 1.2 Purpose 35
- 2. Normative references 36
- 3. Definitions, acronyms, and abbreviations 37
 - 3.1 Definitions 37
 - 3.2 Acronyms and abbreviations 38
- 4. Format conventions 42
 - 4.1 General 42
 - 4.2 Fields 42
 - 4.3 Numbers 43
 - 4.4 Strings 43
 - 4.5 Reserved fields and values 43
- 5. General description 44
 - 5.1 Introduction 44
 - 5.2 Special application spaces 44
 - 5.2.1 Smart utility network (SUN) 44
 - 5.2.2 Rail communications and control (RCC) 44
 - 5.2.3 Television white space (TVWS) 45
 - 5.2.4 Radio frequency identification (RFID) 45
 - 5.2.5 Low-energy, critical infrastructure monitoring (LECIM) 45
 - 5.2.6 Medical body area network (MBAN) services 45
 - 5.3 Components of the IEEE 802.15.4 WPAN 45
 - 5.4 Multi-PHY management (MPM) of the SUN WPAN 45
 - 5.5 Network topologies 46
 - 5.5.1 Star network formation 46
 - 5.5.2 Peer-to-peer network formation 47
 - 5.6 Architecture 48
 - 5.6.1 PHY 49
 - 5.6.2 MAC sublayer 49
 - 5.7 Functional overview 50
 - 5.7.1 Superframe structure 50
 - 5.7.1.1 Beacon superframe 50
 - 5.7.1.2 DSME multi-superframe structure 51
 - 5.7.1.3 Slotframes 51
 - 5.7.1.4 TMCTP superframe 51
 - 5.7.2 Data transfer model 52
 - 5.7.2.1 Types of data transfer models 52
 - 5.7.2.2 Data transfer to a coordinator 52
 - 5.7.2.3 Data transfer from a coordinator 52
 - 5.7.2.4 Peer-to-peer data transfers 53
 - 5.7.3 Frame structure 53
 - 5.7.4 Access methods 53

5.7.4.1	Frame acknowledgment	53
5.7.4.2	Frak	54
5.7.4.3	Data verification	54
5.7.5	Power consumption considerations	54
5.7.5.1	Low-energy mechanisms	54
5.7.6	Security	55
5.8	Concept of primitives.....	56
5.9	Deprecation of features	56
6.	MAC functional description	57
6.1	Device types and conventions.....	57
6.2	Channel access.....	57
6.2.1	Superframe structure.....	57
6.2.1.1	Contention access period (CAP).....	59
6.2.1.2	Contention-free period (CFP).....	59
6.2.1.3	BOP.....	59
6.2.2	Incoming and outgoing superframe timing.....	59
6.2.3	Enhanced Beacon frame timing for MPM procedure	60
6.2.4	IFS.....	61
6.2.5	Random access methods	61
6.2.5.1	CSMA-CA algorithm.....	61
6.2.5.2	TSCH CCA algorithm	64
6.2.5.3	TSCH CSMA-CA retransmission algorithm	64
6.2.5.4	CSMA-CA with PCA	66
6.2.5.5	LECIM ALOHA PCA	69
6.2.6	TSCH slotframe structure	69
6.2.6.1	General.....	69
6.2.6.2	Absolute slot number (ASN)	70
6.2.6.3	Links	70
6.2.6.4	Multiple slotframes	70
6.2.7	LE functional description.....	71
6.2.7.1	LE contention access period (LE CAP).....	71
6.2.7.2	LE superframe structure.....	71
6.2.7.3	LE-incoming and outgoing superframe timing.....	71
6.2.7.4	LE scan	71
6.2.8	Superframe use for TMCTP operation	72
6.2.9	Rail communications and control network (RCCN) superframe structure.....	72
6.2.10	Channel hopping.....	73
6.3	Starting and maintaining PANs	75
6.3.1	Scanning through channels	75
6.3.1.1	ED channel scan.....	75
6.3.1.2	Active and passive channel scan.....	75
6.3.1.3	Orphan channel scan.....	78
6.3.1.4	RIT passive channel scan.....	80
6.3.2	PAN ID conflict resolution	81
6.3.2.1	Detection.....	81
6.3.2.2	Resolution	82
6.3.3	Starting and realigning a PAN.....	82
6.3.3.1	Starting a PAN	82
6.3.3.2	Realigning a PAN	82
6.3.3.3	Realignment in a PAN	84
6.3.3.4	Updating superframe configuration and channel PIB attributes.....	84
6.3.4	Beacon generation.....	84

6.3.5	Device discovery.....	86
6.3.6	TSCH PAN formation.....	86
6.4	Association and disassociation.....	87
6.4.1	Association.....	87
6.4.2	Disassociation.....	90
6.4.3	Fast association.....	92
6.5	Synchronization.....	93
6.5.1	General.....	93
6.5.2	Synchronization with beacons.....	93
6.5.3	Synchronization without beacons.....	95
6.5.4	Synchronization in TSCH PAN.....	95
6.5.4.1	Timeslot communication.....	96
6.5.4.2	Node synchronization.....	97
6.5.5	Orphaned device realignment.....	98
6.6	Transaction handling.....	98
6.7	Transmission, reception, and acknowledgment.....	99
6.7.1	Transmission.....	99
6.7.2	Reception and rejection.....	101
6.7.3	Extracting pending data from a coordinator.....	102
6.7.4	Use of acknowledgments and retransmissions.....	104
6.7.4.1	No acknowledgment.....	104
6.7.4.2	Acknowledgment.....	105
6.7.4.3	Retransmissions.....	106
6.7.5	Transmission timing restrictions.....	106
6.7.6	Guard time.....	107
6.7.7	Promiscuous mode.....	109
6.7.8	Transmission scenarios.....	109
6.7.9	Device announcement.....	110
6.8	GTS allocation and management.....	111
6.8.1	GTS general requirements.....	111
6.8.2	CAP maintenance.....	112
6.8.3	GTS allocation.....	112
6.8.4	GTS usage.....	113
6.8.5	GTS deallocation.....	114
6.8.6	GTS reallocation.....	115
6.8.7	GTS expiration.....	117
6.9	Ranging.....	117
6.9.1	Ranging requirements.....	117
6.9.2	Set-up activities before a ranging exchange.....	117
6.9.3	Finish-up activities after a ranging exchange.....	117
6.9.4	Managing DPS.....	118
6.9.5	The ranging exchange.....	119
6.10	PHY parameter change notification procedure.....	120
6.10.1	Signaling using Beacon frames.....	120
6.10.2	Signaling using multipurpose frames.....	120
6.11	Deterministic and synchronous multi-channel extension (DSME).....	121
6.11.1	DSME command requirements.....	121
6.11.2	DSME multi-superframe structure.....	121
6.11.3	Channel diversity.....	123
6.11.3.1	Channel adaptation.....	123
6.11.3.2	Channel hopping.....	124
6.11.4	CAP reduction.....	126
6.11.5	DSME GTS allocation and management.....	126
6.11.5.1	DSME GTS allocation.....	127

6.11.5.2	DSME GTS deallocation	130
6.11.5.3	DSME GTS expiration.....	131
6.11.5.4	DSME GTS retrieve.....	131
6.11.5.5	DSME GTS change	132
6.11.6	Beacon scheduling	132
6.11.7	Time synchronization	133
6.11.8	Deferred beacon.....	134
6.11.9	Passive channel scan.....	134
6.12	LE transmission, reception and acknowledgment	134
6.12.1	LE transmission, reception, and acknowledgment with positive handshakes	134
6.12.2	Coordinated sampled listening (CSL).....	135
6.12.2.1	CSL idle listening	136
6.12.2.2	CSL transmission.....	136
6.12.2.3	Unicast transmission	137
6.12.2.4	Broadcast transmission	137
6.12.2.5	CSL reception	138
6.12.2.6	CSL over multiple channels.....	138
6.12.2.7	Turning off CSL mode to reduce latency	138
6.12.3	RIT	138
6.12.3.1	General.....	138
6.12.3.2	Periodic RIT data request transmission and reception.....	139
6.12.3.3	RIT transmission.....	141
6.12.4	Implicit RIT (I-RIT).....	143
6.13	Starting and maintaining TMCTPs	143
6.14	MPM procedure for inter-PHY coexistence	146
6.15	TVWS access procedures	149
6.16	Channel timing management (CTM).....	149
7.	MAC frame formats.....	151
7.1	Device extended address.....	151
7.2	General MAC frame format.....	151
7.2.1	Frame Control field.....	151
7.2.1.1	Frame Type field.....	152
7.2.1.2	Security Enabled field.....	152
7.2.1.3	Frame Pending field.....	152
7.2.1.4	AR field.....	153
7.2.1.5	PAN ID Compression field.....	153
7.2.1.6	Sequence Number Suppression	154
7.2.1.7	IE Present field.....	154
7.2.1.8	Destination Addressing Mode field	154
7.2.1.9	Frame Version field	154
7.2.1.10	Source Addressing Mode field	155
7.2.2	Sequence Number field.....	155
7.2.3	Destination PAN ID field	155
7.2.4	Destination Address field.....	155
7.2.5	Source PAN ID field.....	156
7.2.6	Source Address field.....	156
7.2.7	Auxiliary Security Header field	156
7.2.8	IE field	156
7.2.9	Frame Payload field	156
7.2.10	FCS field.....	156
7.3	Format of individual frame types.....	158
7.3.1	Beacon frame format	158

7.3.1.1	Beacon frame MHR field.....	159
7.3.1.2	IEs field.....	160
7.3.1.3	Superframe Specification field	160
7.3.1.4	GTS Info field.....	161
7.3.1.5	Pending Address field.....	162
7.3.1.6	Beacon Payload field	162
7.3.2	Data frame format.....	163
7.3.2.1	Data frame MHR field	163
7.3.2.2	Data Payload field.....	163
7.3.3	Ack frame format.....	163
7.3.4	MAC command frame format.....	165
7.3.4.1	MHR field	165
7.3.4.2	Command ID field	165
7.3.4.3	Payload field	165
7.3.5	Multipurpose frame format.....	165
7.3.5.1	Frame Type field.....	166
7.3.5.2	Long Frame Control field	166
7.3.5.3	Destination Addressing Mode field	166
7.3.5.4	Source Addressing Mode field	166
7.3.5.5	PAN ID Present field	166
7.3.5.6	Security Enabled field.....	167
7.3.5.7	Sequence Number Suppression field	167
7.3.5.8	Frame Pending field.....	167
7.3.5.9	Frame Version field	167
7.3.5.10	Ack Request field.....	167
7.3.5.11	IEs Present field.....	167
7.3.5.12	Sequence Number field.....	167
7.3.5.13	Destination PAN ID field	167
7.3.5.14	Destination Address field.....	167
7.3.5.15	Source Address field.....	167
7.3.5.16	Auxiliary Security Header field.....	167
7.3.5.17	IEs field.....	168
7.3.5.18	Payload field	168
7.3.6	Extended frame format	168
7.4	IEs	168
7.4.1	IE list termination	168
7.4.2	Header IEs.....	169
7.4.2.1	Header IE format	169
7.4.2.2	Vendor Specific Header IE.....	171
7.4.2.3	CSL IE	171
7.4.2.4	RIT IE	171
7.4.2.5	DSME PAN descriptor IE.....	172
7.4.2.6	Rendezvous Time IE.....	174
7.4.2.7	Time Correction IE.....	174
7.4.2.8	Extended DSME PAN descriptor IE	175
7.4.2.9	Fragment Sequence Context Description (FSCD) IE	176
7.4.2.10	Simplified Superframe Specification IE	177
7.4.2.11	Simplified GTS Specification IE	178
7.4.2.12	LECM Capabilities IE	178
7.4.2.13	RCC Capabilities IE.....	180
7.4.2.14	RCCN Descriptor IE.....	182
7.4.2.15	Global Time IE	183
7.4.2.16	DA IE.....	183
7.4.2.17	Header Termination 1 IE	184

7.4.2.18	Header Termination 2 IE	184
7.4.3	Payload IEs	184
7.4.3.1	Encapsulated Service Data Unit (ESDU) IE.....	184
7.4.3.2	MLME IE.....	185
7.4.3.3	Payload Termination IE	185
7.4.4	Nested IE.....	185
7.4.4.1	Format of Nested IE.....	185
7.4.4.2	TSCH Synchronization IE	188
7.4.4.3	TSCH Slotframe and Link IE	188
7.4.4.4	TSCH Timeslot IE	190
7.4.4.5	Hopping timing IE	191
7.4.4.6	Enhanced Beacon Filter IE	191
7.4.4.7	MAC Metrics IE	192
7.4.4.8	All MAC Metrics IE	192
7.4.4.9	Coexistence Specification IE.....	193
7.4.4.10	SUN Device Capabilities IE	193
7.4.4.11	SUN FSK Generic PHY IE.....	199
7.4.4.12	Mode Switch Parameter IE	200
7.4.4.13	PHY Parameter Change IE	200
7.4.4.14	O-QPSK PHY Mode IE.....	201
7.4.4.15	PCA Allocation IE.....	201
7.4.4.16	LECIM DSSS Operating Mode IE	202
7.4.4.17	LECIM FSK Operating Mode IE.....	204
7.4.4.18	TVWS PHY Operating Mode Description IE	205
7.4.4.19	TVWS Device Capabilities IE.....	208
7.4.4.20	TVWS Device Category IE	213
7.4.4.21	TVWS Device Identification IE	213
7.4.4.22	TVWS Device Location IE.....	214
7.4.4.23	TVWS Channel Information Query IE	215
7.4.4.24	TVWS Channel Information Source IE.....	217
7.4.4.25	CTM IE.....	218
7.4.4.26	Timestamp IE.....	219
7.4.4.27	Timestamp Difference IE.....	219
7.4.4.28	TMCTP Specification IE	219
7.4.4.29	RCC PHY Operating Mode IE	220
7.4.4.30	Vendor Specific Nested IE	221
7.4.4.31	Channel hopping IE	221
7.5	MAC commands.....	222
7.5.1	Command ID field	222
7.5.2	Association Request command.....	223
7.5.3	Association Response command	224
7.5.4	Disassociation Notification command	225
7.5.5	Data Request command	226
7.5.6	PAN ID Conflict Notification command.....	227
7.5.7	Orphan Notification command	227
7.5.8	Beacon Request command.....	228
7.5.9	Enhanced Beacon Request command.....	228
7.5.10	Coordinator realignment command	228
7.5.11	GTS request command.....	230
7.5.12	DSME Association Request command.....	230
7.5.13	DSME Association Response command	232
7.5.14	DSME GTS Request command	233
7.5.15	DSME GTS Response command.....	235
7.5.16	DSME GTS Notify command.....	237

7.5.17	DSME Information Request command.....	238
7.5.18	DSME Information Response command.....	238
7.5.19	DSME Beacon Allocation Notification command.....	239
7.5.20	DSME Beacon Collision Notification command.....	240
7.5.21	DSME Link Report command.....	240
7.5.22	RIT Data Request command.....	241
7.5.23	DBS Request command.....	242
7.5.24	DBS Response command.....	243
7.5.25	RIT Data Response command.....	244
7.5.26	Vendor Specific command.....	244
8.	MAC services.....	245
8.1	Overview.....	245
8.2	MAC management service.....	245
8.2.1	Primitives supported by the MLME-SAP interface.....	245
8.2.2	Common requirements for MLME primitives.....	247
8.2.3	Association primitives.....	248
8.2.3.1	MLME-ASSOCIATE.request.....	248
8.2.3.2	MLME-ASSOCIATE.indication.....	249
8.2.3.3	MLME-ASSOCIATE.response.....	251
8.2.3.4	MLME-ASSOCIATE.confirm.....	252
8.2.4	Disassociation primitives.....	254
8.2.4.1	MLME-DISASSOCIATE.request.....	254
8.2.4.2	MLME-DISASSOCIATE.indication.....	256
8.2.4.3	MLME-DISASSOCIATE.confirm.....	256
8.2.5	Communications notification primitives.....	257
8.2.5.1	MLME-BEACON-NOTIFY.indication.....	257
8.2.5.2	MLME-COMM-STATUS.indication.....	260
8.2.5.3	MLME-IE-NOTIFY.indication.....	262
8.2.6	Primitives for reading and writing PIB attributes.....	264
8.2.6.1	MLME-GET.request.....	264
8.2.6.2	MLME-GET.confirm.....	264
8.2.6.3	MLME-SET.request.....	265
8.2.6.4	MLME-SET.confirm.....	265
8.2.7	GTS management primitives.....	266
8.2.7.1	MLME-GTS.request.....	266
8.2.7.2	MLME-GTS.confirm.....	267
8.2.7.3	MLME-GTS.indication.....	268
8.2.8	Primitives for orphan notification.....	269
8.2.8.1	MLME-ORPHAN.indication.....	269
8.2.8.2	MLME-ORPHAN.response.....	270
8.2.9	Primitives for resetting the MAC sublayer.....	271
8.2.9.1	MLME-RESET.request.....	271
8.2.9.2	MLME-RESET.confirm.....	271
8.2.10	Primitives for specifying the receiver enable time.....	272
8.2.10.1	MLME-RX-ENABLE.request.....	272
8.2.10.2	MLME-RX-ENABLE.confirm.....	273
8.2.11	Primitives for channel scanning.....	274
8.2.11.1	MLME-SCAN.request.....	274
8.2.11.2	MLME-SCAN.confirm.....	277
8.2.12	Primitives for updating the superframe configuration.....	279
8.2.12.1	MLME-START.request.....	279
8.2.12.2	MLME-START.confirm.....	282

8.2.13	Primitives for synchronizing with a coordinator	283
8.2.13.1	MLME-SYNC.request	283
8.2.13.2	MLME-SYNC-LOSS.indication	284
8.2.14	Primitives for requesting data from a coordinator	286
8.2.14.1	MLME-POLL.request	286
8.2.14.2	MLME-POLL.confirm	287
8.2.15	Primitives for specifying dynamic preamble	287
8.2.15.1	MLME-DPS.request	288
8.2.15.2	MLME-DPS.confirm	288
8.2.15.3	MLME-DPS.indication	289
8.2.16	Primitives for channel sounding	289
8.2.16.1	MLME-SOUNDING.request	289
8.2.16.2	MLME-SOUNDING.confirm	289
8.2.17	Primitives for ranging calibration	290
8.2.17.1	MLME-CALIBRATE.request	291
8.2.17.2	MLME-CALIBRATE.confirm	291
8.2.18	Primitives for Beacon Generation	292
8.2.18.1	MLME-BEACON.request	292
8.2.18.2	MLME-BEACON.confirm	294
8.2.18.3	MLME-BEACON-REQUEST.indication	295
8.2.19	Primitives for TSCH	296
8.2.19.1	MLME-SET-SLOTFRAME.request	296
8.2.19.2	MLME-SET-SLOTFRAME.confirm	297
8.2.19.3	MLME-SET-LINK.request	297
8.2.19.4	MLME-SET-LINK.confirm	299
8.2.19.5	MLME-TSCH-MODE.request	300
8.2.19.6	MLME-TSCH-MODE.confirm	301
8.2.19.7	MLME-KEEP-ALIVE.request	301
8.2.19.8	MLME-KEEP-ALIVE.confirm	302
8.2.20	Primitives for DSME GTS management	302
8.2.20.1	MLME-DSME-GTS.request	302
8.2.20.2	MLME-DSME-GTS.indication	305
8.2.20.3	MLME-DSME-GTS.response	306
8.2.20.4	MLME-DSME-GTS.confirm	308
8.2.21	Primitives for reporting the link status	309
8.2.21.1	MLME-DSME-LINK-REPORT.request	309
8.2.21.2	MLME-DSME-LINK-REPORT.indication	310
8.2.21.3	MLME-DSME-LINK-REPORT.confirm	311
8.2.22	Operating parameter change primitives	311
8.2.22.1	MLME-PHY-OP-SWITCH.request	311
8.2.22.2	MLME-PHY-OP-SWITCH.indication	313
8.2.22.3	MLME-PHY-OP-SWITCH.confirm	315
8.2.23	TMCTP DBS allocation primitives	316
8.2.23.1	MLME-DBS.request	316
8.2.23.2	MLME-DBS.indication	317
8.2.23.3	MLME-DBS.response	318
8.2.23.4	MLME-DBS.confirm	319
8.2.24	Primitives for device announcement	320
8.2.24.1	MLME-DA.request primitive	320
8.2.24.2	MLME-DA.indication primitive	321
8.2.24.3	MLME-DA.confirm primitive	321
8.2.25	RIT data commands	322
8.2.25.1	MLME-RIT-REQ.indication	322
8.2.25.2	MLME-RIT-RES.request	324

	8.2.25.3	MLME-RIT-RES.indication	325
	8.2.25.4	MLME-RIT-RES.confirm	327
8.3		MAC data service	328
	8.3.1	MCPS-DATA.request	328
	8.3.2	MCPS-DATA.confirm	332
	8.3.3	MCPS-DATA.indication	335
	8.3.4	MCPS-PURGE.request	338
	8.3.5	MCPS-PURGE.confirm	338
8.4		MAC constants and PIB attributes	339
	8.4.1	MAC constants	339
	8.4.2	MAC PIB attributes	340
	8.4.2.1	General MAC PIB attributes for functional organization	345
	8.4.2.2	TSCH-specific MAC PIB attributes	348
	8.4.2.2.1	TSCH MAC PIB attributes for macSlotframeTable	348
	8.4.2.2.2	TSCH MAC PIB attributes for macLinkTable	349
	8.4.2.2.3	TSCH MAC PIB attributes for macTimeslotTemplate	350
	8.4.2.3	MAC PIB attributes for hopping sequence	351
	8.4.2.4	DSME specific MAC PIB attributes	352
	8.4.2.5	LE specific MAC PIB attributes	355
	8.4.2.6	MAC performance metrics specific MAC PIB attributes	357
	8.4.2.7	Enhanced Beacon Request command specific MAC PIB attributes	358
	8.4.2.8	Enhanced Beacon frame specific MAC PIB attributes	359
9.		Security	360
	9.1	Overview	360
	9.2	Functional description	360
	9.2.1	Outgoing frame security procedure	360
	9.2.2	KeyDescriptor lookup procedure	362
	9.2.3	Incoming frame security procedure, Security Enabled field is set to one	362
	9.2.4	Incoming frame security procedure, Security Enabled field is set to zero	364
	9.2.5	DeviceDescriptor lookup procedure	365
	9.2.6	SecurityLevelDescriptor lookup procedure	366
	9.2.7	Incoming IE security level checking procedure	366
	9.2.8	Incoming IE key usage policy checking procedure	367
	9.2.9	Incoming security level checking procedure	367
	9.2.10	Incoming key usage policy checking procedure	367
	9.3	Security operations	368
	9.3.1	Integer and octet representation	368
	9.3.2	CCM* nonce	368
	9.3.2.1	CCM* nonce for non-TSCH mode	368
	9.3.2.2	CCM* nonce for TSCH mode	368
	9.3.2.3	CCM* nonce for Fragment frames	369
	9.3.3	CCM* prerequisites	369
	9.3.4	CCM* transformation data representation	370
	9.3.4.1	Key and nonce data inputs	370
	9.3.4.2	a data and m data	370
	9.3.4.3	c data output	370
	9.3.5	CCM* inverse transformation data representation	371
	9.3.5.1	Key and nonce data inputs	371
	9.3.5.2	c data and a data	371
	9.3.5.3	m data output	372
	9.4	Auxiliary security header	372
	9.4.1	Security Control field	372

9.4.1.1	Security Level field.....	372
9.4.1.2	Key Identifier Mode field	373
9.4.1.3	Frame Counter Suppression field	374
9.4.1.4	ASN in Nonce.....	374
9.4.2	Frame Counter field.....	374
9.4.3	Key Identifier field.....	375
9.4.3.1	Key Source field	375
9.4.3.2	Key Index field	375
9.5	Security-related MAC PIB attributes.....	375
10.	General PHY requirements.....	381
10.1	General requirements and definitions.....	381
10.1.1	Operating frequency range.....	382
10.1.2	Channel assignments.....	387
10.1.2.1	Channel numbering for 780 MHz band	387
10.1.2.2	Channel numbering for 868 MHz, 915 MHz, and 2450 MHz bands	387
10.1.2.3	Channel numbering for CSS PHY	388
10.1.2.4	Channel numbering for HRP UWB PHY	388
10.1.2.5	Channel numbering for MSK PHY 433 MHz band	389
10.1.2.6	Channel numbering for MSK PHY 2450 MHz band	390
10.1.2.7	Channel numbering for LRP UWB PHY	392
10.1.2.8	Channel numbering for SUN and TVWS PHYs	392
10.1.2.9	Channel numbering for 2380 MHz band.....	395
10.1.2.10	Channel numbering for LECIM PHYs	395
10.1.2.10.1	Channel numbering for LECIM DSSS PHY	396
10.1.2.10.2	Channel numbering for LECIM FSK PHY	396
10.1.2.11	Channel numbering for RCC PHYs.....	397
10.1.3	Minimum LIFS and SIFS periods.....	398
10.1.4	RF power measurement	399
10.1.5	Transmit power	399
10.1.6	Out-of-band spurious emission.....	399
10.1.7	Receiver sensitivity definitions.....	399
10.1.8	Common signaling mode (CSM) for SUN PHY	400
10.2	General radio specifications.....	400
10.2.1	TX-to-RX turnaround time	400
10.2.2	RX-to-TX turnaround time	400
10.2.3	Error-vector magnitude (EVM) definition.....	400
10.2.4	Receiver maximum input level of desired signal.....	401
10.2.5	Receiver ED.....	401
10.2.6	Link quality indicator (LQI).....	402
10.2.7	Clear channel assessment (CCA).....	402
11.	PHY services	404
11.1	Overview.....	404
11.2	PHY constants.....	404
11.3	PHY PIB attributes	404
12.	O-QPSK PHY	411
12.1	PPDU format.....	411
12.1.1	SHR field format.....	411
12.1.1.1	Preamble field	411

12.1.1.2	SFD field.....	411
12.1.2	PHR field format.....	411
12.1.2.1	Frame Length field.....	411
12.1.2.2	PHY Payload field.....	411
12.2	Modulation and spreading.....	412
12.2.1	Data rate.....	412
12.2.2	Reference modulator diagram.....	412
12.2.3	Bit-to-symbol mapping.....	412
12.2.4	Symbol-to-chip mapping.....	412
12.2.5	O-QPSK modulation.....	414
12.2.6	Pulse shape.....	414
12.2.7	Chip transmission order.....	415
12.3	O-QPSK PHY RF requirements.....	415
12.3.1	Operating frequency range.....	415
12.3.2	Transmit power spectral density (PSD) mask.....	416
12.3.3	Symbol rate.....	416
12.3.4	Receiver sensitivity.....	416
12.3.5	Receiver interference rejection.....	416
12.3.6	TX-to-RX turnaround time.....	417
12.3.7	RX-to-TX turnaround time.....	417
12.3.8	EVM.....	417
12.3.9	Transmit center frequency tolerance.....	417
12.3.10	Transmit power.....	417
12.3.11	Receiver maximum input level of desired signal.....	417
12.3.12	Receiver ED.....	417
12.3.13	LQI.....	417
13.	Binary phase-shift keying (BPSK) PHY.....	418
13.1	PPDU format.....	418
13.2	Modulation and spreading.....	418
13.2.1	BPSK PHY data rates.....	418
13.2.2	Reference modulator.....	418
13.2.3	Differential encoding.....	418
13.2.4	Bit-to-chip mapping.....	419
13.2.5	BPSK modulation.....	419
13.2.5.1	Pulse shape.....	419
13.2.5.2	Chip transmission order.....	419
13.3	BPSK PHY RF requirements.....	419
13.3.1	Operating frequency range.....	419
13.3.2	915 MHz band transmit PSD mask.....	419
13.3.3	Symbol rate.....	420
13.3.4	Receiver sensitivity.....	420
13.3.5	Receiver interference rejection.....	420
13.3.6	TX-to-RX turnaround time.....	420
13.3.7	RX-to-TX turnaround time.....	420
13.3.8	EVM.....	421
13.3.9	Transmit center frequency tolerance.....	421
13.3.10	Transmit power.....	421
13.3.11	Receiver maximum input level of desired signal.....	421
13.3.12	Receiver ED.....	421
13.3.13	LQI.....	421
14.	Amplitude shift keying (ASK) PHY.....	422

14.1	Status of ASK PHY	422
14.2	PPDU format.....	422
14.2.1	Preamble field for ASK PHY	422
14.2.2	SFD for ASK PHY	422
14.3	Modulation and spreading	422
14.3.1	ASK PHY data rates	422
14.3.2	Reference modulator.....	423
14.3.3	Bit-to-symbol mapping.....	423
14.3.4	Symbol-to-chip mapping	423
14.3.5	ASK modulation	424
14.3.6	Pulse shape.....	426
14.3.7	Chip transmission order.....	426
14.4	ASK PHY RF requirements.....	426
14.4.1	Operating frequency range.....	426
14.4.2	915 MHz band transmit PSD mask.....	426
14.4.3	Symbol rate	426
14.4.4	Receiver sensitivity.....	427
14.4.5	Receiver interference rejection	427
14.4.6	TX-to-RX turnaround time	427
14.4.7	RX-to-TX turnaround time	427
14.4.8	EVM.....	427
14.4.9	Transmit center frequency tolerance.....	427
14.4.10	Transmit power	427
14.4.11	Receiver maximum input level of desired signal.....	428
14.4.12	Receiver ED.....	428
14.4.13	LQI.....	428
14.4.14	Example of PSSS encoding	428
15.	Chirp spread spectrum (CSS) PHY	430
15.1	CSS PPDU format	430
15.1.1	Preamble field.....	430
15.1.2	SFD field.....	430
15.1.3	PHR field	431
15.1.4	PHY Payload field	431
15.2	Modulation and spreading	431
15.2.1	Data rates	431
15.2.2	Reference modulator.....	431
15.2.3	De-multiplexer (DEMUX).....	431
15.2.4	Serial-to-parallel mapping	431
15.2.5	Data-symbol-to-bi-orthogonal-codeword mapping	432
15.2.6	Parallel-to-serial converter and QPSK symbol mapping.....	436
15.2.7	DQPSK coding	436
15.2.8	DQPSK-to-DQCSK modulation.....	437
15.2.9	CSK generator.....	437
15.2.10	Bit interleaver	437
15.3	Waveform and subchirp sequences.....	438
15.3.1	Graphical presentation of chirp symbols (subchirp sequences).....	438
15.3.2	Active usage of time gaps.....	438
15.3.3	Mathematical representation of the continuous time CSS base-band signal	439
15.3.4	Raised cosine window for chirp pulse shaping.....	441
15.3.5	Subchirp transmission order	441
15.3.6	Example of CSK signal generation.....	442
15.4	CSS RF requirements.....	443

15.4.1	Transmit power spectral density (PSD) mask and signal tolerance.....	443
15.4.2	Symbol rate.....	444
15.4.3	Receiver sensitivity.....	444
15.4.4	Receiver interference rejection.....	444
15.4.5	TX-to-RX turnaround time.....	444
15.4.6	RX-to-TX turnaround time.....	444
15.4.7	Transmit center frequency tolerance.....	444
15.4.8	Transmit power.....	445
15.4.9	Receiver maximum input level of desired signal.....	445
15.4.10	Receiver ED.....	445
15.4.11	LQI.....	445
16.	HRP UWB PHY.....	446
16.1	General.....	446
16.2	HRP UWB PPDU format.....	446
16.2.1	PPDU encoding process.....	447
16.2.2	Symbol structure.....	449
16.2.3	PSDU timing parameters.....	450
16.2.4	Preamble timing parameters.....	452
16.2.5	SHR field.....	454
16.2.5.1	SYNC field.....	454
16.2.5.2	SFD field.....	457
16.2.6	PHR field.....	457
16.2.7	PHY Payload field.....	458
16.3	Modulation.....	459
16.3.1	Modulation mathematical framework.....	459
16.3.2	Spreading.....	459
16.3.3	FEC.....	461
16.3.3.1	Reed-Solomon encoding.....	461
16.3.3.2	Systematic convolutional encoding.....	462
16.4	RF requirements.....	463
16.4.1	Operating frequency bands.....	463
16.4.2	Channel assignments.....	464
16.4.3	Regulatory compliance.....	464
16.4.4	Operating temperature range.....	464
16.4.5	Baseband impulse response.....	464
16.4.6	Transmit PSD mask.....	466
16.4.7	Chip rate clock and chip carrier alignment.....	467
16.4.8	TX-to-RX turnaround time.....	467
16.4.9	RX-to-TX turnaround time.....	467
16.4.10	Transmit center frequency tolerance.....	467
16.4.11	Receiver maximum input level of desired signal.....	467
16.4.12	Receiver ED.....	467
16.4.13	LQI.....	467
16.4.14	CCA.....	467
16.5	HRP UWB PHY optional pulse shapes.....	467
16.5.1	HRP UWB PHY optional chirp on UWB (CoU) pulses.....	468
16.5.2	HRP UWB PHY optional continuous spectrum (CS) pulses.....	469
16.5.3	HRP UWB PHY linear combination of pulses (LCP).....	470
16.6	Extended preamble for optional CCA mode 6.....	471
16.7	Ranging.....	472
16.7.1	Ranging counter.....	472
16.7.2	Crystal characterization.....	472

16.7.2.1	Ranging tracking offset.....	472
16.7.2.2	Ranging tracking interval.....	472
16.7.3	Ranging FoM.....	473
17.	GFSK PHY.....	475
17.1	PPDU formats.....	475
17.2	Modulation.....	475
17.2.1	GFSK PHY data rates.....	475
17.2.2	Reference modulator diagram.....	475
17.2.3	Data whitening.....	475
17.2.4	GFSK modulation.....	476
17.3	GFSK PHY RF requirements.....	476
17.3.1	Operating frequency range.....	476
17.3.2	Transmit PSD mask.....	476
17.3.3	Symbol rate.....	477
17.3.4	Receiver sensitivity.....	477
17.3.5	Receiver interference rejection.....	477
17.3.6	TX-to-RX turnaround time.....	477
17.3.7	RX-to-TX turnaround time.....	477
17.3.8	Transmit center frequency tolerance.....	477
17.3.9	Transmit power.....	477
17.3.10	Receiver maximum input level of desired signal.....	477
17.3.11	Receiver ED.....	478
17.3.12	LQI.....	478
18.	MSK PHY.....	479
18.1	PPDU formats.....	479
18.2	Data rate.....	479
18.3	SFD for the MSK PHY.....	479
18.4	MSK modulation.....	480
18.4.1	Reference modulator diagram.....	480
18.4.2	Data whitening.....	480
18.4.3	Bit-to-symbol mapping.....	480
18.4.4	Signal modulation.....	480
18.5	MSK PHY requirements.....	481
18.5.1	Operating frequency range.....	481
18.5.2	Transmit PSD mask.....	481
18.5.3	Symbol rate.....	481
18.5.4	Transmit center frequency tolerance.....	482
18.5.5	Transmit power.....	482
18.5.6	Receiver maximum input level of desired signal.....	482
18.5.7	Modulation frequency deviation tolerance.....	482
18.5.8	Zero crossing tolerance.....	482
19.	LRP UWB PHY specification.....	483
19.1	Overview.....	483
19.2	LRP UWB PHY symbol structure.....	483
19.2.1	Base mode LRP UWB PHY symbol structure.....	483
19.2.1.1	Base mode LRP UWB PHY PSDU synchronization signal.....	484
19.2.2	Extended mode LRP UWB PHY symbol structure.....	484
19.2.2.1	Extended mode LRP UWB PHY PSDU synchronization signal.....	485

19.2.3	Long-range mode LRP UWB PHY symbol structure	486
19.2.3.1	Long-range mode LRP UWB PHY PSDU synchronization signal	486
19.3	LRP UWB SHR	487
19.3.1	LRP UWB SHR preamble	487
19.3.1.1	LRP UWB base mode SHR preamble	487
19.3.1.2	RP UWB extended mode SHR preamble	487
19.3.1.3	LRP UWB long-range mode SHR preamble	487
19.3.2	LRP UWB SHR SFD	487
19.4	LRP UWB PHR	487
19.4.1	Encoding Type field	488
19.4.2	Header Extension field	488
19.4.3	SECDED field	489
19.4.4	Frame Length field	489
19.4.5	LEIP Length field	489
19.4.6	LEIP Position field	489
19.5	LRP UWB PSDU	490
19.6	LRP UWB location enhancing information postamble	490
19.7	LRP UWB transmitter specification	490
19.7.1	Pulse shape	490
19.7.2	Pulse timing	491
19.7.3	Transmit PSD mask	491
19.8	LRP UWB receiver specification	492
20.	SUN FSK PHY	493
20.1	Introduction	493
20.2	PPDU format for SUN FSK	493
20.2.1	SHR field format	494
20.2.1.1	Preamble field	494
20.2.1.2	SFD	494
20.2.2	PHR field format	495
20.2.3	Mode Switch PHR	495
20.2.4	PHY Payload field	497
20.3	Modulation and coding for SUN FSK	497
20.3.1	Reference modulator	499
20.3.2	Bit-to-symbol mapping	500
20.3.3	Modulation quality	501
20.3.3.1	Frequency deviation tolerance	501
20.3.3.2	Zero crossing tolerance	502
20.3.4	FEC	502
20.3.5	Code-symbol interleaving	505
20.4	Data whitening for SUN FSK	506
20.5	Mode switch mechanism for SUN FSK	506
20.6	SUN FSK PHY RF requirements	509
20.6.1	Operating frequency range	509
20.6.2	Regulatory compliance	509
20.6.3	Radio frequency tolerance	509
20.6.4	Channel switch time	510
20.6.5	Transmitter symbol rate	510
20.6.6	Transmit spectral mask	510
20.6.7	Receiver sensitivity	510
20.6.8	Receiver interference rejection	511
20.6.9	TX-to-RX turnaround time	511
20.6.10	RX-to-TX turnaround time	511

20.6.11	Transmit power	511
20.6.12	Receiver maximum input level of desired signal.....	511
20.6.13	Receiver ED	511
20.6.14	LQI.....	511
21.	SUN OFDM PHY	512
21.1	Introduction.....	512
21.2	PPDU format for SUN OFDM	512
21.2.1	Short Training field (STF).....	512
21.2.1.1	Frequency domain STF.....	512
21.2.1.2	Time domain STF generation	515
21.2.1.3	Time domain STF repetition.....	515
21.2.1.4	STF normalization	516
21.2.2	Long Training field (LTF).....	516
21.2.2.1	Frequency domain LTF	516
21.2.2.2	Time domain LTF generation.....	519
21.2.2.3	LTF normalization	519
21.2.3	PHR.....	519
21.2.4	PSDU field.....	520
21.3	Data rates for SUN OFDM	520
21.4	Modulation and coding for SUN OFDM.....	521
21.4.1	Reference modulator diagram.....	521
21.4.2	Bit-to-symbol mapping	521
21.4.3	PIB attribute values for phySymbolsPerOctet	523
21.4.4	FEC	523
21.4.5	Interleaver	524
21.4.6	Frequency spreading.....	526
21.4.6.1	Frequency spreading by 2x	526
21.4.6.2	Frequency spreading by 4x	526
21.4.6.3	No spreading.....	527
21.4.7	Pilot tones/null tones.....	527
21.4.8	Cyclic prefix (CP).....	530
21.4.9	PPDU Tail field	530
21.4.10	Pad field	530
21.4.11	Scrambler and scrambler seeds.....	531
21.5	SUN OFDM PHY RF requirements	532
21.5.1	Operating frequency range.....	532
21.5.2	Transmit power spectral density (PSD) mask.....	532
21.5.3	Receiver sensitivity.....	532
21.5.4	Adjacent channel rejection.....	532
21.5.5	Alternate channel rejection	533
21.5.6	TX-to-RX turnaround time	533
21.5.7	RX-to-TX turnaround time	533
21.5.8	EVM definition.....	533
21.5.9	Transmit center frequency and symbol tolerance	535
21.5.10	Transmit power.....	535
21.5.11	Receiver maximum input level of desired signal.....	535
21.5.12	Receiver ED	535
21.5.13	LQI.....	535
22.	SUN O-QPSK PHY	536
22.1	Introduction.....	536

22.2	PPDU format for SUN O-QPSK	536
22.2.1	SHR field format	536
22.2.1.1	Preamble field format	536
22.2.1.2	SFD field format	537
22.2.2	PHR field format	537
22.2.3	PHY Payload field	538
22.3	Modulation and coding for SUN O-QPSK	538
22.3.1	Reference modulator	538
22.3.2	SHR coding and spreading	539
22.3.3	PHR coding and spreading	540
22.3.4	PSDU coding and spreading for DSSS	540
22.3.5	PSDU coding and spreading for MDSSS	542
22.3.6	FEC	543
22.3.7	Code-bit interleaving	545
22.3.8	Bit differential encoding (BDE)	546
22.3.9	DSSS bit-to-chip mapping	547
22.3.10	MDSSS bit-to-chip mapping	551
22.3.11	Chip whitening	555
22.3.12	Pilot insertion	556
22.3.13	Modulation parameters for O-QPSK	557
22.4	Support of legacy devices of the 780 MHz, 915 MHz, and 2450 MHz O-QPSK PHYs	558
22.5	SUN O-QPSK PHY RF requirements	558
22.5.1	Operating frequency range	558
22.5.2	Transmit power spectral density (PSD) mask	558
22.5.3	Receiver sensitivity	559
22.5.4	Adjacent channel rejection	559
22.5.5	TX-to-RX turnaround time	560
22.5.6	RX-to-TX turnaround time	560
22.5.7	EVM definition	560
22.5.8	Transmit center frequency and symbol tolerance	560
22.5.9	Transmit power	561
22.5.10	Receiver maximum input level of desired signal	561
22.5.11	Receiver ED	561
22.5.12	LQI	561
22.5.13	CCA	561
23.	LECIM DSSS PHYs	562
23.1	PPDU format for DSSS	562
23.2	Modulation and spreading	562
23.2.1	Data rate	562
23.2.2	Reference modulator diagram	563
23.2.3	Convolutional FEC encoding	563
23.2.4	Interleaver	564
23.2.4.1	256-bit fragment size	564
23.2.4.2	384-bit fragment size	564
23.2.4.3	512-bit fragment size	565
23.2.5	Differential encoding	565
23.2.6	Bit-to-symbol and symbol-to-chip encoding	566
23.2.6.1	Gold code generator	566
23.2.6.2	Orthogonal variable spreading factor (OVSF) code generator	567
23.2.7	BPSK/O-QPSK modulation	570
23.2.7.1	BPSK modulation	570
23.2.7.2	O-QPSK modulation	570

23.3	PSDU fragmentation	570
23.3.1	Configuration	571
23.3.2	Fragmentation	571
23.3.3	Fragment packet.....	572
23.3.4	Calculating FICS field using MIC	572
23.3.5	Fragment acknowledgment and retransmission.....	573
23.3.6	Frak	573
	23.3.6.1 Frak policy	573
	23.3.6.2 Frak format	574
23.3.7	Reassembly	575
23.4	DSSS PHY RF requirements	575
23.4.1	Radio frequency tolerance	575
23.4.2	Channel switch time.....	575
23.4.3	Transmit spectral mask	575
23.4.4	Receiver sensitivity	575
23.4.5	Receiver interference rejection	576
23.4.6	TX-to-RX turnaround time	577
23.4.7	RX-to-TX turnaround time	577
23.4.8	Transmit power	577
24.	LECIM FSK PHY specification	578
24.1	General.....	578
24.2	PPDU format for LECIM FSK PHY	578
24.2.1	SHR field format.....	578
	24.2.1.1 Preamble field format	578
	24.2.1.2 SFD field format	578
24.2.2	PHR field format.....	578
24.2.3	PHY Payload field	579
24.3	Modulation and coding for LECIM FSK PHY	579
24.3.1	Reference modulator.....	579
24.3.2	Bit-to-symbol mapping	580
24.3.3	Modulation quality.....	581
	24.3.3.1 Frequency deviation tolerance	581
	24.3.3.2 Zero crossing tolerance	581
24.3.4	FEC	581
24.3.5	Code-bit interleaving	582
24.3.6	Spreading	583
24.4	Data whitening for LECIM FSK PHY	584
24.5	LECIM FSK PHY RF requirements.....	585
24.5.1	Operating frequency range.....	585
24.5.2	Radio frequency tolerance	585
24.5.3	Channel switch time.....	585
24.5.4	Transmit spectral mask	585
24.5.5	Receiver sensitivity	585
24.5.6	TX-to-RX turnaround time	586
24.5.7	RX-to-TX turnaround time	586
24.5.8	Transmit power	586
25.	TVWS-FSK PHY	587
25.1	PPDU format for TVWS-FSK.....	587
25.1.1	SHR field format.....	587
	25.1.1.1 Preamble field format	587

25.1.1.2	SFD field format	587
25.1.2	PHR field format	587
25.1.3	PHY Payload field	588
25.2	Modulation and coding for TVWS-FSK	588
25.2.1	Reference modulator	589
25.2.2	FEC and interleaving	589
25.2.3	Data whitening	589
25.2.4	Spreading	589
25.2.5	Bit-to-symbol mapping	590
25.2.6	Modulation quality	590
25.2.7	Values for phySymbolsPerOctet	590
25.3	TVWS-FSK RF requirements	591
25.3.1	Operating frequency range	591
25.3.2	Clock frequency and timing accuracy	591
25.3.3	Channel switch time	591
25.3.4	Receiver sensitivity	591
25.3.5	TX-to-RX turnaround time	591
25.3.6	RX-to-TX turnaround time	591
25.3.7	Receiver maximum input level of desired signal	591
25.3.8	Receiver ED	591
25.3.9	LQI	591
26.	TVWS-OFDM PHY	592
26.1	General	592
26.2	PPDU format for TVWS-OFDM	592
26.2.1	STF	592
26.2.1.1	Frequency domain STF	592
26.2.1.2	Time domain STF generation	593
26.2.1.3	Time domain STF repetition	594
26.2.1.4	STF power boosting	594
26.2.2	LTF	594
26.2.2.1	Frequency domain LTF	594
26.2.2.2	Time domain LTF generation	595
26.2.3	PHR field format	596
26.2.4	PSDU field	596
26.3	System parameters for TVWS-OFDM	597
26.4	Modulation and coding for TVWS-OFDM	597
26.4.1	Reference modulator	597
26.4.2	Bit-to-symbol mapping	598
26.4.3	FEC	599
26.4.4	Interleaver	599
26.4.5	Pilot tones/null tones	601
26.4.6	CP	602
26.4.7	PPDU Tail field	602
26.4.8	Pad field	602
26.4.9	Scrambler and scrambler seeds	602
26.5	TVWS-OFDM RF requirements	603
26.5.1	Operating frequency range	603
26.5.2	Pulse shaping	603
26.5.3	Transmit power spectral density (PSD) mask	603
26.5.4	Receiver sensitivity	603
26.5.5	TX-to-RX turnaround time	603
26.5.6	RX-to-TX turnaround time	603

26.5.7	EVM definition	603
26.5.8	Transmit center frequency and symbol tolerance	605
27.	TVWS-NB-OFDM PHY	606
27.1	PPDU format for TVWS-NB-OFDM	606
27.1.1	Short Training field (STF)	606
27.1.1.1	Frequency domain STF	606
27.1.1.2	Time domain STF generation	609
27.1.1.3	Time domain STF repetition	609
27.1.1.4	STF normalization	610
27.1.2	Long training field (LTF)	610
27.1.2.1	Frequency domain LTF generation	610
27.1.2.2	Time domain LTF generation	613
27.1.2.3	Time domain LTF repetition	614
27.1.2.4	LTF normalization	614
27.1.3	PHR	615
27.1.4	PHY Payload field	615
27.2	System parameters for TVWS-NB-OFDM	615
27.3	Modulation and coding parameters for TVWS-NB-OFDM	616
27.3.1	Reference modulator	616
27.3.2	Scrambler and scrambler seed	617
27.3.3	Outer encoding	617
27.3.4	Inner encoding	618
27.3.5	Pad bit insertion	620
27.3.6	Spreader	620
27.3.7	Bit interleaving	621
27.3.8	Subcarrier mapping	621
27.3.9	Frequency interleaving	623
27.3.10	Pilot tones	624
27.3.11	Cyclic prefix	624
27.3.12	Pulse shaping	624
27.3.13	PIB attribute values for phySymbolsPerOctet	625
27.4	Channel aggregation for TVWS-NB-OFDM	625
27.5	TVWS-NB-OFDM RF requirements	625
27.5.1	Operating frequency range	625
27.5.2	Receiver sensitivity	625
27.5.3	TX-to-RX turnaround time	626
27.5.4	RX-to-TX turnaround time	626
27.5.5	EVM definition	626
27.5.6	Transmit center frequency and symbol tolerance	627
28.	RCC LMR PHY	628
28.1	RCC PHY overview	628
28.2	PPDU format	628
28.2.1	SHR	628
28.2.2	PHR	629
28.2.3	PHY payload	629
28.2.4	Tail bits	629
28.3	FEC	629
28.4	Interleaver	630
28.5	Data whitening	630
28.6	Modulation	631

28.6.1	GMSK.....	631
28.6.2	4-FSK.....	631
28.6.3	QPSK.....	632
28.6.4	p/4 DQPSK.....	633
28.6.5	DSSS DPSK.....	633
28.7	Reference modulator.....	635
28.8	LMR PHY RF requirements.....	635
28.8.1	Transmitter symbol rate tolerance.....	635
28.8.2	Channel switching time.....	635
28.8.3	Error vector magnitude.....	635
28.8.4	Receiver sensitivity.....	635
28.8.5	Receiver interference rejection.....	635
28.8.6	Receiver maximum input level of desired signal.....	636
28.8.7	TX-to-RX turnaround time.....	636
28.8.8	RX-to-TX turnaround time.....	636
28.8.9	Receiver ED.....	636
28.8.10	LQI.....	636
29.	RCC DSSS BPSK PHY.....	637
29.1	Overview.....	637
29.2	RCC DSSS BPSK PHY specification.....	637
Annex A	(informative) Bibliography.....	638
Annex B	(normative) CCM* mode of operation.....	640
Annex C	(informative) Test vectors for cryptographic building blocks.....	646
Annex D	(informative) Protocol implementation conformance statement (PICS) proforma.....	659
Annex E	(informative) MPSK PHY.....	678
Annex F	(normative) Time-slot relaying based link extension (TRLE).....	683