

ISO/IEC TR 23008-15:2018-08 (E)

Information technology - High efficiency coding and media delivery in heterogeneous environments - Part 15: Signalling, backward compatibility and display adaptation for HDR/WCG video

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	3
5	Conventions	4
5.1	General	4
5.2	Arithmetic operators	5
5.3	Bit-wise operators	5
5.4	Assignment operators	6
5.5	Relational, logical and other operators	6
5.6	Mathematical functions	6
5.7	Order of operations	7
6	Overview	8
7	HEVC signalling mechanisms applicable to HDR/WCG video	9
7.1	General	9
7.2	VUI syntax elements	9
7.3	SEI messages applicable for HDR/WCG video	10
7.3.1	General	10
7.3.2	Mastering display colour volume SEI message	10
7.3.3	Content light level information SEI message	11
7.3.4	Ambient viewing environment SEI message	11
7.3.5	Alternative transfer characteristics SEI message	11
7.3.6	Tone mapping information SEI message	11
7.3.7	Colour remapping information SEI message	12
7.4	Overview of PQ and HLG transfer functions	13
7.4.1	General	13
7.4.2	Reference PQ EOTF	14
7.4.3	Reference HLG OETF	15
7.5	ICTCP colour representation	16
7.5.1	General	16
7.5.2	Pre-encoding process	17
7.5.3	Encoding process	20
7.5.4	Decoding process	22
7.5.5	Post-decoding process	22
8	Bitstream SDR backward compatibility with single-layer coding	24
8.1	General	24
8.2	Approach 1: usage of HLG for "static" bitstream SDR backward compatibility	24
8.2.1	General	24

8.2.2	HLG pre-encoding conversion process	25
8.2.3	Encoding process	27
8.2.4	Decoding process	29
8.2.5	HLG post-decoding conversion	29
8.2.6	Colour representation conversion: YCbCr to RGB	30
8.3	Approach 2: usage of SEI messages for "dynamic" bitstream SDR backward compatibility	30
8.3.1	General	30
8.3.2	CRI applied in YCbCr 4:2:0 domain	31
8.3.3	CRI applied in YCbCr 4:4:4 domain	32
8.3.4	TMI applied in RGB 4:4:4 domain	33
8.3.5	Derivation of DRA functions	34
8.3.6	Settings with colour remapping information SEI message	35
8.3.7	Settings with tone mapping information SEI message	36
9	Bitstream SDR backward compatibility with dual-layer SHVC coding	37
9.1	General	37
9.2	Encoding and decoding stages	37
10	Display adaptation	39
10.1	General	39
10.2	Display SDR backward compatibility	39
10.2.1	Conversion and coding process example	39
10.2.2	Using colour remapping information SEI message	41
	Bibliography	43