ISO/IEC 7811-2:2018 (E)

Identification cards — Recording technique — Part 2: Magnetic stripe: Low coercivity

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Conformance

5 Physical characteristics of the identification card

- 5.1 General
- 5.2 Magnetic stripe area warpage
- 5.3 Surface distortions

6 Physical characteristics of the magnetic stripe

- 6.1 Height and surface profile of the magnetic stripe area
- 6.1.1 Surface profile of the magnetic stripe area
- 6.1.2 Height of the magnetic stripe area
- 6.2 Surface roughness
- 6.3 Adhesion of stripe to card
- 6.4 Wear of magnetic stripe from read/write head
- 6.5 Resistance to chemicals

7 Performance characteristics for the magnetic material

- 7.1 General
- 7.2 Testing and operating environment
- 7.3 Signal amplitude requirements for magnetic media

8 Encoding technique

9 Encoding specification, general

- 9.1 Angle of recording
- 9.2 Nominal bit density
- 9.3 Signal amplitude requirements for tracks 1, 2 and 3
- 9.4 Bit configuration
- 9.5 Direction of recording
- 9.6 Leading and trailing zeroes

10 Encoding specifications

- 10.1 Alphanumeric track, Track 1
- 10.1.1 Average bit density
- 10.1.2 Flux transition spacing variation
- 10.1.3 Coded character set
- 10.1.4 Maximum number of characters for ID-1 type card
- 10.2 Numeric track, Track 2
- 10.2.1 Average bit density
- 10.2.2 Flux transition spacing variation
- 10.2.3 Coded character set
- 10.2.4 Maximum number of characters for ID-1 type card
- 10.3 Numeric track, Track 3
- 10.3.1 Average bit density
- 10.3.2 Flux transition spacing variation

10.3.3 Coded character set
10.3.4 Maximum number of characters for ID-1 type card

11 Error detection

11.1 General
11.2 Parity
11.3 Longitudinal redundancy check (LRC)

12 Location of encoded tracks

Annex A (informative) Magnetic stripe read compatibility — ISO/IEC 7811-2, ISO/IEC 7811-6

Annex B (informative) Magnetic stripe abrasivity

Page count: 19