ISO/IEC 30141:2018-08 (E)

Internet of Things (IoT) - Reference Architecture

CONTENTS

FOREWORD 6
INTRODUCTION 7
1 Scope 9
2 Normative references 9
3 Terms and definitions 9
4 Abbreviated terms 9
5 Internet of Things Reference Architecture (IoT RA) conformance 10
6 IoT RA goals and objectives 10
6.1 General 10
6.2 Characteristics 11
6.3 Conceptual Model 11
6.4 Reference Model and architecture views 11
7 Characteristics of IoT systems 12
7.1 General 12
7.2 IoT system trustworthiness characteristics 13
7.2.1 General 13
7.2.2 Availability 14
7.2.3 Confidentiality 14
7.2.4 Integrity 15
7.2.5 Protection of personally identifiable information (PII) 15
7.2.6 Reliability 16
7.2.7 Resilience 17
7.2.8 Safety 17
7.3 IoT system architecture characteristics 18
7.3.1 Composability 18
7.3.2 Functional and management capability separation 18
7.3.3 Heterogeneity 19
7.3.4 Highly distributed systems 20
7.3.5 Legacy support 20
7.3.6 Modularity 21
7.3.7 Network connectivity 21
7.3.8 Scalability 22
7.3.9 Shareability 22
7.3.10 Unique identification 23
7.3.11 Well-defined components 23
7.4 IoT system functional characteristics 24
7.4.1 Accuracy 24
7.4.2 Auto-configuration 25
7.4.3 Compliance 25
7.4.4 Content-awareness 26
7.4.5 Context-awareness 26
7.4.6 Data characteristics – volume, velocity, veracity, variability and variety 27

7.4.7 Discoverability 27
7.4.8 Flexibility 28
7.4.9 Manageability 29
7.4.10 Network communication 29
7.4.11 Network management and operation 30
7.4.12 Real-time capability 31
7.4.13 Self-description 31
7.4.14 Service subscription 32
8 IoT Conceptual Model (CM) 32
8.1 Main purpose 32
8.2 Concepts in the IoT CM 33
8.2.1 IoT entities and domains 33
8.2.2 Identity 35
8.2.3 Services, network, IoT device and IoT gateway 36
8.2.4 IoT-User 38
8.2.5 Virtual entity, Physical Entity and IoT device 39
8.3 High level view of CM 41
9 IoT Reference Model (RM) 42
9.1 The IoT Reference Model context 42
9.2 IoT RMs 42
9.2.1 Entity-based RM 42
9.2.2 Domain-based RM 44
9.2.3 Relation between entity-based RM and domain-based RM 46
10 IoT Reference Architecture (RA) views 46
10.1 General description 46
10.2 IoT RA functional view 47
10.2.1 General 47
10.2.2 Intra-domain functional components 47
10.2.3 Cross-domain capabilities 50
10.3 IoT RA system deployment view 51
10.3.1 General 51
10.3.2 Systems/sub-systems in Physical Entity Domain (PED) 52
10.3.3 Systems/sub-systems in Sensing & Controlling Domain (SCD) 52
10.3.4 Systems/sub-systems in Application & Service Domain (ASD) 52
10.3.5 Systems/sub-systems in Operation & Management Domain (OMD) 53
10.3.6 Systems/sub-systems in User Domain (UD) 53
10.3.7 Systems/sub-systems in Resource Access & Interchange Domain (RAID) 53
10.4 IoT RA networking view 54
10.4.1 Communications networks 54
10.4.2 Communication networks implementation 55
10.5 IoT RA usage view 56
10.5.1 General description 56
10.5.2 Description of the roles, sub-roles and related activities 56
10.5.3 Mapping activities, roles and IoT systems in domains 61

11 IoT trustworthiness 64
11.1 General 64
11.2 Safety 65
11.3 Security 66
11.3.1 General 66
11.3.2 IoT system Information Security Management System (ISMS) 66
11.3.3 IoT system & product Security Life Cycle Reference Model 68
11.4 Privacy and PII Protection 69
11.5 Reliability 72
11.6 Resilience 73
11.7 Trustworthiness and the Reference Architecture 74
Annex A (informative) Interpreting UML Class diagram for Conceptual Model 76
Annex B (informative) Entity relationship tables for the CM 77
B.1 IoT entities and domains 77
B.2 Identity 78
B.3 Services, network, IoT device and IoT gateway 78
B.4 IoT-User 79
B.5 Virtual entity, Physical Entity and IoT device 80
Annex C (informative) Relation between CM, RMs and RAs 81
Bibliography 83

Figure 1 – From generic Reference Architecture to context specific architecture 8
Figure 2 – IoT RA structure 11
Figure 3 – RM and architecture views 12
Figure 4 – Entity and domain concepts of the CM 33
Figure 5 – Domain interactions of the CM 34
Figure 6 – Identity concept of the CM 35
Figure 7 – Service, network, IoT device and IoT gateway concepts of the CM 36
Figure 8 – IoT-User concepts of the CM 38
Figure 9 – Virtual entity, Physical Entity, and IoT device concepts of the CM 39
Figure 10 – High level view of CM 41
Figure 11 – Entity-based IoT RM 42
Figure 12 – Domain and entity relationship, and representative conceptual entities in IoT systems 44
Figure 13 – Domain-based IoT RM 44
Figure 14 – Relation between entity-based RM and domain-based RM 46
Figure 15 – IoT RA functional view –decomposition of IoT RA functional components 47
Figure 16 – IoT RA system deployment view 52
Figure 17 – IoT RA networking view 54
Figure 18 – Roles present when the system is in use 57
Figure 19 – IoT service provider sub-roles and activities 59
Figure 20 – IoT service developer sub-roles and activities 60
Figure 21 IoT User sub roles and activities 61

Figure 22 – Activities of device and application development 63
Figure 23 – Using device data for security-related analytics and operations 64
Figure 24 – IoT product Security Life Cycle Reference Model 69
Figure A.1 – Generalization 76
Figure A.2 – Association 76
Figure C.1 – Relation between IoT CM, RM, and RA 82

Table 1 – Characteristics of IoT systems 13
Table 2 – Overview of activities and roles 62
Table B.1 – Entity 77
Table B.2 – Domain 77
Table B.3 – Digital Entity 77
Table B.4 – Physical Entity 77
Table B.5 – IoT-User 77
Table B.6 – Network 78
Table B.7 – Identifier 78
Table B.8 – Endpoint 78
Table B.9 – IoT gateway 78
Table B.10 – IoT device 79
Table B.11 – Service 79
Table B.12 – Human user 79
Table B.13 – Digital user 79
Table B.14 – Application 80
Table B.15 – Sensor 80
Table B.16 – Actuator 80
Table B.17 – Virtual entity 80